

ZYVORAI LABS · CUSTOMER DOCUMENTATION

Machina

Page-by-Page Product Manual

2026-10-03

Page-by-page guides

Each guide follows: Purpose → When to use it → How to get there → What you can do → Related pages.

Every route is also listed in the [complete page index](#).

Core

Page	What it covers
Capabilities	Capabilities — Machina Core page at <code>/capabilities</code> .
Create new guest VM	Create a new libvirt VM.
Node Devices	Node Devices — Machina Core page at <code>/devices</code> .
Fleet	Fleet — Machina Core page at <code>/fleet</code> .
Dashboard	Host dashboard — VM inventory pulse, Vessel container shortcuts when Podman/Docker is connected, and quick links.
SSH — hypervisor	Host SSH — Machina Core page at <code>/host-ssh</code> .
Import guest VM	Import VM — Machina Core page at <code>/import</code> .
Systemd Services	Services — Machina Core page at <code>/services</code> .
Sprites	Instant, disposable sandbox VMs — boot on libvirt/QEMU, Cloud Hypervisor, or Firecracker, TTL-reaped automatically, no persistent state.
VM detail: Guest policy	Restrict what individual containers inside a VM may do: which networks they reach, which programs they run, which devices they open and where they write. The rules are enforced inside the guest by GuestKit's agent (<code>guestkitd</code>) with its own eBPF programs. Machina sends them through the QEMU guest agent, so no network path into the guest is needed.
Virtual Machines	Virtual machine inventory for this libvirt host.

Fleet Cloud

Page	What it covers
Create Fleet Cloud instance	Create Instance — Machina Fleet Cloud page at <code>/fleet-cloud/create</code> .
Flavors	Flavors — Machina Fleet Cloud page at <code>/fleet-cloud/flavors</code> .
Floating IPs	Floating IPs — Machina Fleet Cloud page at <code>/fleet-cloud/floating-ips</code> .
Heat Orchestration	Heat Orchestration — Machina Fleet Cloud page at <code>/fleet-cloud/heat</code> .
Identity	Identity — Machina Fleet Cloud page at <code>/fleet-cloud/identity</code> .
Images	Images — Machina Fleet Cloud page at <code>/fleet-cloud/images</code> .
Fleet Cloud Instances	Instances — Machina Fleet Cloud page at <code>/fleet-cloud/instances</code> .
SSH keypairs	Keypairs — Machina Fleet Cloud page at <code>/fleet-cloud/keypairs</code> .

Page	What it covers
Load Balancers	Load Balancers — Machina Fleet Cloud page at /fleet-cloud/load-balancers .
Networking	Networking — Machina Fleet Cloud page at /fleet-cloud/networking .
Security Groups	Security Groups — Machina Fleet Cloud page at /fleet-cloud/security-groups .
Server Groups	Server Groups — Machina Fleet Cloud page at /fleet-cloud/server-groups .
Network topology	Network Topology — Machina Fleet Cloud page at /fleet-cloud/topology .
Volume Snapshots	Volume Snapshots — Machina Fleet Cloud page at /fleet-cloud/volume-snapshots .
Volumes	Volumes — Machina Fleet Cloud page at /fleet-cloud/volumes .
Fleet Cloud	Overview — Machina Fleet Cloud page at /fleet-cloud .

Infrastructure

Page	What it covers
Backups (Snapshot Backups)	Snapshot Backups — Machina Infrastructure page at /backups .
Container Pods	Podman pods via Vessel — create and manage shared-namespace container groups (not Kubernetes pods).
Containers	Local Podman/Docker containers via Vessel — list, create, lifecycle, and live stats on this host.
Disk Images	Disk Images — Machina Infrastructure page at /disk-images .
Host Networking	Host Networking — Machina Infrastructure page at /host-networking .
Networks	Networks — Machina Infrastructure page at /networks .
Network Filters	Network Filters — Machina Infrastructure page at /nwfilters .
Secrets	Secrets — Machina Infrastructure page at /secrets .
Snapshots	Snapshots — Machina Infrastructure page at /snapshots .
Storage pools	Storage Pools — Machina Infrastructure page at /storage .

Kubernetes

Page	What it covers
Kata + Cloud Hypervisor	Kata + Cloud Hypervisor — Machina Kubernetes page at /k8s/kata .
Kubernetes Workloads	K8s Workloads — Machina Kubernetes page at /k8s/workloads .
Kubernetes	Kubernetes — Machina Kubernetes page at /k8s .

Monitoring

Page	What it covers
Web sessions	Web Sessions — Machina Monitoring page at /admin/sessions .

Page	What it covers
Audit Log	Audit Log — Machina Monitoring page at <code>/audit</code> .
Live Metrics	Live Metrics — Machina Monitoring page at <code>/events</code> .
Daemon Jobs	Daemon Jobs — Machina Monitoring page at <code>/jobs</code> .
System Logs	System Logs — Machina Monitoring page at <code>/logs</code> .
Host overview	Host Overview — Machina Monitoring page at <code>/node</code> .
System Check	System Check — Machina Monitoring page at <code>/system-check</code> .

Platform

Page	What it covers
API Docs	API Docs — Platform surface.
Activity Monitor	Activity Monitor — Machina Platform page at <code>/platform/activity</code> .
AI Providers	AI Providers — Machina Platform page at <code>/platform/ai-providers</code> .
Alert Rules	Threshold alert rules on VM CPU and memory: notify (via Alerts / webhooks) when a metric crosses a bound.
API keys	API Keys — Machina Platform page at <code>/platform/api-keys</code> .
Applications	Applications — Machina Platform page at <code>/platform/applications</code> .
Backup & Restore	Fleet backups: a timeline of backup runs, backup destinations (NFS, S3/MinIO or local), recurring schedules by project or tag, and one-off backups of a single VM.
Register Server	Bare Metal — Machina Platform page at <code>/platform/baremetal</code> .
Blueprint Studio	Blueprints — Machina Platform page at <code>/platform/blueprints</code> .
Cloud-Init Studio	Cloud-Init Studio — Machina Platform page at <code>/platform/cloud-init</code> .
Content Library	Images & ISOs — Machina Platform page at <code>/platform/content</code> .
Advanced VM install	Advanced Create — Machina Platform page at <code>/platform/create-advanced</code> .
Create VM from ISO	Create ISO — Machina Platform page at <code>/platform/create-iso</code> .
Datacenter	Datacenter View — Machina Platform page at <code>/platform/datacenter</code> .
Developer	Developer Hub — Machina Platform page at <code>/platform/developer</code> .
Host Enrollment	Join new KVM hypervisors to the control plane. You generate a one-time join token here and run the install command on the new host; its <code>machina-agent</code> then registers with the controller.
Enterprise Features	Enterprise Features — Machina Platform page at <code>/platform/enterprise</code> .
Platform events	Event Log — Machina Platform page at <code>/platform/events</code> .
Fleet snapshot schedules	Fleet Snapshots — Machina Platform page at <code>/platform/fleet-snapshots</code> .
GPU Command Center	GPU Command Center — Machina Platform page at <code>/platform/gpu</code> .

Page	What it covers
High Availability	Fleet high availability: which hosts are healthy, fence events, and HA restarts of VMs from failed hosts. The controller fences a failed host before it restarts that host's VMs elsewhere, so a VM never runs twice.
Machine Finder	Machine Finder: opens the fleet VM list in its topology lens (<code>/platform/vms?lens=topology</code>) to find any VM by host, network or name.
Hosts	Every hypervisor enrolled with the controller: online/offline state, agent heartbeat, capacity and the VMs it runs. This is where you start any host-level task in the fleet.
Launchpad (on Mission Control)	Launchpad tiles live on Mission Control (<code>/platform</code>) — there is no separate <code>/platform/launchpad</code> route.
Maintenance	Maintenance — Machina Platform page at <code>/platform/maintenance</code> .
Marketplace	Marketplace — Machina Platform page at <code>/platform/marketplace</code> .
Migration Assistant	Migration Radar: bring VMs into Machina from VMware vCenter, ESXi, OVF/OVA, VMDK or cloud images. HyperSDK discovers and converts source VMs; GuestKit checks disks offline before and after conversion.
Network canvas	Network Canvas — Machina Platform page at <code>/platform/network-canvas</code> .
Networks	The fleet network pane: libvirt networks across hosts, overlay segments with east-west policy, and IPAM pools that hand out addresses from a segment CIDR.
Alerts	Alerts — Machina Platform page at <code>/platform/notifications</code> .
Observability	Observability — Machina Platform page at <code>/platform/observability</code> .
Placement & HA	Disaster Recovery — Machina Platform page at <code>/platform/placement</code> .
Policy rules	Policy — Machina Platform page at <code>/platform/policy</code> .
Stage Manager	Stage Manager — Machina Platform page at <code>/platform/projects</code> .
Recommendations	Recommendations — Machina Platform page at <code>/platform/recommendations</code> .
Runbook catalog	Reports — Machina Platform page at <code>/platform/reports</code> .
Scheduled Jobs	Recurring controller operations from a whitelist, for example periodic host inventory refresh.
Settings	One hub for platform configuration: general and cluster preferences, identity and SSO, users and groups, API keys, AI providers, Zyra, network, policy and quotas, webhooks, reports, console, keychain and updates.
Security Operations Center	Security Operations — Machina Platform page at <code>/platform/soc</code> .
Storage (Atlas)	Storage (Atlas) — Machina Platform page at <code>/platform/storage-atlas</code> .
Storage Tiers	Storage Tiers — Machina Platform page at <code>/platform/storage-tiers</code> .
Storage (Disk Utility)	Disk Utility — Machina Platform page at <code>/platform/storage</code> .
Support Assistant	Support — Machina Platform page at <code>/platform/support</code> .
Tasks	The controller's orchestration queue. Every long-running operation (VM create, migrate, backup, agent upgrade, ...) is a task with an operation name, status, progress and message.

Page	What it covers
Marketplace (Templates)	Templates — Machina Platform page at <code>/platform/templates</code> .
Topology	Topology — Machina Platform page at <code>/platform/topology</code> .
Upgrade Matrix	Version compatibility between the controller and host agents (controller version, minimum and recommended agent) and a per-host Upgrade Agent action.
Users & Groups	Users & Groups — Machina Platform page at <code>/platform/users</code> .
AI VM Builder	VM Builder — Machina Platform page at <code>/platform/vm-builder</code> .
Machine Finder	Fleet VM finder across enrolled hosts.
Webhooks	Webhooks — Machina Platform page at <code>/platform/webhooks</code> .
Mission Control	Mission Control — multi-host platform overview.
Settings	Daemon and UI settings, including Fleet Cloud wiring.

Platform Security

Page	What it covers
Security Center	Fleet security overview: the infrastructure security graph, critical findings, natural-language event search, and the eBPF sensor matrix showing <code>machina-bpfd</code> on every host as reported through its agent.
Zyra Approvals	Approvals — Machina Platform / Security page at <code>/platform/zyra/approvals</code> .
Configure Zyra	Configure Zyra — Machina Platform / Security page at <code>/platform/zyra/configure</code> .
Incident Commander	Incident Commander — Machina Platform / Security page at <code>/platform/zyra/incidents</code> .
VM Rightsizing	Rightsizing — Machina Platform / Security page at <code>/platform/zyra/rightsizing</code> .
Native eBPF	Operate Machina's built-in eBPF datapath on a host. One root service, <code>machina-bpfd</code> , loads Machina's own kernel programs for flow visibility, policy enforcement, load balancing, DDoS protection, VM isolation and scheduling. This page is the console for it; there is no separate Cilium, Tetragon, Netra or PacketWolf agent to install.
Machina Zyra OS	Zyra AI assistant for Machina operations.

107 guides. Regenerate: `node scripts/customer-docs/generate-guide-index.mjs` .

Capabilities

Purpose

Capabilities — Machina Core page at `/capabilities` .

When to use it

- Operate **Capabilities** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/capabilities`
- Nav: **Core** → **Capabilities** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Capabilities / System Info**.
3. Refresh.
4. **Empty:** —.
5. **Success:** Arch/features listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Host overview](#)
 - [Node Devices](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Create new guest VM

Purpose

Create a new libvirt VM.

When to use it

- Operate **Create new guest VM** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/create`
- Nav: **Core** → **Create VM** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Modes: install vs golden; Source & OS → Disk → Network → Cloud-init → Review.**
3. Install from media or Clone golden image.
4. Browse ISO.
5. Create VM.
6. Save defaults.
7. **Empty:** Need pool/volume or new disk.
8. **Success:** Job/console opens; guest listed on `/vms`.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Virtual Machines](#)
 - [Disk Images](#)
 - [Storage pools](#)
 - [Create VM from ISO](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Node Devices

Purpose

Node Devices — Machina Core page at `/devices`.

When to use it

- Operate **Node Devices** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/devices`
- Nav: **Core** → **Node Devices** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Refresh.
3. **Empty:** No devices found.
4. **Success:** PCI/USB tree visible.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Host overview](#)
 - [Capabilities](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Fleet

Purpose

Fleet — Machina Core page at `/fleet` .

When to use it

- Operate **Fleet** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet`
- Nav: **Core** → **Fleet** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Peer list; placement vCPU/mem.**
3. Refresh.
4. Create on best peer.
5. Start/Shutdown/Stop peer VMs.
6. Placement suggest.
7. **Empty:** No fleet peers → add peers in Settings.
8. **Success:** Peers online; VMs aggregated.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Virtual Machines](#)
 - [Hosts](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Dashboard

Purpose

Host dashboard — VM inventory pulse, Vessel container shortcuts when Podman/Docker is connected, and quick links.

When to use it

- Operate **Dashboard** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/`
- Nav: **Core** → **Dashboard** (or spotlight / Finder search)

Notes

- If control-plane proxy URL is set, `/` may redirect to `/platform` (Mission Control).

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Guest strip; K8s status card**.
3. Refresh.
4. Create VM.
5. Create container.
6. Reboot/Shutdown host.
7. Open Platform.
8. Run system check.
9. **Empty**: Stats show 0 guests — use Create VM.
10. **Success**: Guests count + running badge update; metrics populate.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Virtual Machines](#)
 - [Create new guest VM](#)
 - [Mission Control](#)
 - [System Check](#)
 - [Containers](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Page index](#)
-

SSH — hypervisor

Purpose

Host SSH — Machina Core page at `/host-ssh` .

When to use it

- Operate **SSH — hypervisor** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/host-ssh`
- Nav: **Core** → **Host SSH** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Quick user cards**.
3. Pick user (root/admin).
4. Connect SSH console.
5. **Empty**: Hostname undetermined → back to Dashboard.
6. **Success**: Shell session connected.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Dashboard](#)
 - [Host overview](#)
 - [Getting Started](#)
 - [Mission Control](#)
 - [Page index](#)
-

Import guest VM

Purpose

Import VM — Machina Core page at `/import` .

When to use it

- Operate **Import guest VM** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/import`
- Nav: **Core** → **Import VM** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Source path picker**.
3. Browse disk.
4. Import from Fleet Cloud Images.
5. Create VM.
6. **Empty**: Need readable disk image.
7. **Success**: Domain defined; appears on `/vms`.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Virtual Machines](#)
 - [Disk Images](#)
 - [Images](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Systemd Services

Purpose

Services — Machina Core page at `/services` .

When to use it

- Operate **Systemd Services** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/services`
- Nav: **Core** → **Services** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Start/Stop/Enable units.
3. View journal.
4. **Empty:** —.
5. **Success:** Unit Active.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Host overview](#)
 - [System Logs](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Sprites

Purpose

Instant, disposable sandbox VMs — boot on libvirt/QEMU, Cloud Hypervisor, or Firecracker, TTL-reaped automatically, no persistent state.

When to use it

- Operate **Sprites** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/sprites`
- Nav: **Core** → **Sprites** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. New Sprite.
3. Refresh.
4. Delete.
5. **Empty:** No sprites running → New Sprite.
6. **Success:** Sprite running with TTL.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Virtual Machines](#)
 - [Create new guest VM](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

VM detail: Guest policy

Purpose

Restrict what individual containers **inside a VM** may do: which networks they reach, which programs they run, which devices they open and where they write. The rules are enforced inside the guest by GuestKit's agent (`guestkitd`) with its own eBPF programs. Machina sends them through the QEMU guest agent, so no network path into the guest is needed.

When to use it

- A VM runs Docker, Podman or Kubernetes workloads and one container should only reach, say, its database
- You want to block unexpected binaries, writable+executable memory, or writes outside a data directory for one container
- You need evidence first: audit mode reports what *would* be blocked

How to get there

- Open a VM (**Virtual Machines** → **VM name**) and pick the **Guest policy** tab.
- The VM must be running.

Before you start

- QEMU guest agent running in the VM.
- GuestKit (`guestkitd` and `guestkitctl`) installed in the guest, with `capabilities.ebpf: true` in `/etc/guestkit/agent-policy.yaml` . Without the opt-in the tab reports that guest eBPF is disabled.
- Guest kernel with BTF and cgroup v2. The MAC section also needs `bpf` in the guest's active LSM list.
- Viewing needs any role; applying needs **Admin**.

What you can do

The tab has two sections. Each one lists the containers that already have rules, with their mode and audited hits, and a form to apply new rules.

Container network policy

1. Enter the container name or id.
2. Choose which directions to police (egress, ingress).
3. Add allow rules, one per line, for example `egress 10.0.0.0/8 tcp 5432` or `egress 0.0.0.0/0 udp 53` .
4. Apply in **Audit (report only)**. Watch the hit counters.

Container MAC (BPF-LSM)

- **Deny exec** with an allowlist (`/usr/bin/python3`, `/app/server`)
- **Deny W+X** memory mappings
- **Restrict devices** with an allowlist (`c 10:200`, `b 8:*`)
- **Restrict writes** to allowlisted paths (`/tmp`, `/data`)

Audit, then enforce

- **Audit** is the default and only reports violations.

- **Enforce (leased)** denies them for the lease you enter (1–3600 s). The deadline lives in the guest's policy map, so the guest kernel reverts to audit by itself when it expires, even if Machina is unreachable.
- Nothing is persisted. A guest reboot or `guestkitd` restart clears the rules.

If something is wrong

- **Guest agent not connected:** start `qemu-guest-agent` in the VM.
- **eBPF disabled in guest:** set `capabilities.ebpf: true` in the guest's agent policy and restart `guestkitd`.
- **Container not found:** use the name or id shown by `docker ps` / `podman ps` / `crictl ps` in the guest.

Related pages

- [Virtual Machines](#)
 - [Native eBPF](#)
 - [Page index](#)
-

Virtual Machines

Purpose

Virtual machine inventory for this libvirt host.

When to use it

- Operate **Virtual Machines** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/vms`
- Nav: **Core** → **Virtual Machines** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Search; tag filter; Table/Grid; pin.**
3. Create VM.
4. Import VM.
5. Start/Stop/Pause/Resume.
6. Console/SSH.
7. Bulk delete.
8. Export JSON/CSV.
9. **Empty:** No guests → Create VM / Import.
10. **Success:** VM appears running; console opens.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create new guest VM](#)
 - [Import guest VM](#)
 - [VM detail: Guest policy](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Create Fleet Cloud instance

Purpose

Create Instance — Machina Fleet Cloud page at `/fleet-cloud/create` .

When to use it

- Operate **Create Fleet Cloud instance** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/create`
- Nav: **Fleet Cloud** → **Create Instance** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Wizard fields**.
3. Pick image/flavor/network/keypair/SGs.
4. Create instance.
5. **Empty**: No flavors → create flavor first.
6. **Success**: Instance listed running.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Images](#)
 - [Flavors](#)
 - [Fleet Cloud Instances](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Flavors

Purpose

Flavors — Machina Fleet Cloud page at `/fleet-cloud/flavors` .

When to use it

- Operate **Flavors** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/flavors`
- Nav: **Fleet Cloud** → **Flavors** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create flavor.
3. Delete.
4. Open.
5. **Empty:** No flavors from Compute.
6. **Success:** Flavor selectable in create.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create Fleet Cloud instance](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Floating IPs

Purpose

Floating IPs — Machina Fleet Cloud page at `/fleet-cloud/floating-ips` .

When to use it

- Operate **Floating IPs** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/floating-ips`
- Nav: **Fleet Cloud** → **Floating IPs** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Instance forwards**.
3. Add forward.
4. Refresh.
5. **Empty**: No native FIP pool — use port forward.
6. **Success**: Forward works to guest.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud Instances](#)
 - [Networking](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Heat Orchestration

Purpose

Heat Orchestration — Machina Fleet Cloud page at `/fleet-cloud/heat` .

When to use it

- Operate **Heat Orchestration** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/heat`
- Nav: **Fleet Cloud** → **Heat Orchestration** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create stack.
3. Delete.
4. **Empty:** No stacks.
5. **Success:** Stack CREATE_COMPLETE.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Identity

Purpose

Identity — Machina Fleet Cloud page at `/fleet-cloud/identity` .

When to use it

- Operate **Identity** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/identity`
- Nav: **Fleet Cloud** → **Identity** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Projects**.
3. Create project.
4. Enable.
5. **Empty**: No projects.
6. **Success**: Project selectable.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud Instances](#)
 - [Users & Groups](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Images

Purpose

Images — Machina Fleet Cloud page at `/fleet-cloud/images` .

When to use it

- Operate **Images** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/images`
- Nav: **Fleet Cloud** → **Images** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Register image.
3. Delete.
4. Refresh.
5. **Empty:** Empty catalog → register.
6. **Success:** Image ACTIVE for boot.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create Fleet Cloud instance](#)
 - [Import guest VM](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Fleet Cloud Instances

Purpose

Instances — Machina Fleet Cloud page at `/fleet-cloud/instances` .

When to use it

- Operate **Fleet Cloud Instances** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/instances`
- Nav: **Fleet Cloud** → **Instances** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Project scope**.
3. Create instance.
4. Start/Stop/Reboot.
5. Refresh.
6. Console.
7. **Empty**: No instances → Create.
8. **Success**: Instance ACTIVE.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create Fleet Cloud instance](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

SSH keypairs

Purpose

Keypairs — Machina Fleet Cloud page at `/fleet-cloud/keypairs` .

When to use it

- Operate **SSH keypairs** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/keypairs`
- Nav: **Fleet Cloud** → **Keypairs** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Import.
3. Delete.
4. Refresh.
5. **Empty:** Import-only (no generate).
6. **Success:** Keypair listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create Fleet Cloud instance](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Load Balancers

Purpose

Load Balancers — Machina Fleet Cloud page at `/fleet-cloud/load-balancers` .

When to use it

- Operate **Load Balancers** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/load-balancers`
- Nav: **Fleet Cloud** → **Load Balancers** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create.
3. Add members.
4. **Empty:** No load balancers.
5. **Success:** LB listening with members.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud Instances](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Networking

Purpose

Networking — Machina Fleet Cloud page at `/fleet-cloud/networking` .

When to use it

- Operate **Networking** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/networking`
- Nav: **Fleet Cloud** → **Networking** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Networks/ports**.
3. Create network.
4. Create port.
5. Delete.
6. Refresh.
7. **Empty:** —.
8. **Success:** Network/port created.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Network topology](#)
 - [Security Groups](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Security Groups

Purpose

Security Groups — Machina Fleet Cloud page at `/fleet-cloud/security-groups` .

When to use it

- Operate **Security Groups** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/security-groups`
- Nav: **Fleet Cloud** → **Security Groups** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create group.
3. Add rules.
4. Delete.
5. **Empty:** No security groups.
6. **Success:** Rules applied; attachable.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud Instances](#)
 - [Create Fleet Cloud instance](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Server Groups

Purpose

Server Groups — Machina Fleet Cloud page at `/fleet-cloud/server-groups` .

When to use it

- Operate **Server Groups** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/server-groups`
- Nav: **Fleet Cloud** → **Server Groups** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Add to group.
3. Delete.
4. Refresh.
5. **Empty:** No anti-affinity groups yet.
6. **Success:** Group has members.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud Instances](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Network topology

Purpose

Network Topology — Machina Fleet Cloud page at `/fleet-cloud/topology` .

When to use it

- Operate **Network topology** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/topology`
- Nav: **Fleet Cloud** → **Network Topology** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Inspect graph.
3. **Empty:** Empty until nets/instances.
4. **Success:** Topology shows nets+VMs.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Networking](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Volume Snapshots

Purpose

Volume Snapshots — Machina Fleet Cloud page at `/fleet-cloud/volume-snapshots` .

When to use it

- Operate **Volume Snapshots** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/volume-snapshots`
- Nav: **Fleet Cloud** → **Volume Snapshots** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create snapshot.
3. Delete.
4. Refresh.
5. **Empty:** No snapshots.
6. **Success:** Snapshot listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Volumes](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Volumes

Purpose

Volumes — Machina Fleet Cloud page at `/fleet-cloud/volumes` .

When to use it

- Operate **Volumes** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud/volumes`
- Nav: **Fleet Cloud** → **Volumes** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Project**.
3. Create volume.
4. Attach/Detach.
5. Delete.
6. Refresh.
7. **Empty**: No volumes in this project.
8. **Success**: Attached to instance.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Volume Snapshots](#)
 - [Fleet Cloud Instances](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Fleet Cloud

Purpose

Overview — Machina Fleet Cloud page at `/fleet-cloud` .

When to use it

- Operate **Fleet Cloud** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/fleet-cloud`
- Nav: **Fleet Cloud** → **Overview** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Sub-nav**.
3. Create instance.
4. Open Instances/Images/Volumes quick links.
5. **Empty:** —.
6. **Success:** Cards navigate; counts sensible.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Fleet Cloud Instances](#)
 - [Create Fleet Cloud instance](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Backups (Snapshot Backups)

Purpose

Snapshot Backups — Machina Infrastructure page at `/backups` .

When to use it

- Operate **Backups (Snapshot Backups)** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/backups`
- Nav: **Infrastructure** → **Snapshot Backups** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. New Backup.
3. Scheduled Backup.
4. Verify checksums.
5. **Empty:** No backups.
6. **Success:** Backup completed/verified.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Time Machine](#)
 - [Snapshots](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Container Pods

Purpose

Podman pods via Vessel — create and manage shared-namespaces container groups (not Kubernetes pods).

When to use it

- Operate **Container Pods** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/containers/pods`
- Nav: **Infrastructure** → **Container Pods** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create pod.
3. Start/Stop.
4. Refresh.
5. **Empty:** No pods.
6. **Success:** Pod running.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Containers](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Containers

Purpose

Local Podman/Docker containers via Vessel — list, create, lifecycle, and live stats on this host.

When to use it

- Operate **Containers** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/containers`
- Nav: **Infrastructure** → **Containers** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create container.
3. Start/Stop.
4. Refresh.
5. **Empty**: No containers (Vessel/Podman/Docker).
6. **Success**: Container running.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Container Pods](#)
 - [Dashboard](#)
 - [Getting Started](#)
 - [Mission Control](#)
 - [Page index](#)
-

Disk Images

Purpose

Disk Images — Machina Infrastructure page at `/disk-images` .

When to use it

- Operate **Disk Images** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/disk-images`
- Nav: **Infrastructure** → **Disk Images** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create VM.
3. Import VM.
4. Open Jobs.
5. **Empty:** No disk images found.
6. **Success:** Image path usable in create/import.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create new guest VM](#)
 - [Import guest VM](#)
 - [Daemon Jobs](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Host Networking

Purpose

Host Networking — Machina Infrastructure page at `/host-networking` .

When to use it

- Operate **Host Networking** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/host-networking`
- Nav: **Infrastructure** → **Host Networking** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Bridges/routes/DNS/firewall**.
3. Create Bridge.
4. Add Rule.
5. Refresh diagnostics.
6. **Empty:** —.
7. **Success:** Bridge/rule applied.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Networks](#)
 - [Host overview](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Networks

Purpose

Networks — Machina Infrastructure page at `/networks` .

When to use it

- Operate **Networks** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/networks`
- Nav: **Infrastructure** → **Networks** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create network.
3. Start/Stop.
4. Edit XML.
5. **Empty:** No libvirt networks.
6. **Success:** Network active.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Networks](#)
 - [Network Filters](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Network Filters

Purpose

Network Filters — Machina Infrastructure page at `/nwfilters` .

When to use it

- Operate **Network Filters** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/nwfilters`
- Nav: **Infrastructure** → **Network Filters** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create Filter.
3. **Empty:** No network filters.
4. **Success:** Filter defined.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Networks](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Secrets

Purpose

Secrets — Machina Infrastructure page at `/secrets` .

When to use it

- Operate **Secrets** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/secrets`
- Nav: **Infrastructure** → **Secrets** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create/delete secret.
3. **Empty:** No secrets found.
4. **Success:** Secret listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Enterprise Features](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Snapshots

Purpose

Snapshots — Machina Infrastructure page at `/snapshots` .

When to use it

- Operate **Snapshots** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/snapshots`
- Nav: **Infrastructure** → **Snapshots** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Per-VM**.
3. Create.
4. Revert.
5. Delete.
6. Refresh.
7. **Empty**: No snapshots.
8. **Success**: Snapshot listed; revert OK.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Virtual Machines](#)
 - [Fleet snapshot schedules](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Storage pools

Purpose

Storage Pools — Machina Infrastructure page at `/storage` .

When to use it

- Operate **Storage pools** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/storage`
- Nav: **Infrastructure** → **Storage Pools** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Pool** → **volumes**.
3. Create volume.
4. Clone.
5. Resize.
6. Refresh.
7. **Empty**: No storage pools / No volumes.
8. **Success**: Volume listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Storage \(Disk Utility\)](#)
 - [Disk Images](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Kata + Cloud Hypervisor

Purpose

Kata + Cloud Hypervisor — Machina Kubernetes page at `/k8s/kata` .

When to use it

- Operate **Kata + Cloud Hypervisor** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/k8s/kata`
- Nav: **Kubernetes** → **Kata + Cloud Hypervisor** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Install sequence.
3. Apply RuntimeClass.
4. Refresh contexts.
5. **Empty:** Need cluster context.
6. **Success:** RuntimeClass present; pod with kata-clh.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Kubernetes](#)
 - [Kubernetes Workloads](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Kubernetes Workloads

Purpose

K8s Workloads — Machina Kubernetes page at `/k8s/workloads` .

When to use it

- Operate **Kubernetes Workloads** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/k8s/workloads`
- Nav: **Kubernetes → K8s Workloads** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Deployments/pods/services**.
3. Refresh.
4. Scale/rollout.
5. Apply.
6. Delete.
7. **Empty**: No workloads in this scope.
8. **Success**: Deployment Ready.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Kubernetes](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Kubernetes

Purpose

Kubernetes — Machina Kubernetes page at `/k8s`.

When to use it

- Operate **Kubernetes** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/k8s`
- Nav: **Kubernetes** → **Kubernetes** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Cluster/node status**.
3. Refresh contexts.
4. Open workloads.
5. Open Security Center.
6. **Empty**: No cluster nodes.
7. **Success**: Nodes Ready.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Kubernetes Workloads](#)
 - [Kata + Cloud Hypervisor](#)
 - [Security Center](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Web sessions

Purpose

Web Sessions — Machina Monitoring page at `/admin/sessions` .

When to use it

- Operate **Web sessions** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/admin/sessions`
- Nav: **Monitoring** → **Web Sessions** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Revoke (root only).
3. **Empty:** No active sessions.
4. **Success:** Session list matches logins.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Audit Log](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Audit Log

Purpose

Audit Log — Machina Monitoring page at `/audit` .

When to use it

- Operate **Audit Log** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/audit`
- Nav: **Monitoring** → **Audit Log** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Refresh now.
3. **Empty:** —.
4. **Success:** Audit rows after actions.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Platform events](#)
 - [Web sessions](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Live Metrics

Purpose

Live Metrics — Machina Monitoring page at `/events` .

When to use it

- Operate **Live Metrics** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/events`
- Nav: **Monitoring** → **Live Metrics** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Per-VM metrics**.
3. Refresh.
4. **Empty**: No running VMs with metrics.
5. **Success**: Charts update for running guests.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Host overview](#)
 - [Virtual Machines](#)
 - [Activity Monitor](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Daemon Jobs

Purpose

Daemon Jobs — Machina Monitoring page at `/jobs` .

When to use it

- Operate **Daemon Jobs** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/jobs`
- Nav: **Monitoring** → **Daemon Jobs** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Job list**.
3. Refresh.
4. Open job.
5. Create VM link.
6. **Empty**: No jobs yet.
7. **Success**: Job succeeded.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create new guest VM](#)
 - [Disk Images](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

System Logs

Purpose

System Logs — Machina Monitoring page at `/logs` .

When to use it

- Operate **System Logs** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/logs`
- Nav: **Monitoring** → **System Logs** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Unit/priority filters**.
3. Filter.
4. Follow journal.
5. **Empty:** —.
6. **Success:** Log lines stream.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Host overview](#)
 - [Systemd Services](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Host overview

Purpose

Host Overview — Machina Monitoring page at `/node` .

When to use it

- Operate **Host overview** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/node`
- Nav: **Monitoring** → **Host Overview** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Resource gauges; history charts**.
3. Refresh.
4. Install/start libvirt.
5. Kill process.
6. Package upgrade links.
7. **Empty**: Could not load host info.
8. **Success**: CPU/mem/disk gauges live.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Live Metrics](#)
 - [Systemd Services](#)
 - [System Logs](#)
 - [Host Networking](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

System Check

Purpose

System Check — Machina Monitoring page at `/system-check`.

When to use it

- Operate **System Check** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/system-check`
- Nav: **Monitoring** → **System Check** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Check categories**.
3. Run again.
4. **Empty:** —.
5. **Success:** All checks pass / actionable fails listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Dashboard](#)
 - [Host overview](#)
 - [Capabilities](#)
 - [Getting Started](#)
 - [Mission Control](#)
 - [Page index](#)
-

API Docs

Purpose

API Docs — Platform surface.

When to use it

- Open this page when the job matches the purpose above
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/api-docs`
- Nav: **Platform** → **API Docs** (or spotlight / Finder search)

What you can do

1. Open `/api-docs` against the Machina daemon (`https://<host>:5092`).
2. Use filters and host/VM selectors when the page provides them.
3. Drill into a VM, host, or Fleet Cloud resource for consoles and detail panels.
4. For mutating actions (create/delete VM, apply firewall, Fleet Cloud change): confirm the target host and role (Admin/Operator).

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud, Transiva, or Launchpad to be enabled.

Related pages

- [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Activity Monitor

Purpose

Activity Monitor — Machina Platform page at `/platform/activity` .

When to use it

- Operate **Activity Monitor** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/activity`
- Nav: **Platform** → **Activity Monitor** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **VMs / Hosts**.
3. Refresh.
4. Switch scope.
5. **Empty**: No running VMs / No hosts.
6. **Success**: Live CPU/mem/PSI.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machine Finder](#)
 - [Hosts](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

AI Providers

Purpose

AI Providers — Machina Platform page at `/platform/ai-providers` .

When to use it

- Operate **AI Providers** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/ai-providers`
- Nav: **Platform** → **AI Providers** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Add provider.
3. Save.
4. Delete.
5. **Empty:** —.
6. **Success:** Provider usable by Zyra.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machina Zyra OS](#)
 - [Settings](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Alert Rules

Purpose

Threshold alert rules on VM CPU and memory: notify (via Alerts / webhooks) when a metric crosses a bound.

When to use it

- Open this page when the job matches the purpose above
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/alert-rules`
- Nav: **Platform** → **Alert Rules** (or spotlight / Finder search)

What you can do

1. Open `/platform/alert-rules` against the Machina daemon (`https://<host>:5092`).
2. Use filters and host/VM selectors when the page provides them.
3. Drill into a VM, host, or Fleet Cloud resource for consoles and detail panels.
4. For mutating actions (create/delete VM, apply firewall, Fleet Cloud change): confirm the target host and role (Admin/Operator).

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud, HyperSDK, or Launchpad to be enabled.

Related pages

- [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

API keys

Purpose

API Keys — Machina Platform page at `/platform/api-keys` .

When to use it

- Operate **API keys** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/api-keys`
- Nav: **Platform** → **API Keys** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Create key.
3. Rotate.
4. Delete.
5. **Empty:** Create bearer for CI.
6. **Success:** `machina_*` key shown once.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Developer](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Applications

Purpose

Applications — Machina Platform page at `/platform/applications` .

When to use it

- Operate **Applications** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/applications`
- Nav: **Platform** → **Applications** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **App Launchpad icons**.
3. New Application.
4. Start all.
5. Stop all.
6. Backup all VMs.
7. **Empty**: No application groups → Create Application (need VMs).
8. **Success**: Group starts/stops as stack.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machine Finder](#)
 - [Time Machine](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Backup & Restore

Purpose

Fleet backups: a timeline of backup runs, backup destinations (NFS, S3/MinIO or local), recurring schedules by project or tag, and one-off backups of a single VM.

When to use it

- Register where backups are stored
- Back up every VM in a project or with a tag on a schedule, with retention
- Queue an immediate full or incremental backup of one VM
- Restore a VM

How to get there

- Route: `/platform/backups`
- Nav: **Platform** → **Backup & Restore** (or spotlight / Finder search)

What you can do

1. **Backup destinations:** register an NFS, S3 or local target and pick the default target.
2. **Queue VM backup:** enter a VM id, choose **Full backup** (whole qcow2) or **Incremental** (chains on the previous completed backup on that host), then **Queue backup**. The job shows up in [Tasks](#).
3. **New backup schedule:** name, interval in hours, retain count, and an optional project or tag filter. **Active schedules** lists them; delete with confirmation.
4. **Restore VM from backup:** restore runs from the VM detail page, where each VM's backup history lives ([Browse VMs](#)).

If something is wrong

- **Incremental fails:** there is no completed full backup for that VM on its current host yet; run a full one first.
- **S3 target errors:** check endpoint, bucket and credentials, and that the hosts can reach the endpoint.
- Snapshot schedules (not backups) live in [Fleet snapshot schedules](#).

Related pages

- [Backups \(Snapshot Backups\)](#)
 - [Machine Finder](#)
 - [Fleet snapshot schedules](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Register Server

Purpose

Bare Metal — Machina Platform page at `/platform/baremetal` .

When to use it

- Operate **Register Server** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/baremetal`
- Nav: **Platform** → **Bare Metal** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Register Server (BMC).
3. **Empty:** No bare metal servers.
4. **Success:** Server registered.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machina Zyra OS](#)
 - [Security Center](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Blueprint Studio

Purpose

Blueprints — Machina Platform page at `/platform/blueprints`.

When to use it

- Operate **Blueprint Studio** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/blueprints`
- Nav: **Platform** → **Blueprints** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Launchpad / Studio**.
3. New shortcut.
4. Create from VMs.
5. AI generate.
6. Run.
7. Delete.
8. **Empty**: Create shortcut to populate Launchpad.
9. **Success**: Blueprint run → tasks.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Tasks](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Cloud-Init Studio

Purpose

Cloud-Init Studio — Machina Platform page at `/platform/cloud-init`.

When to use it

- Operate **Cloud-Init Studio** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/cloud-init`
- Nav: **Platform** → **Cloud-Init Studio** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Edit.
3. Validate `#cloud-config`.
4. **Empty:** —.
5. **Success:** Validation OK.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create VM from ISO](#)
 - [Create new guest VM](#)
 - [Create Fleet Cloud instance](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Content Library

Purpose

Images & ISOs — Machina Platform page at `/platform/content` .

When to use it

- Operate **Content Library** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/content`
- Nav: **Platform** → **Images & ISOs** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **All / Pending / Approved**.
3. Upload.
4. Download URL.
5. Create from ISO.
6. Approve.
7. **Empty**: No images → upload for approval.
8. **Success**: Image Approved.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create VM from ISO](#)
 - [Marketplace \(Templates\)](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Advanced VM install

Purpose

Advanced Create — Machina Platform page at `/platform/create-advanced` .

When to use it

- Operate **Advanced VM install** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/create-advanced`
- Nav: **Platform** → **Advanced Create** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Default DHCP**.
3. virt-install path/URL.
4. Create from ISO.
5. **Empty:** —.
6. **Success:** Install task running.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Create VM from ISO](#)
 - [Create new guest VM](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Create VM from ISO

Purpose

Create ISO — Machina Platform page at `/platform/create-iso`.

When to use it

- Operate **Create VM from ISO** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/create-iso`
- Nav: **Platform** → **Create ISO** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Network: Default DHCP**.
3. Create.
4. Import .pub.
5. Open Content Library.
6. **Empty**: No approved ISOs → Content Library.
7. **Success**: VM task queued; appears in Finder.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Content Library](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Datacenter

Purpose

Datacenter View — Machina Platform page at `/platform/datacenter` .

When to use it

- Operate **Datacenter** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/datacenter`
- Nav: **Platform** → **Datacenter View** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Multi-hypervisor scope**.
3. Refresh inventory.
4. **Empty**: Empty inventory → enroll hosts.
5. **Success**: Hosts listed with honest scope.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Hosts](#)
 - [Topology](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Developer

Purpose

Developer Hub — Machina Platform page at `/platform/developer` .

When to use it

- Operate **Developer** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/developer`
- Nav: **Platform → Developer Hub** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **SDK & Terraform / API Console**.
3. OpenAPI.
4. Try API Console.
5. **Empty:** —.
6. **Success:** Spec loads; call succeeds.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [API keys](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Host Enrollment

Purpose

Join new KVM hypervisors to the control plane. You generate a one-time join token here and run the install command on the new host; its `machina-agent` then registers with the controller.

When to use it

- Adding a new hypervisor to the fleet
- Re-enrolling a host after a reinstall
- Auditing which join tokens were issued, used or revoked

How to get there

- Route: `/platform/enroll`
- Nav: **Platform** → **Add Host** (or spotlight / Finder search)

What you can do

1. Under **Join token**, generate a token. The **Active token** panel shows the token, its expiry and a ready-made **Install command**; copy either.
2. On the new KVM host (with libvirt installed), run the install command, or `machina-agent join --controller URL --token TOKEN`.
3. The host appears on [Hosts](#) once its first heartbeat arrives. Run **Validate** there.
4. **Recent tokens** lists issued tokens with their state. Used and revoked tokens stay for audit.

If something is wrong

- **Token expired:** generate a new one; tokens are single-use and time-limited.
- **Host never appears:** check that the host resolves and reaches the controller URL in the command, and that `machina-agent` is running (`journalctl -u machina-agent`).
- Deploying the controller and agent together on a test host: `./scripts/deploy-remote.sh USER@HOST --platform`.

Related pages

- [Hosts](#)
 - [Upgrade Matrix](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Enterprise Features

Purpose

Enterprise Features — Machina Platform page at `/platform/enterprise`.

When to use it

- Operate **Enterprise Features** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/enterprise`
- Nav: **Platform** → **Enterprise Features** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Secrets / FIPS etc..**
3. Register provider.
4. Sync.
5. Save policy.
6. **Empty:** —.
7. **Success:** Policy saved.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Settings](#)
 - [Secrets](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Platform events

Purpose

Event Log — Machina Platform page at `/platform/events` .

When to use it

- Operate **Platform events** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/events`
- Nav: **Platform** → **Event Log** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **All / Audit / Events / Tasks**.
3. Apply filters.
4. Refresh.
5. **Empty**: No platform events.
6. **Success**: Filtered rows appear.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Audit Log](#)
 - [Tasks](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Fleet snapshot schedules

Purpose

Fleet Snapshots — Machina Platform page at `/platform/fleet-snapshots` .

When to use it

- Operate **Fleet snapshot schedules** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/fleet-snapshots`
- Nav: **Platform** → **Fleet Snapshots** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Project/tag filters**.
3. Add schedule.
4. Delete.
5. **Empty**: No fleet schedules yet.
6. **Success**: Schedule listed/enabled.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Snapshots](#)
 - [Time Machine](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

GPU Command Center

Purpose

GPU Command Center — Machina Platform page at `/platform/gpu` .

When to use it

- Operate **GPU Command Center** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/gpu`
- Nav: **Platform** → **GPU Command Center** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Browse hosts.
3. Create VM here.
4. Open Zyra.
5. **Empty:** No GPU inventory → tag hosts.
6. **Success:** GPUs discovered.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Hosts](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

High Availability

Purpose

Fleet high availability: which hosts are healthy, fence events, and HA restarts of VMs from failed hosts. The controller fences a failed host before it restarts that host's VMs elsewhere, so a VM never runs twice.

When to use it

- Confirm the fleet is healthy and fencing is configured
- Review what happened after a host failure (fence and HA events)
- Fence a host by hand when you know it is broken

How to get there

- Route: `/platform/ha`
- Nav: **Platform** → **High Availability** (or spotlight / Finder search)

What you can do

1. **Host Fencing** lists hosts and their state. **Fence** on a host (with confirmation) isolates it; use it only when the host is really unhealthy.
2. **Fence Events** shows each fence attempt and its result.
3. **HA Events** shows VMs restarted on other hosts after a failure.

How automatic HA works:

- A host whose agent heartbeat is older than **90 s** is considered failed. The controller scans for failed hosts every **45 s**.
- Before recovering VMs it fences the host: IPMI power-off from the controller when the host has BMC details, otherwise the command in `MACHINA_FENCE_COMMAND`.
- If fencing fails, VMs are **not** restarted unless the operator opted in with `allow_unfenced`.
- Only one controller acts at a time when several run (leader lease).

If something is wrong

- **"Enroll hosts to enable fencing"**: no hosts yet; see [Host Enrollment](#).
- **Fence fails**: check BMC address and credentials on the host (Bare Metal) or the fence command, and that the controller can reach the BMC network.
- Details for admins: `docs/controller-ha.md` in the repository.

Related pages

- [Placement & HA](#)
- [Hosts](#)
- [Maintenance](#)
- [Getting Started](#)
- [Dashboard](#)
- [Mission Control](#)
- [Page index](#)

Machine Finder

Purpose

Machine Finder: opens the fleet VM list in its topology lens (`/platform/vms?lens=topology`) to find any VM by host, network or name.

When to use it

- Open this page when the job matches the purpose above
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/hosts/finder`
- Nav: **Platform** → **Machine Finder** (or spotlight / Finder search)

What you can do

1. Open `/platform/hosts/finder` against the Machina daemon (`https://<host>:5092`).
2. Use filters and host/VM selectors when the page provides them.
3. Drill into a VM, host, or Fleet Cloud resource for consoles and detail panels.
4. For mutating actions (create/delete VM, apply firewall, Fleet Cloud change): confirm the target host and role (Admin/Operator).

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud, HyperSDK, or Launchpad to be enabled.

Related pages

- [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Hosts

Purpose

Every hypervisor enrolled with the controller: online/offline state, agent heartbeat, capacity and the VMs it runs. This is where you start any host-level task in the fleet.

When to use it

- Check whether a host is online and its agent heartbeat is current
- Find hosts that went offline (`?filter=offline`)
- Re-sync inventory after changes made outside Machina
- Validate a newly joined host before you place VMs on it

How to get there

- Route: `/platform/hosts`
- Nav: **Platform** → **Hosts** (or spotlight / Finder search)

What you can do

1. The list shows each managed host with status and last heartbeat. Use search, or open `?filter=offline` to see only offline hosts.
2. **Sync all** asks every agent to refresh its VM, storage and network inventory.
3. Select a host and **Open host** for its detail page (VMs, capacity, maintenance mode, agent version).
4. **Validate** runs host join validation (agent reachable, libvirt connected, versions compatible) and shows the result under **Validation**.
5. **Open in Machine Finder** jumps to the fleet VM list filtered to that host.

If something is wrong

- **No hosts:** enroll one from [Host Enrollment](#).
- **Host offline:** on the host, check `systemctl status machina-agent` and that it can reach the controller on port 5093 (and the controller can reach the agent on 50051).
- A host whose heartbeat is older than 90 seconds is treated as failed by HA; see [High Availability](#).

Related pages

- [Host Enrollment](#)
 - [Machine Finder](#)
 - [High Availability](#)
 - [Upgrade Matrix](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Launchpad (on Mission Control)

Purpose

Launchpad tiles live on Mission Control (`/platform`) — there is no separate `/platform/launchpad` route.

When to use it

- Operate **Launchpad (on Mission Control)** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/launchpad`
- Nav: **Platform → Launchpad (Mission Control)** (or spotlight / Finder search)

Notes

- There is **no** standalone `/platform/launchpad` route — Launchpad tiles are embedded on Mission Control.

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Operations launchpad on Mission Control**.
3. Open `/platform`.
4. Use Operations launchpad tiles (Create VM, Security, Finder, Recovery, GPU, Migration, Templates, Cinema, Live Wall).
5. **Empty:** There is no separate `/platform/launchpad` route.
6. **Success:** Tile opens the target surface.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Mission Control](#)
 - [Blueprint Studio](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Page index](#)
-

Maintenance

Purpose

Maintenance — Machina Platform page at `/platform/maintenance` .

When to use it

- Operate **Maintenance** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/maintenance`
- Nav: **Platform** → **Maintenance** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Schedule window.
3. Apply upgrades.
4. Enroll host.
5. **Empty:** No hosts / No windows.
6. **Success:** Window scheduled.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Upgrade Guide](#)
 - [Host Enrollment](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Marketplace

Purpose

Marketplace — Machina Platform page at `/platform/marketplace` .

When to use it

- Operate **Marketplace** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/marketplace`
- Nav: **Platform** → **Marketplace** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Featured**.
3. Install / Installed plugins.
4. **Empty**: No plugins available.
5. **Success**: Plugin Installed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Marketplace \(Templates\)](#)
 - [Applications](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Migration Assistant

Purpose

Migration Radar: bring VMs into Machina from VMware vCenter, ESXi, OVF/OVA, VMDK or cloud images. HyperSDK discovers and converts source VMs; GuestKit checks disks offline before and after conversion.

When to use it

- Plan a move off VMware: scan a vCenter or ESXi host and review what will convert cleanly
- Import a single OVF/OVA, VMDK or cloud image
- Follow GuestKit offline inspection and doctor jobs

How to get there

- Route: `/platform/migration`
- Nav: **Platform** → **Migration Assistant** (or spotlight / Finder search)

What you can do

1. Pick a source: **VMware vCenter**, **ESXi Host**, **OVF / OVA File**, **VMDK File** or **Cloud Image**.
2. **Scan & migrate**: run a scan; **Scan results** list discovered VMs with **Migration Advisor Warnings** (drivers, firmware, disk layout).
3. For one VM, **Open import wizard** (single-VM import).
4. **GuestKit jobs** (`?tab=jobs`) is the queue of offline inspect / doctor / migrate-plan jobs; enter a disk path such as `/var/lib/libvirt/images/vm.qcow2` to run one.
5. **HyperSDK proxy explorer** lets admins call provider-specific HyperSDK API paths directly.

If something is wrong

- **HyperSDK or GuestKit tabs disabled**: the integration is not enabled on the controller (`GUESTKIT_ENABLED` , HyperSDK settings).
- **No scan yet**: pick a source and provide its credentials first.

Related pages

- [Import guest VM](#)
 - [Placement & HA](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Network canvas

Purpose

Network Canvas — Machina Platform page at `/platform/network-canvas`.

When to use it

- Operate **Network canvas** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/network-canvas`
- Nav: **Platform** → **Network Canvas** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Canvas interactions**.
3. Inspect paths.
4. Open Security.
5. **Empty:** —.
6. **Success:** Path/trace visible.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Networks](#)
 - [Security Center](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Networks

Purpose

The fleet network pane: libvirt networks across hosts, overlay segments with east-west policy, and IPAM pools that hand out addresses from a segment CIDR.

When to use it

- Make an existing libvirt network (for example `virbr0`) known to the platform, or create a bridge-backed VM network
- Build Tier-0 (uplink) / Tier-1 (workload) overlay segments with east-west defaults
- Allocate addresses from IPAM pools instead of tracking them by hand

How to get there

- Route: `/platform/networks`
- Nav: **Platform** → **Networks** (or spotlight / Finder search)

What you can do

1. **Networks:** import libvirt networks from online hosts, or create a bridge-backed network. Search with the filter box; **Activate** / **Deactivate** / remove per row.
2. **Overlay segments:** **Create segment** with a CIDR, gateway, east-west default (allow or deny) and an optional Zyra firewall profile. Open a segment to see its allowed and blocked paths and micro-segmentation grade.
3. **IPAM pools:** segments with IPAM enabled show reservations and the next free offset.
4. **Emergency Unlock Segment** lifts a segment's east-west deny when it is blocking legitimate traffic during an incident.

If something is wrong

- **No networks yet:** import from a host that is online, or create one.
- East-west policy here is simulated and planned at the platform level; host-level packet enforcement is done by [Native eBPF](#).

Related pages

- [Networks](#)
 - [Network canvas](#)
 - [Security Center](#)
 - [Native eBPF](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Alerts

Purpose

Alerts — Machina Platform page at `/platform/notifications` .

When to use it

- Operate **Alerts** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/notifications`
- Nav: **Platform** → **Alerts** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Open runbook/action.
3. Acknowledge.
4. **Empty:** No alerts — you are caught up.
5. **Success:** Alert cleared.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Security Operations Center](#)
 - [Platform events](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Observability

Purpose

Observability — Machina Platform page at `/platform/observability` .

When to use it

- Operate **Observability** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/observability`
- Nav: **Platform** → **Observability** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **SLO / traces panels**.
3. Refresh.
4. **Empty**: No SLO policies / No API traces.
5. **Success**: Metrics & traces present.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Activity Monitor](#)
 - [Live Metrics](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Placement & HA

Purpose

Disaster Recovery — Machina Platform page at `/platform/placement`.

When to use it

- Operate **Placement & HA** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/placement`
- Nav: **Platform** → **Disaster Recovery** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Recs / migrations / fence / HA events**.
3. Toggle DRS auto-migrate.
4. Refresh.
5. Migrate (precheck).
6. **Empty**: Cluster load balanced (no recs).
7. **Success**: Migration job recorded.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [HA Events](#)
 - [Migration Radar](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Policy rules

Purpose

Policy — Machina Platform page at `/platform/policy` .

When to use it

- Operate **Policy rules** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/policy`
- Nav: **Platform** → **Policy** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Save quota.
3. **Empty:** —.
4. **Success:** Quota saved.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Users & Groups](#)
 - [Stage Manager](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Stage Manager

Purpose

Stage Manager — Machina Platform page at `/platform/projects` .

When to use it

- Operate **Stage Manager** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/projects`
- Nav: **Platform** → **Stage Manager** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Spaces**.
3. Open Machine Finder.
4. Assign project labels.
5. **Empty**: No workspace spaces yet.
6. **Success**: Space shows VMs.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machine Finder](#)
 - [Users & Groups](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Recommendations

Purpose

Recommendations — Machina Platform page at `/platform/recommendations` .

When to use it

- Operate **Recommendations** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/recommendations`
- Nav: **Platform** → **Recommendations** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Act on / dismiss recs.
3. **Empty:** Estate looks good.
4. **Success:** Rec applied or cleared.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [VM Rightsizing](#)
 - [Activity Monitor](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Runbook catalog

Purpose

Reports — Machina Platform page at `/platform/reports` .

When to use it

- Operate **Runbook catalog** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/reports`
- Nav: **Platform** → **Reports** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Export CSV/HTML/PDF.
3. Open compliance.
4. **Empty:** No runbooks.
5. **Success:** Export downloads.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Security Center](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Scheduled Jobs

Purpose

Recurring controller operations from a whitelist, for example periodic host inventory refresh.

When to use it

- Open this page when the job matches the purpose above
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/scheduled-jobs`
- Nav: **Platform** → **Scheduled Jobs** (or spotlight / Finder search)

What you can do

1. Open `/platform/scheduled-jobs` against the Machina daemon (`https://<host>:5092`).
2. Use filters and host/VM selectors when the page provides them.
3. Drill into a VM, host, or Fleet Cloud resource for consoles and detail panels.
4. For mutating actions (create/delete VM, apply firewall, Fleet Cloud change): confirm the target host and role (Admin/Operator).

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud, HyperSDK, or Launchpad to be enabled.

Related pages

- [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Settings

Purpose

One hub for platform configuration: general and cluster preferences, identity and SSO, users and groups, API keys, AI providers, Zyra, network, policy and quotas, webhooks, reports, console, keychain and updates.

When to use it

- Configuring SSO or adding users
- Creating API keys for automation
- Setting policy (for example, require confirmation for production VM deletion) or quotas
- Connecting AI providers for Zyra

How to get there

- Route: `/platform/settings`
- Nav: **Platform** → **Settings** (or spotlight / Finder search)

What you can do

1. Pick a section on the left: **General, Identity & SSO, Users & Groups, Security, API Keys, AI Providers, Zyra, Network, Infrastructure, Policy & Quotas, Apps & Integrations, Webhooks, Reports, Console, Keychain, Stage Manager, Updates.**
2. Many sections show a summary with an **Open full ... workspace** link to the dedicated page.
3. **Security** holds cluster-wide switches such as **Require confirmation for production VM deletion** (deletes queue for approval), air-gap bundles with artifact checksums, and tenant policy export as YAML (**Generate YAML**).
4. **Policy & Quotas** opens the full policy rules and project quota workspace.
5. Integrations moved here: the old `/platform/integrations` URL opens `?section=integrations`.

If something is wrong

- **Section read-only:** your role is not Admin.
- Host-level daemon settings (PAM, TLS, libvirt URI) are in `/etc/machina/config.toml`, not here; see the admin configuration guide.

Related pages

- [AI Providers](#)
 - [Configure Zyra](#)
 - [Users](#)
 - [API keys](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Security Operations Center

Purpose

Security Operations — Machina Platform page at `/platform/soc` .

When to use it

- Operate **Security Operations Center** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/soc`
- Nav: **Platform** → **Security Operations** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Overview / Alerts / Detections / Attack surface / Integrations**.
3. Run ingest.
4. New playbook.
5. Enable forwarders.
6. **Empty:** —.
7. **Success:** Alerts/detections populate.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Security Center](#)
 - [Mission Control](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Page index](#)
-

Storage (Atlas)

Purpose

Storage (Atlas) — Machina Platform page at `/platform/storage-atlas` .

When to use it

- Operate **Storage (Atlas)** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/storage-atlas`
- Nav: **Platform** → **Storage (Atlas)** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Backend cards (Ceph/NFS/ZFS)**.
3. New volume.
4. Restore.
5. **Empty**: Atlas disabled / unreachable.
6. **Success**: Backend healthy; volume ops.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Storage \(Disk Utility\)](#)
 - [Time Machine](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Storage Tiers

Purpose

Storage Tiers — Machina Platform page at `/platform/storage-tiers`.

When to use it

- Operate **Storage Tiers** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/storage-tiers`
- Nav: **Platform** → **Storage Tiers** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Define/edit tiers.
3. **Empty:** No storage tiers.
4. **Success:** Tier list non-empty.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Storage \(Disk Utility\)](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Storage (Disk Utility)

Purpose

Disk Utility — Machina Platform page at `/platform/storage` .

When to use it

- Operate **Storage (Disk Utility)** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/storage`
- Nav: **Platform** → **Disk Utility** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Disks / Pools / Tiers / Backup SLA**.
3. Sync hosts.
4. Add pool.
5. New volume.
6. Delete.
7. **Empty**: No storage pools → import/add.
8. **Success**: Pool active; volume created.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Storage pools](#)
 - [Storage \(Atlas\)](#)
 - [Storage Tiers](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Support Assistant

Purpose

Support — Machina Platform page at `/platform/support` .

When to use it

- Operate **Support Assistant** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/support`
- Nav: **Platform** → **Support** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Export support bundle.
3. **Empty:** —.
4. **Success:** Bundle downloads.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Platform events](#)
 - [System Logs](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Tasks

Purpose

The controller's orchestration queue. Every long-running operation (VM create, migrate, backup, agent upgrade, ...) is a task with an operation name, status, progress and message.

When to use it

- Follow a long operation you started elsewhere
- Find out why something failed
- Check controller health

How to get there

- Route: `/platform/tasks`
- Nav: **Platform** → **Tasks** (or spotlight / Finder search)

What you can do

1. Filter by status: **All**, **Pending**, **Running**, **Completed**, **Failed**.
2. **Filter by operation** (for example `vm.migrate`); **Clear filter** resets it.
3. Open a row for **Task detail**: operation, target, progress, message, the controller that ran it, and created/updated times.
4. **Controller health** shows the result of `GET /api/v1/health` .

If something is wrong

- **Task stuck in Pending**: the controller worker or (with NATS) the task bus is not processing; check controller health and logs.
- **Failed**: the message carries the error and usually a remediation hint.
- Scripts can poll the same data at `/api/v1/tasks/{task_id}` .

Related pages

- [Platform events](#)
 - [Activity Monitor](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Marketplace (Templates)

Purpose

Templates — Machina Platform page at `/platform/templates` .

When to use it

- Operate **Marketplace (Templates)** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/templates`
- Nav: **Platform** → **Templates** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Fleet catalog**.
3. Sync git.
4. Restore defaults.
5. Refresh.
6. Launch from template.
7. **Empty**: Marketplace empty → sync/restore.
8. **Success**: Template usable in create.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Content Library](#)
 - [Mission Control](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Page index](#)
-

Topology

Purpose

Topology — Machina Platform page at `/platform/topology` .

When to use it

- Operate **Topology** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/topology`
- Nav: **Platform** → **Topology** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Enroll host.
3. Import networks.
4. **Empty:** Enroll hosts and import networks.
5. **Success:** Twin graph populated.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Datacenter](#)
 - [Networks](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Upgrade Matrix

Purpose

Version compatibility between the controller and host agents (controller version, minimum and recommended agent) and a per-host **Upgrade Agent** action.

When to use it

- Before or after upgrading the controller, to see which agents are behind
- Rolling agent upgrades, one host at a time

How to get there

- Route: `/platform/upgrade`
- Nav: **Platform** → **Upgrade Matrix** (or spotlight / Finder search)

What you can do

1. **Upgrade Matrix** shows the controller version, the minimum and the recommended agent version.
2. **Hosts** lists each host's agent version against that matrix.
3. Follow the **Upgrade Guide** for each host:
 1. Put the host into maintenance mode from [Hosts](#).
 2. Click **Upgrade Agent**; this enqueues a `host.agent.upgrade` task.
 3. Watch it in [Tasks](#).
 4. When the agent heartbeat is back, take the host out of maintenance.

If something is wrong

- **No hosts enrolled:** enroll a host first.
- **Upgrade task fails:** check the task message in Tasks and `journalctl -u machina-agent` on the host.
- Backing up before upgrades and upgrading the controller and daemon themselves: see the operator runbook (`docs/handbook/runbook.md`).

Related pages

- [Maintenance](#)
 - [Hosts](#)
 - [Tasks](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Users & Groups

Purpose

Users & Groups — Machina Platform page at `/platform/users` .

When to use it

- Operate **Users & Groups** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/users`
- Nav: **Platform** → **Users & Groups** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Workspaces**.
3. Add user.
4. Delete.
5. Open Machine Finder.
6. **Empty**: No workspaces yet.
7. **Success**: User listed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Stage Manager](#)
 - [API keys](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

AI VM Builder

Purpose

VM Builder — Machina Platform page at `/platform/vm-builder` .

When to use it

- Operate **AI VM Builder** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/vm-builder`
- Nav: **Platform** → **VM Builder** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Prompt → Suggest.
3. Create VM.
4. **Empty:** —.
5. **Success:** Queued create with sized spec.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machina Zyra OS](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Machine Finder

Purpose

Fleet VM finder across enrolled hosts.

When to use it

- Operate **Machine Finder** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/vms`
- Nav: **Platform** → **Virtual Machines** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Lenses: Grid/Gallery/Table/Topology/Timeline/Heatmap/Migration; Smart Folders; tags.**
3. New VM.
4. Open Cinema.
5. SSH.
6. Power.
7. Delete.
8. Prune missing.
9. **Empty:** No machines → create VM / change folder.
10. **Success:** VM in folder; power state updates.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Mission Control](#)
 - [Hosts](#)
 - [Create VM from ISO](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Page index](#)
-

Webhooks

Purpose

Webhooks — Machina Platform page at `/platform/webhooks` .

When to use it

- Operate **Webhooks** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/webhooks`
- Nav: **Platform** → **Webhooks** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Add endpoint.
3. Delete.
4. View deliveries.
5. **Empty:** No webhook endpoints.
6. **Success:** Delivery succeeds.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [API keys](#)
 - [Platform events](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Mission Control

Purpose

Mission Control — multi-host platform overview.

When to use it

- Operate **Mission Control** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform`
- Nav: **Platform** → **Mission Control** (or spotlight / Finder search)

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **?mission=1** geography; host/VM sidebar rail.
3. Create VM (wizard).
4. Use Launchpad tiles.
5. Power VM.
6. Ask Zyra.
7. Geography expand.
8. Live Wall.
9. **Empty:** No hosts → Add host / enroll.
10. **Success:** Hosts online; VM create task; hero Operational.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machine Finder](#)
 - [Hosts](#)
 - [Time Machine](#)
 - [Host Enrollment](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Settings

Purpose

Daemon and UI settings, including Fleet Cloud wiring.

When to use it

- Open this page when the job matches the purpose above
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/settings`
- Nav: **Platform** → **Settings** (or spotlight / Finder search)

What you can do

1. Open `/settings` against the Machina daemon (`https://<host>:5092`).
2. Use filters and host/VM selectors when the page provides them.
3. Drill into a VM, host, or Fleet Cloud resource for consoles and detail panels.
4. For mutating actions (create/delete VM, apply firewall, Fleet Cloud change): confirm the target host and role (Admin/Operator).

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud, Transiva, or Launchpad to be enabled.

Related pages

- [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Security Center

Purpose

Fleet security overview: the infrastructure security graph, critical findings, natural-language event search, and the eBPF sensor matrix showing `machina-bpfd` on every host as reported through its agent.

When to use it

- Daily security review of the fleet
- Search events in plain language ("show every process that opened port 8080 last week")
- Check that every host's eBPF sensor is reporting

How to get there

- Route: `/platform/zeus/security`
- Nav: **Security Center** (or spotlight / Finder search)

What you can do

1. **Critical / Requires attention** summarise findings that need action.
2. **Infrastructure security graph** links hosts, VMs, networks and findings.
3. **Zeus security search** takes a natural-language query and returns matching events.
4. **eBPF sensor matrix / Sensor registry** list each host's `machina-bpfd` (version, mode, health). A host shown as **machina-bpfd unreachable** has no running bpfd or no agent link.
5. **Open Native eBPF** goes to the per-host console. The sub-nav also has Kubernetes, Cloud SGs, Connectivity, Policy Studio, Threat Hunting and Enforcement.

If something is wrong

- **machina-bpfd unreachable:** on that host, `systemctl status machina-bpfd machina-agent` .
- **Search returns nothing:** check that AI providers are configured for Zyra and that hosts are sending events.

Related pages

- [Native eBPF](#)
 - [Security Operations Center](#)
 - [Machina Zyra OS](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Zyra Approvals

Purpose

Approvals — Machina Platform / Security page at `/platform/zyra/approvals`.

When to use it

- Operate **Zyra Approvals** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/zyra/approvals`
- Nav: **Platform / Security → Approvals** (or spotlight / Finder search)

Notes

- Formerly documented under `/platform/zeus*` (except Zeus Security Center, which remains `/platform/zeus/security`).

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Approve / Deny.
3. **Empty:** No pending approvals.
4. **Success:** Queue empty after approve.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Incident Commander](#)
 - [Tasks](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Configure Zyra

Purpose

Configure Zyra — Machina Platform / Security page at `/platform/zyra/configure` .

When to use it

- Operate **Configure Zyra** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/zyra/configure`
- Nav: **Platform / Security → Configure Zyra** (or spotlight / Finder search)

Notes

- Formerly documented under `/platform/zeus*` (except Zeus Security Center, which remains `/platform/zeus/security`).

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Save air-gap.
3. Enable memory.
4. Save prompt.
5. **Empty:** —.
6. **Success:** Settings saved.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Machina Zyra OS](#)
 - [AI Providers](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Incident Commander

Purpose

Incident Commander — Machina Platform / Security page at `/platform/zyra/incidents` .

When to use it

- Operate **Incident Commander** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/zyra/incidents`
- Nav: **Platform / Security → Incident Commander** (or spotlight / Finder search)

Notes

- Formerly documented under `/platform/zeus*` (except Zeus Security Center, which remains `/platform/zeus/security`).

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Open approvals.
3. Runbook.
4. **Empty:** —.
5. **Success:** Incident advanced/closed.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Zyra Approvals](#)
 - [Security Operations Center](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

VM Rightsizing

Purpose

Rightsizing — Machina Platform / Security page at `/platform/zyra/rightsizing` .

When to use it

- Operate **VM Rightsizing** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/zyra/rightsizing`
- Nav: **Platform / Security → Rightsizing** (or spotlight / Finder search)

Notes

- Formerly documented under `/platform/zeus*` (except Zeus Security Center, which remains `/platform/zeus/security`).

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Queue single resize.
3. **Empty:** —.
4. **Success:** Resize task queued.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Recommendations](#)
 - [Machine Finder](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Native eBPF

Purpose

Operate Machina's built-in eBPF datapath on a host. One root service, `machina-bpfd`, loads Machina's own kernel programs for flow visibility, policy enforcement, load balancing, DDoS protection, VM isolation and scheduling. This page is the console for it; there is no separate Cilium, Tetragon, Netra or PacketWolf agent to install.

When to use it

- See which VMs talk to what (flows, DNS, L7, per-VM byte accounting)
- Block or allow traffic with policies, first in **observe**, then **enforce** under a lease
- Load-balance services on the uplink, absorb floods (Shield), or isolate a node during an incident
- Check what the running kernel supports before turning on a feature

How to get there

- Route: `/platform/zyra/security/native-bpf`
- Nav: **Security Center** → **Native eBPF** (or spotlight / Finder search for "eBPF")
- Per-VM container rules live in a different place: VM detail → **Guest policy** (see [Guest policy](#))

Before you start

- `machina-bpfd` must be running on the host (`systemctl status machina-bpfd`). If it is not, the page shows "bpfd unavailable" and every tab stays empty.
- **Overview** → **programs compiled = no** means the build had no eBPF toolchain; the admin runs `make bpfd-deps` and rebuilds.
- Viewing needs any logged-in role. Every change (mode, policies, attach, leases) is **Admin** only.

Tabs

The page has 22 tabs. The first eight are the core console; the rest are one tab per datapath feature.

Tab	What it shows / does
Overview	Version, mode (observe / enforce + lease left), kernel feature pills (<code>btf</code> , <code>tcx</code> , <code>lsm_bpf</code> , <code>sched_ext</code> , <code>xsk</code> ...), policy count, attached interfaces, flow / drop / anomaly counters. Switch mode and manage policies here.
Flows	Live connection table per VM (5-tuple, bytes, verdict). Filter by VM.
L7	Parsed HTTP / DNS / TLS-SNI requests by protocol.
Accounting	Per-VM byte and packet counters; reset one VM or all.
Live	Streaming events (net, dns, l7, proc, anomaly topics) over SSE.
DNS & processes	DNS answers seen and which host processes opened sockets.
Captures	Start a ring-buffer packet capture on one interface and download it as pcapng for Wireshark.
QoS & telemetry	Per-VM rate limits and the datapath telemetry counters.

Tab	What it shows / does
Service LB	Uplink service load balancing (VIP → backends, weighted, with health).
VM Edge	Per-VM tap programs: anti-spoof, isolation, QEMU sandbox.
Shield	XDP DDoS shield on the uplink: per-source SYN / UDP / ICMP rate limits with allow and deny lists; shows the top over-rate sources.
TCP Health	Retransmits, RTT and ICMP errors per peer.
TLS / JA4	TLS client fingerprints (JA4) and SNI seen per VM.
Node Isolation	Incident kill-switch for the host: drop everything except an allowlist, with its own 10–900 s lease. Refuses to arm unless SSH or an exempt CIDR is allowlisted.
Net changes	Audit of netlink changes (links, addresses, routes) on the host.
L7 sampling	Sampled L7 payload metadata for low-overhead visibility.
VM runtime	Per-VM runtime intelligence (vCPU exits, block and network activity from QEMU).
VMM guard	BPF-LSM guard around QEMU processes (audit, or enforce under a lease; needs <code>lsm_bpf</code>).
Direct redirect	Opt-in per VM: frames for the VM on an outer interface go straight into its tap (and back with reverse), bypassing the bridge. Idle unless the enforcement lease is live.
QUIC LB	Connection-ID aware QUIC load balancing on the uplink.
AF_XDP	Zero-copy AF_XDP sockets for a chosen interface (never the default-route NIC).
Scheduler	<code>machina-scx</code> <code>sched_ext</code> VM scheduler: status, start / stop under a lease (needs <code>sched_ext</code>).

Safe workflow for enforcement

1. Add the policy while the host is in **observe**. Misses are counted, nothing is dropped.
2. Watch **Flows** / **Live** for the hits you expect. Fix the rule until only unwanted traffic would be blocked.
3. Switch to **enforce** with a lease (default 900 s). The lease is checked in the datapath, so drops stop on time even if bpfd stalls.
4. Extend the lease only once you are sure. A bpfd restart always comes back in observe: mode and leases are never persisted.

Guard rails you will see: auto-attach only touches VM taps (`vnet*` / `tap*`), default-deny is never attached to an uplink, and direct redirect refuses a physical NIC unless forced. Test new enforcement on a lab host first.

Fleet view

On the controller, **Security Center** aggregates every host's dataplane (`/api/v1/zeus-security/native-dataplane`) and pushes per-host changes through the host's agent. Use this page for one host, Security Center for the fleet.

If something is wrong

- **bpfd unavailable:** start the unit, then check `journalctl -u machina-bpfd` .
- **A tab says the kernel lacks a feature:** compare the Overview feature pills with the kernel requirements in the admin docs.
- **Enforcement went back to observe:** the lease expired or bpfd restarted. This is by design.

Related pages

- [Security Center](#)
 - [Guest policy](#)
 - [Network Canvas](#)
 - [Getting Started](#)
 - [Page index](#)
-

Machina Zyra OS

Purpose

Zyra AI assistant for Machina operations.

When to use it

- Operate **Machina Zyra OS** when your job matches this page
- Use Mission Control (`/platform`) for fleet-wide work; use Core routes for this host only
- Confirm PAM/OIDC login and roles if actions are missing

How to get there

- Route: `/platform/zyra`
- Nav: **Platform / Security** → **Zyra AI** (or spotlight / Finder search)

Notes

- Formerly documented under `/platform/zeus*` (except Zeus Security Center, which remains `/platform/zeus/security`).

Operate from the console (UX)

1. Open the route against the Machina daemon (`https://<host>:5092`) and wait for live data.
2. Filters / tabs: **Fleet / Graph Brain / Memory / Security / Knowledge (?tab=)**.
3. Open Firewall.
4. Register BMC.
5. Run runbooks.
6. Open apps.
7. **Empty:** No bare-metal → register BMC.
8. **Success:** Tab data loads; sensors enrolled.

If the page stays empty, check daemon health (`/api/v1/health`), libvirt connectivity, and whether the feature requires Fleet Cloud or Mission Control enrollment.

Related pages

- [Configure Zyra](#)
 - [Security Center](#)
 - [Incident Commander](#)
 - [Getting Started](#)
 - [Dashboard](#)
 - [Mission Control](#)
 - [Page index](#)
-

Machina — Complete page index

Every primary navigable dashboard route.

Generated: 2026-10-03 · 106 routes

Regenerate: `node scripts/customer-docs/generate-page-index.mjs`

Core

Page	Route	Purpose	Guide
Dashboard	<code>/</code>	Host dashboard — VM inventory pulse, Vessel container shortcuts when Podman/Docker is connected, and quick links.	Open
Virtual Machines	<code>/vms</code>	Virtual machine inventory for this libvirt host.	Open
Create VM	<code>/create</code>	Create a new libvirt VM.	Open
Import VM	<code>/import</code>	Import VM — Machina Core page at <code>/import</code> .	Open
Sprites	<code>/sprites</code>	Instant, disposable sandbox VMs — boot on libvirt/QEMU, Cloud Hypervisor, or Firecracker, TTL-reaped automatically, no persistent state.	Open
Fleet	<code>/fleet</code>	Fleet — Machina Core page at <code>/fleet</code> .	Open
Host SSH	<code>/host-ssh</code>	Host SSH — Machina Core page at <code>/host-ssh</code> .	Open
Capabilities	<code>/capabilities</code>	Capabilities — Machina Core page at <code>/capabilities</code> .	Open
Node Devices	<code>/devices</code>	Node Devices — Machina Core page at <code>/devices</code> .	Open
Services	<code>/services</code>	Services — Machina Core page at <code>/services</code> .	Open

Platform

Page	Route	Purpose	Guide
Mission Control	<code>/platform</code>	Mission Control — multi-host platform overview.	Open
Virtual Machines	<code>/platform/vms</code>	Fleet VM finder across enrolled hosts.	Open
Hosts	<code>/platform/hosts</code>	Hosts — Machina Platform page at <code>/platform/hosts</code> .	Open
Machine Finder	<code>/platform/hosts/finder</code>	Machine Finder: opens the fleet VM list in its topology lens (<code>/platform/vms?lens=topology</code>) to find any VM by host, network or name.	Open
Applications	<code>/platform/applications</code>	Applications — Machina Platform page at <code>/platform/applications</code> .	Open
Launchpad (Mission Control)	<code>/platform/launchpad</code>	Launchpad tiles live on Mission Control (<code>/platform</code>) — there is no separate <code>/platform/launchpad</code> route.	Open
Datacenter View	<code>/platform/datacenter</code>	Datacenter View — Machina Platform page at <code>/platform/datacenter</code> .	Open
Disk Utility	<code>/platform/storage</code>	Disk Utility — Machina Platform page at <code>/platform/storage</code> .	Open

Page	Route	Purpose	Guide
Storage (Atlas)	/platform/storage-atlas	Storage (Atlas) — Machina Platform page at /platform/storage-atlas .	Open
Storage Tiers	/platform/storage-tiers	Storage Tiers — Machina Platform page at /platform/storage-tiers .	Open
Networks	/platform/networks	Networks — Machina Platform page at /platform/networks .	Open
Images & ISOs	/platform/content	Images & ISOs — Machina Platform page at /platform/content .	Open
Templates	/platform/templates	Templates — Machina Platform page at /platform/templates .	Open
Cloud-Init Studio	/platform/cloud-init	Cloud-Init Studio — Machina Platform page at /platform/cloud-init .	Open
Create ISO	/platform/create-iso	Create ISO — Machina Platform page at /platform/create-iso .	Open
Bare Metal	/platform/baremetal	Bare Metal — Machina Platform page at /platform/baremetal .	Open
Migration Assistant	/platform/migration	Migration Assistant — Machina Platform page at /platform/migration .	Open
VM Builder	/platform/vm-builder	VM Builder — Machina Platform page at /platform/vm-builder .	Open
Advanced Create	/platform/create-advanced	Advanced Create — Machina Platform page at /platform/create-advanced .	Open
Blueprints	/platform/blueprints	Blueprints — Machina Platform page at /platform/blueprints .	Open
Tasks	/platform/tasks	Tasks — Machina Platform page at /platform/tasks .	Open
Network Canvas	/platform/network-canvas	Network Canvas — Machina Platform page at /platform/network-canvas .	Open
Security Operations	/platform/soc	Security Operations — Machina Platform page at /platform/soc .	Open
Policy	/platform/policy	Policy — Machina Platform page at /platform/policy .	Open
Webhooks	/platform/webhooks	Webhooks — Machina Platform page at /platform/webhooks .	Open
Backup & Restore	/platform/backups	Backup & Restore — Machina Platform page at /platform/backups .	Open
Fleet Snapshots	/platform/fleet-snapshots	Fleet Snapshots — Machina Platform page at /platform/fleet-snapshots .	Open
Disaster Recovery	/platform/placement	Disaster Recovery — Machina Platform page at /platform/placement .	Open

Page	Route	Purpose	Guide
High Availability	/platform/ha	High Availability — Machina Platform page at /platform/ha .	Open
Upgrade Matrix	/platform/upgrade	Upgrade Matrix — Machina Platform page at /platform/upgrade .	Open
Maintenance	/platform/maintenance	Maintenance — Machina Platform page at /platform/maintenance .	Open
Recommendations	/platform/recommendations	Recommendations — Machina Platform page at /platform/recommendations .	Open
Alerts	/platform/notifications	Alerts — Machina Platform page at /platform/notifications .	Open
Alert Rules	/platform/alert-rules	Threshold alert rules on VM CPU and memory: notify (via Alerts / webhooks) when a metric crosses a bound.	Open
Scheduled Jobs	/platform/scheduled-jobs	Recurring controller operations from a whitelist, for example periodic host inventory refresh.	Open
Observability	/platform/observability	Observability — Machina Platform page at /platform/observability .	Open
Activity Monitor	/platform/activity	Activity Monitor — Machina Platform page at /platform/activity .	Open
Topology	/platform/topology	Topology — Machina Platform page at /platform/topology .	Open
Reports	/platform/reports	Reports — Machina Platform page at /platform/reports .	Open
GPU Command Center	/platform/gpu	GPU Command Center — Machina Platform page at /platform/gpu .	Open
Settings	/platform/settings	Settings — Machina Platform page at /platform/settings .	Open
Users & Groups	/platform/users	Users & Groups — Machina Platform page at /platform/users .	Open
Stage Manager	/platform/projects	Stage Manager — Machina Platform page at /platform/projects .	Open
Add Host	/platform/enroll	Add Host — Machina Platform page at /platform/enroll .	Open
API Keys	/platform/api-keys	API Keys — Machina Platform page at /platform/api-keys .	Open
Marketplace	/platform/marketplace	Marketplace — Machina Platform page at /platform/marketplace .	Open
AI Providers	/platform/ai-providers	AI Providers — Machina Platform page at /platform/ai-providers .	Open
Enterprise Features	/platform/enterprise	Enterprise Features — Machina Platform page at /platform/enterprise .	Open

Page	Route	Purpose	Guide
Developer Hub	/platform/developer	Developer Hub — Machina Platform page at /platform/developer .	Open
Support	/platform/support	Support — Machina Platform page at /platform/support .	Open
Event Log	/platform/events	Event Log — Machina Platform page at /platform/events .	Open
Settings	/settings	Daemon and UI settings, including Fleet Cloud wiring.	Open
API Docs	/api-docs	API Docs — Platform surface.	Open

Platform / Security

Page	Route	Purpose	Guide
Zyra AI	/platform/zyra	Zyra AI assistant for Machina operations.	Open
Configure Zyra	/platform/zyra/configure	Configure Zyra — Machina Platform / Security page at /platform/zyra/configure .	Open
Zeus Security	/platform/zeus/security	Zeus Security — Machina Platform / Security page at /platform/zeus/security .	Open
Native eBPF	/platform/zyra/security/native-bpf	Native eBPF: per-host machina-bpfd status, observe/enforce mode under a lease, deny/allow policies, flows, DNS, L7, load balancing, CNI and guest policy across 22 tabs.	Open
Incident Commander	/platform/zyra/incidents	Incident Commander — Machina Platform / Security page at /platform/zyra/incidents .	Open
Approvals	/platform/zyra/approvals	Approvals — Machina Platform / Security page at /platform/zyra/approvals .	Open
Rightsizing	/platform/zyra/rightsizing	Rightsizing — Machina Platform / Security page at /platform/zyra/rightsizing .	Open

Infrastructure

Page	Route	Purpose	Guide
Storage Pools	/storage	Storage Pools — Machina Infrastructure page at /storage .	Open
Disk Images	/disk-images	Disk Images — Machina Infrastructure page at /disk-images .	Open
Snapshots	/snapshots	Snapshots — Machina Infrastructure page at /snapshots .	Open
Snapshot Backups	/backups	Snapshot Backups — Machina Infrastructure page at /backups .	Open
Networks	/networks	Networks — Machina Infrastructure page at /networks .	Open
Network Filters	/nwfilters	Network Filters — Machina Infrastructure page at /nwfilters .	Open
Host Networking	/host-networking	Host Networking — Machina Infrastructure page at /host-networking .	Open

Page	Route	Purpose	Guide
Secrets	<code>/secrets</code>	Secrets — Machina Infrastructure page at <code>/secrets</code> .	Open
Containers	<code>/containers</code>	Local Podman/Docker containers via Vessel — list, create, lifecycle, and live stats on this host.	Open
Container Pods	<code>/containers/pods</code>	Podman pods via Vessel — create and manage shared-namespace container groups (not Kubernetes pods).	Open

Kubernetes

Page	Route	Purpose	Guide
Kubernetes	<code>/k8s</code>	Kubernetes — Machina Kubernetes page at <code>/k8s</code> .	Open
K8s Workloads	<code>/k8s/workloads</code>	K8s Workloads — Machina Kubernetes page at <code>/k8s/workloads</code> .	Open
Kata + Cloud Hypervisor	<code>/k8s/kata</code>	Kata + Cloud Hypervisor — Machina Kubernetes page at <code>/k8s/kata</code> .	Open

Fleet Cloud

Page	Route	Purpose	Guide
Overview	<code>/fleet-cloud</code>	Overview — Machina Fleet Cloud page at <code>/fleet-cloud</code> .	Open
Instances	<code>/fleet-cloud/instances</code>	Instances — Machina Fleet Cloud page at <code>/fleet-cloud/instances</code> .	Open
Create Instance	<code>/fleet-cloud/create</code>	Create Instance — Machina Fleet Cloud page at <code>/fleet-cloud/create</code> .	Open
Server Groups	<code>/fleet-cloud/server-groups</code>	Server Groups — Machina Fleet Cloud page at <code>/fleet-cloud/server-groups</code> .	Open
Keypairs	<code>/fleet-cloud/keypairs</code>	Keypairs — Machina Fleet Cloud page at <code>/fleet-cloud/keypairs</code> .	Open
Flavors	<code>/fleet-cloud/flavors</code>	Flavors — Machina Fleet Cloud page at <code>/fleet-cloud/flavors</code> .	Open
Volumes	<code>/fleet-cloud/volumes</code>	Volumes — Machina Fleet Cloud page at <code>/fleet-cloud/volumes</code> .	Open
Volume Snapshots	<code>/fleet-cloud/volume-snapshots</code>	Volume Snapshots — Machina Fleet Cloud page at <code>/fleet-cloud/volume-snapshots</code> .	Open
Images	<code>/fleet-cloud/images</code>	Images — Machina Fleet Cloud page at <code>/fleet-cloud/images</code> .	Open
Networking	<code>/fleet-cloud/networking</code>	Networking — Machina Fleet Cloud page at <code>/fleet-cloud/networking</code> .	Open
Security Groups	<code>/fleet-cloud/security-groups</code>	Security Groups — Machina Fleet Cloud page at <code>/fleet-cloud/security-groups</code> .	Open

Page	Route	Purpose	Guide
Floating IPs	<code>/fleet-cloud/floating-ips</code>	Floating IPs — Machina Fleet Cloud page at <code>/fleet-cloud/floating-ips</code> .	Open
Load Balancers	<code>/fleet-cloud/load-balancers</code>	Load Balancers — Machina Fleet Cloud page at <code>/fleet-cloud/load-balancers</code> .	Open
Network Topology	<code>/fleet-cloud/topology</code>	Network Topology — Machina Fleet Cloud page at <code>/fleet-cloud/topology</code> .	Open
Heat Orchestration	<code>/fleet-cloud/heat</code>	Heat Orchestration — Machina Fleet Cloud page at <code>/fleet-cloud/heat</code> .	Open
Identity	<code>/fleet-cloud/identity</code>	Identity — Machina Fleet Cloud page at <code>/fleet-cloud/identity</code> .	Open

Monitoring

Page	Route	Purpose	Guide
Host Overview	<code>/node</code>	Host Overview — Machina Monitoring page at <code>/node</code> .	Open
Live Metrics	<code>/events</code>	Live Metrics — Machina Monitoring page at <code>/events</code> .	Open
System Check	<code>/system-check</code>	System Check — Machina Monitoring page at <code>/system-check</code> .	Open
Daemon Jobs	<code>/jobs</code>	Daemon Jobs — Machina Monitoring page at <code>/jobs</code> .	Open
System Logs	<code>/logs</code>	System Logs — Machina Monitoring page at <code>/logs</code> .	Open
Audit Log	<code>/audit</code>	Audit Log — Machina Monitoring page at <code>/audit</code> .	Open
Web Sessions	<code>/admin/sessions</code>	Web Sessions — Machina Monitoring page at <code>/admin/sessions</code> .	Open

Related

- [Customer docs home](#)
- [Page-by-page guides](#)