

## ANILOX ROLL'S PARAMETERS HAVE MAXIMUM 10 PRINTING UNITS

<b>Printer:</b>	Gallus EM 340 S Updated
<b>Units:</b>	10
<b>Date:</b>	7/9/2020

<b>State/Province:</b>	a
<b>Country/Time:</b>	a/GMT+7
<b>Product:</b>	a

<b>Customer</b>	a
<b>PO Code:</b>	a
<b>MO Code:</b>	a

<b>Typical Printing:</b>	Paper packaging (Uncoated paper)
<b>Name of Material:</b>	Art paper
<b>Type of Material:</b>	Uncoated paper

<b>Type of Ink:</b>	Water-based Ink
<b>Number of Colors:</b>	1
<b>Size:</b>	435.0

<b>Resolution (lpi):</b>	45
<b>Type of Trame:</b>	AM
<b>Angle:</b>	C=7.5, K=37.5, M=67.5, Y=82.5

<b>No.:</b>	1
<b>Color:</b>	Y

<b>Typical Printing:</b>	Full plate Solid & Varnish (rubber roll)
<b>Anilox Line Screen:</b>	200
<b>Anilox Volume (BCM):</b>	9.6
<b>Opening:</b>	120
<b>Wall:</b>	7
<b>Anilox Angle:</b>	45
<b>Anilox Shape:</b>	Diamond
<b>Depth Cell:</b>	34
<b>DO (%):</b>	28
<b>Doctor Blades:</b>	250