ANILOX ROLL'S PARAMETERS HAVE MAXIMUM 10 PRINTING UNITS

Printer:	Gallus EM 340 S Updated
Units:	10
Date:	7/9/2020

State/Province:	a
Country/Time:	a/GMT+7
Product:	a

Customer	a
PO Code:	a
MO Code:	a

Typical Printing:	Paper packaging (Coated paper)
Name of Material:	Couche 2 Matte
Type of Material:	Coated paper

Type of Ink:	Water-based Ink
Number of Colors:	2
Size:	435.0

Resolution (lpi):	133 (1)
Type of Trame:	AM
Angle:	C=7.5, K=37.5, M=67.5, Y=82.5

No.:	1
Color:	K
Typical Printing:	Trame & Solid (doctor blade)
Anilox Line Screen:	500
Anilox Volume (BCM):	4.1
Opening:	47
Wall:	4
Anilox Angle:	60
Anilox Shape:	Hexan
Depth Cell:	13
DO (%):	28
Doctor Blades:	200

No.:	2
Color:	PANTONE P 6-16 U
Typical Printing:	Trame & Solid (rubber roll blade)
Anilox Line Screen:	400
Anilox Volume (BCM):	4.0
Opening:	58
Wall:	5
Anilox Angle:	60
Anilox Shape:	Hexan
Depth Cell:	16
DO (%):	28
Doctor Blades:	200

No.:	3
Color:	K
Typical Printing:	Line & Text (doctor blade)
Anilox Line Screen:	360
Anilox Volume (BCM):	4.7
Opening:	65
Wall:	5
Anilox Angle:	60
Anilox Shape:	Hexan
Depth Cell:	18
DO (%):	28
Doctor Blades:	200

No.:	4
Color:	PANTONE P 6-16 U
Typical Printing:	Line & Solid (doctor blade)
Anilox Line Screen:	400
Anilox Volume (BCM):	5.6
Opening:	58
Wall:	5
Anilox Angle:	60
Anilox Shape:	Hexan
Depth Cell:	16
DO (%):	20
Doctor Blades:	200