

ANILOX ROLL'S PARAMETERS HAVE MAXIMUM 10 PRINTING UNITS

Printer:	Gallus TCS 250
Units:	10
Date:	8/9/2020

State/Province:	a
Country/Time:	a/GMT+7
Product:	a

Customer	a
PO Code:	a
MO Code:	a

Typical Printing:	Flexible packaging (film / foil)
Name of Material:	Fastcoat
Type of Material:	Film / foil

Type of Ink:	UV Ink
Number of Colors:	1
Size:	265.0

Resolution (lpi):	100 (2)
Type of Trame:	AM
Angle:	C=7.5, K=37.5, M=67.5, Y=82.5

No.:	1
Color:	Y
Typical Printing:	Solid
Anilox Line Screen:	300
Anilox Volume (BCM):	6.5
Opening:	79
Wall:	6
Anilox Angle:	60
Anilox Shape:	Hexan
Depth Cell:	22
DO (%):	28
Doctor Blades:	240

No.:	2
Color:	Y
Typical Printing:	Trame & Solid (doctor blade)
Anilox Line Screen:	700
Anilox Volume (BCM):	4.0
Opening:	33
Wall:	3
Anilox Angle:	60
Anilox Shape:	Hexan
Depth Cell:	9
DO (%):	28
Doctor Blades:	150

No.:
Color:
Typical P
Anilox Lin Screen:
Anilox Vo (BCM):
Opening:
Wall:
Anilox An
Anilox Sh
Depth Ce
DO (%):
Doctor BL