



UNIFIED MODELING LANGUAGE (UML)

11. USE CASE DIAGRAM


Nguyen Thi Thu Trang
trangntt@soict.hust.edu.vn



@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 2

Content


- ➔ 1. Requirement modeling with use-case
- 2. Actors
- 3. Use cases
- 4. Use case diagrams



@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 3

Purpose of Requirement


- Establish and maintain agreement with the customers and other stakeholders on what the software should do.
- Give software developers a better understanding of the requirements of the software.
- Delimit the software.
- Provide a basis for planning the technical contents of the iterations.
- Provide a basis for estimating cost and time to develop the software.
- Define a user interface of the software.











@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 4

What Is Software Behavior?

- Software behavior is how a software acts and reacts.
 - It comprises the actions and activities of a software.
- Software behavior is captured in use cases.
 - Use cases describe the interactions between the software and (parts of) its environment.








@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 13

Content



1. Requirement modeling with use-case
- ➔ 2. Actors
3. Use cases
4. Use case diagrams



@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 14

3. Use Cases


- Define a set of use-case instances, where each instance is a sequence of actions a software performs that yields an observable result of value to a particular actor.
 - A use case models a **dialogue** between one or more actors and the software
 - A use case describes the **actions the software takes** to deliver something of value to the actor



15



Some guidelines to extract use cases

- Pay attention to a verb in the problem description, and then extract a series of Actions as a UC.
- Ensure that there are no any excesses and deficiencies between the problem description and Use cases extracted.
- Check the consistency between Use Cases and related Actors.
- Conduct a survey to learn whether customers, business representatives, analysts, and developers all understand the names and descriptions of the use cases



@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 16


Exercise: Find use cases



@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 17

Content


1. Requirement modeling with use-case
2. Actors
3. Use cases
- ➔ 4. Use case diagrams




@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 18

Overview of Use-Case Diagram

- A diagram modeling the dynamic aspects of softwares that describes a software's functional requirements in terms of use cases.
- A model of the software's intended functions (use cases) and its environment (actors).




```
graph LR; Student((Student)) --> ViewReportCard([View Report Card]); Student --> RegisterCourses([Register for Courses]); Student --> Login([Login]);
```




@Nguyễn Thị Thu Trang, trangntt@soict.hust.edu.vn 19

Association between actor and use case


- Establish the actors that interact with related use cases
 - Associations clarify the **communication** between the actor and use case.
 - Association indicate that the actor and the use case instance of the software communicate with one another, each one able to **send and receive messages**.
- The arrow head is optional but it's commonly used to denote the initiator.



```
graph LR; Actor((Actor)) -- Association --> UseCase([Use Case]);
```



Communicates-Association



```
graph TD; Actor1((Actor 1)) --> UseCase([Use Case]); Actor2((Actor 2)) --- UseCase; Actor3((Actor 3)) --- UseCase;
```

- A channel of communication between an actor and a use case.
- A line is used to represent a communicates-association.
 - An arrowhead indicates who initiates each interaction.
 - No arrowhead indicates either end **can** initiate each interaction.

