


2151013087

Wireshark Lab: IP v8.1

Supplement to *Computer Networking: A Top-Down Approach*, 8th ed., J.F. Kurose and K.W. Ross

“Tell me and I forget. Show me and I remember. Involve me and I understand.” Chinese proverb

© 2005-2021, J.F Kurose and K.W. Ross, All Rights Reserved



In this lab, we'll investigate the celebrated IP protocol, focusing on the IPv4 and IPv6 datagram. This lab has three parts. In the first part, we'll analyze packets in a trace of IPv4 datagrams sent and received by the `traceroute` program (the `traceroute` program itself is explored in more detail in the Wireshark ICMP lab). We'll study IP fragmentation in Part 2 of this lab, and take a quick look at IPv6 in Part 3 of this lab.

Before getting started, you'll probably want to review sections 1.4.3 in the text¹ and section 3.4 of [RFC 2151](#) to update yourself on the operation of the `traceroute` program. You'll also want to read Section 4.3 in the text, and probably also have [RFC 791](#) on hand as well, for a discussion of the IP protocol. If you answer the questions on IP fragmentation, you'll definitely also want to review material on IP fragmentation. Although we've removed the topic of IP fragmentation from the 8th edition of our textbook (to make room for new material), you can find material on IP fragmentation from the 7th edition of our textbook (and earlier) at http://gaia.cs.umass.edu/kurose_ross/Kurose_Ross_7th_edition_section_4.3.2.pdf. [RFC 8200](#) is the full RFC for IPv6, but reading that is a bit of overkill for this lab; you can review IPv6 by consulting Section 4.3.4 in the textbook.

Capturing packets from an execution of `traceroute`

In order to generate a trace of IPv4 datagrams for the first two parts of this lab, we'll use the `traceroute` program to send datagrams of two different sizes to `gaia.cs.umass.edu`. Recall that `traceroute` operates by first sending one or more datagrams with the time-to-live (TTL) field in the IP header set to 1; it then sends a series

¹ References to figures and sections are for the 8th edition of our text, *Computer Networks, A Top-down Approach*, 8th ed., J.F. Kurose and K.W. Ross, Addison-Wesley/Pearson, 2020. Our website for this book is http://gaia.cs.umass.edu/kurose_ross. You'll find lots of interesting open material there.

of one or more datagrams towards the same destination with a TTL value of 2; it then sends a series of datagrams towards the same destination with a TTL value of 3; and so on. Recall that a router must decrement the TTL in each received datagram by 1 (actually, RFC 791 says that the router must decrement the TTL by *at least* one). If the TTL reaches 0, the router returns an ICMP message (type 11 – TTL-exceeded) to the sending host. As a result of this behavior, a datagram with a TTL of 1 (sent by the host executing `traceroute`) will cause the router one hop away from the sender to send an ICMP TTL-exceeded message back to the sender; the datagram sent with a TTL of 2 will cause the router two hops away to send an ICMP message back to the sender; the datagram sent with a TTL of 3 will cause the router three hops away to send an ICMP message back to the sender; and so on. In this manner, the host executing `traceroute` can learn the IP addresses of the routers between itself and the destination by looking at the source IP addresses in the datagrams containing the ICMP TTL-exceeded messages.

Let's run `traceroute` and have it send datagrams of two different sizes. The larger of the two datagram lengths will require `traceroute` messages to be fragmented across multiple IPv4 datagrams.

- **Linux/MacOS.** With the Linux/MacOS `traceroute` command, the size of the UDP datagram sent towards the final destination can be explicitly set by indicating the number of bytes in the datagram; this value is entered in the `traceroute` command line immediately after the name or address of the destination. For example, to send `traceroute` datagrams of 2000 bytes towards `gaia.cs.umass.edu`, the command would be:

```
%traceroute gaia.cs.umass.edu 2000
```

- **Windows.** The `tracert` program provided with Windows does not allow one to change the size of the ICMP message sent by `tracert`. So it won't be possible to use a Windows machine to generate ICMP messages that are large enough to force IP fragmentation. However, you can use `tracert` to generate small, fixed length packets to perform Part 1 of this lab. At the DOS command prompt enter:

```
>tracert gaia.cs.umass.edu
```

If you want to do the second part of this lab, you can download a packet trace file that was captured on one of the author's computers².

Do the following:

- Start up Wireshark and begin packet capture. (*Capture->Start* or click on the blue shark fin button in the top left of the Wireshark window).

² You can download the zip file <http://gaia.cs.umass.edu/wireshark-labs/wireshark-traces-8.1.zip> and extract the trace file `ip-wireshark-trace1-1.pcapng`. This trace file can be used to answer these Wireshark lab questions without actually capturing packets on your own. The trace was made using Wireshark running on one of the author's computers, while performing the steps in this Wireshark lab. Once you've downloaded a trace file, you can load it into Wireshark and view the trace using the *File* pull down menu, choosing *Open*, and then selecting the trace file name.

- Enter two `traceroute` commands, using `gaia.cs.umass.edu` as the destination, the first with a length of 56 bytes. Once that command has finished executing, enter a second `traceroute` command for the same destination, but with a length of 3000 bytes.
- Stop Wireshark tracing.

If you're unable to run Wireshark on a live network connection, you can use the packet trace file, *ip-wireshark-trace1-1.pcapng*, referenced in footnote 2. You may well find it valuable to download this trace even if you've captured your own trace and use it, as well as your own trace, as you explore the questions below.

Part 1: Basic IPv4

In your trace, you should be able to see the series of UDP segments (in the case of MacOS/Linux) or ICMP Echo Request messages (Windows) sent by `traceroute` on your computer, and the ICMP TTL-exceeded messages returned to your computer by the intermediate routers. In the questions below, we'll assume you're using a MacOS/Linux computer; the corresponding questions for the case of a Windows machine should be clear. Your screen should look similar to the screenshot in Figure 2, where we have used the display filter "`udp||icmp`" (see the light-green-filled display-filter field in Figure 2) so that only UDP and/or ICMP protocol packets are displayed.






Figure 2: Wireshark screenshot, showing UDP and ICMP packets in the tracefile *ip-wireshark-trace1-1.pcapng*

Answer the following questions³. If you're doing this lab as part of class, your teacher will provide details about how to hand in assignments, whether written or in an LMS.

1. Select the first UDP segment sent by your computer via the `traceroute` command to `gaia.cs.umass.edu`. (Hint: this is 44th packet in the trace file in the *ip-wireshark-trace1-1.pcapng* file in footnote 2). Expand the Internet Protocol part of the packet in the packet details window. What is the IP address of your computer?



2. What is the value in the time-to-live (TTL) field in this IPv4 datagram's header?




3. What is the value in the **upper layer protocol field** in this IPv4 datagram's header? [Note: the answers for Linux/MacOS differ from Windows here].

³ For the author's class, when answering the following questions with hand-in assignments, students sometimes need to print out specific packets (see the introductory Wireshark lab for an explanation of how to do this) and indicate where in the packet they've found the information that answers a question. They do this by marking paper copies with a pen or annotating electronic copies with text in a colored font. There are also learning management system (LMS) modules for teachers that allow students to answer these questions online and have answers auto-graded for these Wireshark labs at http://gaia.cs.umass.edu/kurose_ross/lms.htm

the value in the upper layer protocol field is ICMP (0x01)


4. How many bytes are in the IP header?

20bytes



5. How many bytes are in the payload of the IP datagram? Explain how you determined the number of payload bytes.

89bytes total => payload bytes = 89 – 20 (header) = 69 bytes



6. Has this IP datagram been fragmented? Explain how you determined whether or not the datagram has been fragmented.

According to the figure 1, under flags section, the more fragments bit = 0, so the data is not fragmented

Next, let's look at the *sequence* of UDP segments being sent from your computer via traceroute, destined to 128.119.245.12. The display filter that you can enter to do this is "ip.src==192.168.86.61 and ip.dst==128.119.245.12 and udp and !icmp". This will allow you to easily move sequentially through just the datagrams containing just these segments. Your screen should look similar to Figure 3.

No.	Time	Source	Destination	Protocol	Length	Info
44	1.865637	192.168.86.61	128.119.245.12	UDP	70	64928 → 33435 Len=28
48	1.874016	192.168.86.61	128.119.245.12	UDP	70	64928 → 33436 Len=28
50	1.875401	192.168.86.61	128.119.245.12	UDP	70	64928 → 33437 Len=28
52	1.876720	192.168.86.61	128.119.245.12	UDP	70	64928 → 33438 Len=28
56	1.885567	192.168.86.61	128.119.245.12	UDP	70	64928 → 33439 Len=28
58	1.889002	192.168.86.61	128.119.245.12	UDP	70	64928 → 33440 Len=28
60	1.892656	192.168.86.61	128.119.245.12	UDP	70	64928 → 33441 Len=28
62	1.907036	192.168.86.61	128.119.245.12	UDP	70	64928 → 33442 Len=28
64	1.928173	192.168.86.61	128.119.245.12	UDP	70	64928 → 33443 Len=28
67	1.940279	192.168.86.61	128.119.245.12	UDP	70	64928 → 33444 Len=28
69	1.951481	192.168.86.61	128.119.245.12	UDP	70	64928 → 33445 Len=28
71	1.965335	192.168.86.61	128.119.245.12	UDP	70	64928 → 33446 Len=28
73	1.975799	192.168.86.61	128.119.245.12	UDP	70	64928 → 33447 Len=28
75	1.991739	192.168.86.61	128.119.245.12	UDP	70	64928 → 33448 Len=28
77	2.008887	192.168.86.61	128.119.245.12	UDP	70	64928 → 33449 Len=28
78	2.025822	192.168.86.61	128.119.245.12	UDP	70	64928 → 33450 Len=28

Internet Protocol Version 4, Src: 192.168.86.61, Dst: 128.119.245.12	
0100 = Version: 4	
.... 0101 = Header Length: 20 bytes (5)	
Differentially Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)	
Total Length: 56	
Identification: 0xfdb6 (64950)	
Flags: 0x0000	
Fragment offset: 0	
Time to live: 8	
Protocol: UDP (17)	
Header checksum: 0x2895 [validation disabled]	
[Header checksum status: Unverified]	
Source: 192.168.86.61	
Destination: 128.119.245.12	
User Datagram Protocol, Src Port: 64928, Dst Port: 33456	
Source Port: 64928	
Destination Port: 33456	

Figure 3: Wireshark screen shot, showing up segments in the tracefile *ip-wireshark-trace1-1.pcapng* using the display filter *ip.src==192.168.86.61 and ip.dst==128.119.245.12 and udp and !icmp*

7. Which fields in the IP datagram *always* change from one datagram to the next within this series of UDP segments sent by your computer destined to 128.119.245.12, via traceroute? Why?

Time to Live (TTL) field: The TTL field in the IP datagram is used to limit the number of hops a packet can take before it is discarded. Each router along the path decrements the TTL value by 1, and when the TTL reaches 0, the packet is discarded and an ICMP message is sent back to the source. As traceroute works by incrementing the TTL value and sending packets with different TTL values, this field will change from one datagram to the next.

Source IP address: The source IP address in the IP datagram will also change from one datagram to the next. This is because traceroute sends each packet with a different source IP address, to try to detect the path taken by the packet through the network.

Identification field: The identification field in the IP datagram is used to identify a particular packet, and it is typically incremented for each new packet sent by the computer. Therefore, this field will change from one datagram to the next.

Checksum field: The checksum field in the IP datagram is used to verify the integrity of the packet during transmission. As the contents of each packet will be different, due to the different TTL values and source IP addresses used, the

checksum field will also change from one datagram to the next.

```
> Frame 1065: 103 bytes on wire (824 bits), 103 bytes captured (824 bits) on interface \Device\NPF_{B48D7B08-844...}
> Ethernet II, Src: IntelCor_d4:00:ad (48:51:c5:d4:00:ad), Dst: WatchGua_03:da:c5 (00:01:21:03:da:c5)
✓ Internet Protocol Version 4, Src: 10.17.30.87, Dst: 40.81.252.176
    0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
        Total Length: 89
        Identification: 0x13a9 (5033)
    > 000. .... = Flags: 0x0
        ...0 0000 0000 0000 = Fragment Offset: 0
        Time to Live: 128
        Protocol: UDP (17)
        Header Checksum: 0x0000 [validation disabled]
        [Header checksum status: Unverified]
        Source Address: 10.17.30.87
        Destination Address: 40.81.252.176
    > User Datagram Protocol, Src Port: 51470, Dst Port: 3544
    > Teredo IPv6 over UDP tunneling
    > Internet Protocol Version 6, Src: fe80::ffff:ffff:ffff:ffff, Dst: ff02::2
    > Internet Control Message Protocol v6
```

8. Which fields in this sequence of IP datagrams (containing UDP segments) stay constant? Why?

The fields that stay constant are: Version (since we are using IPv4), header length (since these are UDP packets), source IP (since all packets are sent from my computer), destination IP (since we are sending to the same host), Differentiated Services (since all packets are UDP), Upper Layer Protocol (since these are UDP packets)

9. Describe the pattern you see in the values in the Identification field of the IP datagrams being sent by your computer.


They are incrementing with each datagram.

Now let's take a look at the ICMP packets being returned to your computer by the intervening routers where the TTL value was decremented to zero (and hence caused the ICMP error message to be returned to your computer). The display filter that you can use to show just these packets is "ip.dst==192.168.86.61 and icmp".

10. What is the upper layer protocol specified in the IP datagrams returned from the routers? [Note: the answers for Linux/macOS differ from Windows here].

the most common diagnostic tool is "tracert" (short for "traceroute"), which uses ICMP (Internet Control Message Protocol) as the upper layer protocol in the IP datagrams returned from the routers.

11. Are the values in the Identification fields (across the sequence of all of ICMP packets from all of the routers) similar in behavior to your answer to question 9 above?



They are incrementing with each datagram.

12. Are the values of the TTL fields similar, across all of ICMP packets from all of the routers? The TTL values in ICMP packets may be similar in some cases, but this cannot be assumed to be true across all routers and packets.

Capturing from Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

No.	Time	Source	Destination	Protocol	Length	Info
214	7.054750	fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	103	Router Solicitation
222	7.284317	fe80::8000:f227:d7a... fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	151	Router Advertisement
1383	32.332777	fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	103	Router Solicitation
1393	32.450217	fe80::8000:f227:d7a... fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	151	Router Advertisement
2431	58.598308	fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	103	Router Solicitation
2435	58.783510	fe80::8000:f227:d7a... fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	151	Router Advertisement

> Frame 1393: 151 bytes on wire (1208 bits), 151 bytes captured (1208 bits) on interface \Device\NPF_{B4807B08-844...}

> Ethernet II, Src: WatchGua_03:da:c5 (00:01:21:03:da:c5), Dst: IntelCor_d4:00:ad (48:51:c5:d4:00:ad)

> Internet Protocol Version 4, Src: 40.81.252.176, Dst: 10.17.30.87

> 0100 = Version: 4

> 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

> Total Length: 89

> Identification: 0x13d7 (5079)

> 0000 = Flags: 0x0

> ...0 0000 0000 0000 = Fragment Offset: 0

> Time to Live: 128

> Protocol: UDP (17)

> Header Checksum: 0x0000 [validation disabled]

> [Header checksum status: Unverified]

> Source Address: 10.17.30.87

> Destination Address: 40.81.252.176

> User Datagram Protocol, Src Port: 51470, Dst Port: 3544

> Teredo IPv6 over UDP tunneling

> Internet Protocol Version 6, Src: fe80::ffff:ffff:ffff:ff02::2, Dst: fe80::ffff:ffff:ffff:ff02::2

> Internet Control Message Protocol v6

Capturing from Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

No.	Time	Source	Destination	Protocol	Length	Info
214	7.054750	fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	103	Router Solicitation
222	7.284317	fe80::8000:f227:d7a... fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	151	Router Advertisement
1383	32.332777	fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	103	Router Solicitation
1393	32.450217	fe80::8000:f227:d7a... fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	151	Router Advertisement
2431	58.598308	fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	103	Router Solicitation
2435	58.783510	fe80::8000:f227:d7a... fe80::ffff:ffff:ffff:ff02::2	ff02::2	ICMPv6	151	Router Advertisement

> Frame 2431: 103 bytes on wire (824 bits), 103 bytes captured (824 bits) on interface \Device\NPF_{B4807B08-844...}

> Ethernet II, Src: IntelCor_d4:00:ad (48:51:c5:d4:00:ad), Dst: WatchGua_03:da:c5 (00:01:21:03:da:c5)

> Internet Protocol Version 4, Src: 10.17.30.87, Dst: 40.81.252.176

> 0100 = Version: 4

> 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

> Total Length: 89

> Identification: 0x13d7 (5079)

> 0000 = Flags: 0x0

> ...0 0000 0000 0000 = Fragment Offset: 0

> Time to Live: 128

> Protocol: UDP (17)

> Header Checksum: 0x0000 [validation disabled]

> [Header checksum status: Unverified]

> Source Address: 10.17.30.87

> Destination Address: 40.81.252.176

> User Datagram Protocol, Src Port: 51470, Dst Port: 3544

> Teredo IPv6 over UDP tunneling

> Internet Protocol Version 6, Src: fe80::ffff:ffff:ffff:ff02::2, Dst: ff02::2


> Internet Control Message Protocol v6

Part 2: Fragmentation

In this section, we'll look at a large (3000-byte) UDP segment sent by the `traceroute` program that is fragmented into multiple IP datagrams. We recommend that you first consult the material on IP fragmentation from the 7th edition of our textbook (and earlier) at http://gaia.cs.umass.edu/kurose_ross/Kurose_Ross_7th_edition_section_4.3.2.pdf

Sort the packet listing from Part 1, with any display filters cleared, according to time, by clicking on the *Time* column.

- Find **the first IP datagram containing** the first part of the segment sent to 128.119.245.12 sent by your computer via the `traceroute` command to `gaia.cs.umass.edu`, *after* you specified that the `traceroute` packet length should be 3000. (Hint: This is packet 179 in the `ip-wireshark-trace1-1.pcapng` trace file in footnote 2. Packets 179, 180, and 181 are three IP datagrams created by fragmenting the first single 3000-byte UDP segment sent to 128.119.145.12). Has that segment been fragmented across more than one IP datagram? (Hint: the answer is yes⁴!)




- What information in **the IP header** indicates that this datagram been **fragmented**?
The Flags bit for more fragments is set, indicating that the datagram has been fragmented. Since the fragment offset is 0, we know that this is the first fragment. This first datagram has a total length of 576, including the header.

Wireshark packet capture showing ICMP Echo (ping) requests. The packet list shows five packets from 147.243.19.81 to 10.17.30.87, all with status '590 Destination unreachable (Port unreachable)'. The packet details for packet 2431 are expanded, showing the IP header fields: Version: 4, Header Length: 20 bytes (5), Differentiated Services Field: 0x00, Total Length: 576, Identification: 0x0bd9 (3033), Flags: 0x00, Time to Live: 119, Protocol: ICMP (1), Header Checksum: 0x6638, Source Address: 147.243.19.81, and Destination Address: 10.17.30.87.

15. What information in the IP header for this packet indicates whether this is the first fragment versus a latter fragment? **INCLUDE IN QUESTION 14**
16. How many bytes are there in is this IP datagram (header plus payload)? **576 – 20 = 556**
17. Now inspect the datagram containing the second fragment of the fragmented UDP segment. What information in the IP header indicates that this is *not* the first datagram fragment?
18. What fields change in the IP header between the first and second fragment?
The IP header fields that changed between the fragments are: total length, flags, fragment offset, and checksum
19. Now find the IP datagram containing the **third fragment** of the original UDP segment. What information in the IP header indicates that this is the last fragment

of that segment?



Part 3: IPv6

In this final section we'll take a quick look at the IPv6 datagram using Wireshark. You'll probably want to review section 4.3.4 in the text. Because the Internet is still primarily at IPv4 network (see section 4.3.4), and your own computer or your ISP may not be configured for IPv6, let's look at a trace of already captured packets that contain some IPv6 packets. To generate this trace, our web browser opened the youtube.com homepage. Youtube (and Google) provide fairly widespread support for IPv6.

Open the file *ip-wireshark-trace2-1.pcapng* in the .zip file of traces given in footnote 2. Your Wireshark display should look similar to Figure 4.





Figure 4: Wireshark screenshot, showing the first set of captured packets in *ip-wireshark-trace2-1.pcapng*. If you look at the Source column, you'll see some IPv6 addresses!

Let's start by taking a closer look at the 20th packet in this trace, sent at $t=3.814489$. This is a DNS request (contained in an IPv6 datagram) to an IPv6 DNS server for the IPv6 address of youtube.com. The DNS AAAA request type is used to resolve names to IPv6 IP addresses.

Answer the following questions:

20. What is the IPv6 address of the computer making the DNS AAAA request? This is the source address of the 20th packet in the trace. Give the IPv6 source address for this datagram in the exact same form as displayed in the Wireshark window⁵.



fe80::8000:f227:d7ae:34f

21. What is the IPv6 destination address for this datagram? Give this IPv6 address in the exact same form as displayed in the Wireshark window.

⁵ Recall that an IPv6 address is shown as 8 sets of 4 hexadecimal digits, with each set separated by colons, and with leading zeros omitted. If an IPv6 address has two colons in a row ('::'), this is shorthand meaning that all of the intervening bytes between the two colons are zero. Thus, for example, fe80::1085:6434:583:e79 is shorthand for fe80:0000:0000:0000:1085:6434:0583:0e79. Make sure you understand this example.

fe80::ffff:ffff:ffff

Wireshark packet capture showing a Teredo IPv6 over UDP tunneling packet. The packet is from 10.17.30.87 to 142.250.4.104. The payload is a Teredo IPv6 over UDP tunneling packet. The flow label is 0x00000000.

Identification: 0x9950 (2384)
0000 = Flags: 0x0
0... .. = Reserved bit: Not set
.0... .. = Don't fragment: Not set
..0... .. = More fragments: Not set
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 111
Protocol: UDP (17)
Header Checksum: 0xf48a [validation disabled]
[Header checksum status: Unverified]
Source Address: 40.81.252.176
Destination Address: 10.17.30.87
> User Datagram Protocol, Src Port: 3544, Dst Port: 51470
> Teredo IPv6 over UDP tunneling
Internet Protocol Version 6, Src: fe80::8000:f227:d7ae:34f, Dst: fe80::ffff:ffff:ffff
0110 = Version: 6
.... 0000 0000 = Traffic Class: 0x00 (DSCP: CS0, ECN: Not-ECT)
.... 0000 0000 0000 0000 = Flow Label: 0x000000
Payload Length: 48
Next Header: ICMPv6 (58)
Hop Limit: 255
Source Address: fe80::8000:f227:d7ae:34f
Destination Address: fe80::ffff:ffff:ffff
Internet Control Message Protocol v6
Type: Router Advertisement (134)
Code: 0
Checksum: 0x649d [correct]
[Checksum Status: Good]
Cur hop limit: 0
Flags: 0x00, Prf (Default Router Preference): Medium
0... .. = Managed address configuration: Not set
..0... .. = Other configuration: Not set

22. What is the value of the flow label for this datagram?

20 bytes

Wireshark packet capture showing a differentiated services field. The packet is from 10.17.30.87 to 208.67.222.222. The payload is a differentiated services field. The flow label is 0x00000000.

Frame 78: 151 bytes on wire (1208 bits), 151 bytes captured (1208 bits) on interface \Device\NPF_{B4807B08-...}
> Ethernet II, Src: MatchGua_03:da:c5 (00:01:21:03:da:c5), Dst: IntelCor_d4:00:ad (48:51:c5:d4:00:ad)
> Internet Protocol Version 4, Src: 40.81.252.176, Dst: 10.17.30.87
0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x20 (DSCP: CS1, ECN: Not-ECT)
0010 00.. = Differentiated Services Codepoint: Class Selector 1 (8)
.... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
Total Length: 137
Identification: 0x094f (2383)
0000 = Flags: 0x0
0... .. = Reserved bit: Not set
.0... .. = Don't fragment: Not set
..0... .. = More fragments: Not set
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 111
Protocol: UDP (17)
Header Checksum: 0xf48b [validation disabled]
[Header checksum status: Unverified]
Source Address: 40.81.252.176
Destination Address: 10.17.30.87
> User Datagram Protocol, Src Port: 3544, Dst Port: 51470
> Teredo IPv6 over UDP tunneling
Internet Protocol Version 6, Src: fe80::8000:f227:d7ae:34f, Dst: fe80::ffff:ffff:ffff
0110 = Version: 6
.... 0000 0000 = Traffic Class: 0x00 (DSCP: CS0, ECN: Not-ECT)
.... 0000 00.. = Differentiated Services Codepoint: Default (0)
.... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport
.... 0000 0000 0000 0000 = Flow Label: 0x000000
Payload Length: 48
Next Header: ICMPv6 (58)
Hop Limit: 255

23. How much payload data is carried in this datagram?

The screenshot shows a Wireshark packet capture of a DNS query and response. The selected packet is a DNS Standard query response (packet 53) from 208.67.222.222 to 10.17.30.87. The packet details show it's a response to a query for 't-ring-fallbacks2.msedge.net'. The payload length is 48 bytes.

24. What is the upper layer protocol to which this datagram's payload will be delivered at the destination?

The screenshot shows a Wireshark packet capture of a DNS query and response. The selected packet is a DNS Standard query response (packet 53) from 208.67.222.222 to 10.17.30.87. The packet details show it's a response to a query for 't-ring-fallbacks2.msedge.net'. The payload length is 48 bytes.

Lastly, find the IPv6 DNS response to the IPv6 DNS AAAA request made in the 20th packet in this trace. This DNS response contains IPv6 addresses for youtube.com.

25. How many IPv6 addresses are returned in the response to this AAAA request?

2

Wireshark packet capture showing an ICMPv6 response to a AAAA request. The packet list shows six ICMPv6 packets. The packet details pane for packet 2307 shows the IPv6 header and the ICMPv6 payload, which contains two IPv6 addresses: 2a00:1450:4001:809::200e and 2a00:1450:4001:809::200f.

No.	Time	Source	Destination	Protocol	Length	Info
1191	20.394168	fe80::8000:f227:d7a...	fe80::ffff:ffff:ffff	ICMPv6	151	
1660	45.991537	fe80::8000:f227:d7a...	fe80::ffff:ffff:ffff	ICMPv6	151	
2307	70.262435	fe80::8000:f227:d7a...	fe80::ffff:ffff:ffff	ICMPv6	151	
2739	93.090954	fe80::8000:f227:d7a...	fe80::ffff:ffff:ffff	ICMPv6	151	
3425	122.679389	fe80::8000:f227:d7a...	fe80::ffff:ffff:ffff	ICMPv6	151	
3912	147.229323	fe80::8000:f227:d7a...	fe80::ffff:ffff:ffff	ICMPv6	151	

Frame 2307: 151 bytes on wire (1208 bits), 151 bytes captured (1208 bits) on interface \Device\NPF_{B48D7B08-8...}

Ethernet II, Src: WatchGua_03:da:c5 (00:01:21:03:da:c5), Dst: IntelCor_d4:00:ad (48:51:c5:d4:00:ad)

Internet Protocol Version 4, Src: 40.81.252.176, Dst: 10.17.30.87

User Datagram Protocol, Src Port: 3544, Dst Port: 51470

Teredo IPv6 over UDP tunneling

Internet Protocol Version 6, Src: fe80::8000:f227:d7ae:34f, Dst: fe80::ffff:ffff:ffff

0110 = Version: 6

.... 0000 0000 = Traffic Class: 0x00 (DSCP: CS0, ECN: Not-ECT)

.... 0000 0000 0000 0000 = Flow Label: 0x000000

Payload Length: 48

Next Header: ICMPv6 (58)

Hop Limit: 255

Source Address: fe80::8000:f227:d7ae:34f

Destination Address: fe80::ffff:ffff:ffff

Internet Control Message Protocol v6

26. What is the first of the IPv6 addresses returned by the DNS for youtube.com (in the *ip-wireshark-trace2-1.pcapng* trace file, this is also the address that is numerically the smallest)? Give this IPv6 address in the exact same shorthand form as displayed in the Wireshark window.

AAAA 2a00:1450:4001:809::200e