

08/03/23

Lower bounds for OPE w/ linear realizability and uniform coverage.

Recap

Linear MDP $M = (\mathcal{S}, \mathcal{A}, H, \{r_h\}_{h \in [H]}, \{\theta_h\}_{h \in [H]})$

$$r_h(s, a) = \phi(s, a)^T \theta_h, \quad p_h(s' | s, a) = \langle \phi(s, a), \mu_h(s') \rangle$$

• D-optimal design covariance:

$$\Sigma = \mathbb{E}_{(s, a) \sim p} [\phi(s, a) \phi(s, a)^T]$$

where $p \in \arg \max_{\substack{p \in \Delta(\mathcal{X} \times \mathcal{A})}} \log \det (\mathbb{E}_{(s, a) \sim p} [\phi(s, a) \cdot \phi(s, a)^T])$

$$|\text{supp}(p)| \leq \frac{d(d+1)}{2}$$

property: $\forall x \in \mathbb{R}^d, \quad x^T \Sigma^{-1} x \leq d$

• Offline RL from exploratory data sets

H datasets $P_h = \left\{ (s_i, a_i, s'_i, r(s_i, a_i)) \right\}_{i=1}^N$

Given i, h : independent samples $s'_i \sim P_h(\cdot | s_i, a_i)$

Assumption "the dataset is exploratory over all dimension"

$$\frac{1}{N} \sum_{i=1}^N \phi(s_i, a_i) \phi(s_i, a_i)^T \geq \frac{1}{\kappa} \Sigma$$

where Σ is the D-optimal design covariance

Alg: let $\hat{\pi} = \text{LSVI}(\{P_h\}_{h \in [H]}, \phi)$

Then:

$$V_1^{\pi^*}(s_1) - \underset{\text{up. 1.5}}{V_1^{\hat{\pi}}(s_1)} \leq \varepsilon \quad \text{if} \quad N \geq \frac{\text{poly}(H, d, \log(1/\delta), \kappa)}{\varepsilon^2}$$

Today what are necessary conditions for generalizations?

In particular, we will evaluate realizability in RL
(RL w/ $H=1$)

In supervised learning^v, realizability is sufficient

e.g. PAC w/ 0-1 loss: $\text{risk}(h_{\text{ERM}}) = \Theta\left(\frac{\text{dvc}}{n}\right)$
w/ realizability

informally, in RL, only realizability is not sufficient for
existence of an sample-efficient algorithm, in the information-theoretic
(minimax) sense.

• Offline policy evaluation (OPE) problem

(perhaps the simplest problem in all RL problems)

Given $\pi: S \rightarrow \Delta(A)$ and a feature mapping $\phi: S \times A \rightarrow \mathbb{R}^d$, the goal:

output an accurate estimate of V^π using collected datasets $\{D_h\}_{h=1}^H$

using as few samples as possible.

- Realizability assumption (R)

$$\forall \pi : S \longrightarrow \Delta(A), \exists \theta_1^\pi, \dots, \theta_H^\pi \in \mathbb{R}^d :$$

$$Q_h^\pi(s,a) = \phi(s,a)^\top \theta_h^\pi \quad \forall (h,s,a)$$

- Data coverage assumption (strongest possible) (D)

$$\mathbb{E}_{(s,a) \sim \mu_h} [\phi(s,a) \phi(s,a)^\top] = \frac{1}{d} I$$

(μ_h satisfies D-optimal design)

- Theorem Assume (R). For any algorithm that takes as input both a policy π and a feature mapping. \exists MDP satisfying (D) s.t.:
 $\forall \pi: S \rightarrow \Delta(A)$, the algorithm requires $\Omega\left(\left(\frac{d}{\epsilon}\right)^H\right)$ samples to output the value of π up to a constant additive error w/p a.l. 0.9

• Lemma (Distinguish Bernoulli random variables)

• $\alpha \sim \text{Unif}(\{\alpha^+, \alpha^-\})$ where

$$\alpha^- = \frac{1}{2} - \frac{\epsilon}{2}$$

$$\alpha^+ = \frac{1}{2} + \frac{\epsilon}{2}$$

• $x_1, \dots, x_n \stackrel{iid}{\sim} \text{Ber}(\alpha)$

• $\forall f: \{0,1\}^n \longrightarrow \{\alpha^-, \alpha^+\}$

$$\Pr(f(x_1, \dots, x_n) \neq \alpha) > \underbrace{\frac{1}{4} \left(1 - \sqrt{1 - \exp\left(\frac{-n\epsilon^2}{1 - \epsilon^2}\right)} \right)}_{\delta \in (0, 0.25)}$$

$$n = \frac{1 - \epsilon^2}{\epsilon^2} \ln \left(\frac{1}{8\delta(1 - \delta)} \right)$$

If:


$$0.9 \leq \Pr(f(x_1, \dots, x_n) = \alpha) < 1 - \delta$$

$$\Rightarrow \delta \geq 0.1 \Rightarrow n \geq \Omega \left(\frac{1 - \epsilon^2}{\epsilon^2} \right)$$

• Hard instances of MDP

Goal: { construct MDPs that satisfy realizability (R)
construct offline data that satisfy (D)
reduction to testing problems

$$\begin{aligned}\phi(s_h^c, a_1) &= e_c \\ \phi(s_h^c, a_2) &= e_c + \hat{d} \\ \phi(s_h^{d+1}, a) &= (e_1 + e_2 + \dots + e_d) / \hat{d}^{1/2}\end{aligned}$$



start here

$$Q_h^\pi(s_h^c, a_1) = r_0 \hat{d}^{(H-h)/2}$$

$$Q_h^\pi(s_h^{d+1}, a) = r_0 \hat{d}^{(H-h+1)/2}$$

$$Q_h^\pi(s, a) = \phi(s, a)^T w_h^\pi$$

Q

$$Q_h^\pi(s, a) = \phi(s, a)^T$$

$$\begin{bmatrix} r_0 \hat{d}^{(H-h)/2} \\ \vdots \\ r_0 \hat{d}^{1/2} \\ Q_h^\pi(s_h^1, a_2) \\ \vdots \\ Q_h^\pi(s_h^{\hat{d}}, a_2) \end{bmatrix}$$

$$\hat{d} = \frac{d}{2}$$

$$\hat{d} = \frac{d}{2}$$

$$R(s_h^c, a) = \begin{cases} 1 & \text{wp } \frac{(1+r_0)}{2} \\ -1 & \text{wp } \frac{(1-r_0)}{2} \end{cases}$$

- Dataset: μ_h is uniform over $\{(s_h^c, a_1), (s_h^c, a_2)\}_{c \in [\hat{d}]}$

$$\mathbb{E}_{(s,a) \sim \mu_h} [\phi(s,a) \phi(s,a)^T] = \frac{1}{\hat{d}} \mathbf{I}$$

- Reduction to testing:

- the policy value to estimate: $V_1^\pi(s_1^{\hat{d}+1}) = r_0 \hat{d}^{H/2}$

- consider 2 instances: (I) $r_0 = 0 \rightarrow V_1^\pi(s_1^{\hat{d}+1}) = 0$

- (II) $r_0 = \hat{d}^{-H/2} \rightarrow V_1^\pi(s_1^{\hat{d}+1}) = 1$

- if the algorithm wants to output an estimate that is correct up to 0.5 error, then it must need to distinguish two problem instances (I) and (II)

Consider any algorithm:

$$\text{Alg}: (\{p_h\}_{h \in [H]}, \phi) \rightarrow \mathbb{R}$$

- Given datasets $\{D_h\}_{h \in [L]}$ (and Φ), the algorithm need to identify which of the two instances (I) and (II) that the datasets come from
- Note that for both (I) and (II):
 - data distribution, transition kernels are the same
 - rewards are zero everywhere except in the last layer H
- Thus, to distinguish (I) and (II), the algorithm need to distinguish the reward distribution:

$$r = \begin{cases} 1 & \text{wp } \frac{1}{2} \\ -1 & \text{wp } \frac{1}{2} \end{cases} \quad \hat{d}^{H/2}$$

$$\text{and } r = \begin{cases} 1 & \text{wp } \frac{1+d}{2} \\ -1 & \text{wp } \frac{1-d}{2} \end{cases} \quad \hat{d}^{H/2}$$

$$\Rightarrow n = \Omega(\hat{d}^H) = \Omega\left(\left(\frac{d}{2}\right)^H\right)$$