

Text analysis

- What? Why

encode text data into numeric variables-empirical analysis

Common Sources of Text Data: Corporate Annual Reports, News and Social Media, Government and Legal Documents

A set of documents is called a corpus (plural corpora)

- Text Cleaning and Preprocessing

- Tokenize: parse documents into smaller units, such as words or phrases

Tokenization

- Split up a document into tokens
- Common tokens
 - Words: e.g., "hello", "blueno", "laptop", etc.
 - Punctuation: e.g., . , " ' ! ? , etc.
- Other tokens
 - Replace very uncommon words with an unknown token: <UNKNOWN>
 - End sentences (or sentence like structures) with a stop token: <STOP>
 - Replace all numbers with a single token: e.g., 100 → <NUM>
 - Replace common words ("a", "the", etc.) with <SWRD>
- Tokenization is a pain (there are lots of edge cases), but luckily, it is a solved problem
- "The dog ran in the park joyously!" →
c("<SWRD>", "dog", "ran", "<SWRD>", "<SWRD>", "park", "<UNKNOWN>", "!", "<STOP>")

- Remove stop words (e.g., a, the, and etc.)

Stop words: those that appear frequently in text analysis but contribute less to understanding the meaning of a sentence

- Stemming & Lemmatization: standardize words with similar meaning

Stemming & Lemmatization

- Goal: standardize words with a similar meaning
- **Stemming** reduces words to their base, or root, form
- **Lemmatization** makes words grammatically comparable (e.g., am, are, is → be)

He ate a tasty cookie yesterday, and he is eating tastier cookies today.

stemming

He ate a tasty cookie yesterday, and he is eat tasti cookie today.

lemmatization

He eat a tasty cookie yesterday, and he is eat tasty cookie today.

- Normalize

Image Source

e.g, "luv", "yay", "ew", "wtf"

- Topic modeling

Topic models allow us to cluster similar documents in a corpus together. They require no prior information, training set, or labelling of texts before estimation.

- LDA model

Latent Dirichlet Allocation (LDA) model

a probabilistic language model

Idea:

The number of topics, K , is selected by the researcher

Each of the K topics is a probability distribution (a Dirichlet distribution) over a fixed vocabulary of N words

Each of the D documents is a probability distribution (a Dirichlet distribution) over the K topics

Each word in each document is drawn from the topic-specific probability distribution (multinomial distribution) over words

Procedures:

1. Determine the proportion of topics in the article (Dirichlet distribution).
2. For each word, select the topic first, then select the word within the topic (multinomial distribution).
3. Reverse inference, inferring hidden themes from documents.

Reference:

<https://cs.brown.edu/courses/cs100/lectures/lecture24.pdf>

https://lse-me314.github.io/lecturenotes/ME314_day11.pdf