```
in/sentence_bert_config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/sentence_bert_config.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/adapter_config.json "HTTP/1.1 404 Not Found"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/config.json "HTTP/1.1 200 OK"
Loading weights:
100%|[redacted]| 199/199 [00:00<00:00, 2850.56it/s]
XLMRobertaModel LOAD REPORT from:
sentence-transformers/paraphrase-multilingual-mpnet-base-v2
Key                    | Status     |  |
------------------------+------------+--+-
embeddings.position_ids | UNEXPECTED |  |

Notes:
- UNEXPECTED:   can be ignored when loading from different task/architecture; not ok if you expect identical arch.
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/config.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/tokenizer_config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/tokenizer_config.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/tree/main/additional_chat_templates?recursive=false&expand=false "HTTP/1.1 404 Not Found"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/tree/main?recursive=true&expand=false "HTTP/1.1 200 OK"
```

```
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2 "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/1_Pooling/config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/1_Pooling%2Fconfig.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2 "HTTP/1.1 200 OK"
/home/hothai/Smart-Doc-AI/main.py:34: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use timezone-aware objects to represent datetimes in UTC: datetime.datetime.now(datetime.UTC).
  ts = datetime.utcnow().strftime("%Y%m%d_%H%M%S")
/home/hothai/Smart-Doc-AI/main.py:47: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use timezone-aware objects to represent datetimes in UTC: datetime.datetime.now(datetime.UTC).
  data.append({"role": role, "content": content, "ts": datetime.utcnow().isoformat()})
INFO:logs.logs:Query: tóm tắt
INFO:logs.logs:Retrieved 2 documents
INFO:httpx:HTTP Request: POST https://api.groq.com/openai/v1/chat/completions "HTTP/1.1 404 Not Found"
────────────────────────────────────── Traceback (most recent call last) ──────────────────────────────────────

  /home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/streamlit/runtime/scriptrunner/exec_code.py:129 in exec_func_with_error_handling

  /home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/streamlit/runtime/scriptrunner/script_runner.py:689 in code_to_exec

  /home/hothai/Smart-Doc-AI/main.py:211 in <module>

    208 │   │   with st.chat_message("assistant"):
    209 │   │   │   llm = get_llm(st.session_state.selected_model)
    210 │   │   │   answer = ask_question(query, st.session_state.retriever, llm)
❱ 211 │   │   │   st.markdown(answer)
    212 │   │
    213 │   │   st.session_state.messages.append({"role": "assistant", "content": answ
    214 │   │   append_history("assistant", answer)

  /home/hothai/Smart-Doc-AI/modules/rag/pipeline.py:45 in ask_question

    42 │   │   Answer:
    43 │   │   """
    44 │
```

```
❱ 45 │   response = llm.invoke(prompt)
  46 │
  47 │   return response.content
  48
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/langchain_core/language_models/chat_models.py:454 in invoke

```
  451 │   │   │   "AIMessage",
  452 │   │   │   cast(
  453 │   │   │   │   "ChatGeneration",
❱ 454 │   │   │   │   self.generate_prompt(
  455 │   │   │   │   │   [self._convert_input(input)],
  456 │   │   │   │   │   stop=stop,
  457 │   │   │   │   │   callbacks=config.get("callbacks"),
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/langchain_core/language_models/chat_models.py:1185 in generate_prompt

```
 1182 │   │   **kwargs: Any,
 1183 │   ) -> LLMResult:
 1184 │   │   prompt_messages = [p.to_messages() for p in prompts]
❱ 1185 │   │   return self.generate(prompt_messages, stop=stop, callbacks=callbacks,
 1186 │
 1187 │   @override
 1188 │   async def agenerate_prompt(
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/langchain_core/language_models/chat_models.py:995 in generate

```
  992 │   │   for i, m in enumerate(input_messages):
  993 │   │   │   try:
  994 │   │   │   │   results.append(
❱ 995 │   │   │   │   │   self._generate_with_cache(
  996 │   │   │   │   │   │   m,
  997 │   │   │   │   │   │   stop=stop,
  998 │   │   │   │   │   │   run_manager=run_managers[i] if run_managers else None
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/langchain_core/language_models/chat_models.py:1297 in _generate_with_cache

```
 1294 │   │   │   │   chunks.append(chunk)
 1295 │   │   │   result = generate_from_stream(iter(chunks))
 1296 │   │   elif inspect.signature(self._generate).parameters.get("run_manager"):
❱ 1297 │   │   │   result = self._generate(
 1298 │   │   │   │   messages, stop=stop, run_manager=run_manager, **kwargs
 1299 │   │   │   )
 1300 │   │   else:
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/langchain_groq/chat_models.py:621 in _generate

```
  618 │   │   │   **params,
  619 │   │   │   **kwargs,
  620 │   │   }
❱ 621 │   │   response = self.client.create(messages=message_dicts, **params)
  622 │   │   return self._create_chat_result(response, params)
  623 │
  624 │   async def _agenerate(
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/groq/resources/chat/completions.py:461 in create

```
  458 │   │
  459 │   │     timeout: Override the client-level default timeout for this request
  460 │   │   """
❱ 461 │   │   return self._post(
  462 │   │   │   "/openai/v1/chat/completions",
  463 │   │   │   body=maybe_transform(
  464 │   │   │   │   {
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/groq/_base_client.py:1242 in post

```
 1239 │   │   opts = FinalRequestOptions.construct(
 1240 │   │   │   method="post", url=path, json_data=body, files=to_httpx_files(fil
 1241 │   │   )
❱ 1242 │   │   return cast(ResponseT, self.request(cast_to, opts, stream=stream, str
 1243 │
 1244 │   def patch(
 1245 │   │   self,
```

/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/groq/_base_client.py:1044 in request

```
 1041 │   │   │   │   │   err.response.read()
 1042 │   │   │   │
 1043 │   │   │   │   log.debug("Re-raising status error")
❱ 1044 │   │   │   │   raise self._make_status_error_from_response(err.response) fro
 1045 │   │   │
 1046 │   │   │   break
 1047
```

NotFoundError: Error code: 404 - {'error': {'message': 'The model `qwen3-32b` does not exist or you do not have access to it.', 'type': 'invalid_request_error', 'code':

'model_not_found'}}
Accessing `__path__` from `.models.aria.image_processing_aria`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.aria.image_processing_pil_aria`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.auto.image_processing_auto`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.beit.image_processing_beit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.beit.image_processing_pil_beit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bit.image_processing_bit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bit.image_processing_pil_bit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.blip.image_processing_blip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.blip.image_processing_pil_blip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bridgetower.image_processing_bridgetower`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bridgetower.image_processing_pil_bridgetower`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chameleon.image_processing_chameleon`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chameleon.image_processing_pil_chameleon`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chinese_clip.image_processing_chinese_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chinese_clip.image_processing_chinese_pil_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chmv2.image_processing_chmv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.clip.image_processing_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.clip.image_processing_pil_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.cohere2_vision.image_processing_cohere2_vision`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.conditional_detr.image_processing_conditional_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.conditional_detr.image_processing_pil_conditional_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.convnext.image_processing_convnext`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.convnext.image_processing_pil_convnext`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl.image_processing_deepseek_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl.image_processing_pil_deepseek_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl_hybrid.image_processing_deepseek_vl_hybrid`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl_hybrid.image_processing_pil_deepseek_vl_hybrid`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deformable_detr.image_processing_deformable_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deformable_detr.image_processing_pil_deformable_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deit.image_processing_deit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deit.image_processing_pil_deit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.depth_pro.image_processing_depth_pro`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.detr.image_processing_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.detr.image_processing_pil_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.dinov3_vit.image_processing_dinov3_vit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.donut.image_processing_donut`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.donut.image_processing_pil_donut`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.dpt.image_processing_dpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.dpt.image_processing_pil_dpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientloftr.image_processing_efficientloftr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientloftr.image_processing_pil_efficientloftr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientnet.image_processing_efficientnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientnet.image_processing_pil_efficientnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.emu3.image_processing_emu3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.eomt.image_processing_eomt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.eomt.image_processing_pil_eomt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ernie4_5_vl_moe.image_processing_ernie4_5_vl_moe`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ernie4_5_vl_moe.image_processing_pil_ernie4_5_vl_moe`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.flava.image_processing_flava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.flava.image_processing_pil_flava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.fuyu.image_processing_fuyu`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.fuyu.image_processing_pil_fuyu`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.gemma3.image_processing_gemma3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.gemma3.image_processing_pil_gemma3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.gemma4.image_processing_gemma4`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.gemma4.image_processing_pil_gemma4`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm46v.image_processing_glm46v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm46v.image_processing_pil_glm46v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm4v.image_processing_glm4v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm4v.image_processing_pil_glm4v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm_image.image_processing_glm_image`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm_image.image_processing_pil_glm_image`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glpn.image_processing_glpn`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glpn.image_processing_pil_glpn`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.got_ocr2.image_processing_got_ocr2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.got_ocr2.image_processing_pil_got_ocr2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.grounding_dino.image_processing_grounding_dino`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.grounding_dino.image_processing_pil_grounding_dino`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics.image_processing_idefics`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics.image_processing_pil_idefics`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics2.image_processing_idefics2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.idefics2.image_processing_pil_idefics2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics3.image_processing_idefics3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics3.image_processing_pil_idefics3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.imagegpt.image_processing_imagegpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.imagegpt.image_processing_pil_imagegpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.janus.image_processing_janus`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.janus.image_processing_pil_janus`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.kosmos2_5.image_processing_kosmos2_5`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.kosmos2_5.image_processing_pil_kosmos2_5`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv2.image_processing_layoutlmv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv2.image_processing_pil_layoutlmv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv3.image_processing_layoutlmv3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv3.image_processing_pil_layoutlmv3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.levit.image_processing_levit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.levit.image_processing_pil_levit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.lfm2_vl.image_processing_lfm2_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.lightglue.image_processing_lightglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.lightglue.image_processing_pil_lightglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llama4.image_processing_llama4`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava.image_processing_llava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava.image_processing_pil_llava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_next.image_processing_llava_next`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_next.image_processing_pil_llava_next`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_onevision.image_processing_llava_onevision`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_onevision.image_processing_pil_llava_onevision`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mask2former.image_processing_mask2former`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mask2former.image_processing_pil_mask2former`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.maskformer.image_processing_maskformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.maskformer.image_processing_pil_maskformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mllama.image_processing_mllama`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mllama.image_processing_pil_mllama`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilenet_v1.image_processing_mobilenet_pil_v1`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilenet_v1.image_processing_mobilenet_v1`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.mobilenet_v2.image_processing_mobilenet_v2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilenet_v2.image_processing_pil_mobilenet_v2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilevit.image_processing_mobilevit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilevit.image_processing_pil_mobilevit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.nougat.image_processing_nougat`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.nougat.image_processing_pil_nougat`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.oneformer.image_processing_oneformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.oneformer.image_processing_pil_oneformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ovis2.image_processing_ovis2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ovis2.image_processing_pil_ovis2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlv2.image_processing_owlv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlv2.image_processing_pil_owlv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlvit.image_processing_owlvit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlvit.image_processing_pil_owlvit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.paddleocr_vl.image_processing_paddleocr_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.paddleocr_vl.image_processing_pil_paddleocr_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.perceiver.image_processing_perceiver`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.perceiver.image_processing_pil_perceiver`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.perception_lm.image_processing_perception_lm`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.phi4_multimodal.image_processing_phi4_multimodal`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pi0.image_processing_pi0`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pix2struct.image_processing_pil_pix2struct`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pix2struct.image_processing_pix2struct`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pixtral.image_processing_pil_pixtral`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pixtral.image_processing_pixtral`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.poolformer.image_processing_pil_poolformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.poolformer.image_processing_poolformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_chart2table.image_processing_pil_pp_chart2table`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_chart2table.image_processing_pp_chart2table`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_doclayout_v2.image_processing_pp_doclayout_v2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_doclayout_v3.image_processing_pp_doclayout_v3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_lcnet.image_processing_pp_lcnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_ocrv5_server_det.image_processing_pp_ocrv5_server_det`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.pp_ocrv5_server_rec.image_processing_pp_ocrv5_server_rec`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.prompt_depth_anything.image_processing_pil_prompt_depth_anything`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.prompt_depth_anything.image_processing_prompt_depth_anything`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pvt.image_processing_pil_pvt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pvt.image_processing_pvt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.qwen2_vl.image_processing_pil_qwen2_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.qwen2_vl.image_processing_qwen2_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.rt_detr.image_processing_pil_rt_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.rt_detr.image_processing_rt_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam.image_processing_pil_sam`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam.image_processing_sam`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam2.image_processing_sam2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam3.image_processing_sam3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.segformer.image_processing_pil_segformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.segformer.image_processing_segformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.seggpt.image_processing_pil_seggpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.seggpt.image_processing_seggpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.siglip.image_processing_pil_siglip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip.image_processing_siglip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip2.image_processing_pil_siglip2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip2.image_processing_siglip2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.slanext.image_processing_slanext`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.smolvlm.image_processing_pil_smolvlm`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.smolvlm.image_processing_smolvlm`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superglue.image_processing_pil_superglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superglue.image_processing_superglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superpoint.image_processing_pil_superpoint`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superpoint.image_processing_superpoint`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.swin2sr.image_processing_pil_swin2sr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.swin2sr.image_processing_swin2sr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.textnet.image_processing_pil_textnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.textnet.image_processing_textnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.timm_wrapper.image_processing_timm_wrapper`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.tvp.image_processing_pil_tvp`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.tvp.image_processing_tvp`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.uvdoc.image_processing_uvdoc`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.video_llama_3.image_processing_pil_video_llama_3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.video_llama_3.image_processing_video_llama_3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.video_llava.image_processing_video_llava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.videomae.image_processing_pil_videomae`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.videomae.image_processing_videomae`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vilt.image_processing_pil_vilt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vilt.image_processing_vilt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vit.image_processing_pil_vit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vit.image_processing_vit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitmatte.image_processing_pil_vitmatte`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitmatte.image_processing_vitmatte`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitpose.image_processing_pil_vitpose`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitpose.image_processing_vitpose`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vivit.image_processing_vivit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.yolos.image_processing_pil_yolos`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.yolos.image_processing_yolos`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.zoedepth.image_processing_pil_zoedepth`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.zoedepth.image_processing_zoedepth`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.aria.image_processing_aria`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.aria.image_processing_pil_aria`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.auto.image_processing_auto`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.beit.image_processing_beit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.beit.image_processing_pil_beit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bit.image_processing_bit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bit.image_processing_pil_bit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.blip.image_processing_blip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.blip.image_processing_pil_blip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bridgetower.image_processing_bridgetower`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.bridgetower.image_processing_pil_bridgetower`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chameleon.image_processing_chameleon`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chameleon.image_processing_pil_chameleon`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chinese_clip.image_processing_chinese_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chinese_clip.image_processing_chinese_pil_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.chmv2.image_processing_chmv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.clip.image_processing_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.clip.image_processing_pil_clip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.cohere2_vision.image_processing_cohere2_vision`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.conditional_detr.image_processing_conditional_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.conditional_detr.image_processing_pil_conditional_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.convnext.image_processing_convnext`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.convnext.image_processing_pil_convnext`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl.image_processing_deepseek_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl.image_processing_pil_deepseek_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl_hybrid.image_processing_deepseek_vl_hybrid`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deepseek_vl_hybrid.image_processing_pil_deepseek_vl_hybrid`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deformable_detr.image_processing_deformable_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deformable_detr.image_processing_pil_deformable_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deit.image_processing_deit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.deit.image_processing_pil_deit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.depth_pro.image_processing_depth_pro`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.detr.image_processing_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.detr.image_processing_pil_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.dinov3_vit.image_processing_dinov3_vit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.donut.image_processing_donut`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.donut.image_processing_pil_donut`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.dpt.image_processing_dpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.dpt.image_processing_pil_dpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientloftr.image_processing_efficientloftr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientloftr.image_processing_pil_efficientloftr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientnet.image_processing_efficientnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.efficientnet.image_processing_pil_efficientnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.emu3.image_processing_emu3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.eomt.image_processing_eomt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.eomt.image_processing_pil_eomt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ernie4_5_vl_moe.image_processing_ernie4_5_vl_moe`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ernie4_5_vl_moe.image_processing_pil_ernie4_5_vl_moe`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.flava.image_processing_flava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.flava.image_processing_pil_flava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.fuyu.image_processing_fuyu`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.fuyu.image_processing_pil_fuyu`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.gemma3.image_processing_gemma3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.gemma3.image_processing_pil_gemma3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.gemma4.image_processing_gemma4`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.gemma4.image_processing_pil_gemma4`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm46v.image_processing_glm46v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm46v.image_processing_pil_glm46v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm4v.image_processing_glm4v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm4v.image_processing_pil_glm4v`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm_image.image_processing_glm_image`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glm_image.image_processing_pil_glm_image`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glpn.image_processing_glpn`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.glpn.image_processing_pil_glpn`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.got_ocr2.image_processing_got_ocr2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.got_ocr2.image_processing_pil_got_ocr2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.grounding_dino.image_processing_grounding_dino`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.grounding_dino.image_processing_pil_grounding_dino`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics.image_processing_idefics`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.idefics.image_processing_pil_idefics`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics2.image_processing_idefics2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics2.image_processing_pil_idefics2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics3.image_processing_idefics3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.idefics3.image_processing_pil_idefics3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.imagegpt.image_processing_imagegpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.imagegpt.image_processing_pil_imagegpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.janus.image_processing_janus`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.janus.image_processing_pil_janus`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.kosmos2_5.image_processing_kosmos2_5`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.kosmos2_5.image_processing_pil_kosmos2_5`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv2.image_processing_layoutlmv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv2.image_processing_pil_layoutlmv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv3.image_processing_layoutlmv3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.layoutlmv3.image_processing_pil_layoutlmv3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.levit.image_processing_levit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.levit.image_processing_pil_levit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.lfm2_vl.image_processing_lfm2_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.lightglue.image_processing_lightglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.lightglue.image_processing_pil_lightglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llama4.image_processing_llama4`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava.image_processing_llava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava.image_processing_pil_llava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_next.image_processing_llava_next`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_next.image_processing_pil_llava_next`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_onevision.image_processing_llava_onevision`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.llava_onevision.image_processing_pil_llava_onevision`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mask2former.image_processing_mask2former`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mask2former.image_processing_pil_mask2former`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.maskformer.image_processing_maskformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.maskformer.image_processing_pil_maskformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mllama.image_processing_mllama`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mllama.image_processing_pil_mllama`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.mobilenet_v1.image_processing_mobilenet_pil_v1`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilenet_v1.image_processing_mobilenet_v1`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilenet_v2.image_processing_mobilenet_v2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilenet_v2.image_processing_pil_mobilenet_v2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilevit.image_processing_mobilevit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.mobilevit.image_processing_pil_mobilevit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.nougat.image_processing_nougat`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.nougat.image_processing_pil_nougat`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.oneformer.image_processing_oneformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.oneformer.image_processing_pil_oneformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ovis2.image_processing_ovis2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.ovis2.image_processing_pil_ovis2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlv2.image_processing_owlv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlv2.image_processing_pil_owlv2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlvit.image_processing_owlvit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.owlvit.image_processing_pil_owlvit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.paddleocr_vl.image_processing_paddleocr_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.paddleocr_vl.image_processing_pil_paddleocr_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.perceiver.image_processing_perceiver`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.perceiver.image_processing_pil_perceiver`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.perception_lm.image_processing_perception_lm`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.phi4_multimodal.image_processing_phi4_multimodal`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pi0.image_processing_pi0`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pix2struct.image_processing_pil_pix2struct`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pix2struct.image_processing_pix2struct`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pixtral.image_processing_pil_pixtral`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pixtral.image_processing_pixtral`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.poolformer.image_processing_pil_poolformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.poolformer.image_processing_poolformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_chart2table.image_processing_pil_pp_chart2table`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_chart2table.image_processing_pp_chart2table`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_doclayout_v2.image_processing_pp_doclayout_v2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_doclayout_v3.image_processing_pp_doclayout_v3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.pp_lcnet.image_processing_pp_lcnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_ocrv5_server_det.image_processing_pp_ocrv5_server_det`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pp_ocrv5_server_rec.image_processing_pp_ocrv5_server_rec`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.prompt_depth_anything.image_processing_pil_prompt_depth_anything`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.prompt_depth_anything.image_processing_prompt_depth_anything`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pvt.image_processing_pil_pvt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.pvt.image_processing_pvt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.qwen2_vl.image_processing_pil_qwen2_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.qwen2_vl.image_processing_qwen2_vl`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.rt_detr.image_processing_pil_rt_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.rt_detr.image_processing_rt_detr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam.image_processing_pil_sam`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam.image_processing_sam`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam2.image_processing_sam2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.sam3.image_processing_sam3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.segformer.image_processing_pil_segformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.segformer.image_processing_segformer`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.seggpt.image_processing_pil_seggpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.seggpt.image_processing_seggpt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip.image_processing_pil_siglip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip.image_processing_siglip`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip2.image_processing_pil_siglip2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.siglip2.image_processing_siglip2`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.slanext.image_processing_slanext`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.smolvlm.image_processing_pil_smolvlm`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.smolvlm.image_processing_smolvlm`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superglue.image_processing_pil_superglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superglue.image_processing_superglue`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superpoint.image_processing_pil_superpoint`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.superpoint.image_processing_superpoint`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.swin2sr.image_processing_pil_swin2sr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.swin2sr.image_processing_swin2sr`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.textnet.image_processing_pil_textnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.textnet.image_processing_textnet`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.timm_wrapper.image_processing_timm_wrapper`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.tvp.image_processing_pil_tvp`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.tvp.image_processing_tvp`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.uvdoc.image_processing_uvdoc`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.video_llama_3.image_processing_pil_video_llama_3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.video_llama_3.image_processing_video_llama_3`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.video_llava.image_processing_video_llava`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.videomae.image_processing_pil_videomae`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.videomae.image_processing_videomae`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vilt.image_processing_pil_vilt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vilt.image_processing_vilt`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vit.image_processing_pil_vit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vit.image_processing_vit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitmatte.image_processing_pil_vitmatte`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitmatte.image_processing_vitmatte`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vitpose.image_processing_pil_vitpose`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.

Accessing `__path__` from `.models.vitpose.image_processing_vitpose`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.vivit.image_processing_vivit`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.yolos.image_processing_pil_yolos`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.yolos.image_processing_yolos`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.zoedepth.image_processing_pil_zoedepth`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
Accessing `__path__` from `.models.zoedepth.image_processing_zoedepth`. Returning `__path__` instead. Behavior may be different and this alias will be removed in future versions.
INFO:logs.logs:Processing 2 chunks
INFO:sentence_transformers.SentenceTransformer:Load pretrained SentenceTransformer: sentence-transformers/paraphrase-multilingual-mpnet-base-v2
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/modules.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/modules.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/config_sentence_transformers.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/config_sentence_transformers.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/config_sentence_transformers.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/config_sentence_transformers.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/README.md "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/README.md "HTTP/1.1 200 OK"

INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/modules.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/modules.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/sentence_bert_config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/sentence_bert_config.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/adapter_config.json "HTTP/1.1 404 Not Found"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/config.json "HTTP/1.1 200 OK"
Loading weights:
100%|[redacted]| 199/199 [00:00<00:00, 2341.80it/s]
XLMRobertaModel LOAD REPORT from: sentence-transformers/paraphrase-multilingual-mpnet-base-v2
Key | Status | |
---+---+--+-
embeddings.position_ids | UNEXPECTED | |

Notes:
- UNEXPECTED: can be ignored when loading from different task/architecture; not ok if you expect identical arch.
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/config.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/tokenizer_config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multiling

```
ual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/tokenizer_config.json
"HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/tree/main/additional_chat_templates?recursive=false&expand=false "HTTP/1.1 404 Not Found"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/tree/main?recursive=true&expand=false "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2 "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/resolve/main/1_Pooling/config.json "HTTP/1.1 307 Temporary Redirect"
INFO:httpx:HTTP Request: HEAD
https://huggingface.co/api/resolve-cache/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2/4328cf26390c98c5e3c738b4460a05b95f4911f5/1_Pooling%2Fconfig.json "HTTP/1.1 200 OK"
INFO:httpx:HTTP Request: GET
https://huggingface.co/api/models/sentence-transformers/paraphrase-multilingual-mpnet-base-v2 "HTTP/1.1 200 OK"
/home/hothai/Smart-Doc-AI/main.py:34: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use timezone-aware objects to represent datetimes in UTC: datetime.datetime.now(datetime.UTC).
  ts = datetime.utcnow().strftime("%Y%m%d_%H%M%S")
/home/hothai/Smart-Doc-AI/main.py:47: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use timezone-aware objects to represent datetimes in UTC: datetime.datetime.now(datetime.UTC).
  data.append({"role": role, "content": content, "ts": datetime.utcnow().isoformat()})
INFO:logs.logs:Query: tóm tắt
INFO:logs.logs:Retrieved 2 documents
INFO:httpx:HTTP Request: POST https://api.groq.com/openai/v1/chat/completions
"HTTP/1.1 200 OK"
^C  Stopping...
^C  Stopping...
Traceback (most recent call last):
  File "/usr/lib/python3.12/weakref.py", line 666, in _exitfunc
    f()
  File "/usr/lib/python3.12/weakref.py", line 590, in __call__
    return info.func(*info.args, **(info.kwargs or {}))
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^
  File "/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/torch/library.py", line 479, in _del_library
    m.reset()
  File
"/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/streamlit/web/bootstrap.py", line 43, in signal_handler
```

```
    server.stop()
  File
"/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/streamlit/web/server/server.p
y", line 550, in stop
    self._runtime.stop()
  File
"/home/hothai/Smart-Doc-AI/venv/lib/python3.12/site-packages/streamlit/runtime/runtime.py"
, line 351, in stop
    async_objs.eventloop.call_soon_threadsafe(stop_on_eventloop)
  File "/usr/lib/python3.12/asyncio/base_events.py", line 840, in call_soon_threadsafe
    self._check_closed()
  File "/usr/lib/python3.12/asyncio/base_events.py", line 541, in _check_closed
    raise RuntimeError('Event loop is closed')
RuntimeError: Event loop is closed
^C
(venv) hothai@hothai-VMware-Virtual-Platform:~/Smart-Doc-AI$ ^C
(venv) hothai@hothai-VMware-Virtual-Platform:~/Smart-Doc-AI$
```