



Advanced Technology

- **AI-Powered 3-Level Scalable BMS** AI-driven two-tier architecture expandable to three levels, enabling intelligent cell-to-system monitoring and busbar coordination.
- **47+ Inverter Brand Compatibility** seamless integration via CAN bus across diverse energy storage systems.
- **High-Rate Charge/Discharge + Active Balancing** ensures long-term battery reliability.
- **Proprietary Thermal Balance System** $\pm 3^{\circ}\text{C}$ cell temperature control helps improve temperature uniformity and supports long service life.

Flexible Configuration

- **Modular Stack Design** frameless, plug-and-play stacking with flexible 64 kWh to 921 kWh capacity for all applications.
- **High-Capacity Single Rack** holds up to 15 packs in series, rated at 241 kWh to meet C&I energy demands.
- **Industrial BMS with Auto-Voltage Matching** ensures safe and stable operation with flexible series/parallel configuration.
- **8,000 Cycles** designed for daily cycling to deliver strong ROI on C&I storage projects.

Convenient Installation

- **Ergonomic Rack Design** max height of 1.8m ensures safe, accessible maintenance without overhead operation.
- **Sleek Modular Build** modern minimalist design with stacking ease lowers installation and maintenance costs.
- **Plug-and-Play Connectivity** quick connectors with auto-configuration enable simple setup, no special skills needed.
- **Crane-Free Installation** can be assembled manually, reducing complexity and cost across all site types.

Localized Technical Support

- **End-to-End Service Support** from design and construction to operation and recycling—a complete service cycle for maximizing project value.
- **Hybrid Training System** combined online and offline training covering product knowledge, operation skills, and maintenance for rapid client readiness.
- **Secure & Tracked Logistics** professional warehousing and door-to-door delivery ensure timely, safe arrival with full-chain traceability.
- **Localized Technical Network** on-site installation, maintenance, and troubleshooting supported by a reliable warranty for consistent system performance.

Model	XH-112		XH-241	
Product Name	Stacked PDU			
PDU Model	CFE - PDU 1000 - 200 - B			
Installation Method	Racks			
Humidity	0 – 95 % RH (non-condensing)			
Nominal Voltage	1000 Vdc			
Max. Rated Current	200 A			
Size	440 × 837 × 225 mm			
Product Name	Stacked PACK			
Battery Type	LiFePO4			
Battery Model	CFE - PA51 - 314 - B			
Total Energy	16.07 kWh			
Nominal Voltage	51.2 V			
Capacity	314 Ah			
Size	440 × 837 × 225 mm			
System Name	Stackable energy storage system			
Nominal Voltage	358.4 V		768 V	
Voltage Range	324.8 - 403.2 V		696 - 864 V	
Max. Charging Current	150 A			
Max. Discharge Current	200 A			
Size (mm)	440 × 837 × 1850 mm		880 × 837 × 1850 mm	
Communication Method	CAN / RS485 / Wi-Fi			
Charge Operating Temperature	-10 to 70 °C			
Discharge Operating Temperature	-20 to 70 °C			
Humidity	0 – 95 % RH (non-condensing)			
Altitude	≤2000m			
Installation Method	Stack			
Cycle Life	≥8000 Cycles (@25 ± 2 °C, 0.5C / 0.5C, 80%DoD)			

CFE ESS Co., Ltd.

CFE has offices & warehouses in the following regions where you can get in touch with us:

Europe: Rotterdam (Netherlands) Africa: Johannesburg (South Africa)

Asia: Xi'an, Shenzhen, Tianjin, Hefei, Hong Kong (China) , and Yangon (Myanmar)

Tel: (+86) 029 38367888 Web: www.cfess.cn E-mail: cfenergy@cfess.cn