



GAS & RADIATION DETECTION

Calibration Gas Mixtures

Certified gas for accurate, reliable detectors

by **DLV CORPORATION**

8
new mixtures

3 · 8 · 10 L
cylinder sizes

BS4 valve
on every cylinder

12 months
expiry

CALIBRATION GAS & EQUIPMENT

Keep every gas detector reading true

Gas detectors drift over time. Regular bump tests and calibration with a known gas mixture confirm that each detector alarms at the right level. This range covers solvent-vapour (THF / Octane) mixtures and multi-gas mixtures for 4- and 5-gas personal monitors.

3 L carbon steel cylinder

THF / Octane in nitrogen

 Filling pressure **4.00 kg/cm²**

 Content of gas **12.00 liters** Prep.

 tolerance **±10%** Certificate

 accuracy **±2%** Stability **12**

 months Cylinder basis **Outright**

3 mixtures · page 3

10 L carbon steel cylinder

THF / Octane in nitrogen

 Filling pressure **4.00 kg/cm²**

 Content of gas **See product**

 Prep. tolerance **±10%** Certificate

 accuracy **±2%** Stability **12**

 months Cylinder basis **Outright**

3 mixtures · page 4

8 L aluminium cylinder

 5-gas mixture, balance N₂

 Cylinder **Refillable**

 Pressure **35 bar**

 Relativity **±5%**

 Expiry **12 months**

 Certificate **COA included**

 Valve **BS4**

2 mixtures · page 5



Bump testing

Confirm sensors and alarms respond before each shift.



Full calibration

Set span on fixed and portable detectors to a certified value.



Solvent vapour (THF / Octane)

Check LEL and VOC detectors in coating, printing and chemical plants.



Confined space & marine

O₂, CO, H₂S, CH₄ and CO₂ mixtures for multi-gas monitors.



Every cylinder ships ready to use

Filled to order with a BS4 valve and supplied with its certificate. Tell us your detector brand and model and we will confirm the right regulator and flow.

THF / OCTANE · N2 BALANCE

3 liter W/C carbon steel cylinder

3 mixtures

 New cylinder, BS4 valve · 4.00 kg/cm² · 12.00 liters of gas

REF 23.3.4.1.77

US\$ 2,160

THF 0.5% · Octane 0.05% · N2 99.45%

COMPOSITION

Tetrahydrofuran (THF)	0.5%
Octane	0.05%
Nitrogen (N2)	99.45%

SPECIFICATION

Filling pressure	4.00 kg/cm ²
Content of gas	12.00 liters
Tolerance / accuracy	±10% / ±2%
Stability · basis	12 months · Outright

Description: CALIBRATION GAS MIXTURE IN NEW 03 liter W/C CARBON STEEL CYLINDER, C/W BS4 VALVE, 0.5% THF : 0.05% Octane : 99.45% N2

REF 23.3.4.1.76

US\$ 2,160

THF 1.0% · Octane 0.1% · N2 balance

COMPOSITION

Tetrahydrofuran (THF)	1.0%
Octane (OCT)	0.1%
Nitrogen (N2)	Balance

SPECIFICATION

Filling pressure	4.00 kg/cm ²
Content of gas	12.00 liters
Tolerance / accuracy	±10% / ±2%
Stability · basis	12 months · Outright

Description: CALIBRATION GAS MIXTURE IN NEW 03 liter W/C CARBON STEEL CYLINDER, C/W BS4 VALVE, THF 1.0%, OCT 0.1% N2 BASED GAS.

REF 23.3.4.1.75

US\$ 1,350

THF 1.5% · Octane 0.15% · N2 balance

COMPOSITION

Tetrahydrofuran (THF)	1.5%
Octane (OCT)	0.15%
Nitrogen (N2)	Balance

SPECIFICATION

Filling pressure	4.00 kg/cm ²
Content of gas	12.00 liters
Tolerance / accuracy	±10% / ±2%
Stability · basis	12 months · Outright

Description: CALIBRATION GAS MIXTURE IN NEW 03 liter W/C CARBON STEEL CYLINDER, C/W BS4 VALVE, THF 1.5%, OCT 0.15% N2 BASED GAS.

THF / OCTANE · N2 BALANCE

10 liter W/C carbon steel cylinder

3 mixtures

 New cylinder, BS4 valve - 4.00 kg/cm² filling pressure

REF 23.3.4.1.80

US\$ 1,890

THF 0.5% · Octane 0.05% · N2 balance

COMPOSITION

Tetrahydrofuran (THF)	0.5%
Octane (OCT)	0.05%
Nitrogen (N2)	Balance

SPECIFICATION

Filling pressure	4.00 kg/cm ²
Content of gas	40.00 liters
Tolerance / accuracy	±10% / ±2%
Stability · basis	12 months · Outright

Description: CALIBRATION GAS MIXTURE IN NEW 10 liter W/C CARBON STEEL CYLINDER, C/W BS4 VALVE, THF 0.5%, OCT 0.05% N2 BASED GAS.

REF 23.3.4.1.79

US\$ 1,890

THF 1.0% · Octane 0.1% · N2 balance

COMPOSITION

Tetrahydrofuran (THF)	1.0%
Octane (OCT)	0.1%
Nitrogen (N2)	Balance

SPECIFICATION

Filling pressure	4.00 kg/cm ²
Content of gas	12.00 liters
Tolerance / accuracy	±10% / ±2%
Stability · basis	12 months · Outright

Description: CALIBRATION GAS MIXTURE IN NEW 10 liter W/C CARBON STEEL CYLINDER, C/W BS4 VALVE, THF 1.0%, OCT 0.1% N2 BASED GAS.

REF 23.3.4.1.78

US\$ 1,890

THF 1.5% · Octane 0.15% · N2 balance

COMPOSITION

Tetrahydrofuran (THF)	1.5%
Octane (OCT)	0.15%
Nitrogen (N2)	Balance

SPECIFICATION

Filling pressure	4.00 kg/cm ²
Content of gas	40.00 liters
Tolerance / accuracy	±10% / ±2%
Stability · basis	12 months · Outright

Description: CALIBRATION GAS MIXTURE IN NEW 10 liter W/C CARBON STEEL CYLINDER, C/W BS4 VALVE, THF 1.5%, OCT 0.15% N2 BASED GAS.

5-GAS MIXTURES · N2 BALANCE

8 liter aluminium cylinder

Newcylinder,BS4valve-refillable-35bar-CertificateofAnalysis included

2 mixtures

REF 23.3.4.1.3287

US\$ 1,130

O2 18% · CO 100 ppm · H2S 25 ppm · CH4 50% LEL ·
CO2 2500 ppm

COMPOSITION

Oxygen (O2)	18% vol
Carbon monoxide (CO)	100 ppm
Hydrogen sulphide (H2S)	25 ppm
Methane (CH4)	50% LEL
Carbon dioxide (CO2)	2500 ppm vol
Nitrogen (N2)	Balance

SPECIFICATIO

N	Refillable aluminium
Cylinder	35 bar
Pressure	±5%
Relativity	12 months
Expiry	COA included
Certificate	BS4
Valve	

Description: CALIBRATION GAS MIXTURE IN NEW 08 liter COMES WITH ALUMINUM CYLINDER, BS4 VALVE.
GAS MIXTURE: O2 18% VOL CO 100 ppm H2S 25 ppm CH4 50% LEL CO2 2500 PPM VOL Balance N2

REF 23.3.4.1.3286

US\$ 1,130

O2 20.9% · CO 500 ppm · H2S 50 ppm · CH4 60%
LEL · CO2 2.5%

COMPOSITION

Oxygen (O2)	20.9% vol
Carbon monoxide (CO)	500 ppm
Hydrogen sulphide (H2S)	50 ppm
Methane (CH4)	60% LEL
Carbon dioxide (CO2)	2.5% vol
Nitrogen (N2)	Balance

SPECIFICATIO

N	Refillable aluminium
Cylinder	35 bar
Pressure	±5%
Relativity	12 months
Expiry	COA included
Certificate	BS4
Valve	

Description: CALIBRATION GAS MIXTURE IN NEW 08 liter COMES WITH ALUMINUM CYLINDER, BS4 VALVE.
GAS MIXTURE: O2 20.9% VOL CO 500 ppm H2S 50 ppm CH4 60% LEL CO2 2.5% VOL Balance N2

PRICE LIST 2026

All mixtures at a glance

Ref	Gas mixture	Cylinder	Price (USD)
23.3.4.1.77	THF 0.5% · Octane 0.05% · N2 99.45%	3 L carbon steel	2,160
23.3.4.1.76	THF 1.0% · Octane 0.1% · N2	3 L carbon steel	2,160
23.3.4.1.75	THF 1.5% · Octane 0.15% · N2	3 L carbon steel	1,350
23.3.4.1.80	THF 0.5% · Octane 0.05% · N2	10 L carbon steel	1,890
23.3.4.1.79	THF 1.0% · Octane 0.1% · N2	10 L carbon steel	1,890
23.3.4.1.78	THF 1.5% · Octane 0.15% · N2	10 L carbon steel	1,890
23.3.4.1.3287	O2 18% · CO 100 ppm · H2S 25 ppm · CH4 50% LEL · CO2 2500 ppm · N2	8 L aluminium	1,130
23.3.4.1.3286	O2 20.9% · CO 500 ppm · H2S 50 ppm · CH4 60% LEL · CO2 2.5% · N2	8 L aluminium	1,130

Prices are per cylinder in US dollars, converted from our VND list price at 25,951 VND = 1 USD (market rate, 25/09/2026) and rounded to the nearest \$10. Prices exclude VAT and delivery and may change without notice.

1 Choose

Pick the mixture by its REF code, or send us your detector model.

2 Request a quote

Call, WhatsApp or Zalo us with the REF codes and quantities.

3 Receive

Cylinders are filled to order and delivered with their certificate.

DLV CORPORATION



PHONE/WHATS APP

(+84) 347 099 905



ZALO OA

zalo.me/2640689488672783975



EMAIL

info@dlvcorp.com



WEBSITE

calibrationgas.handyman.vn

29 Nguyen Van Quy Street, Tan Thuan Ward, Ho Chi Minh City, Vietnam · Tax code 0307940363