Aim:

Write code to calculate roots of a quadratic equation

Write a class QuadraticRoots with main method. The method receives three arguments, write code to parse them into double type.

For example:

```
if the values 2, 5, 3 are passed as arguments, then the output should be First root
is : -1.0 Second root is : -1.5
If the values 3, 2, 1 are passed then the output should be Roots are imaginary
Similarly, if the values 2, 4, 2 are passed then the output should be Roots are equa
l and value is : -1.0
```

Note: Make sure to use the print() and not the println() method.

Note: Please don't change the package name.

Source Code:

q10851/QuadraticRoots.java

```
package q10851;
class QuadraticRoots{
   double a,b,c;
   void getData(String c1,String c2,String c3)
    a=Double.valueOf(c1);
    b=Double.valueOf(c2);
    c=Double.valueOf(c3);
 }
   void roots ()
      double d;
      if(a==0)
         double root;
         root=-c/b;
         System.out.println("linear equation "+root);
  }
      else
      {
         d=(b*b)-(4*a*c);
         if(d==0)
            double root=-b/(2*a);
            System.out.println("Roots are equal and value is : "+root);
   }
         else if(d>0)
            double r1,r2;
            r1=(-b+Math.sqrt(d))/(2*a);
            r2=(-b-Math.sqrt(d))/(2*a);
```

SasiInstitute of Technology and Engineering (Autonomous) 2022-2026-CSE-AIML

```
System.out.println("First root is : "+r1+" Second root is : "+r2);
  }
         else
          System.out.println("Roots are imaginary");
  }
 }
  public static void main(String a[])
      QuadraticRoots r=new QuadraticRoots();
      r.getData(a[0],a[1],a[2]);
      r.roots();
}
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
First root is : -0.6047152924789525 Second root is : -1.3952847075210475

```
Test Case - 2
User Output
Roots are equal and value is : -1.0
```

```
Test Case - 3
User Output
Roots are imaginary
```