



Chiang Mai University

AnyaspyAC

Suthana Kwaonueng, Theerada Siri, Sorawach Utas

2026-07-14


```
    }
    return res;
}

void cal_fac(){
    fac[0] = 1;
    for(int i=1;i<N;++i) fac[i] = fac[i-1] * i % MOD;
    faci[N-1] = bigmod(fac[N-1], MOD-2);
    for(int i=N-2;i>=0;--i) faci[i] = faci[i+1] * (i+1) % MOD;
}
```

Cnr.h

Description: this is ok

cc78ad, 11 lines

```
long long Cnr(int n, int k) {
    if(k<0 || n<k)return 0;
    if(k==0 or n==k)return 1;
    /*
    double res = 1;
    for (int i = 1; i <= k; ++i)
        res = res * (n - k + i) / i;
    return (long long)(res + 0.01);
    */
    return fac[n] * faci[k] % MOD * faci[n-k] % MOD;
}
```

lucas.h

Description: for large n and small modulo, the complexity is O(p * log-p(n)), p must be prime

10284e, 36 lines

```
// Standard nCr modulo p for small n and r
long long nCr_small(long long n, long long r, int p) {
    if (r < 0 || r > n) return 0;
    if (r == 0 || r == n) return 1;
    if (r > n / 2) r = n - r;

    long long num = 1, den = 1;
    for (int i = 0; i < r; ++i) {
        num = (num * (n - i)) % p;
        den = (den * (i + 1)) % p;
    }

    // Modular inverse using Fermat's Little Theorem (den^(p-2) % p)
    auto power = [&](long long base, long long exp) {
        long long res = 1;
        base %= p;
        while (exp > 0) {
            if (exp % 2 == 1) res = (res * base) % p;
            base = (base * base) % p;
            exp /= 2;
        }
        return res;
    };

    return (num * power(den, p - 2)) % p;
}

// Lucas Theorem Implementation
long long lucas(long long n, long long k, int p) {
    // Base cases
    if (k == 0) return 1;
    if (n < k) return 0;

    // Recursive step: nCr % p = ( (n/p)C(k/p) * (n%p)C(k%p) ) % p
    return (lucas(n / p, k / p, p) * nCr_small(n % p, k % p, p)
        ) % p;
}
```

factoradix.h

Description: for that factorial base number finding nth permutation blablabla, also this using 0 base indexing, i.e. your 1st lexicographically permutation now is start at 0th

<ext/pb.ds/assoc.container.hpp>, <ext/pb.ds/tree.policy.hpp>e835c3, 57 lines

typedef __gnu_pbds::tree<int, __gnu_pbds::null_type, less<int>, __gnu_pbds::rb_tree_tag, __gnu_pbds::tree_order_statistics_node_update> ordered_set;

```
ordered_set st;

vector<int> factoradix_to_permutation(int n, vector<int> &
    factoradix){
    st.clear(); for(int i=1;i<=n;++i) st.ins(i);
    int cl = 0;
    while((int)factoradix.size() < n){
        factoradix.pb(0); ++cl;
    }

    vector<int> res;
    for(int i=(int)factoradix.size()-1;i>=0;--i){
        auto it = st.find_by_order(factoradix[i]);
        res.pb(*it);
        st.erase(it);
    }

    while(cl-->0) factoradix.pop_back();

    return res;
}
```

```
vector<int> permutation_to_factoradix(int n, vector<int> &
    permutation){
    st.clear(); for(int i=1;i<=n;++i) st.ins(i);
    vector<int> res;
    for(int i=0;i<(int)permutation.size();++i){
        int cnt = st.order_of_key(permutation[i]);
        res.pb(cnt);
        auto it = st.find_by_order(cnt); st.erase(it);
    }
    reverse(all(res));
    while(!res.empty() and res.back() == 0)res.pop_back();

    return res;
}

vector<int> decimal_to_factoradix(ll n){
    vector<int> res;
    int d = 1;
    while(n > 0){
        res.pb(n % d);
        n/=d; ++d;
    }
    return res;
}

ll factoradix_to_decimal(vector<int> &cur){
    ll res = 0;
    ll d = 1;
    for(int i=0;i<(int)cur.size();++i){
        res += d*cur[i];
        d*=(i+1);
    }
    return res;
}
```

div-ceil-floor.h

Description: to stop c++ fucked up negative case of ceil, floor

2834e8, 9 lines

```
long long div_floor(__int128 a, long long b){
    __int128 q = a / b;
    __int128 r = a % b;
    if (r != 0 && ((a < 0) != (b < 0))) --q;
    return (long long)q;
}

long long div_ceil(__int128 a, long long b){
    return -div_floor(-a, b);
}
```

sieve.h

Description: construct is O(sqrt(n)), can use to find all prime factor of a number in O(log n)

b28bf2, 10 lines

```
vector<bool> is_prime(M+1, true);
void sieve(){
    is_prime[0] = is_prime[1] = false;
    for (int i = 2; i <= M; i++) {
        if (is_prime[i]) {
            for (ll j = (ll)i * i; j <= M; j += i)
                is_prime[j] = false;
        }
    }
}
```

linear-sieve.h

Description: lp[i] = minimum prime that divide i

8c3e32, 17 lines

```
vector<int> lp(N+1);
vector<int> pr;

void sieve(){
    for (int i=2; i <= N; ++i) {
        if (lp[i] == 0) {
            lp[i] = i;
            pr.push_back(i);
        }
        for (int j = 0; i * pr[j] <= N; ++j) {
            lp[i * pr[j]] = pr[j];
            if (pr[j] == lp[i]) {
                break;
            }
        }
    }
}
```

phi-sieve.h

b11905, 13 lines

```
vector<int> phi(M+1);

void phi_1_to_n() {
    for (int i = 0; i <= M; i++)
        phi[i] = i;

    for (int i = 2; i <= M; i++) {
        if (phi[i] == i) {
            for (int j = i; j <= M; j += i)
                phi[j] -= phi[j] / i;
        }
    }
}
```

phi-function.h

fb8d57, 13 lines

```
int phi(int n) {
    int result = n;
    for (int i = 2; i * i <= n; i++) {
```

```
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            result -= result / i;
        }
    }
    if (n > 1)
        result -= result / n;
    return result;
}
```

mobius-function.h

c6a8f4, 10 lines

```
int mob[N+1];
void mobius() {
    mob[1] = 1;
    for (int i = 2; i <= N; i++){
        mob[i]--;
        for (int j = i + i; j <= N; j += i) {
            mob[j] -= mob[i];
        }
    }
}
```

miller-rabin.h

Description: randomize primality test $O(\log n^{**2})$ b45121, 52 lines

```
using u64 = uint64_t;
using u128 = __uint128_t;

u64 bigmod(u64 base, u64 e, u64 mod){
    u64 result = 1;
    base %= mod;
    while(e){
        if(e & 1)
            result = (u128)result * base % mod;
        base = (u128)base * base % mod;
        e >>= 1;
    }
    return result;
}
```

```
bool check_composite(u64 n, u64 a, u64 d, int s){
    u64 x = bigmod(a, d, n);
    if(x == 1 || x == n - 1)
        return false;
    for(int r = 1; r < s; r++){
        x = (u128)x * x % n;
        if(x == n - 1)
            return false;
    }
    return true;
}
```

```
//random number generator
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
count());
long long rnd(long long x, long long y) {
    return uniform_int_distribution<long long>(x, y)(rng);
}
```

```
// return true if n is probably prime, else return false.
bool MillerRabin(u64 n, int iter=5){
    if(n < 4){
        return n == 2 || n == 3;
    }
    int s = 0;
    u64 d = n-1;
    while((d & 1) == 0){
```

```
        d >>= 1;
        s++;
    }

    for(int i = 0; i < iter; i++){
        long long a = rnd(2, n-2);
        if(check_composite(n, a, d, s))
            return false;
    }
    return true;
}
```

pollard-rho.h

Description: randomize factorization in $O(n^{**1/4} * \log n)$ d08505, 22 lines

```
#define uid(a, b) uniform_int_distribution<long long>(a, b)(rng
)
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
count());

long long mult(long long a, long long b, long long mod) {
    return (__int128)a * b % mod;
}

long long f(long long x, long long c, long long mod) {
    return (mult(x, x, mod) + c) % mod;
}

long long rho(long long n, long long x0=2, long long c=1) {
    long long x = x0, y = x0, g = 1;
    while (g == 1) {
        x = f(x, c, n);
        y = f(f(y, c, n), c, n);
        g = __gcd(abs(x - y), n);
    }

    if(g == n) return rho(n, uid(2, n-1), uid(-2, 2)); //uid is
uniform long
    else return g;
}
```

discrete-log.h

Description: Returns minimum x for which $a^{**x} === b \pmod m$ 17650d, 32 lines

```
int solve(int a, int b, int m) {
    a %= m, b %= m;
    int k = 1, add = 0, g;
    while ((g = __gcd(a, m)) > 1) {
        if (b == k)
            return add;
        if (b % g)
            return -1;
        b /= g, m /= g, ++add;
        k = (k * 111 * a / g) % m;
    }

    int n = sqrt(m) + 1;
    int an = 1;
    for (int i = 0; i < n; ++i)
        an = (an * 111 * a) % m;

    map<int, int> vals;
    for (int q = 0, cur = b; q <= n; ++q) {
        vals[cur] = q;
        cur = (cur * 111 * a) % m;
    }

    for (int p = 1, cur = k; p <= n; ++p) {
        cur = (cur * 111 * an) % m;
```

```
        if (vals.count(cur)) {
            int ans = n * p - vals[cur] + add;
            return ans;
        }
    }
    return -1;
}
```

primitive-root.h

Description: The following code assumes that the modulo p is a prime number. To make it works for any value of p, we must add calculation of phi(p) c6d472, 30 lines

```
int powmod (int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int (res * 111 * a % p), --b;
        else
            a = int (a * 111 * a % p), b >>= 1;
    return res;
}

int generator (int p) {
    vector<int> fact;
    int phi = p-1, n = phi; // cal phi p by assuming it's
prime
    for (int i=2; i*i<=n; ++i)
        if (n % i == 0) {
            fact.push_back (i);
            while (n % i == 0)
                n /= i;
        }
    if (n > 1)
        fact.push_back (n);

    for (int res=2; res<=p; ++res) {
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod (res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}
```

diophantine.h

4fcad2, 89 lines

```
ll gcd(ll a, ll b, ll& x, ll& y) { //gcd extended
    if (b == 0) {
        x = 1;
        y = 0;
        return a;
    }
    ll x1, y1;
    ll d = gcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
    return d;
}

bool find_any_solution(ll a, ll b, ll c, ll &x0, ll &y0, ll &g)
{
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) {
        return false;
    }

    x0 *= c / g;
    y0 *= c / g;
```

```

    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}

void shift_solution(ll & x, ll & y, ll a, ll b, ll cnt) { //
    make sure that a,b coprime
    x += cnt * b;
    y -= cnt * a;
}

ll find_all_solutions(ll a, ll b, ll c, ll minx, ll maxx, ll
    miny, ll maxy) {
    ll x, y, g;
    if (!find_any_solution(a, b, c, x, y, g))
        return 0;
    a /= g;
    b /= g;

    ll sign_a = a > 0 ? +1 : -1;
    ll sign_b = b > 0 ? +1 : -1;

    shift_solution(x, y, a, b, (minx - x) / b);
    if (x < minx)
        shift_solution(x, y, a, b, sign_b);
    if (x > maxx)
        return 0;
    ll lx1 = x;

    shift_solution(x, y, a, b, (maxx - x) / b);
    if (x > maxx)
        shift_solution(x, y, a, b, -sign_b);
    ll rx1 = x;

    shift_solution(x, y, a, b, -(miny - y) / a);
    if (y < miny)
        shift_solution(x, y, a, b, -sign_a);
    if (y > maxy)
        return 0;
    ll lx2 = x;

    shift_solution(x, y, a, b, -(maxy - y) / a);
    if (y > maxy)
        shift_solution(x, y, a, b, sign_a);
    ll rx2 = x;

    if (lx2 > rx2)
        swap(lx2, rx2);

    ll lx = max(lx1, lx2);
    ll rx = min(rx1, rx2);
    if (lx > rx)
        return 0;

    return (rx - lx) / abs(b) + 1;
}

//number of solution of ax + by = c in general
ll number_of_solution(ll a, ll b, ll c, ll x1, ll x2, ll y1, ll
    y2){
    if(a == 0 and b == 0 and c == 0) return (x2-x1+1)*(y2-y1+1);
    else if(a == 0 and b == 0) return 0;
    else if(a == 0){
        if(c%b!=0 or y1>c/b or y2<c/b) return 0;
        else return (x2-x1+1);
    } else if(b == 0){
        if(c%a!=0 or x1>c/a or x2<c/a) return 0;
        else return (y2-y1+1);
    } else {
        return find_all_solutions(a, b, c, x1, x2, y1, y2);
    }
}

```

```

    }
}

crt.h
class CRT { // ChineseRemainderTheorem
    typedef long long vlong;
    typedef pair<vlong,vlong> pll;
    vector<pll> equations;

public:
    void clear() {
        equations.clear();
    }
    void addEquation( vlong r, vlong m ) {
        equations.push_back({r, m});
    }

    void ext_gcd(vlong a, vlong b, vlong& x, vlong& y) {
        if (b == 0) {
            x = 1;
            y = 0;
            return;
        }
        vlong x1, y1;
        ext_gcd(b, a % b, x1, y1);
        x = y1;
        y = x1 - y1 * (a / b);
    }

    pll solve() {
        if (equations.size() == 0) return {-1,-1};

        vlong a1 = equations[0].first;
        vlong m1 = equations[0].second;
        a1 %= m1;
        for ( int i = 1; i < (int)equations.size(); i++ ) {
            vlong a2 = equations[i].first;
            vlong m2 = equations[i].second;

            vlong g = __gcd(m1, m2);
            if ( a1 % g != a2 % g ) return {-1,-1};
            vlong p, q;
            ext_gcd(m1/g, m2/g, p, q);

            vlong mod = m1 / g * m2;
            p = (p%mod+mod)%mod, q = (q%mod+mod)%mod;
            vlong x = ( (__int128)a1 * (m2/g) % mod * q % mod +
                (__int128)a2 * (m1/g) % mod * p % mod ) % mod;
            a1 = x;
            if ( a1 < 0 ) a1 += mod;
            m1 = mod;
        }
        return {a1, m1};
    }
};

```

2.3 General Data Structures & Algorithms

```

order-statistics-tree.h
<ext/pb_ds/assoc.container.hpp>
using namespace __gnu_pbds;
template <typename T>
using ordered_set =
    tree<T, null_type, less<T>, rb_tree_tag,
        tree_order_statistics_node_update>;
ordered_set<int> st;

```

```

//st.order_of_key(x) - find # of elements in st stricly less
    than x, i.e. index of x
//st.size() - size of st
//st.find_by_order(x) - return iterator point to xth indexed
    element
//st.clear() - clear container

```

fenwick-tree.h

```

Description: use 1 base indexing
vector<long long>bit;

void add(int i, int k){
    while(i<(int)bit.size()){
        bit[i]+=k;
        i+=i&-i;
    }
}

ll F(int i){
    ll sum=0;
    while(i>0){
        sum+=bit[i];
        i-=i&-i;
    }
    return sum;
}

void build_bit(vl &a){
    bit=a;
    for(int i=1;i<(int)bit.size();++i){
        int p=i+(i&-i);//index to parent
        if(p<(int)bit.size())bit[p]+=bit[i];
    }
}

```

dsu.h

```

Description: O(n) amortized by inverse ackerman function
int parent[N], _rank[N];

int find_set(int v) {
    if (v == parent[v])
        return v;
    return parent[v] = find_set(parent[v]);
}

void make_set(int v) {
    parent[v] = v;
    _rank[v] = 1;
}

void union_sets(int a, int b) {
    a = find_set(a);
    b = find_set(b);
    if (a != b) {
        if (_rank[a] < _rank[b])
            swap(a, b);
        parent[b] = a;
        _rank[a] += _rank[b];
    }
}

```

dijkstra.h

```

Description: 0/1 bfs can be done using deque
//initialize dist, proc
for (int i = 1; i <= m; i++) dist[i] = INF;
dist[x] = 0;

```

```
priority_queue<pair<ll, int>>q;
q.push({0,x});
while (!q.empty()) {
    int a = q.top().second; q.pop();
    if (proc[a]) continue;
    proc[a] = true;
    for (auto u : adj[a]) {
        int b = u.first, w = u.second;
        if (dist[a]+w < dist[b]) {
            dist[b] = dist[a]+w;
            q.push({-dist[b],b});
        }
    }
}
```

floyd-warshall-stp.h

Description: before k-th phase d[i][j] = stp len from i to j using only vertices from set 1,2,...k-1 as internal path, the beginning and end of path are not restricted by this property.

```
ab1def, 10 lines
//don't forget to initialize the base case of weight
//this work for negative weight without negative cycle
for (int k = 0; k < n; ++k) {
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < n; ++j) {
            if (d[i][k] < INF && d[k][j] < INF)
                d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
        }
    }
}
```

digit-dp-example.h

```
d01123, 31 lines
ll dp[20][11][2][2];
vector<int> num;

ll construct(int pos, int d, int flag, bool isStarted){
    if(pos == (int)num.size()){
        //return isStarted;
        return 1;
    }

    if(dp[pos][d][flag][isStarted] != -1)return dp[pos][d][flag][isStarted];

    int LMT;
    if(flag == 0){
        LMT = num[pos];
    } else {
        LMT = 9;
    }

    //placing current digits
    ll res = 0;
    for(int i=0;i<=LMT;++i){
        if((i == 0 and isStarted and i == d) or (i != 0 and i == d))continue;
        //by the condition adjacent digits must not be the same
        int nflag = flag;
        if(i < LMT and flag == 0)nflag = 1;

        res += construct(pos+1, i, nflag, (isStarted or i>0));
    }

    return dp[pos][d][flag][isStarted] = res;
}
```

LIS-example.h

Description: this can also be use to find minimum partition on posit by finding maximum anti-chain

```
<algorithm>, <iostream>, <vector> 9406b2, 24 lines
using namespace std;

int main() {
    int n;
    cin >> n;
    vector<int> x(n);
    for (int i = 0; i < n; ++i) cin >> x[i];

    vector<int> best(n + 1);
    best[0] = 0;
    int result = 0;
    for (int i = 0; i < n; ++i) {
        int len = lower_bound(best.begin(), best.begin() + result + 1, x[i]) - best.begin();
        if (len > result) {
            result = len;
            best[len] = x[i];
        } else {
            best[len] = min(best[len], x[i]);
        }
    }

    cout << result << endl;
}
```

lca.h

Description: I can implement simpler one than this, also don't forget to initialize adj

```
0ae36f, 35 lines
const int LOG = 20;
int dep[N], parent[N];
int up[N][LOG]; // 2^j-th ancestor of n

void dfs(int a,int e){
    for(auto b:adj[a]){
        if(b == e)continue;
        dep[b] = dep[a] + 1;
        parent[b] = a;
        up[b][0] = parent[b];
        for(int i=1;i<LOG;++i){
            up[b][i] = up[parent[b][i-1]][i-1];
        }
        dfs(b,a);
    }
}

int lca(int a, int b){
    if(dep[a]<dep[b])swap(a,b);
    int k = dep[a] - dep[b];
    for(int i=LOG-1;i>=0;--i){
        if(k & (1<<i)){
            a = up[a][i];
        }
    }

    if(a == b)return a;
    for(int i=LOG-1;i>=0;--i){
        if(up[a][i] != up[b][i]){
            a = up[a][i];
            b = up[b][i];
        }
    }

    return up[a][0];
}
```

kth-ancestor.h

```
3b29e6, 9 lines
int kth_ancestor(int node,int k){
    if(dep[node] < k)return -1;
    for(int i = 0;i < LOG; ++i){
        if(k & (1<<i)){
            node = up[node][i];
        }
    }
    return node;
}
```

tree-hashing.h

Description: very acurate rooted tree hashing(I don't know how), don't forget to check tree invariant such as tree size and numbers of centroid

```
ce088b, 18 lines
map<vector<int>, int> hasher;

int hashify(vector<int> x) {
    sort(x.begin(), x.end());
    if(!hasher[x]) {
        hasher[x] = hasher.size();
    }
    return hasher[x];
}

int _hash(int v, int e, vector<vector<int>>&adj) { // get a "hash" of v's subtree, e is parent vertex
    vector<int> children;
    for(int u: adj[v]) {
        if( u == e )continue;
        children.push_back(_hash(u, v, adj));
    }
    return hashify(children);
}
```

prim-mst.h

Description: unlike kruskal, prim's algorithm assume all vertices belong in same graph

```
a70ceb, 23 lines
vector<pair<int,int>>adj[N+1];
bool taken[N+1];
priority_queue<pair<int,int>>PQ;

void process(int v){
    taken[v]=1;
    for(auto&p:adj[v]){
        int b=p.second, w=p.first;
        if(!taken[b])PQ.push({-w,-b});
    }
}

ll mst(){
    process(1);
    ll mst_cost=0;
    while(!PQ.empty()){
        pair<int,int> front=PQ.top(); PQ.pop();
        int u=-front.second, w=-front.first;
        if(!taken[u])
            mst_cost+=w, process(u);
    }
    return mst_cost;
}
```

superset-and-subset-iteration.h

Description: both work in O(3**n)

```
204064, 12 lines
for (int s = 0; s < (1<<n); s++) {
    for (int t = s; t < (1<<n); t = (t+1)|s) {
        // t is a superset of s
    }
}
```

```
    }
}

for (int s = 0; s < (1<<n); s++) {
    for (int t = s; ; t = (t-1)&s) {
        // t is a subset of s
        if (t == 0) break;
    }
}
```

gp-hash-table.h

<ext/pb_ds/assoc.container.hpp>3b295b, 7 lines

```
using namespace __gnu_pbds;

const int RANDOM = chrono::high_resolution_clock::now().
    time_since_epoch().count();
struct chash {
    int operator() (int x) const { return x ^ RANDOM; }
};
gp_hash_table<int, int, chash> table;
```

segment-tree-lazy-propagation.h

Description: monoid combiner function740cd4, 59 lines

```
vector<long long> tree,lazy;
void update(int node,int n_l,int n_r,int q_l,int q_r,long long
value){
    // Push: Process and clear pending lazy tags down to
    children
    if(lazy[node]!=0){
        tree[node]+=(long long) (n_r-n_l+1)*lazy[node];
        if(n_l!=n_r){
            lazy[2*node]+=lazy[node];
            lazy[2*node+1]+=lazy[node];
        }
        lazy[node] = 0;
    }

    if(n_r<q_l || q_r<n_l)return;

    // update tree node and set lazy tags for children
    if(q_l<=n_l && n_r<=q_r){
        tree[node]+=(long long) (n_r-n_l+1)*value;
        if(n_l!=n_r){
            lazy[2*node]+=value;
            lazy[2*node+1]+=value;
        }
        return;
    }

    int mid = (n_r+n_l)/2;
    update(2*node,n_l,mid,q_l,q_r,value);
    update(2*node+1,mid+1,n_r,q_l,q_r,value);

    tree[node] = tree[2*node] + tree[2*node+1];
}

long long f(int node,int n_l,int n_r,int q_l,int q_r){
    // Push: Process and clear pending lazy tags down to
    children
    if(lazy[node]!=0){
        tree[node]+=(long long) (n_r-n_l+1)*lazy[node];
        if(n_l!=n_r){
            lazy[2*node] += lazy[node];
            lazy[2*node+1] += lazy[node];
        }
        lazy[node] = 0;
    }
}
```

```
    if(n_r<q_l || q_r<n_l)return 0;

    if(q_l<=n_l && n_r<=q_r)return tree[node];

    int mid = (n_l+n_r)/2;
    return f(2*node,n_l,mid,q_l,q_r) + f(2*node+1,mid+1,n_r,q_l
,q_r);
}

int build_tree(vi &a,int n){
    tree.clear(); lazy.clear();
    int m=n;
    while(__builtin_popcount(m)!=1)++m;
    tree.resize(2*m+10,0); lazy.resize(2*m+10,0);
    for(int i=0;i<n;++i)tree[i+m]=a[i];
    for(int i=m-1;i>=1;--i)tree[i]=tree[2*i]+tree[2*i+1];
    return m;
}
```

tarjan-scc.h

Description: we can use this to solve 2-SAT3e5381, 35 lines

```
//Tarjan's algorithm
vi adj[N+1];
int id[N+1], low[N+1];
bool vst[N+1], in_stack[N+1];

stack<int>st;
vector<vi>scc;
vi comp;
int tin=0;
void dfs(int a){
    st.push(a);
    vst[a]=in_stack[a]=1;
    id[a]=low[a]=tin++;

    for(auto&b:adj[a]){
        if(!vst[b]){
            dfs(b);
            low[a]=min(low[a],low[b]); //Backtrack low-link
            value
        } else if(in_stack[b]){
            //Backtrack low-link value
            low[a]=min(low[a],low[b]);
        }
    }
    if(id[a] == low[a]){ //pop scc
        while(!st.empty()){
            int v=st.top();
            comp.pb(v), st.pop();
            in_stack[v]=0;
            if(v==a)break; //stop when scc is found
        }
    }
    if(!comp.empty()){
        scc.pb(comp), comp.clear();
    }
}
```

bridge-finding.h

Description: this not work for multigraph, I'm too lazy too fix for now747a19, 29 lines

```
/*
    dfs-tree bridge finding algorithm
    let lvl[root] = 1 (root = 1)
*/
int root = 1;
vector<pair<int,int>> bridge;
int dp[N+1], lvl[N+1];
```

```
void dfs_tree(int a, int e){
    if(a == root)lvl[a] = 1;
    dp[a] = 0;
    for(auto &b:adj[a]){
        if(b == e)continue;

        if(lvl[b] == 0){
            lvl[b] = lvl[a] + 1;
            dfs_tree(b, a);
            dp[a] += dp[b];
        } else if(lvl[b] < lvl[a]){
            dp[a]++;
        } else if(lvl[b] > lvl[a]){
            dp[a]--;
        }

        if(lvl[a] > 1 and dp[a] == 0){
            bridge.pb({min(a,e), max(a,e)});
        }
    }
}
```

gauss-jordan-elimination.h

d847fe, 48 lines

```
const double EPS = 1e-9;
const int INF = 2; // it doesn't actually have to be infinity
or a big number

int gauss (vector < vector<double> > a, vector<double> & ans) {
    int n = (int) a.size();
    int m = (int) a[0].size() - 1;

    vector<int> where (m, -1);
    for (int col=0, row=0; col<m && row<n; ++col) {
        int sel = row;
        for (int i=row; i<n; ++i)
            if (abs (a[i][col]) > abs (a[sel][col]))
                sel = i;

        if (abs (a[sel][col]) < EPS)
            continue;

        for (int i=col; i<=m; ++i)
            swap (a[sel][i], a[row][i]);
        where[col] = row;

        for (int i=0; i<n; ++i)
            if (i != row) {
                double c = a[i][col] / a[row][col];
                for (int j=col; j<=m; ++j)
                    a[i][j] -= a[row][j] * c;
            }
        ++row;
    }

    ans.assign (m, 0);
    for (int i=0; i<m; ++i)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];

    for (int i=0; i<n; ++i) {
        double sum = 0;
        for (int j=0; j<m; ++j)
            sum += ans[j] * a[i][j];
        if (abs (sum - a[i][m]) > EPS)
            return 0; // contradiction means no solution
    }
}
```

```
for (int i=0; i<m; ++i)
    if (where[i] == -1)
        return INF; //infinite solution
return 1; //unique solution
}
```

2.4 General Data Structures & Algorithms

aho-corasick-automaton.h
Description: trie structure can be infer from this
a41621, 53 lines

```
const int K = 26;

struct Vertex {
    int next[K];
    bool output = false;
    int p = -1;
    char pch;
    int link = -1;
    int go[K];

    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};

vector<Vertex> t(1);

void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = t.size();
            t.emplace_back(v, ch);
        }
        v = t[v].next[c];
    }
    t[v].output = true;
}

int go(int v, char ch);

int get_link(int v) {
    if (t[v].link == -1) {
        if (v == 0 || t[v].p == 0)
            t[v].link = 0;
        else
            t[v].link = go(get_link(t[v].p), t[v].pch);
    }
    return t[v].link;
}

int go(int v, char ch) {
    int c = ch - 'a';
    if (t[v].go[c] == -1) {
        if (t[v].next[c] != -1)
            t[v].go[c] = t[v].next[c];
        else
            t[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
    }
    return t[v].go[c];
}
```

string-hashing.h

ba27df, 17 lines

```
typedef __int128 HASH;
HASH p[NN], h[NN];
constexpr HASH M = 1000000000000000003;
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
#define uid(a, b) uniform_int_distribution<long long>(a, b)(rng)

void compute_hash(string const& s){
    p[0] = 1, p[1] = uid(256, M-1);
    for(ll i=0;i<(int)s.length();++i){
        p[i+1] = p[i]*p[1]%M;
        h[i+1] = (h[i]*p[1] + s[i])%M;
    }
}

HASH sub_hash(ll l, ll r){ //range half-open [l, r)
    return (h[r] - p[r-l]*h[l]%M + M)%M;
}
```

suffix-automaton.h
Description: I vaguely remember how to use this
fe30a6, 52 lines

```
struct state {
    int len, link;
    map<char, int> next;
    map<char, int> go;
};

const int MAXLEN = 100001; //this one is 10^5 becareful
state st[MAXLEN * 2];
int sz, last;

void sa_init() {
    st[0].len = 0;
    st[0].link = -1;
    sz++;
    last = 0;
}

void sa_extend(char c) {
    int cur = sz++;
    st[cur].len = st[last].len + 1;
    int p = last;
    while (p != -1 && !st[p].next.count(c)) {
        st[p].next[c] = cur;
        p = st[p].link;
    }
    if (p == -1) {
        st[cur].link = 0;
    } else {
        int q = st[p].next[c];
        if (st[p].len + 1 == st[q].len) {
            st[cur].link = q;
        } else {
            int clone = sz++;
            st[clone].len = st[p].len + 1;
            st[clone].next = st[q].next;
            st[clone].link = st[q].link;
            while (p != -1 && st[p].next[c] == q) {
                st[p].next[c] = clone;
                p = st[p].link;
            }
            st[q].link = st[cur].link = clone;
        }
    }
    last = cur;
}
```

```
int sa_go(int v, char c) {
    if (st[v].go.count(c)) return st[v].go[c];
    if (st[v].next.count(c)) return st[v].go[c] = st[v].next[c];
    if (st[v].link == -1) return st[v].go[c] = 0; // fallback to root
    return st[v].go[c] = sa_go(st[v].link, c);
}
```

kmp.h
Description: we only need prefix function, pi[i] is the length of the longest proper prefix of the substring s[0...i] which is also a suffix of this substring, suffix link can be infer from this.
4dfee5, 37 lines

```
int b[N];
int cnt = 0;

void knp_proc(string t,string p){
    int i=0,j=-1;b[0] = -1;
    while(i<(int)p.length()){
        while(j>=0 && p[i]!=p[j]) j =b[j];
        ++i;++j;
        b[i] = j;
    }
}

void knp_search(string t,string p){//count number of occurence of p in t
    int i=0,j=0;
    while(i<(int)t.length()){
        while(j>=0 && t[i] != p[j]) j = b[j];
        ++i;++j;
        if(j==(int)p.length()){
            ++cnt;
            j = b[j];
        }
    }
}

vector<int> prefix_function(string s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}
```

z-function.h
Description: Description: z[i] is the length of the longest common prefix between s and the suffix of s starting at i.
9a2512, 18 lines

```
vector<int> z_function(string s) {
    int n = s.size();
    vector<int> z(n);
    int l = 0, r = 0;
    for(int i = 1; i < n; i++) {
        if(i < r) {
            z[i] = min(r - i, z[i - l]);
        }
        while(i + z[i] < n && s[z[i]] == s[i + z[i]]) {
            z[i]++;
        }
    }
}
```



```
        if(i + z[i] > r) {
            l = i;
            r = i + z[i];
        }
    }
    return z;
}
```

manacher.h

3069fe, 38 lines

```
//sub-palindrome queries
vector<int> manacher_odd(string s) {
    int n = s.size();
    s = "$" + s + "^";
    vector<int> p(n + 2);
    int l = 1, r = 1;
    for(int i = 1; i <= n; i++) {
        p[i] = max(0, min(r - i, p[l + (r - i)]));
        while(s[i - p[i]] == s[i + p[i]]) {
            p[i]++;
        }
        if(i + p[i] > r) {
            l = i - p[i], r = i + p[i];
        }
    }
    return vector<int>(begin(p) + 1, end(p) - 1);
}

vector<int> manacher(string s) {
    string t;
    for(auto c: s) {
        t += string("#") + c;
    }
    auto res = manacher_odd(t + "#");
    return vector<int>(begin(res) + 1, end(res) - 1);
}

//beware the range is inclusive and therefore not half-open ->
[l, r]
bool is_palindrome(int l, int r, vector<int> &v){
    if(v[l + r] < (r - l + 1))return false;
    return true;
}

}
```

```
vector<int> build_manacher(string s){ //0 base index string
    auto v = manacher(s);
    for(auto&x:v)--x;
    return v;
}
```

suffix-array.h

Description: I don't fucking know how to use this

4ca004, 53 lines

```
vector<int> sort_cyclic_shifts(string const& s) {
    int n = s.size();
    const int alphabet = 256;

    vector<int> p(n), c(n), cnt(max(alphabet, n), 0);
    for (int i = 0; i < n; i++)
        cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (int i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    int classes = 1;
    for (int i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])
            classes++;
    }
```

```
        c[p[i]] = classes - 1;
    }

    vector<int> pn(n), cn(n);
    for (int h = 0; (1 << h) < n; ++h) {
        for (int i = 0; i < n; i++) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0)
                pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (int i = 0; i < n; i++)
            cnt[c[pn[i]]]++;
        for (int i = 1; i < classes; i++)
            cnt[i] += cnt[i-1];
        for (int i = n-1; i >= 0; i--)
            p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0;
        classes = 1;
        for (int i = 1; i < n; i++) {
            pair<int, int> cur = {c[p[i]], c[(p[i] + (1 << h))
                % n]};
            pair<int, int> prev = {c[p[i-1]], c[(p[i-1] + (1 <<
                h)) % n]};
            if (cur != prev)
                ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}

vector<int> suffix_array_construction(string s) {
    s += "$";
    vector<int> sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}
```

lyndon-factorization.h

Description: hope that we may never need this

a3cc8c, 40 lines

```
vector<string> duval(string const& s) {
    int n = s.size();
    int i = 0;
    vector<string> factorization;
    while (i < n) {
        int j = i + 1, k = i;
        while (j < n && s[k] <= s[j]) {
            if (s[k] < s[j])
                k = i;
            else
                k++;
            j++;
        }
        while (i <= k) {
            factorization.push_back(s.substr(i, j - k));
            i += j - k;
        }
    }
    return factorization;
}
```

```
string min_cyclic_string(string s) {
    s += s;
    int n = s.size();
    int i = 0, ans = 0;
    while (i < n / 2) {
```

```
        ans = i;
        int j = i + 1, k = i;
        while (j < n && s[k] <= s[j]) {
            if (s[k] < s[j])
                k = i;
            else
                k++;
            j++;
        }
        while (i <= k)
            i += j - k;
    }
    return s.substr(ans, n / 2);
}
```

2.5 Geometry

geometry.h

963fd3, 167 lines

```
//Geometry
#pragma GCC target("avx2")
#pragma GCC optimize("O3")
#pragma GCC optimize("unroll-loops")

typedef long long int ll;
typedef long double ld;
typedef complex<ld> pt;
struct line {
    pt P, D; bool S = false;
    line(pt p, pt q, bool b = false) : P(p), D(q - p), S(b) {}
    line(pt p, ld th) : P(p), D(polar((ld)1, th)) {}
};
struct circ { pt C; ld R; };

#define X real()
#define Y imag()
#define CRS(a, b) (conj(a) * (b)).Y //scalar cross product
#define DOT(a, b) (conj(a) * (b)).X //dot product
#define U(p) ((p) / abs(p)) //unit vector in direction of p (
    don't use if Z(p) == true)
#define Z(x) (abs(x) < EPS)
#define A(a) (a).begin(), (a).end() //shortens sort(),
    upper_bound(), etc. for vectors
```

```
//constants (INF and EPS may need to be modified)
ld PI = acos(-1), INF = 1e20, EPS = 1e-12;
pt I = {0, 1};
```

```
//true if d1 and d2 parallel (zero vectors considered parallel
to everything)
bool parallel(pt d1, pt d2) { return Z(d1) || Z(d2) || Z(CRS(U(
d1), U(d2))); }
```

```
/"above" here means if l & p are rotated such that l.D points
in the +x direction, then p is above l. Returns arbitrary
boolean if p is on l
bool above_line(pt p, line l) { return CRS(p - l.P, l.D) > 0; }
```

```
//true if p is on line l
bool on_line(pt p, line l) { return parallel(l.P - p, l.D) &&
    (l.S || DOT(l.P - p, l.P + l.D - p) <= EPS); }
```

```
//returns 0 for no intersection, 2 for infinite intersections,
1 otherwise. p holds intersection pt
ll intscct(line l1, line l2, pt& p) {
    if(parallel(l1.D, l2.D)) //note that two parallel segments
        sharing one endpoint are considered to have infinite
        intersections here
        return 2 * (on_line(l1.P, l2) || on_line(l1.P + l1.D, l2)
            || on_line(l2.P, l1) || on_line(l2.P + l2.D, l1));
```

```

    pt q = l1.P + l1.D * CRS(l2.D, l2.P - l1.P) / CRS(l2.D, l1.D)
    ;
    if(on_line(q, l1) && on_line(q, l2)) { p = q; return 1; }
    return 0;
}

//closest pt on l to p
pt cl_pt_on_l(pt p, line l) {
    pt q = l.P + DOT(U(l.D), p - l.P) * U(l.D);
    if(on_line(q, l)) return q;
    return abs(p - l.P) < abs(p - l.P - l.D) ? l.P : l.P + l.D;
}

//distance from p to l
ld dist_to(pt p, line l) { return abs(p - cl_pt_on_l(p, l)); }

//p reflected over l
pt refl_pt(pt p, line l) { return conj((p - l.P) / U(l.D)) * U(l.D) + l.P; }

//ray r reflected off l (if no intersection, returns original ray)
line reflect_line(line r, line l) {
    pt p; if(intsct(r, l, p) - 1) return r;
    return line(p, p + INF * (p - refl_pt(r.P, l)), 1);
}

//altitude from p to l
line alt(pt p, line l) { l.S = 0; return line(p, cl_pt_on_l(p, l)); }

//angle bisector of angle abc
line ang_bis(pt a, pt b, pt c) { return line(b, b + INF * (U(a - b) + U(c - b)), 1); }

//perpendicular bisector of l (assumes l.S == 1)
line perp_bis(line l) { return line(l.P + l.D / (ld)2, arg(l.D * I)); }

//orthocenter of triangle abc
pt orthocent(pt a, pt b, pt c) { pt p; intsct(alt(a, line(b, c)), alt(b, line(a, c)), p); return p; }

//incircle of triangle abc
circ incirc(pt a, pt b, pt c) {
    pt cent; intsct(ang_bis(a, b, c), ang_bis(b, a, c), cent);
    return {cent, dist_to(cent, line(a, b))};
}

//circumcircle of triangle abc
circ circumcirc(pt a, pt b, pt c) {
    pt cent; intsct(perp_bis(line(a, b, 1)), perp_bis(line(a, c, 1)), cent);
    return {cent, abs(cent - a)};
}

//is pt p inside the (not necessarily convex) polygon given by poly
bool in_poly(pt p, vector<pt>& poly) {
    line l = line(p, {INF, INF * PI}, 1);
    bool ans = false;
    pt lst = poly.back(); tmp;
    for(pt q : poly) {
        line s = line(q, lst, 1); lst = q;
        if(on_line(p, s)) return false; //change if border included
        else if(intsct(l, s, tmp)) ans = !ans;
    }
    return ans;
}

```

```

//area of polygon, vertices in order (cw or ccw)
ld area(vector<pt>& poly) {
    ld ans = 0;
    pt lst = poly.back();
    for(pt p : poly) ans += CRS(lst, p), lst = p;
    return abs(ans / 2);
}

//perimeter of polygon, vertices in order (cw or ccw)
ld perim(vector<pt>& poly) {
    ld ans = 0;
    pt lst = poly.back();
    for(pt p : poly) ans += abs(lst - p), lst = p;
    return ans;
}

//centroid of polygon, vertices in order (cw or ccw)
pt centroid(vector<pt>& poly) {
    ld area = 0;
    pt lst = poly.back(), ans = {0, 0};
    for(pt p : poly) {
        area += CRS(lst, p);
        ans += CRS(lst, p) * (lst + p) / (ld)3;
        lst = p;
    }
    return ans / area;
}

//invert a point over a circle (doesn't work for center of circle)
pt circInv(pt p, circ c) {
    return c.R * c.R / conj(p - c.C) + c.C;
}

//vector of intersection pts of two circls (up to 2) (if circles same, returns empty vector)
vector<pt> intsctCC(circ c1, circ c2) {
    if(c1.R < c2.R) swap(c1, c2);
    pt d = c2.C - c1.C;
    if(Z(abs(d) - c1.R - c2.R)) return {c1.C + polar(c1.R, arg(c2.C - c1.C))};
    if(!Z(d) && Z(abs(d) - c1.R + c2.R)) return {c1.C + c1.R * U(d)};
    if(abs(abs(d) - c1.R) >= c2.R - EPS) return {};
    ld th = acosl((c1.R * c1.R + norm(d) - c2.R * c2.R) / (2 * c1.R * abs(d)));
    return {c1.C + polar(c1.R, arg(d) + th), c1.C + polar(c1.R, arg(d) - th)};
}

//vector of intersection pts of a line and a circ (up to 2)
vector<pt> intsctCL(circ c, line l) {
    vector<pt> v, ans;
    if(parallel(l.D, c.C - l.P)) v = {c.C + c.R * U(l.D), c.C - c.R * U(l.D)};
    else v = intsctCC(c, circ(refl_pt(c.C, l), c.R));
    for(pt p : v) if(on_line(p, l)) ans.push_back(p);
    return ans;
}

//external tangents of two circles (negate c2.R for internal tangents)
vector<line> circTangents(circ c1, circ c2) {
    pt d = c2.C - c1.C;
    ld dr = c1.R - c2.R, d2 = norm(d), h2 = d2 - dr * dr;
    if(Z(d2) || h2 < 0) return {};
    vector<line> ans;
    for(ld sg : {-1, 1}) {

```

```

        pt u = (d * dr + d * I * sqrt(h2) * sg) / d2;
        ans.push_back(line(c1.C + u * c1.R, c2.C + u * c2.R, 1));
    }
    if(Z(h2)) ans.pop_back();
    return ans;
}

```

closest-pair-of-points.h

85eeeb, 67 lines

```

struct pt {
    int x, y, id;
};

struct cmp_x {
    bool operator()(const pt & a, const pt & b) const {
        return a.x < b.x || (a.x == b.x && a.y < b.y);
    }
};

struct cmp_y {
    bool operator()(const pt & a, const pt & b) const {
        return a.y < b.y;
    }
};

int n;
vector<pt> a;

double mindist;
pair<int, int> best_pair;

void upd_ans(const pt & a, const pt & b) {
    double dist = sqrt((a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y));
    if (dist < mindist) {
        mindist = dist;
        best_pair = {a.id, b.id};
    }
}

vector<pt> t;

void rec(int l, int r) {
    if (r - l <= 3) {
        for (int i = l; i < r; ++i) {
            for (int j = i + 1; j < r; ++j) {
                upd_ans(a[i], a[j]);
            }
        }
        sort(a.begin() + l, a.begin() + r, cmp_y());
        return;
    }

    int m = (l + r) >> 1;
    int midx = a[m].x;
    rec(l, m);
    rec(m, r);

    merge(a.begin() + l, a.begin() + m, a.begin() + m, a.begin() + r, t.begin(), cmp_y());
    copy(t.begin(), t.begin() + r - l, a.begin() + l);

    int tsz = 0;
    for (int i = l; i < r; ++i) {
        if (abs(a[i].x - midx) < mindist) {
            for (int j = tsz - 1; j >= 0 && a[i].y - t[j].y < mindist; --j)
                upd_ans(a[i], t[j]);
            t[tsz++] = a[i];

```

```
        }
    }
}

void call_rec(){
    t.resize(n);
    sort(a.begin(), a.end(), cmp_x());
    mindist = 1E20;
    rec(0, n);
}
```

2.6 Advanced Algorithms

fft.h
Description: from cp algorithm the inplace-computation fft part
cbf4b6, 62 lines

```
using cd = complex<double>;
const double PI = acos(-1);

int reverse(int num, int lg_n) {
    int res = 0;
    for (int i = 0; i < lg_n; i++) {
        if (num & (1 << i))
            res |= 1 << (lg_n - 1 - i);
    }
    return res;
}

void fft(vector<cd> & a, bool invert) {
    int n = a.size();
    int lg_n = 0;
    while ((1 << lg_n) < n)
        lg_n++;

    for (int i = 0; i < n; i++) {
        if (i < reverse(i, lg_n))
            swap(a[i], a[reverse(i, lg_n)]);
    }

    for (int len = 2; len <= n; len <= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            cd w(1);
            for (int j = 0; j < len / 2; j++) {
                cd u = a[i+j], v = a[i+j+len/2] * w;
                a[i+j] = u + v;
                a[i+j+len/2] = u - v;
                w *= wlen;
            }
        }
    }

    if (invert) {
        for (cd & x : a)
            x /= n;
    }
}

vector<int> multiply(vector<int> const& a, vector<int> const& b) {
    vector<cd> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    int n = 1;
    while (n < ((int)a.size() + (int)b.size())
           n <= 1;
    fa.resize(n);
    fb.resize(n);

    fft(fa, false);
    fft(fb, false);
```

```
    for (int i = 0; i < n; i++)
        fa[i] *= fb[i];
    fft(fa, true);

    vector<int> result(n);
    for (int i = 0; i < n; i++)
        result[i] = round(fa[i].real());
    return result;
}
```

persistent-segment-tree.h
Description: Warning!This implementation is not garbage collected, so the tree nodes aren't deleted even if the instance of the segment tree is taken out of scope.
c4a26b, 37 lines

```
struct Node {
    ll val;
    Node *l, *r;

    Node(ll x) : val(x), l(nullptr), r(nullptr) {}
    Node(Node *ll, Node *rr) {
        l = ll, r = rr;
        val = 0;
        if (l) val += l->val;
        if (r) val += r->val;
    }
    Node(Node *cp) : val(cp->val), l(cp->l), r(cp->r) {}
};

int n, cnt = 1;
ll a[200001];
Node *roots[200001];

Node *build(int l = 1, int r = n) {
    if (l == r) return new Node(a[l]);
    int mid = (l + r) / 2;
    return new Node(build(l, mid), build(mid + 1, r));
}

Node *update(Node *node, int val, int pos, int l = 1, int r = n) {
    if (l == r) return new Node(val);
    int mid = (l + r) / 2;
    if (pos > mid) return new Node(node->l, update(node->r, val, pos, mid + 1, r));
    else return new Node(update(node->l, val, pos, l, mid), node->r);
}

ll query(Node *node, int a, int b, int l = 1, int r = n) {
    if (l > b || r < a) return 0;
    if (l >= a && r <= b) return node->val;
    int mid = (l + r) / 2;
    return query(node->l, a, b, l, mid) + query(node->r, a, b, mid + 1, r);
}
```

mo2D.h
9df2fb, 49 lines
/* always use zero based indexing*/
/* there N/B blocks so left move ~ N/B*B + Q*B, right move ~ N/B*B + (N/B)*B */
/* so $O(N^2/B + N + QB) \sim O((N+Q)\sqrt{N})$ when $B = \sqrt{N}$ */
/* when $Q \cdot N$ it's $\sim O(N^3/2)$ */
void remove(int idx); // TODO: remove value at idx from data structure
void add(int idx); // TODO: add value at idx from data structure

```
int get_answer(); // TODO: extract the current answer of the data structure

int block_size;

struct Query {
    int l, r, idx;
    bool operator<(Query other) const
    {
        return make_pair(l / block_size, r) <
               make_pair(other.l / block_size, other.r);
    }
};

vector<int> mo_s_algorithm(vector<Query>& queries) {
    vector<int> answers(queries.size());
    sort(queries.begin(), queries.end());

    // TODO: initialize data structure

    int cur_l = 0;
    int cur_r = -1;
    // invariant: data structure will always reflect the range [cur_l, cur_r]
    for (Query q : queries) {
        while (cur_l > q.l) {
            cur_l--;
            add(cur_l);
        }
        while (cur_r < q.r) {
            cur_r++;
            add(cur_r);
        }
        while (cur_l < q.l) {
            remove(cur_l);
            cur_l++;
        }
        while (cur_r > q.r) {
            remove(cur_r);
            cur_r--;
        }
        answers[q.idx] = get_answer();
    }
    return answers;
}
```

mo3D.h
dc4a5e, 62 lines
/* always use zero based indexing*/
/* ~ $O(N^5/3)$ */
int block_size;

struct Query {
 int l, r, t, idx;
 bool operator<(Query other) const
 {
 return make_tuple(l / block_size, r / block_size, t) <
 make_tuple(other.l / block_size, other.r / block_size, other.t);
 }
};

int ans[N];
void mo_s_algorithm(vector<Query>& queries) {
 sort(queries.begin(), queries.end());
 // TODO: initialize data structure

 int cur_l = 0;
 int cur_r = -1;

```
int cur_t = -1;
// invariant: data structure will always reflect the range
[cur_l, cur_r]
for (Query q : queries) {
    while (cur_l > q.l) {
        cur_l--;
        //add(cur_l)
    }
    while (cur_r < q.r) {
        cur_r++;
        //add(cur_r)
    }
    while (cur_l < q.l) {
        //remove(cur_l);
        cur_l++;
    }
    while (cur_r > q.r) {
        //remove(cur_r);
        cur_r--;
    }

    while(cur_t < q.t){
        cur_t++;
        //update
    }
    while(cur_t > q.t){
        //update rollback
        cur_t--;
    }
    ans[q.idx] = get_answer(); // declare array for this
}

void getBlockSize(int n, int q){
    if (q >= n) {
        // most common: Q ~ N
        block_size = max(1, (int)pow(n, 2.0/3.0));
    } else {
        // general cube-root rule
        block_size = max(1, (int)pow((long double)n*n / q,
            1.0/3.0));
    }
    // then sort your queries by (L/B, R/B, T) or via Hilbert
}
```

cht.h

87ad47, 28 lines

```
struct line {
    long long m, c;
    long long eval(long long x) { return m * x + c; }
    long double intersectX(line l) { return (long double) (c -
        l.c) / (l.m - m); }
};

deque<line> dq;
dq.push_front({0, 0});//cant be put in global, remove this to
    local function
//if query ask for minimum remove this line after 1st insertion

//TODO NOTE**: maximum and minimum value exist in bot left
    most and rightmost of convex hull so do search on both l
    to r and r to l

//constructing hull from l to r, maintain correct hull at
    rightmost
/* ***inserting line (maximum hull)
line cur = line{...some m, ...some c}
while(dq.size()>=2<=cur.intersectX(dq.back())
    <=cur.intersectX(dq[dq.size()-2]))dq.pop_back();
```

```
        dq.pb(cur);
    }
}
//constructing hull from r to l, maintain correct hull at
    leftmost
/* inserting line (maximum hull)
line cur = line{...some m, ...some c}
while(dq.size()>=2<=cur.intersectX(dq[0])>=cur.intersectX(
    dq[1])){
    dq.pop_front();
}
dq.push_front(cur);
}
```

dinic.h

ce6220, 82 lines

```
//COPY FROM BENQ GITHUB I dont fucking know how this work
//General graphs: O(V^2E);
//Bipartite matching(unit caps): O(E sqrt2(V))
struct Dinic {
    using F = long long; // flow type
    struct Edge { int to; F flow, cap; };
    int N;
    vector<Edge> edges;
    vector<vector<int>> adj;
    vector<int> level;
    vector<vector<int>::iterator> it;

    // Initialize Dinic for a graph with _N vertices (0-indexed
        or 1-indexed)
    void init(int _N) {
        N = _N;
        adj.assign(N, {});
        edges.clear();
        level.resize(N);
        it.resize(N);
    }

    // Add edge u -> v with capacity 'cap', and reverse edge v
        -> u with capacity 'rev_cap'
    void addEdge(int u, int v, F cap, F rev_cap = 0) {
        // forward edge
        adj[u].push_back((int)edges.size());
        edges.push_back({v, 0, cap});
        // reverse edge
        adj[v].push_back((int)edges.size());
        edges.push_back({u, 0, rev_cap});
    }

    // Build level graph via BFS
    bool bfs(int s, int t) {
        fill(level.begin(), level.end(), -1);
        for (int i = 0; i < N; i++) it[i] = adj[i].begin();
        queue<int> q;
        level[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (int idx : adj[u]) {
                const Edge &e = edges[idx];
                if (level[e.to] < 0 && e.flow < e.cap) {
                    level[e.to] = level[u] + 1;
                    q.push(e.to);
                }
            }
        }
        return level[t] >= 0;
    }
}
```

```
// DFS to send flow
F dfs(int u, int t, F pushed) {
    if (u == t || pushed == 0) return pushed;
    for (; it[u] != adj[u].end(); ++it[u]) {
        int idx = *it[u];
        Edge &e = edges[idx];
        if (level[e.to] != level[u] + 1 || e.flow == e.cap)
            continue;
        F tr = dfs(e.to, t, min(pushed, e.cap - e.flow));
        if (tr > 0) {
            e.flow += tr;
            edges[idx ^ 1].flow -= tr; // reverse edge
            return tr;
        }
    }
    return 0;
}

// Compute max flow from s to t
F maxFlow(int s, int t) {
    F flow = 0;
    while (bfs(s, t)) {
        while (F pushed = dfs(s, t, numeric_limits<F>::max
            ())) {
            flow += pushed;
        }
        return flow;
    }

    // After maxFlow, vertices reachable from s in residual
        graph have level >= 0.
    // Edges from reachable u to unreachable v form a min-cut.
};
```

articulation-points.h

Description: IS-CUTPOINT(v) in this code is not implemented, also I never use this and don't know how does this works23f413, 37 lines

```
int n; // number of nodes
vector<vector<int>> adj; // adjacency list of graph

vector<bool> visited;
vector<int> tin, low;
int timer;

void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = low[v] = timer++;
    int children=0;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            low[v] = min(low[v], tin[to]);
        } else {
            dfs(to, v);
            low[v] = min(low[v], low[to]);
            if (low[to] >= tin[v] && p!=-1)
                IS_CUTPOINT(v);
            ++children;
        }
    }
    if(p == -1 && children > 1)
        IS_CUTPOINT(v);
}

void find_cutpoints() {
    timer = 0;
    visited.assign(n, false);
}
```

```

tin.assign(n, -1);
low.assign(n, -1);
for (int i = 0; i < n; ++i) {
    if (!visited[i])
        dfs(i);
}
}

```

hld.h

Description: the most batshit insane code in this template-book hope that in whatever circumstances it never required this fucker

e4ffaf, 148 lines

```
vector<int>adj[N];
```

```

void add_edges(int a, int b){
    adj[a].pb(b);
    adj[b].pb(a);
}

```

```

const int LOG = 20;
int timer = 0, seg_tree_size = 0;
int depth[N], parent[N], n_subtree[N], heavyChild[N], chain[N],
    SegTreePos[N];

```

```

int cost[N];
int up[N][LOG]; // 2^j-th ancestor of n

```

```

/*SegTree*/
//finding max edge query
ll tree[4*N];
void update(int node,int n_l,int n_r,int q_i,int value){
    if(n_r<q_i || q_i<n_l) return;
    if(q_i==n_l && n_r==q_i){
        tree[node] = value;
        return;
    }
    int mid = (n_r+n_l)/2;
    update(2*node,n_l,mid,q_i,value);
    update(2*node+1,mid+1,n_r,q_i,value);
    tree[node] = max(tree[2*node], tree[2*node+1]);
}

```

```

long long f(int node,int n_l,int n_r,int q_l,int q_r){
    if(n_r<q_l || q_r<n_l) return 0;
    if(q_l<=n_l && n_r<=q_r) return tree[node];
    int mid = (n_l+n_r)/2;
    return max(f(2*node,n_l,mid,q_l,q_r) , f(2*node+1,mid+1,n_r,
        ,q_l,q_r));
}

```

/*SegTree*/

//preprocessing the arrays above

```

void dfs(int a,int e){
    chain[a] = a;
    n_subtree[a] = 1;
    int bestSon = -1, hmax = -1;
    for(auto b:adj[a]){
        if(b == e) continue;
        depth[b] = depth[a] + 1;
        parent[b] = a;
        up[b][0] = parent[b];
        for(int i=1;i<LOG;++i){
            up[b][i] = up[up[b][i-1]][i-1];
        }
        dfs(b,a);
        n_subtree[a] += n_subtree[b];
        if(n_subtree[b] > hmax){
            hmax = n_subtree[b], bestSon = b;
        }
    }
}

```

```

    heavyChild[a] = bestSon;
}

void computeHeavyChains(int a, int e){
    if(heavyChild[a] != -1){
        chain[heavyChild[a]] = chain[a];
    }
    for(auto b:adj[a]){
        if(b == e) continue;
        computeHeavyChains(b, a);
    }
}

void setHeavyChains(int a, int e){
    SegTreePos[a] = timer++;
    if(heavyChild[a] != -1){
        setHeavyChains(heavyChild[a], a);
        int w = 0;
        for(auto b:adj[a]){
            if(b == heavyChild[a]){
                w = 1;
                break;
            }
        }
        //setting cost of heavyChild[a] = weight of edge (a,
        heavyChild[a])
        cost[heavyChild[a]] = w; //change when tree is weighted
    }
    for(auto b:adj[a]){
        if(b == e || heavyChild[a] == b) continue;
        cost[b] = 1; //change when tree is weighted
        setHeavyChains(b, a);
    }
}

```

```

void buildSegTree(int n_node){
    seg_tree_size = n_node;
    while(__builtin_popcount(seg_tree_size)!=1)++seg_tree_size;
    for(int i=0;i<n_node;++i){
        update(1,0,seg_tree_size-1,SegTreePos[i], cost[i]);
    }
    for(int i=seg_tree_size-1;i>=1;--i){
        tree[i] = max(tree[2*i], tree[2*i+1]);
    }
}

```

```

ll queryPath(int mother, int son){
    ll ans = LONG_MIN;
    while(chain[mother] != chain[son]){
        if(chain[son] == son){
            ans = max(ans,f(1,0,seg_tree_size-1,SegTreePos[son],
                SegTreePos[son]));
        } else {
            ans = max(ans, f(1,0,seg_tree_size-1,SegTreePos[
                chain[son]],SegTreePos[son]));
        }
        son = parent[chain[son]];
    }

    ans = max(ans, f(1,0,seg_tree_size-1,SegTreePos[mother]+1,
        SegTreePos[son]));

    return ans;
}

```

```

int lca(int a, int b){
    if(depth[a]<depth[b]) swap(a,b);
    int k = depth[a] - depth[b];
    for(int i=LOG-1;i>=0;--i){

```

```

        if(k & (1<<i)){
            a = up[a][i];
        }

        if(a == b) return a;
        for(int i=LOG-1;i>=0;--i){
            if(up[a][i] != up[b][i]){
                a = up[a][i];
                b = up[b][i];
            }
        }
        return up[a][0];
}

ll query(int x, int y){
    int l = lca(x,y);
    return max( queryPath(l, x), queryPath(l, y)); //combine
        the answer
}

void hld_init(int n){
    dfs(0,-1);
    computeHeavyChains(0,-1);
    setHeavyChains(0,-1);
    buildSegTree(n);
}

```

divide-and-conquer-dp.h

108b88, 55 lines

//TODO: initialize dp , initialize cost() function of use slide
(
//ll dp[N][M];

//generic implementation for sliding range technique for logn
cost()
//(persistent segtree alternative)

```

ll ccost = 0;
int cl = 0, cr = -1;
void slide(int l, int r){
    while(cr < r){
        ++cr;
        //add();
        //...
    }
    while(cl > l){
        --cl;
        //add();
        //...
    }
    while(cr > r){
        //remove();
        //...
        --cr;
    }
    while(cl < l){
        //remove();
        //...
        ++cl;
    }
}

```

```

void compute(int l, int r, int optl, int optr, int j){
    if(l>r) return;

```

```

    int mid = (l+r)>>1;
    //pair<ll, int> best = {0,-1};
    //pair<ll, int> best = {LINF,-1};

```

```
//dp is satisfy quadrangle IE if cost() satisfy quadrangle
IE
//if cost() is QF => opt() is nondecreasing
for(int k=optl;k<=min(mid,optl);++k){
    slide(k,mid);
    //best = max(best, {(k>0)?dp[k-1][j-1]:0} + ccost, k);
    //best = min(best, {(k>0)?dp[k-1][j-1]:0} + ccost, k);
}

//dp[mid][j] = max(dp[mid][j], best.first);
//dp[mid][j] = min(dp[mid][j], best.first);
int opt = best.second;
if(1!=r){
    compute(1,mid-1,optl,opt,j);
    compute(mid+1,r,opt,optl,j);
}
}

//TODO: set dp to LINF or -LINF
```

cellul4r (3)

Ohm (4)

Mathematics (5)

5.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{aligned} ax + by &= e \\ cx + dy &= f \end{aligned} \Rightarrow \begin{aligned} x &= \frac{ed - bf}{ad - bc} \\ y &= \frac{af - ec}{ad - bc} \end{aligned}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

Non-distinct roots r become polynomial factors, e.g.
 $a_n = (d_1n + d_2)r^n$.

5.2 Trigonometry

$$\begin{aligned} \sin(v + w) &= \sin v \cos w + \cos v \sin w \\ \cos(v + w) &= \cos v \cos w - \sin v \sin w \end{aligned}$$

$$\begin{aligned} \tan(v + w) &= \frac{\tan v + \tan w}{1 - \tan v \tan w} \\ \sin v + \sin w &= 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2} \\ \cos v + \cos w &= 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2} \end{aligned}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$\begin{aligned} a \cos x + b \sin x &= r \cos(x - \phi) \\ a \sin x + b \cos x &= r \sin(x + \phi) \end{aligned}$$

where $r = \sqrt{a^2 + b^2}$, $\phi = \text{atan2}(b, a)$.

5.3 Geometry

5.3.1 Triangles

Side lengths: a, b, c

Semiperimeter: $p = \frac{a + b + c}{2}$

Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$

Circumradius: $R = \frac{abc}{4A}$

Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles):

$$m_a = \frac{1}{2} \sqrt{2b^2 + 2c^2 - a^2}$$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$

Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents: $\frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$


5.3.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° ,
 $ef = ac + bd$, and $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$.

5.3.3 Spherical coordinates



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \text{atan2}(y, x) \end{aligned}$$

5.4 Derivatives/Integrals

$$\begin{aligned} \frac{d}{dx} \arcsin x &= \frac{1}{\sqrt{1 - x^2}} & \frac{d}{dx} \arccos x &= -\frac{1}{\sqrt{1 - x^2}} \\ \frac{d}{dx} \tan x &= 1 + \tan^2 x & \frac{d}{dx} \arctan x &= \frac{1}{1 + x^2} \\ \int \tan ax &= -\frac{\ln |\cos ax|}{a} & \int x \sin ax &= \frac{\sin ax - ax \cos ax}{a^2} \\ \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \text{erf}(x) & \int x e^{ax} dx &= \frac{e^{ax}}{a^2} (ax - 1) \end{aligned}$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

5.5 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$1 + 2 + 3 + \dots + n = \frac{n(n + 1)}{2}$$

$$1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(2n + 1)(n + 1)}{6}$$

$$1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^2(n + 1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n + 1)(2n + 1)(3n^2 + 3n - 1)}{30}$$

5.6 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty)$$

$$\ln(1 + x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1)$$

$$\sqrt{1 + x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, \quad (-\infty < x < \infty)$$
$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, \quad (-\infty < x < \infty)$$

5.7 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

5.7.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\text{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1 - p)^{n - k}$$
$$\mu = np, \sigma^2 = np(1 - p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small p .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1 - p)^{k - 1}, \quad k = 1, 2, \dots$$
$$\mu = \frac{1}{p}, \sigma^2 = \frac{1 - p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\text{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, \quad k = 0, 1, 2, \dots$$
$$\mu = \lambda, \sigma^2 = \lambda$$

5.7.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\text{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b - a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$
$$\mu = \frac{a + b}{2}, \sigma^2 = \frac{(b - a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$
$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x - \mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

Chicken McNugget Theorem

The **Chicken McNugget Theorem** (or **Postage Stamp Problem** or **Frobenius Coin Problem**) states that for any two **relatively prime positive integers** m, n , the greatest integer that cannot be written in the form $am + bn$ for **nonnegative integers** a, b is $mn - m - n$.

A consequence of the theorem is that there are exactly $\frac{(m - 1)(n - 1)}{2}$ positive integers which cannot be expressed in the form $am + bn$. The proof is based on the fact that in each pair of the form $(k, mn - m - n - k)$, exactly one element is expressible.

Rearrangement Inequality

The **Rearrangement Inequality** states that, if $A = \{a_1, a_2, \dots, a_n\}$ is a **permutation** of a **finite set** (in fact, **multiset**) of **real numbers** and $B = \{b_1, b_2, \dots, b_n\}$ is a permutation of another finite set of real numbers, the quantity $a_1b_1 + a_2b_2 + \dots + a_nb_n$ is maximized when A and B are similarly sorted (that is, if a_i is greater than or equal to exactly i of the other members of A , then b_i is also greater than or equal to exactly i of the other members of B). Conversely, $a_1b_1 + a_2b_2 + \dots + a_nb_n$ is minimized when A and B are oppositely sorted (that is, if a_i is less than or equal to exactly i of the other members of A , then b_i is also greater than or equal to exactly i of the other members B).

Wilson's Theorem

In **number theory**, **Wilson's Theorem** states that if **integer** $p > 1$, then $(p - 1)! + 1$ is divisible by p if and only if p is prime. It was stated by John Wilson. The French mathematician Lagrange proved it in 1771.

Techniques (A)

techniques.txt	159 lines
Recursion	
Divide and conquer	
Finding interesting points in N log N	
Algorithm analysis	
Master theorem	
Amortized time complexity	
Greedy algorithm	
Scheduling	
Max contiguous subvector sum	
Invariants	
Huffman encoding	
Graph theory	
Dynamic graphs (extra book-keeping)	
Breadth first search	
Depth first search	
* Normal trees / DFS trees	
Dijkstra's algorithm	
MST: Prim's algorithm	
Bellman-Ford	
Konig's theorem and vertex cover	
Min-cost max flow	
Lovasz toggle	
Matrix tree theorem	
Maximal matching, general graphs	
Hopcroft-Karp	
Hall's marriage theorem	
Graphical sequences	
Floyd-Warshall	
Euler cycles	
Flow networks	
* Augmenting paths	
* Edmonds-Karp	
Bipartite matching	
Min. path cover	
Topological sorting	
Strongly connected components	
2-SAT	
Cut vertices, cut-edges and biconnected components	
Edge coloring	
* Trees	
Vertex coloring	
* Bipartite graphs (=> trees)	
* 3^n (special case of set cover)	
Diameter and centroid	
K'th shortest path	
Shortest cycle	
Dynamic programming	
Knapsack	
Coin change	
Longest common subsequence	
Longest increasing subsequence	
Number of paths in a dag	
Shortest path in a dag	
Dynprog over intervals	
Dynprog over subsets	
Dynprog over probabilities	
Dynprog over trees	
3^n set cover	
Divide and conquer	
Knuth optimization	
Convex hull optimizations	
RMQ (sparse table a.k.a 2^k-jumps)	
Bitonic cycle	
Log partitioning (loop over most restricted)	
Combinatorics	

Computation of binomial coefficients
Pigeon-hole principle
Inclusion/exclusion
Catalan number
Pick's theorem
Number theory
Integer parts
Divisibility
Euclidean algorithm
Modular arithmetic
* Modular multiplication
* Modular inverses
* Modular exponentiation by squaring
Chinese remainder theorem
Fermat's little theorem
Euler's theorem
Phi function
Frobenius number
Quadratic reciprocity
Pollard-Rho
Miller-Rabin
Hensel lifting
Vieta root jumping
Game theory
Combinatorial games
Game trees
Mini-max
Nim
Games on graphs
Games on graphs with loops
Grundy numbers
Bipartite games without repetition
General games without repetition
Alpha-beta pruning
Probability theory
Optimization
Binary search
Ternary search
Unimodality and convex functions
Binary search on derivative
Numerical methods
Numeric integration
Newton's method
Root-finding with binary/ternary search
Golden section search
Matrices
Gaussian elimination
Exponentiation by squaring
Sorting
Radix sort
Geometry
Coordinates and vectors
* Cross product
* Scalar product
Convex hull
Polygon cut
Closest pair
Coordinate-compression
Quadtrees
KD-trees
All segment-segment intersection
Sweeping
Discretization (convert to events and sweep)
Angle sweeping
Line sweeping
Discrete second derivatives
Strings
Longest common substring
Palindrome subsequences

Knuth-Morris-Pratt
Tries
Rolling polynomial hashes
Suffix array
Suffix tree
Aho-Corasick
Manacher's algorithm
Letter position lists
Combinatorial search
Meet in the middle
Brute-force with pruning
Best-first (A*)
Bidirectional search
Iterative deepening DFS / A*
Data structures
LCA (2^k-jumps in trees in general)
Pull/push-technique on trees
Heavy-light decomposition
Centroid decomposition
Lazy propagation
Self-balancing trees
Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
Monotone queues / monotone stacks / sliding queues
Sliding queue using 2 stacks
Persistent segment tree