



Chiang Mai University

UndefinedAC + HomuraAkemi + Intercontinental Ballistic Missile CMU

Suthana Kwaonueng, Theerada Siri, Paisit Lertananpipat

2025-09-02

- 1 Contest
- 2 Tanya’s Library
- 3 cellul4r
- 4 Mathematics

Contest (1)

template.cpp80 lines

```
#include<bits/stdc++.h>
using namespace std;
void __print(int x) {cerr << x;}
void __print(long x) {cerr << x;}
void __print(long long x) {cerr << x;}
void __print(unsigned x) {cerr << x;}
void __print(unsigned long x) {cerr << x;}
void __print(unsigned long long x) {cerr << x;}
void __print(float x) {cerr << x;}
void __print(double x) {cerr << x;}
void __print(long double x) {cerr << x;}
void __print(char x) {cerr << '\\' << x << '\\';}
void __print(const char *x) {cerr << '\"' << x << '\"';}
void __print(const string &x) {cerr << '\"' << x << '\"';}
void __print(bool x) {cerr << (x ? "true" : "false");}

template<typename T, typename V>
void __print(const pair<T, V> &x);
template<typename T>
void __print(const T &x) {int f = 0; cerr << '{'; for (auto &i:
x) cerr << (f++ ? ", " : ""), __print(i); cerr << "}";}
template<typename T, typename V>
void __print(const pair<T, V> &x) {cerr << '{'; __print(x.first
); cerr << ", "; __print(x.second); cerr << '}';}
void __print() {cerr << "}\n";}
template <typename T, typename... V>
void __print(T t, V... v) {__print(t); if (sizeof...(v)) cerr <<
", "; __print(v...);}

#ifdef DEBUG
#define dbg(x...) cerr << "\e[91m"<<__func__<<": "<<__LINE__<<"
[" << #x << "] = ["; __print(x); cerr << "\e[39m" << endl;
#else
#define dbg(x...)
#endif

typedef long long ll;
typedef long double ld;
typedef complex<ld> cd;

typedef pair<int, int> pi;
typedef pair<ll,ll> pl;
typedef pair<ld,ld> pd;

typedef vector<int> vi;
typedef vector<ld> vd;
typedef vector<ll> vl;
typedef vector<pi> vpi;
typedef vector<pl> vpl;
typedef vector<cd> vcd;
```

```
//template<class T> using pq = priority_queue<T>;
//template<class T> using pqg = priority_queue<T, vector<T>,
greater<T>>;
```

```
#define rep(i, a) for(int i=0;i<a;++i)
#define FOR(i, a, b) for (int i=a; i<(b); i++)
#define F0R(i, a) for (int i=0; i<(a); i++)
#define FORd(i,a,b) for (int i = (b)-1; i >= a; i--)
#define F0Rd(i,a) for (int i = (a)-1; i >= 0; i--)
#define trav(a,x) for (auto& a : x)
#define uid(a, b) uniform_int_distribution<long long>(a, b)(rng
)

#define sz(x) (int)(x).size()
#define mp make_pair
#define pb push_back
#define f first
#define s second
#define lb lower_bound
#define ub upper_bound
#define all(x) x.begin(), x.end()
#define ins insert
```

```
template<class T> bool ckmin(T& a, const T& b) { return b < a ?
a = b, 1 : 0; }
template<class T> bool ckmax(T& a, const T& b) { return a < b ?
a = b, 1 : 0; }
```

```
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
count());
```

```
const char nl = '\n';
const int N = 2e5+3;
const int INF = INT_MAX;
const long long LINF = LLONG_MAX;
```

```
int main(){
ios::sync_with_stdio(false);cin.tie(nullptr);
}
```

.vimrc21 lines

```
"General editor settings
set tabstop=4
set nocompatible
set shiftwidth=4
set expandtab
set autoindent
set smartindent
set ruler
set showcmd
set incsearch
set shellslash
set number
set relativenumber
set cino+=L0
```

```
"keybindings for { completion, "jk" for escape, ctrl-a to
select all
inoremap {<CR> {<CR><Esc>O
inoremap {} {}
imap jk <Esc>
map <C-a> <esc>ggVG<CR>
set belloff=all
```

.bashrc1 lines

```
export PATH=$PATH:~/scripts/
```

build.sh1 lines

```
g++ -static -DLOCAL -lm -s -x c++ -Wall -Wextra -O2 -std=c++17
-o $1 $1.cpp
```

stress.sh22 lines

```
#!/usr/bin/env bash

for ((testNum=0;testNum<$4;testNum++))
do
./$3 > input
./$2 < input > outSlow
./$1 < input > outWrong
H1=`md5sum outWrong`
H2=`md5sum outSlow`
if !(cmp -s "outWrong" "outSlow")
then
echo "Error found!"
echo "Input:"
cat input
echo "Wrong Output:"
cat outWrong
echo "Slow Output:"
cat outSlow
exit
fi
done
echo Passed $4 tests
```

Tanya’s Library (2)

2.1 Template & Utilities

pragma.hDescription: TODOd8191a, 3 lines

```
#pragma GCC target ("avx2")
#pragma GCC optimize ("O3")
#pragma GCC optimize ("unroll-loops")
```

2.2 Basic & Combinatorics

binpow.hDescription: TODOd4debd, 11 lines

```
long long binpow(long long a, int n){
long long res = 1;
while (n>0){
if (n&1){
res = res * a;
}
a = a * a;
n>>=1;
}
return res;
}
```

bigmod.hDescription: TODO91cb0a, 11 lines

```
long long bigmod(long long a, int n){
long long res = 1;
while (n>0){
if (n&1){
res = res * a % MOD;
}
a = a * a % MOD;
n>>=1;
}
return res;
}
```

binomialCoefficients.h

Description: TODO

3f7261, 10 lines

//more practical to precal C[n][r] with pascal triangle...
//...if constrain is O(n^2) able
long long C(int n, int k) {
 if(k==0)return 1;
 else if(k<0 || n<k)return 0;
 double res = 1;
 for (int i = 1; i <= k; ++i)
 res = res * (n - k + i) / i;
 return (long long)(res + 0.01);
}

matrix.h

Description: Nothing to says

5da844, 33 lines

struct Matrix {
 vector<vector<long long>> a;
 int rows, cols;

 Matrix(int r, int c, int val) : rows(r), cols(c), a(r, vector<long long>(c, val)) {}

 Matrix operator *(const Matrix& other) {
 Matrix product(rows, other.cols, 0);

 for (int i = 0; i < rows; ++i) {
 for (int j = 0; j < other.cols; ++j) {
 for (int k = 0; k < cols; ++k) {
 product.a[i][j] += a[i][k] * other.a[k][j]
 % INF;
 product.a[i][j] %= INF;
 }
 }
 }
 return product;
 }
};

Matrix expo_power(Matrix a, long long n, int size){//note n=1
 is equal do nothing,n=2is do once
 Matrix product(size,size,0);
 for(int i=0;i<size;++i)product.a[i][i]=1;
 while(n>0){
 if(n&1){
 product = product * a;
 }
 a = a * a;
 n>>=1;
 }
 return product;
}

mobius-function.h

Description: TODO

c6a8f4, 10 lines

int mob[N+1];
void mobius() {
 mob[1] = 1;
 for (int i = 2; i <= N; i++){
 mob[i]--;
 for (int j = i + i; j <= N; j += i) {
 mob[j] -= mob[i];
 }
 }
}

div-ceil-floor.h

Description: to stop c++ fucked up negative case of ceil, floor

2834e8, 9 lines

long long div_floor(__int128 a, long long b){
 __int128 q = a / b;
 __int128 r = a % b;
 if (r != 0 && ((a < 0) != (b < 0))) --q;
 return (long long)q;
}

long long div_ceil(__int128 a, long long b){
 return -div_floor(-a, b);
}

factoradix.h

Description: TODO

<ext/pbds/assoc-container.hpp>, <ext/pb_ds/tree_policy.hpp>

e835c3, 63 lines

typedef __gnu_pbds::tree<int, __gnu_pbds::null_type, less<int>,
 __gnu_pbds::rb_tree_tag, __gnu_pbds::
 tree_order_statistics_node_update> ordered_set;

ordered_set st;
//st.order_of_key(x) - find # of elements in st stricly less
 than x
//st.size() - size of st
//st.find_by_order(x) - return iterator to the x-th largest
 element
//st.clear() - clear container

vector<int> factoradix_to_permutation(int n, vector<int> &
 factoradix){
 st.clear(); for(int i=1;i<=n;++i) st.ins(i);
 int cl = 0;
 while((int)factoradix.size() < n){
 factoradix.pb(0); ++cl;
 }

 vector<int> res;
 for(int i=(int)factoradix.size()-1;i>=0;--i){
 auto it = st.find_by_order(factoradix[i]);
 res.pb(*it);
 st.erase(it);
 }

 while(cl-->0) factoradix.pop_back();

 return res;
}

vector<int> permutation_to_factoradix(int n, vector<int> &
 permutation){
 st.clear(); for(int i=1;i<=n;++i) st.ins(i);
 vector<int> res;
 for(int i=0;i<(int)permutation.size();++i){
 int cnt = st.order_of_key(permutation[i]);
 res.pb(cnt);
 auto it = st.find_by_order(cnt); st.erase(it);
 }
 reverse(all(res));
 while(!res.empty() and res.back() == 0)res.pop_back();

 return res;
}

vector<int> decimal_to_factoradix(ll n){
 vector<int> res;
 int d = 1;
 while(n > 0){
 res.pb(n % d);
 n/=d; ++d;
 }

factoradix_to_decimal(vector<int> &cur){
 ll res = 0;
 ll d = 1;
 for(int i=0;i<(int)cur.size();++i){
 res += d*cur[i];
 d*=(i+1);
 }
 return res;
}

//TODO using 0 base indexing, i.e. your 1st lexicographically
permutation now is start at 0th

gauss-jordan-elimination.h

Description: TODO

d847fe, 48 lines

const double EPS = 1e-9;
const int INF = 2; // it doesn't actually have to be infinity
 or a big number

int gauss (vector < vector<double> > a, vector<double> & ans) {
 int n = (int) a.size();
 int m = (int) a[0].size() - 1;

 vector<int> where (m, -1);
 for (int col=0, row=0; col<m && row<n; ++col) {
 int sel = row;
 for (int i=row; i<n; ++i)
 if (abs (a[i][col]) > abs (a[sel][col]))
 sel = i;

 if (abs (a[sel][col]) < EPS)
 continue;

 for (int i=col; i<=m; ++i)
 swap (a[sel][i], a[row][i]);
 where[col] = row;

 for (int i=0; i<n; ++i)
 if (i != row) {
 double c = a[i][col] / a[row][col];
 for (int j=col; j<=m; ++j)
 a[i][j] -= a[row][j] * c;
 }
 ++row;
 }

 ans.assign (m, 0);
 for (int i=0; i<m; ++i)
 if (where[i] != -1)
 ans[i] = a[where[i]][m] / a[where[i]][i];

 for (int i=0; i<n; ++i) {
 double sum = 0;
 for (int j=0; j<m; ++j)
 sum += ans[j] * a[i][j];
 if (abs (sum - a[i][m]) > EPS)
 return 0; // contradiction means no solution
 }

 for (int i=0; i<m; ++i)
 if (where[i] == -1)
 return INF; //infinite solution
 return 1; //unique solution
}

2.3 Primes & Factorization

sieve.h

Description: TODO

abb3a3, 22 lines

//construct is O(sqrt(n))
//can use to find all prime factor of a number in O(log n)
const int M = 2e5+1;
vector<bool> is_prime(M+1, true);
void sieve(){
 is_prime[0] = is_prime[1] = false;
 for (int i = 2; i * i <= M; i++) {
 if (is_prime[i]) {
 for (int j = i * i; j <= M; j += i)
 is_prime[j] = false;
 }
 }
 /* log n sieve (use sieve to find all prime factors in O(log n))
 for (int i = 2; i <= M; i++)is_prime[i] = i;
 for (int i = 2; i * i <= M; i++) {
 if (is_prime[i] == i) {
 for (int j = i * i; j <= M; j += i)
 is_prime[j] = i;
 }
 }
 */
}

linear-sieve.h

Description: TODO

d893f1, 18 lines

const int N = 10000000;
vector<int> lp(N+1);*//lp[i] = minimum prime that divide i*
vector<int> pr;

void sieve(){
 for (int i=2; i <= N; ++i) {
 if (lp[i] == 0) {
 lp[i] = i;
 pr.push_back(i);
 }
 for (int j = 0; i * pr[j] <= N; ++j) {
 lp[i * pr[j]] = pr[j];
 if (pr[j] == lp[i]) {
 break;
 }
 }
 }
}

phi-sieve.h

Description: TODO

b4e4ad, 15 lines

//set value for M
const int M = 1e6;
vector<int> phi(M+1);

void phi_1_to_n() {
 for (int i = 0; i <= M; i++)
 phi[i] = i;

 for (int i = 2; i <= M; i++) {
 if (phi[i] == i) {
 for (int j = i; j <= M; j += i)
 phi[j] -= phi[j] / i;
 }
 }
}

phi-function.h

Description: TODO

fb8d57, 14 lines

//O(sqrt n)
int phi(int n) {
 int result = n;
 for (int i = 2; i * i <= n; i++) {
 if (n % i == 0) {
 while (n % i == 0)
 n /= i;
 result -= result / i;
 }
 }
 if (n > 1)
 result -= result / n;
 return result;
}

mobius-function.h

Description: TODO

c6a8f4, 10 lines

int mob[N+1];
void mobius() {
 mob[1] = 1;
 for (int i = 2; i <= N; i++){
 mob[i]--;
 for (int j = i + i; j <= N; j += i) {
 mob[j] -= mob[i];
 }
 }
}

miller-rabin.h

Description: TODO

980e40, 52 lines

//randomize primality test O(logn^2)
using u64 = uint64_t;
using ul28 = __uint128_t;

u64 bigmod(u64 base, u64 e, u64 mod){
 u64 result = 1;
 base %= mod;
 while(e){
 if(e & 1)
 result = (ul28)result * base % mod;
 base = (ul28)base * base % mod;
 e >>= 1;
 }
 return result;
}

bool check_composite(u64 n, u64 a, u64 d, int s){
 u64 x = bigmod(a, d, n);
 if(x == 1 || x == n - 1)
 return false;
 for(int r = 1; r < s; r++){
 x = (ul28)x * x % n;
 if(x == n - 1)
 return false;
 }
 return true;
}

//random number generator temporality disable because my
//template already has it
//mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
long long rnd(long long x, long long y) {
 return uniform_int_distribution<long long>(x, y)(rng);
}

bool MillerRabin(u64 n, int iter=5){ *// return true if n is probably prime, else return false.*
 if(n < 4){
 return n == 2 || n == 3;
 }
 int s = 0;
 u64 d = n-1;
 while((d & 1) == 0){
 d >>= 1;
 s++;
 }

 for(int i = 0; i < iter; i++){
 long long a = rnd(2, n-2);
 if(check_composite(n, a, d, s))
 return false;
 }
 return true;
}

pollard-rho.h

Description: TODO

bc7c06, 20 lines

//randomize factorization in O(n^1/4 * logn)
long long mult(long long a, long long b, long long mod) {
 return (__int128)a * b % mod;
}

long long f(long long x, long long c, long long mod) {
 return (mult(x, x, mod) + c) % mod;
}

long long rho(long long n, long long x0=2, long long c=1) {
 long long x = x0, y = x0, g = 1;
 while (g == 1) {
 x = f(x, c, n);
 y = f(f(y, c, n), c, n);
 g = __gcd(abs(x - y), n);
 }

 if(g == n) return rho(n, uid(2, n-1), uid(-2, 2)); *//uid is uniform long*
 else return g;
}

discrete-log.h

Description: TODO

f7650d, 33 lines

// Returns minimum x for which a ^ x % m = b % m.
int solve(int a, int b, int m) {
 a %= m, b %= m;
 int k = 1, add = 0, g;
 while ((g = __gcd(a, m)) > 1) {
 if (b == k)
 return add;
 if (b % g)
 return -1;
 b /= g, m /= g, ++add;
 k = (k * 111 * a / g) % m;
 }

 int n = sqrt(m) + 1;
 int an = 1;
 for (int i = 0; i < n; ++i)
 an = (an * 111 * a) % m;

 map<int, int> vals;
 for (int q = 0, cur = b; q <= n; ++q) {

```

    vals[cur] = q;
    cur = (cur * lll * a) % m;
}

for (int p = 1, cur = k; p <= n; ++p) {
    cur = (cur * lll * an) % m;
    if (vals.count(cur)) {
        int ans = n * p - vals[cur] + add;
        return ans;
    }
}
return -1;
}

```

primitive-root.h

Description: TODO

c6d472, 34 lines

```

/*
    The following code assumes that the modulo p is a prime
    number.
    To make it works for any value of p, we must add
    calculation of phi(p)
*/
int powmod (int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int (res * lll * a % p), --b;
        else
            a = int (a * lll * a % p), b >>= 1;
    return res;
}

int generator (int p) {
    vector<int> fact;
    int phi = p-1, n = phi; // cal phi p by assuming it's
    prime
    for (int i=2; i*i<=n; ++i)
        if (n % i == 0) {
            fact.push_back (i);
            while (n % i == 0)
                n /= i;
        }
    if (n > 1)
        fact.push_back (n);

    for (int res=2; res<=p; ++res) {
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod (res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}

```

crt.h

Description: TODO

efd085, 51 lines

```

class CRT { // ChineseRemainderTheorem
    typedef long long vlong;
    typedef pair<vlong, vlong> pll;
    vector<pll> equations;

public:
    void clear() {
        equations.clear();
    }
    void addEquation( vlong r, vlong m ) {
        equations.push_back({r, m});
    }
}

```

```

}

void ext_gcd(vlong a, vlong b, vlong& x, vlong& y) {
    if (b == 0) {
        x = 1;
        y = 0;
        return;
    }
    vlong x1, y1;
    ext_gcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
}

pll solve() {
    if (equations.size() == 0) return {-1, -1};

    vlong a1 = equations[0].first;
    vlong m1 = equations[0].second;
    a1 %= m1;
    for ( int i = 1; i < (int)equations.size(); i++ ) {
        vlong a2 = equations[i].first;
        vlong m2 = equations[i].second;

        vlong g = __gcd(m1, m2);
        if ( a1 % g != a2 % g ) return {-1, -1};
        vlong p, q;
        ext_gcd(m1/g, m2/g, p, q);

        vlong mod = m1 / g * m2;
        p = (p%mod+mod)%mod, q = (q%mod+mod)%mod;
        vlong x = ( (__int128)a1 * (m2/g) % mod * q % mod +
            (__int128)a2 * (m1/g) % mod * p % mod ) % mod;
        a1 = x;
        if ( a1 < 0 ) a1 += mod;
        m1 = mod;
    }
    return {a1, m1};
}
}

```

diophantine.h

Description: TODO

4fcad2, 89 lines

```

ll gcd(ll a, ll b, ll& x, ll& y) { //gcd extended
    if (b == 0) {
        x = 1;
        y = 0;
        return a;
    }
    ll x1, y1;
    ll d = gcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
    return d;
}

bool find_any_solution(ll a, ll b, ll c, ll &x0, ll &y0, ll &g)
{
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) {
        return false;
    }

    x0 *= c / g;
    y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}

void shift_solution(ll &x, ll &y, ll a, ll b, ll cnt) { //
    make sure that a,b coprime
    x += cnt * b;
    y -= cnt * a;
}

ll find_all_solutions(ll a, ll b, ll c, ll minx, ll maxx, ll
    miny, ll maxy) {
    ll x, y, g;
    if (!find_any_solution(a, b, c, x, y, g))
        return 0;
    a /= g;
    b /= g;

    ll sign_a = a > 0 ? +1 : -1;
    ll sign_b = b > 0 ? +1 : -1;

    shift_solution(x, y, a, b, (minx - x) / b);
    if (x < minx)
        shift_solution(x, y, a, b, sign_b);
    if (x > maxx)
        return 0;
    ll lx1 = x;

    shift_solution(x, y, a, b, (maxx - x) / b);
    if (x > maxx)
        shift_solution(x, y, a, b, -sign_b);
    ll rx1 = x;

    shift_solution(x, y, a, b, -(miny - y) / a);
    if (y < miny)
        shift_solution(x, y, a, b, -sign_a);
    if (y > maxy)
        return 0;
    ll ly2 = y;

    shift_solution(x, y, a, b, -(maxy - y) / a);
    if (y > maxy)
        shift_solution(x, y, a, b, sign_a);
    ll rx2 = x;

    if (lx2 > rx2)
        swap(lx2, rx2);

    ll lx = max(lx1, lx2);
    ll rx = min(rx1, rx2);
    if (lx > rx)
        return 0;

    return (rx - lx) / abs(b) + 1;
}

//number of solution of ax + by = c in general
ll number_of_solution(ll a, ll b, ll c, ll x1, ll x2, ll y1, ll
    y2){
    if(a == 0 and b == 0 and c == 0)return (x2-x1+1)*(y2-y1+1);
    else if(a == 0 and b == 0) return 0;
    else if(a == 0){
        if(c%b!=0 or y1>c/b or y2<c/b)return 0;
        else return (x2-x1+1);
    } else if(b == 0){
        if(c%a!=0 or x1>c/a or x2<c/a)return 0;
        else return (y2-y1+1);
    } else {
        return find_all_solutions(a, b, c, x1, x2, y1, y2);
    }
}

```

2.4 Arrays & Trees

dsu.h	
Description: TODO	7efb0c, 23 lines
//TODO: initialized parent[] and _rank[] array	
<pre>int find_set(int v) { if (v == parent[v]) return v; return parent[v] = find_set(parent[v]); } void make_set(int v) { parent[v] = v; _rank[v] = 1; } void union_sets(int a, int b) { a = find_set(a); b = find_set(b); if (a != b) { if (_rank[a] < _rank[b]) swap(a, b); parent[b] = a; _rank[a] += _rank[b]; } }</pre>	
fenwick-tree.h	
Description: TODO	a9def9, 27 lines
//TODO: use 1 base indexing only!!! becareful	
vector<long long>bit;	
//range sum point update(k=new_val-old_val)	
void add(int i, int k){//add k to ith data and it's parent range so on	
while(i<(int)bit.size()){	
bit[i]+=k;	
i+=i&-i;//add last set bit	
}	
}	
11 sum(int i){//culmulative sum to ith data	
11 sum=0;	
while(i>0){	
sum+=bit[i];	
i-=i&-i;	
}	
return sum;	
}	
void build_bit(vl &a){	
bit=a;	
for(int i=1;i<(int)bit.size();++i){	
int p=i+(i&-i);//index to parent	
if(p<(int)bit.size())bit[p]+=bit[i];	
}	
}	
normalSegtree.h	
Description: TODO	d1ac68, 30 lines
//TODO: use 0 base indexing, initialize tree[] array (preferably 4 times size of nodes array	
vector<long long>tree;	
void update(int node,int n_l,int n_r,int q_i,long long value){	
if(n_r<q_i q_i<n_l)return;	
if(q_i==n_l && n_r==q_i){	

tree[node] = value;	
return;	
}	
int mid = (n_r+n_l)/2;	
update(2*node,n_l,mid,q_i,value);	
update(2*node+1,mid+1,n_r,q_i,value);	
tree[node] = tree[2*node] + tree[2*node+1];	
}	
long long f(int node,int n_l,int n_r,int q_l,int q_r){	
if(n_r<q_l q_r<n_l)return 0;	
if(q_l<=n_l && n_r<=q_r)return tree[node];	
int mid = (n_l+n_r)/2;	
return f(2*node,n_l,mid,q_l,q_r) + f(2*node+1,mid+1,n_r,q_l	
,q_r);	
}	
int build_tree(vi &a,int n){	
tree.clear();	
int m=n;	
while(__builtin_popcount(m)!=1)++m;	
tree.resize(2*m+10,0);	
for(int i=0;i<n;++i)tree[i+m]=a[i];	
for(int i=m-1;i>=1;--i)tree[i]=tree[2*i]+tree[2*i+1];	
return m;	
}	
lazySegtree.h	
Description: TODO	59e123, 50 lines
//TODO: use 0 base indexing	
vector<long long> tree,lazy;	
void update(int node,int n_l,int n_r,int q_l,int q_r,int value)	
{	
if(lazy[node]!=0){	
tree[node]+=(long long)(n_r-n_l+1)*lazy[node]; // for range + update	
if(n_l!=n_r){	
lazy[2*node]+=lazy[node];	
lazy[2*node+1]+=lazy[node];	
}	
lazy[node] = 0;	
}	
if(n_r<q_l q_r<n_l)return;	
if(q_l<=n_l && n_r<=q_r){	
tree[node]+=(long long)(n_r-n_l+1)*value; // for range + update	
if(n_l!=n_r){	
lazy[2*node]+=value;	
lazy[2*node+1]+=value;	
}	
return;	
}	
int mid = (n_r+n_l)/2;	
update(2*node,n_l,mid,q_l,q_r,value);	
update(2*node+1,mid+1,n_r,q_l,q_r,value);	
tree[node] = tree[2*node] + tree[2*node+1];	
}	
long long f(int node,int n_l,int n_r,int q_l,int q_r){	
if(lazy[node]!=0){	
tree[node]+=(long long)(n_r-n_l+1)*lazy[node];	
if(n_l!=n_r){	
lazy[2*node] += lazy[node];	
lazy[2*node+1] += lazy[node];	
}	
lazy[node] = 0;	
}	
if(n_r<q_l q_r<n_l)return 0;	

if(q_l<=n_l && n_r<=q_r)return tree[node];	
int mid = (n_l+n_r)/2;	
return f(2*node,n_l,mid,q_l,q_r) + f(2*node+1,mid+1,n_r,q_l	
,q_r);	
}	
int build_tree(vi &a,int n){	
tree.clear(); lazy.clear();	
int m=n;	
while(__builtin_popcount(m)!=1)++m;	
tree.resize(2*m+10,0); lazy.resize(2*m+10,0);	
for(int i=0;i<n;++i)tree[i+m]=a[i];	
for(int i=m-1;i>=1;--i)tree[i]=tree[2*i]+tree[2*i+1];	
return m;	
}	
persistent-segtree.h	
Description: TODO	c4a26b, 38 lines
//Warning!This implementation is not garbage collected, so the tree nodes aren't deleted even if the instance of the segment tree is taken out of scope.	
struct Node {	
11 val;	
Node *l, *r;	
Node(11 x) : val(x), l(nullptr), r(nullptr) {}	
Node(Node *ll, Node *rr) {	
l = ll, r = rr;	
val = 0;	
if (l) val += l->val;	
if (r) val += r->val;	
}	
Node(Node *cp) : val(cp->val), l(cp->l), r(cp->r) {}	
};	
int n, cnt = 1;	
11 a[200001];	
Node *roots[200001];	
Node *build(int l = 1, int r = n) {	
if (l == r) return new Node(a[l]);	
int mid = (l + r) / 2;	
return new Node(build(l, mid), build(mid + 1, r));	
}	
Node *update(Node *node, int val, int pos, int l = 1, int r = n	
) {	
if (l == r) return new Node(val);	
int mid = (l + r) / 2;	
if (pos > mid) return new Node(node->l, update(node->r, val,	
pos, mid + 1, r));	
else return new Node(update(node->l, val, pos, l, mid), node	
->r);	
}	
11 query(Node *node, int a, int b, int l = 1, int r = n) {	
if (l > b r < a) return 0;	
if (l >= a && r <= b) return node->val;	
int mid = (l + r) / 2;	
return query(node->l, a, b, l, mid) + query(node->r, a, b,	
mid + 1, r);	
}	
merge-sort-tree.h	
Description: TODO	
<ext/pb_ds/assoc.container.hpp>, <ext/pb_ds/tree.policy.hpp>,<ext/pb_ds/assoc.container.hpp>,<ext/pb_ds/tree.policy.hpp>	
2d0612, 94 lines	
//merge sort tree with segment tree	

```

typedef __gnu_pbds::tree<pair<int,int>, __gnu_pbds::null_type,
    less<pair<int,int>>, __gnu_pbds::rb_tree_tag, __gnu_pbds::
    tree_order_statistics_node_update> ordered_set;
ordered_set st;
//st.order_of_key({x,-1}) - find # of elements in st stricly
    less than x
//st.clear() - clear container

vector<ordered_set> mtree;

ordered_set merge(ordered_set &a, ordered_set &b){
    ordered_set result;
    for(auto&p:a){
        result.ins(p);
    }
    for(auto&p:b){
        result.ins(p);
    }
    return result;
}

void update(int node,int n_l,int n_r,int q_i,int id,int old_val
    ,int value){
    if(n_r<q_i || q_i<n_l)return;
    if(q_i==n_l && n_r==q_i){
        auto it=mtree[node].find({old_val,id});
        mtree[node].erase(it);
        mtree[node].ins({value,id});
        return;
    }
    int mid = (n_r+n_l)/2;
    update(2*node,n_l,mid,q_i,id,old_val,value);
    update(2*node+1,mid+1,n_r,q_i,id,old_val,value);
    auto it=mtree[node].find({old_val,id});
    if(it!=mtree[node].end()){
        mtree[node].erase(it);
        mtree[node].ins({value,id});
    }
}

int f(int node,int n_l,int n_r,int q_l,int q_r, int value){
    if(n_r<q_l || q_r<n_l)return 0;
    if(q_l<=n_l && n_r<=q_r){
        return mtree[node].order_of_key({value,-1});
    }
    int mid = (n_l+n_r)/2;
    return f(2*node,n_l,mid,q_l,q_r,value)+f(2*node+1,mid+1,n_r
        ,q_l,q_r,value);
}

void build_mtree(vi &a){
    int n=(int)a.size();
    int m=n; while(__builtin_popcount(m)!=1)+m;
    //for(int i=0;i<2*m++i)mtree[i].clear();
    mtree.resize(2*m);
    for(int i=0;i<n;++i)mtree[i+m].ins({a[i],i});
    for(int i=m-1;i>1;--i)mtree[i]=merge(mtree[2*i],mtree[2*i
        +1]);
}
//merge sort tree with fenwick tree(BIT) (4 times less space)

typedef __gnu_pbds::tree<pair<int,int>, __gnu_pbds::null_type,
    less<pair<int,int>>, __gnu_pbds::rb_tree_tag, __gnu_pbds::
    tree_order_statistics_node_update> ordered_set;
ordered_set st;
//st.order_of_key(x) - find # of elements in st stricly less
    than x

//TODO: use 1 base indexing

```

```

vector<ordered_set> bit;

void update(int i,int k,int old_value, int new_value){
    while(i<(int)bit.size()){
        auto it=bit[i].find({old_value,k});
        assert(it!=bit[i].end());
        if(it!=bit[i].end()){
            bit[i].erase(it);
        }
        bit[i].ins({new_value,k});
        i+=i&-1;//add last set bit
    }
}

int F(int i, int k){//culmulative sum to ith data
    int sum=0;
    while(i>0){
        sum+=bit[i].order_of_key({k,-1});
        i-=i&-1;
    }
    return sum;
}

void build_bit(vi &a){
    bit.resize((int)a.size());
    for(int i=1;i<(int)a.size();++i)bit[i].ins({a[i],i});
    for(int i=1;i<(int)bit.size();++i){
        int p=i+(i&-1);//index to parent
        if(p<(int)bit.size()){
            for(auto&x:bit[i])bit[p].ins(x);
        }
    }
}

2D-segtree.h
Description: TODO
ee2c74, 82 lines

// 2D segtree stored as tree[4*n][4*m]
vector<vector<ll>> tree;
int n, m; // This shit in global remember
vector<vector<ll>> A; // This shit in global too

void buildY(int vx, int lx, int rx, int vy, int ly, int ry) {
    if (ly == ry) {
        if (lx == rx) {
            tree[vx][vy] = A[lx][ly];
        } else {
            tree[vx][vy] = tree[vx*2][vy] + tree[vx*2+1][vy];
        }
    } else {
        int my = (ly + ry) >> 1;
        buildY(vx, lx, rx, vy*2, ly, my);
        buildY(vx, lx, rx, vy*2+1, my+1, ry);
        tree[vx][vy] = tree[vx][vy*2] + tree[vx][vy*2+1];
    }
}

void buildX(int vx = 1, int lx = 1, int rx = n) {
    if (lx != rx) {
        int mx = (lx+rx)>>1;
        buildX(vx*2, lx, mx);
        buildX(vx*2+1, mx+1, rx);
    }
    buildY(vx, lx, rx, 1, 1, m);
}

void updateY(int vx, int lx, int rx, int x,
    int vy, int ly, int ry, int y, ll val) {
    if (ly == ry) {

```

```

        if (lx == rx) {
            tree[vx][vy] = val;
        } else {
            tree[vx][vy] = tree[vx*2][vy] + tree[vx*2+1][vy];
        }
    } else {
        int my = (ly+ry)>>1;
        if (y <= my)
            updateY(vx,lx,rx,x, vy*2, ly, my, y, val);
        else
            updateY(vx,lx,rx,x, vy*2+1, my+1, ry, y, val);
        tree[vx][vy] = tree[vx][vy*2] + tree[vx][vy*2+1];
    }
}

void updateX(int vx, int lx, int rx, int x, int y, ll val) {
    if (lx != rx) {
        int mx = (lx+rx)>>1;
        if (x <= mx) updateX(vx*2, lx, mx, x, y, val);
        else
            updateX(vx*2+1, mx+1, rx, x, y, val);
    }
    updateY(vx, lx, rx, x, 1, 1, m, y, val);
}

ll queryY(int vx, int vy, int ly, int ry, int y1, int y2) {
    if (y2 < ly || ry < y1) return 0;
    if (y1 <= ly && ry <= y2) return tree[vx][vy];
    int my = (ly+ry)>>1;
    return queryY(vx,vy*2, ly, my, y1,y2)
        + queryY(vx,vy*2+1,my+1, ry, y1,y2);
}

ll queryX(int vx, int lx, int rx,
    int x1, int x2, int y1, int y2) {
    if (x2 < lx || rx < x1) return 0;
    if (x1 <= lx && rx <= x2)
        return queryY(vx, 1, 1, m, y1, y2);
    int mx = (lx+rx)>>1;
    return queryX(vx*2, lx, mx, x1,x2,y1,y2)
        + queryX(vx*2+1, mx+1, rx, x1,x2,y1,y2);
}

void build(int n, int m){
    tree.assign(4*(n+2), vector<ll>(4*(m+2), 0));
    buildX();
}

//using like this n,m= row,col dimenton (1-base index)
//updateX(1,1,n,x,y,v);
//queryX(1,1,n,x1,x2,y1,y2)

```

order-statistics-tree.h

Description: TODO

<ext/pb_ds/assoc.container.hpp>, <ext/pb_ds/tree_policy.hpp> 033b41, 7 lines

```

typedef __gnu_pbds::tree<int, __gnu_pbds::null_type, less<int>,
    __gnu_pbds::rb_tree_tag, __gnu_pbds::
    tree_order_statistics_node_update> ordered_set;

```

```

ordered_set st;
//st.order_of_key(x) - find # of elements in st stricly less
    than x
//st.size() - size of st
//st.find_by_order(x) - return iterator to the x-th largest
    element
//st.clear() - clear container

```

RMQ-1D.h

Description: TODO

e37d08, 25 lines

//general sparse table template(can be use for all other
offline queries)
int rmq[N][20];

void build_rmq(vi &a){
for(int j=0;j<20;++j){
for(int i=0;i<(int)a.size();++i){
if(j==0){
rmq[i][0]=a[i];
} else if(i+(1<<(j-1))<(int)a.size()){
rmq[i][j]=min(rmq[i][j-1],rmq[i+(1<<(j-1))][j-1]);
}
}
}

int query(int l, int r){
int i=l,sub_array_size=r-l+1, ans=INF;
for(int j=0;j<30;++j){
if((1<<j)&(sub_array_size)){
ans=min(ans,rmq[i][j]);
i+=(1<<j);
}
}
return ans;
}

RMQ-2D.h

Description: TODO

0f2f45, 46 lines

//general template for 2D offline queries
int rmq[N][N][20][20]; //N need to be around 1e2

void build_rmq(vector<vi>& a){
for(int j=0;j<20;++j){
for(int k=0;k<20;++k){
for(int r=0;r<(int)a.size();++r){
for(int c=0;c<(int)a[0].size();++c){
if(j==0&&k==0) rmq[r][c][0][0]=a[r][c];
else {
if(j==0 && k>0 && (c+(1<<(k-1))<(int)a[0].size())){
rmq[r][c][j][k]=min(rmq[r][c][j][k-1],
rmq[r][c+(1<<(k-1))][j][k-1]);
} else if(k==0 && j>0 && (r+(1<<(j-1))<(int)a.size())){
rmq[r][c][j][k]=min(rmq[r][c][j-1][k],
rmq[r+(1<<(j-1))][c][j-1][k]);
} else if(c+(1<<(k-1))<(int)a[0].size()
&& r+(1<<(j-1))<(int)a.size()){
rmq[r][c][j][k]=min({rmq[r][c][j-1][k-1],
rmq[r][c+(1<<(k-1))][j-1][k-1],
rmq[r+(1<<(j-1))][c][j-1][k-1],
rmq[r+(1<<(j-1))][c+(1<<(k-1))][j-1][k-1]});
}
}
}
}
}

int query(int r1,int c1,int r2,int c2){
int x=r1,y=c1,h=r2-r1+1,w=c2-c1+1,ans=INF;
for(int j=0;j<30;++j){
if((1<<j)&h){
for(int k=0;k<30;++k){
if((1<<k)&w){
ans=min(ans,rmq[x][y][j][k]);
y+=(1<<k);
}
}
y=c1;
x+=(1<<j);
}
}
return ans;
}

2.5 Hashing & Tables

gp-hash-table.h

Description: TODO

<ext/pb_ds/assoc.container.hpp>

3b295b, 7 lines

using namespace __gnu_pbds;

const int RANDOM = chrono::high_resolution_clock::now().
time_since_epoch().count();
struct chash {
int operator()(int x) const { return x ^ RANDOM; }
};
gp_hash_table<int, int, chash> table;

cht.h
Description: TODO
87ad47, 28 lines
struct line {
long long m, c;
long long eval(long long x) { return m * x + c; }
long double intersectX(line l) { return (long double) (c -
l.c) / (l.m - m); }
};

deque<line> dq;
dq.push_front({0, 0});
cant be put in global, remove this to local function
//if query ask for minimum remove this line after 1st insertion

//TODO NOTE***: maximum and minimum value exist in bot left
most and rightmost of convex hull so do search on both l
to r and r to l

//constructing hull from l to r, maintain correct hull at
rightmost
/* ***inserting line (maximum hull)
line cur = line{...some m, ...some c}
while(dq.size()>=cur.intersectX(dq.back())
<=cur.intersectX(dq[dq.size()-2]))dq.pop_back();
dq.pb(cur);
*/

//constructing hull from r to l, maintain correct hull at
leftmost
/* inserting line (maximum hull)
line cur = line{...some m, ...some c}
while(dq.size()>=cur.intersectX(dq[0])>=cur.intersectX(
dq[1])){
dq.pop_front();
}
dq.push_front(cur);

*/

2.6 Graph Algorithms
dijkstra.h
Description: TODO
3fd08c, 17 lines

//initialize dist, proc
for (int i = 1; i <= m; i++) dist[i] = INF;
dist[x] = 0;
priority_queue<pair<ll, int>>q;
q.push({0,x});
while (!q.empty()) {
int a = q.top().second; q.pop();
if (proc[a]) continue;
proc[a] = true; // this fucker i dont remember all the
time
for (auto u : adj[a]) {
int b = u.first, w = u.second;
if (dist[a]+w < dist[b]) {
dist[b] = dist[a]+w;
q.push({-dist[b],b});
}
}
}

floyd-warshall-stp.h
Description: before k-th phase d[i][j] = stp len from i to j using only ver-
tices from set 1,2,...k-1 as internal path, the beginning and end of path are
not restricted by this property.
ab1def, 10 lines

//don't forget to initialize the base case of weight
//this work for negative weight without negative cycle
for (int k = 0; k < n; ++k) {
for (int i = 0; i < n; ++i) {
for (int j = 0; j < n; ++j) {
if (d[i][k] < INF && d[k][j] < INF)
d[i][j] = min(d[i][j], d[i][k] + d[k][j]);
}
}
}

kruskal-mst.h
Description: TODO
5dd25a, 37 lines

//kruskal
vector<tuple<int,int,int>>el;
int parent[N+1], _rank[N+1];

int find_set(int v) {
if (v == parent[v])
return v;
return parent[v] = find_set(parent[v]);
}

void make_set(int v) {
parent[v] = v;
_rank[v] = 1;
}

void union_sets(int a, int b) {
a = find_set(a);
b = find_set(b);
if (a != b) {
if (_rank[a] < _rank[b])
swap(a, b);
parent[b] = a;
_rank[a] += _rank[b];
}
}


```
11 mst(int n){
    sort(all(el)); for(int i=1;i<=n;++i)make_set(i);
    ll mst_cost=0;
    for(auto&t:el){
        int w=get<0>(t), a=get<1>(t), b=get<2>(t);
        if(find_set(a) != find_set(b)){
            mst_cost+=w, union_sets(a,b);
        }
    }
    return mst_cost;
}
```

prim-mst.h
Description: TODO a70ceb, 24 lines

*//*note: unlike kruskal, prim's algorithm assume all vertices belong in same graph*
vector<pair<int,int>>adj[N+1];
bool taken[N+1];
priority_queue<pair<int,int>>PQ;

```
void process(int v){
    taken[v]=1;
    for(auto&p:adj[v]){
        int b=p.second, w=p.first;
        if(!taken[b])PQ.push({-w,-b});
    }
}
```

```
11 mst(){
    process(1);
    ll mst_cost=0;
    while(!PQ.empty()){
        pair<int,int> front=PQ.top(); PQ.pop();
        int u=-front.second, w=-front.first;
        if(!taken[u])
            mst_cost+=w, process(u);
    }
    return mst_cost;
}
```

dinic.h
Description: TODO ce6220, 82 lines

//COPY FROM BENQ GITHUB I dont fucking know how this work
//General graphs: $O(V^2E)$;
//Bipartite matching(unit caps): $O(E \sqrt{2}(V))$
struct Dinic {
 using F = long long; *// flow type*
 struct Edge { int to; F flow, cap; };
 int N;
 vector<Edge> edges;
 vector<vector<int>> adj;
 vector<int> level;
 vector<vector<int>::iterator> it;

 // Initialize Dinic for a graph with _N vertices (0-indexed or 1-indexed)
 void init(int _N) {
 N = _N;
 adj.assign(N, {});
 edges.clear();
 level.resize(N);
 it.resize(N);
 }

 // Add edge u -> v with capacity 'cap', and reverse edge v -> u with capacity 'rev_cap'

```
void addEdge(int u, int v, F cap, F rev_cap = 0) {  
    // forward edge  
    adj[u].push_back((int)edges.size());  
    edges.push_back({v, 0, cap});  
    // reverse edge  
    adj[v].push_back((int)edges.size());  
    edges.push_back({u, 0, rev_cap});  
}  
  
// Build level graph via BFS  
bool bfs(int s, int t) {  
    fill(level.begin(), level.end(), -1);  
    for (int i = 0; i < N; i++) it[i] = adj[i].begin();  
    queue<int> q;  
    level[s] = 0;  
    q.push(s);  
    while (!q.empty()) {  
        int u = q.front(); q.pop();  
        for (int idx : adj[u]) {  
            const Edge &e = edges[idx];  
            if (level[e.to] < 0 && e.flow < e.cap) {  
                level[e.to] = level[u] + 1;  
                q.push(e.to);  
            }  
        }  
    }  
    return level[t] >= 0;  
}
```

```
// DFS to send flow  
F dfs(int u, int t, F pushed) {  
    if (u == t || pushed == 0) return pushed;  
    for (; it[u] != adj[u].end(); ++it[u]) {  
        int idx = *it[u];  
        Edge &e = edges[idx];  
        if (level[e.to] != level[u] + 1 || e.flow == e.cap)  
            continue;  
        F tr = dfs(e.to, t, min(pushed, e.cap - e.flow));  
        if (tr > 0) {  
            e.flow += tr;  
            edges[idx ^ 1].flow -= tr; // reverse edge  
            return tr;  
        }  
    }  
    return 0;  
}
```

```
// Compute max flow from s to t  
F maxFlow(int s, int t) {  
    F flow = 0;  
    while (bfs(s, t)) {  
        while (F pushed = dfs(s, t, numeric_limits<F>::max())) {  
            flow += pushed;  
        }  
    }  
    return flow;  
}
```

// After maxFlow, vertices reachable from s in residual graph have level >= 0.
// Edges from reachable u to unreachable v form a min-cut.

eulerian-cycle.h
Description: TODO 87df80, 25 lines

//TODO: checking all node degrees is even ?
//TODO: checking if all edges are connectedly reachable

```
stack<int> st;  
vi res;  
st.push(1);  
while(!st.empty()){  
    int v = st.top();  
    if(deg[v] == 0){  
        res.pb(v);  
        st.pop();  
    } else {  
        int rm = -1; //must exist  
        for(auto &b:adj[v]){  
            rm = b;  
            break;  
        }  
        adj[v].erase(rm); deg[v]--;  
        adj[rm].erase(v); deg[rm]--;  
        st.push(rm);  
    }  
}  
//reverse the res if the edge is directed !! also changing the checking condition  
for(auto &x:res)cout << x << " ";  
cout << nl;
```

2.7 Graph Decompositions & Connectivity

articulation-points.h
Description: TODO 23f413, 37 lines

int n; *// number of nodes*
vector<vector<int>> adj; *// adjacency list of graph*

vector<bool> visited;
vector<int> tin, low;
int timer;

```
void dfs(int v, int p = -1) {  
    visited[v] = true;  
    tin[v] = low[v] = timer++;  
    int children=0;  
    for (int to : adj[v]) {  
        if (to == p) continue;  
        if (visited[to]) {  
            low[v] = min(low[v], tin[to]);  
        } else {  
            dfs(to, v);  
            low[v] = min(low[v], low[to]);  
            if (low[to] >= tin[v] && p!=-1)  
                IS_CUTPOINT(v);  
            ++children;  
        }  
    }  
    if(p == -1 && children > 1)  
        IS_CUTPOINT(v);  
}
```

```
void find_cutpoints() {  
    timer = 0;  
    visited.assign(n, false);  
    tin.assign(n, -1);  
    low.assign(n, -1);  
    for (int i = 0; i < n; ++i) {  
        if (!visited[i])  
            dfs (i);  
    }  
}
```

bridge-finding.h

Description: TODO747a19, 30 lines

//NOTE**: not work for multigraph, I'm too lazy too fix for now
/*
 dfs-tree bridge finding algorithm
 let lvl[root] = 1 (root = 1)
*/

int root = 1;
vector<pair<int,int>> bridge;
int dp[N+1], lvl[N+1];

void dfs_tree(int a, int e){
 if(a == root)lvl[a] = 1;
 dp[a] = 0;
 for(auto &b:adj[a]){
 if(b == e)continue;

 if(lvl[b] == 0){
 lvl[b] = lvl[a] + 1;
 dfs_tree(b, a);
 dp[a] += dp[b];
 } else if(lvl[b] < lvl[a]){
 dp[a]++;
 } else if(lvl[b] > lvl[a]){
 dp[a]--;
 }
 }

 if(lvl[a] > 1 and dp[a] == 0){
 bridge.pb({min(a,e), max(a,e)});
 }
}

tarjan-scc.h

Description: TODO3e5381, 35 lines

//Trajan's algorithm
vi adj[N+1];
int id[N+1], low[N+1];
bool vst[N+1], in_stack[N+1];

stack<int>st;
vector<vi>scc;
vi comp;
int tin=0;
void dfs(int a){
 st.push(a);
 vst[a]=in_stack[a]=1;
 id[a]=low[a]=tin++;

 for(auto&b:adj[a]){
 if(!vst[b]){
 dfs(b);
 low[a]=min(low[a],low[b]); //Backtrack low-link value
 } else if(in_stack[b]){
 //Backtrack low-link value
 low[a]=min(low[a],low[b]);
 }
 }

 if(id[a] == low[a]){ //pop scc
 while(!st.empty()){
 int v=st.top();
 comp.pb(v), st.pop();
 in_stack[v]=0;
 if(v==a)break; //stop when scc is found
 }
 }
 if(!comp.empty()){

scc.pb(comp), comp.clear();
}
}

centroid-decomposition.h

Description: TODO70d410, 32 lines

vector<int> adj[N];
bool is_removed[N];
int subtree_size[N];
int get_subtree_size(int node, int parent = -1) {
 subtree_size[node] = 1;
 for (int child : adj[node]) {
 if (child == parent || is_removed[child]) { continue; }
 subtree_size[node] += get_subtree_size(child, node);
 }
 return subtree_size[node];
}

int get_centroid(int node, int tree_size, int parent = -1) {
 for (int child : adj[node]) {
 if (child == parent || is_removed[child]) { continue; }
 if (subtree_size[child] * 2 > tree_size) {
 return get_centroid(child, tree_size, node);
 }
 }
 return node;
}

void build_centroid_decomp(int node = 0) {
 int centroid = get_centroid(node, get_subtree_size(node));
 is_removed[centroid] = true;

 // do something

 for (int child : adj[centroid]) {
 if (is_removed[child]) { continue; }
 build_centroid_decomp(child);
 }
}

hld.h

Description: TODOe4ffaf, 152 lines

/*hld*/
//TODO: initialize constant N
vector<int>adj[N];

void add_edges(int a, int b){
 adj[a].pb(b);
 adj[b].pb(a);
}

const int LOG = 20;
int timer = 0, seg_tree_size = 0;
int depth[N], parent[N], n_subtree[N], heavyChild[N], chain[N],
 SegTreePos[N];
int cost[N];
int up[N][LOG]; // 2^j-th ancestor of n

/*SegTree*/
//finding max edge query
ll tree[4*N];
void update(int node,int n_l,int n_r,int q_i,int value){
 if(n_r<q_i || q_i<n_l)return;
 if(q_i==n_l && n_r==q_i){
 tree[node] = value;
 return;
 }

 int mid = (n_r+n_l)/2;
 update(2*node,n_l,mid,q_i,value);

update(2*node+1,mid+1,n_r,q_i,value);
tree[node] = max(tree[2*node], tree[2*node+1]);
}

long long f(int node,int n_l,int n_r,int q_l,int q_r){
 if(n_r<q_l || q_r<n_l)return 0;
 if(q_l<=n_l && n_r<=q_r)return tree[node];
 int mid = (n_l+n_r)/2;
 return max(f(2*node,n_l,mid,q_l,q_r) , f(2*node+1,mid+1,n_r
 ,q_l,q_r));
}
/*SegTree*/

//preprocessing the arrays above
void dfs(int a,int e){
 chain[a] = a;
 n_subtree[a] = 1;
 int bestSon = -1, hmax = -1;
 for(auto b:adj[a]){
 if(b == e)continue;
 depth[b] = depth[a] + 1;
 parent[b] = a;
 up[b][0] = parent[b];
 for(int i=1;i<LOG;++i){
 up[b][i] = up[up[b][i-1]][i-1];
 }
 dfs(b,a);
 n_subtree[a] += n_subtree[b];
 if(n_subtree[b] > hmax){
 hmax = n_subtree[b], bestSon = b;
 }
 }
 heavyChild[a] = bestSon;
}

void computeHeavyChains(int a, int e){
 if(heavyChild[a] != -1){
 chain[heavyChild[a]] = chain[a];
 }
 for(auto b:adj[a]){
 if(b == e)continue;
 computeHeavyChains(b, a);
 }
}

void setHeavyChains(int a, int e){
 SegTreePos[a] = timer++;
 if(heavyChild[a] != -1){
 setHeavyChains(heavyChild[a], a);
 int w = 0;
 for(auto b:adj[a]){
 if(b == heavyChild[a]){
 w = 1;
 break;
 }
 }
 //setting cost of heavyChild[a] = weight of edge (a,
 heavyChild[a])
 cost[heavyChild[a]] = w; //change when tree is weighted
 }
 for(auto b:adj[a]){
 if(b == e || heavyChild[a] == b)continue;
 cost[b] = 1; //change when tree is weighted
 setHeavyChains(b ,a);
 }
}

void buildSegTree(int n_node){
 seg_tree_size = n_node;

```
while(_builtin_popcount(seg_tree_size)!=1)++seg_tree_size;
for(int i=0;i<n_node;++i){
    update(1,0,seg_tree_size-1,SegTreePos[i], cost[i]);
}
for(int i=seg_tree_size-1;i>=1;--i){
    tree[i] = max(tree[2*i], tree[2*i+1]);
}
}

ll queryPath(int mother, int son){
    ll ans = LONG_MIN;
    while(chain[mother] != chain[son]){
        if(chain[son] == son){
            ans = max(ans,f(1,0,seg_tree_size-1,SegTreePos[son],SegTreePos[son]));
        } else {
            ans = max(ans, f(1,0,seg_tree_size-1,SegTreePos[chain[son]],SegTreePos[son]));
        }
        son = parent[chain[son]];
    }

    ans = max(ans, f(1,0,seg_tree_size-1,SegTreePos[mother]+1,SegTreePos[son]));

    return ans;
}

int lca(int a, int b){
    if(depth[a]<depth[b])swap(a,b);
    int k = depth[a] - depth[b];
    for(int i=LOG-1;i>=0;--i){
        if(k & (1<<i)){
            a = up[a][i];
        }
    }

    if(a == b)return a;
    for(int i=LOG-1;i>=0;--i){
        if(up[a][i] != up[b][i]){
            a = up[a][i];
            b = up[b][i];
        }
    }
    return up[a][0];
}

ll query(int x, int y){
    int l = lca(x,y);
    return max( queryPath(l, x), queryPath(l, y)); //combine the answer
}

void hld_init(int n){
    dfs(0,-1);
    computeHeavyChains(0,-1);
    setHeavyChains(0,-1);
    buildSegTree(n);
}

/*hld*/

lca.h
Description: TODO
//TODO: initialize tree(adj list)
const int LOG = 20;
int dep[N], parent[N];
```

```
int up[N][LOG]; // 2^j-th ancestor of n

void dfs(int a,int e){
    for(auto b:adj[a]){
        if(b == e)continue;
        dep[b] = dep[a] + 1;
        parent[b] = a;
        up[b][0] = parent[b];
        for(int i=1;i<LOG;++i){
            up[b][i] = up[up[b][i-1]][i-1];
        }
        dfs(b,a);
    }
}

int lca(int a, int b){
    if(dep[a]<dep[b])swap(a,b);
    int k = dep[a] - dep[b];
    for(int i=LOG-1;i>=0;--i){
        if(k & (1<<i)){
            a = up[a][i];
        }
    }

    if(a == b)return a;
    for(int i=LOG-1;i>=0;--i){
        if(up[a][i] != up[b][i]){
            a = up[a][i];
            b = up[b][i];
        }
    }
    return up[a][0];
}

kth-ancestor.h
Description: TODO
int kth_ancestor(int node,int k){
    if(dep[node] < k)return -1;
    for(int i = 0;i < LOG; ++i){
        if(k & (1<<i)){
            node = up[node][i];
        }
    }
    return node;
}

tree-hashing.h
Description: TODO
/*
    very acurate rooted tree hashing
    don't forget to check tree invariant such as tree size and
    # of centroid
*/
map<vector<int>, int> hasher;

int hashify(vector<int> x) {
    sort(x.begin(), x.end());
    if(!hasher[x]) {
        hasher[x] = hasher.size();
    }
    return hasher[x];
}

int _hash(int v, int e, vector<vector<int>>&adj) { // get a "
    hash" of v's subtree, e is parent vertex
    vector<int> children;
    for(int u: adj[v]) {
```

```
        if( u == e )continue;
        children.push_back(_hash(u, v, adj));
    }
    return hashify(children);
}

2.8 String Processing
AC-automaton.h
Description: TODO
const int K = 26;

struct Vertex {
    int next[K];
    bool output = false;
    int p = -1;
    char pch;
    int link = -1;
    int go[K];

    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};

vector<Vertex> t(1);

void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = t.size();
            t.emplace_back(v, ch);
        }
        v = t[v].next[c];
    }
    t[v].output = true;
}

int go(int v, char ch);

int get_link(int v) {
    if (t[v].link == -1) {
        if (v == 0 || t[v].p == 0)
            t[v].link = 0;
        else
            t[v].link = go(get_link(t[v].p), t[v].pch);
    }
    return t[v].link;
}

int go(int v, char ch) {
    int c = ch - 'a';
    if (t[v].go[c] == -1) {
        if (t[v].next[c] != -1)
            t[v].go[c] = t[v].next[c];
        else
            t[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
    }
    return t[v].go[c];
}

kmp.h
Description: TODO
int b[N];
int cnt = 0;
```

```
void knp_proc(string t,string p){
    int i=0,j=-1;b[0] = -1;
    while(i<(int)p.length()){
        while(j>=0 && p[i]!=p[j]) j = b[j];
        ++i; ++j;
        b[i] = j;
    }
}

void knp_search(string t,string p){//count number of occurence of p in t
    int i=0,j=0;
    while(i<(int)t.length()){
        while(j>=0 && t[i] != p[j]) j = b[j];
        ++i; ++j;
        if(j==(int)p.length()){
            ++cnt;
            j = b[j];
        }
    }
}

vector<int> prefix_function(string s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}
```

z-function.h

Description: TODO

9a2512, 18 lines

```
vector<int> z_function(string s) {
    int n = s.size();
    vector<int> z(n);
    int l = 0, r = 0;
    for(int i = 1; i < n; i++) {
        if(i < r) {
            z[i] = min(r - i, z[i - 1]);
        }
        while(i + z[i] < n && s[z[i]] == s[i + z[i]]) {
            z[i]++;
        }
        if(i + z[i] > r) {
            l = i;
            r = i + z[i];
        }
    }
    return z;
}
```

manacher.h

Description: TODO

3069fe, 37 lines

```
//sub-palindrome queries
vector<int> manacher_odd(string s) {
    int n = s.size();
    s = "$" + s + "^";
    vector<int> p(n + 2);
    int l = 1, r = 1;
    for(int i = 1; i <= n; i++) {
```

```
        p[i] = max(0, min(r - i, p[l + (r - i)]));
        while(s[i - p[i]] == s[i + p[i]]) {
            p[i]++;
        }
        if(i + p[i] > r) {
            l = i - p[i], r = i + p[i];
        }
    }
    return vector<int>(begin(p) + 1, end(p) - 1);
}
```

```
vector<int> manacher(string s) {
    string t;
    for(auto c: s) {
        t += string("#") + c;
    }
    auto res = manacher_odd(t + "#");
    return vector<int>(begin(res) + 1, end(res) - 1);
}
```

```
bool is_palindrome(int l, int r, vector<int> &v){
    if(v[l + r] < (r - l + 1))return false;
    return true;
}
```

```
vector<int> build_manacher(string s){ //0 base index string
    auto v = manacher(s);
    for(auto&x:v)--x;
    return v;
}
```

string-hashing.h

Description: TODO

ba27df, 17 lines

```
typedef __int128 HASH;
HASH p[NN], h[NN];
constexpr HASH M = 1000000000000000003;
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
    count());//delete this if using my template
#define uid(a, b) uniform_int_distribution<long long>(a, b)(rng)
//delete this if using my template

void compute_hash(string const& s){
    p[0] = 1, p[1] = uid(256, M-1);
    for(ll i=0;i<(int)s.length();++i){
        p[i+1] = p[i]*p[1]%M;
        h[i+1] = (h[i]*p[1] + s[i])%M;
    }
}

HASH sub_hash(ll l, ll r){ //range [l, r)
    return (h[r] - p[r-l]*h[l]%M + M)%M;
}
```

double-hashing-string.h

Description: TODO

276f01, 26 lines

```
//typedef
typedef long long ll;
typedef pair<ll,ll> pl;
#define M 1000000321
#define OP(x, y) pl operator x (pl a, pl b){return {a.first x b
    .first, (a.second y b.second) % M }; }
OP(+, +) OP(*, *) OP(-, + M -)
//random number generator
mt19937 gen(chrono::steady_clock::now().time_since_epoch().
    count());
uniform_int_distribution<ll> dist(256, M - 1);
```

```
//queries - check if S[i:i+l] == S[j:j+l](inclusive), S is a string, [:] is slice
#define H(i, l) (h[(i) + (l)] - h[i] * p[l])
#define EQ(i, j, l) (H(i, l) == H(j, l))
//preprocessing
const int N = 2e5;
string s;
pl p[N], h[N];
ll n;

int main(){
    cin >> n >> s;
    p[0] = {1,1}, p[1] = {dist(gen) | 1, dist(gen) };
    for(ll i=1;i<=(ll)s.length();++i){
        p[i] = p[i-1] * p[1];
        h[i] = h[i-1] * p[1] + make_pair(s[i-1], s[i-1]);
    }
}
```

suffix-array.h

Description: TODO

4ca004, 53 lines

```
vector<int> sort_cyclic_shifts(string const& s) {
    int n = s.size();
    const int alphabet = 256;

    vector<int> p(n), c(n), cnt(max(alphabet, n), 0);
    for (int i = 0; i < n; i++)
        cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (int i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    int classes = 1;
    for (int i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])
            classes++;
        c[p[i]] = classes - 1;
    }

    vector<int> pn(n), cn(n);
    for (int h = 0; (1 << h) < n; ++h) {
        for (int i = 0; i < n; i++) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0)
                pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (int i = 0; i < n; i++)
            cnt[c[pn[i]]]++;
        for (int i = 1; i < classes; i++)
            cnt[i] += cnt[i-1];
        for (int i = n-1; i >= 0; i--)
            p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0;
        classes = 1;
        for (int i = 1; i < n; i++) {
            pair<int, int> cur = {c[p[i]], c[(p[i] + (1 << h))
                % n]};
            pair<int, int> prev = {c[p[i-1]], c[(p[i-1] + (1 <<
                h)) % n]};
            if (cur != prev)
                ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}
```

```
}

vector<int> suffix_array_construction(string s) {
    s += "$";
    vector<int> sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}
```

suffix-automaton.h
Description: TODO

```
struct state {
    int len, link;
    map<char, int> next;
    map<char, int> go;
};

const int MAXLEN = 100001; //this one is 10^5 becareful
state st[MAXLEN * 2];
int sz, last;

void sa_init() {
    st[0].len = 0;
    st[0].link = -1;
    sz++;
    last = 0;
}

void sa_extend(char c) {
    int cur = sz++;
    st[cur].len = st[last].len + 1;
    int p = last;
    while (p != -1 && !st[p].next.count(c)) {
        st[p].next[c] = cur;
        p = st[p].link;
    }
    if (p == -1) {
        st[cur].link = 0;
    } else {
        int q = st[p].next[c];
        if (st[p].len + 1 == st[q].len) {
            st[cur].link = q;
        } else {
            int clone = sz++;
            st[clone].len = st[p].len + 1;
            st[clone].next = st[q].next;
            st[clone].link = st[q].link;
            while (p != -1 && st[p].next[c] == q) {
                st[p].next[c] = clone;
                p = st[p].link;
            }
            st[q].link = st[cur].link = clone;
        }
    }
    last = cur;
}

int sa_go(int v, char c) {
    if (st[v].go.count(c)) return st[v].go[c];
    if (st[v].next.count(c)) return st[v].go[c] = st[v].next[c];
    if (st[v].link == -1) return st[v].go[c] = 0; // fallback to root
    return st[v].go[c] = sa_go(st[v].link, c);
}
```

```
trie.h
Description: TODO
e121b2, 26 lines

// string trie structure
const int K = 26;

struct node{
    int to[K];
    bool output = false;

    node(){
        fill(begin(to), end(to), -1);
    }
};

vector<node>trie(1);

void add(const& string s){
    int v = 0;
    for(char ch: s){
        int c = ch - 'a';
        if(trie[v][c] == -1){
            trie[v][c] = trie.size();
            trie.push_back(node());
        }
        v = trie[v][c];
    }
    trie[v].output = true;
}
```

lyndon-factorization.h
Description: TODO

```
vector<string> duval(string const& s) {
    int n = s.size();
    int i = 0;
    vector<string> factorization;
    while (i < n) {
        int j = i + 1, k = i;
        while (j < n && s[k] <= s[j]) {
            if (s[k] < s[j])
                k = i;
            else
                k++;
            j++;
        }
        while (i <= k) {
            factorization.push_back(s.substr(i, j - k));
            i += j - k;
        }
        return factorization;
    }
}

string min_cyclic_string(string s) {
    s += s;
    int n = s.size();
    int i = 0, ans = 0;
    while (i < n / 2) {
        ans = i;
        int j = i + 1, k = i;
        while (j < n && s[k] <= s[j]) {
            if (s[k] < s[j])
                k = i;
            else
                k++;
            j++;
        }
        while (i <= k)
            i += j - k;
    }
}
```

```
}
return s.substr(ans, n / 2);
}

2.9 Computational Geometry
geometry.h
Description: TODO
963fd3, 167 lines

//Geometry
#pragma GCC target("avx2")
#pragma GCC optimize("O3")
#pragma GCC optimize("unroll-loops")

typedef long long int ll;
typedef long double ld;
typedef complex<ld> pt;
struct line {
    pt P, D; bool S = false;
    line(pt p, pt q, bool b = false) : P(p), D(q - p), S(b) {}
    line(pt p, ld th) : P(p), D(polar((ld)1, th)) {}
};
struct circ { pt C; ld R; };

#define X real()
#define Y imag()
#define CRS(a, b) (conj(a) * (b)).Y //scalar cross product
#define DOT(a, b) (conj(a) * (b)).X //dot product
#define U(p) ((p) / abs(p)) //unit vector in direction of p (
//don't use if Z(p) == true)
#define Z(x) (abs(x) < EPS)
#define A(a) (a).begin(), (a).end() //shortens sort(),
//upper_bound(), etc. for vectors

//constants (INF and EPS may need to be modified)
ld PI = acos(-1), INF = 1e20, EPS = 1e-12;
pt I = {0, 1};

//true if d1 and d2 parallel (zero vectors considered parallel
//to everything)
bool parallel(pt d1, pt d2) { return Z(d1) || Z(d2) || Z(CRS(U(
d1), U(d2))); }

//"above" here means if l & p are rotated such that l.D points
//in the +x direction, then p is above l. Returns arbitrary
//boolean if p is on l
bool above_line(pt p, line l) { return CRS(p - l.P, l.D) > 0; }

//true if p is on line l
bool on_line(pt p, line l) { return parallel(l.P - p, l.D) &&
(l1.S || DOT(l.P - p, l.P + l.D - p) <= EPS); }

//returns 0 for no intersection, 2 for infinite intersections,
//1 otherwise. p holds intersection pt
ll intsct(line l1, line l2, pt& p) {
    if(parallel(l1.D, l2.D)) //note that two parallel segments
//sharing one endpoint are considered to have infinite
//intersections here
        return 2 * (on_line(l1.P, l2) || on_line(l1.P + l1.D, l2)
|| on_line(l2.P, l1) || on_line(l2.P + l2.D, l1));
    pt q = l1.P + l1.D * CRS(l2.D, l2.P - l1.P) / CRS(l2.D, l1.D)
;
    if(on_line(q, l1) && on_line(q, l2)) { p = q; return 1; }
    return 0;
}

//closest pt on l to p
pt cl_pt_on_l(pt p, line l) {
    pt q = l.P + DOT(U(l.D), p - l.P) * U(l.D);
    if(on_line(q, l)) return q;
}
```

```
    return abs(p - l.P) < abs(p - l.P - l.D) ? l.P : l.P + l.D;
}

//distance from p to l
ld dist_to(pt p, line l) { return abs(p - cl_pt_on_l(p, l)); }

//p reflected over l
pt refl_pt(pt p, line l) { return conj((p - l.P) / U(l.D)) * U(l.D) + l.P; }

//ray r reflected off l (if no intersection, returns original ray)
line reflect_line(line r, line l) {
    pt p; if(intsct(r, l, p) - 1) return r;
    return line(p, p + INF * (p - refl_pt(r.P, l)), 1);
}

//altitude from p to l
line alt(pt p, line l) { l.S = 0; return line(p, cl_pt_on_l(p, l)); }

//angle bisector of angle abc
line ang_bis(pt a, pt b, pt c) { return line(b, b + INF * (U(a - b) + U(c - b)), 1); }

//perpendicular bisector of l (assumes l.S == 1)
line perp_bis(line l) { return line(l.P + l.D / (ld)2, arg(l.D * I)); }

//orthocenter of triangle abc
pt orthocent(pt a, pt b, pt c) { pt p; intsct(alt(a, line(b, c)), alt(b, line(a, c)), p); return p; }

//incircle of triangle abc
circ incirc(pt a, pt b, pt c) {
    pt cent; intsct(ang_bis(a, b, c), ang_bis(b, a, c), cent);
    return {cent, dist_to(cent, line(a, b))};
}

//circumcircle of triangle abc
circ circumcirc(pt a, pt b, pt c) {
    pt cent; intsct(perp_bis(line(a, b, l)), perp_bis(line(a, c, l)), cent);
    return {cent, abs(cent - a)};
}

//is pt p inside the (not necessarily convex) polygon given by poly
bool in_poly(pt p, vector<pt>& poly) {
    line l = line(p, {INF, INF * PI}, 1);
    bool ans = false;
    pt lst = poly.back(), tmp;
    for(pt q : poly) {
        line s = line(q, lst, 1); lst = q;
        if(on_line(p, s)) return false; //change if border included
        else if(intsct(l, s, tmp)) ans = !ans;
    }
    return ans;
}

//area of polygon, vertices in order (cw or ccw)
ld area(vector<pt>& poly) {
    ld ans = 0;
    pt lst = poly.back();
    for(pt p : poly) ans += CRS(lst, p), lst = p;
    return abs(ans / 2);
}

//perimeter of polygon, vertices in order (cw or ccw)
```

```
ld perim(vector<pt>& poly) {
    ld ans = 0;
    pt lst = poly.back();
    for(pt p : poly) ans += abs(lst - p), lst = p;
    return ans;
}

//centroid of polygon, vertices in order (cw or ccw)
pt centroid(vector<pt>& poly) {
    ld area = 0;
    pt lst = poly.back(), ans = {0, 0};
    for(pt p : poly) {
        area += CRS(lst, p);
        ans += CRS(lst, p) * (lst + p) / (ld)3;
        lst = p;
    }
    return ans / area;
}

//invert a point over a circle (doesn't work for center of circle)
pt circInv(pt p, circ c) {
    return c.R * c.R / conj(p - c.C) + c.C;
}

//vector of intersection pts of two circs (up to 2) (if circles same, returns empty vector)
vector<pt> intsctCC(circ c1, circ c2) {
    if(c1.R < c2.R) swap(c1, c2);
    pt d = c2.C - c1.C;
    if(Z(abs(d) - c1.R - c2.R)) return {c1.C + polar(c1.R, arg(c2.C - c1.C))};
    if(!Z(d) && Z(abs(d) - c1.R + c2.R)) return {c1.C + c1.R * U(d)};
    if(abs(abs(d) - c1.R) >= c2.R - EPS) return {};
    ld th = acos1((c1.R * c1.R + norm(d) - c2.R * c2.R) / (2 * c1.R * abs(d)));
    return {c1.C + polar(c1.R, arg(d) + th), c1.C + polar(c1.R, arg(d) - th)};
}

//vector of intersection pts of a line and a circ (up to 2)
vector<pt> intsctCL(circ c, line l) {
    vector<pt> v, ans;
    if(parallel(l.D, c.C - l.P)) v = {c.C + c.R * U(l.D), c.C - c.R * U(l.D)};
    else v = intsctCC(c, circ(refl_pt(c.C, l), c.R));
    for(pt p : v) if(on_line(p, l)) ans.push_back(p);
    return ans;
}

//external tangents of two circles (negate c2.R for internal tangents)
vector<line> circTangents(circ c1, circ c2) {
    pt d = c2.C - c1.C;
    ld dr = c1.R - c2.R, d2 = norm(d), h2 = d2 - dr * dr;
    if(Z(d2) || h2 < 0) return {};
    vector<line> ans;
    for(ld sg : {-1, 1}) {
        pt u = (d * dr + d * I * sqrt(h2) * sg) / d2;
        ans.push_back(line(c1.C + u * c1.R, c2.C + u * c2.R, 1));
    }
    if(Z(h2)) ans.pop_back();
    return ans;
}
```

```
closest-pair-of-points.h
Description: TODO
85eeeb, 67 lines

struct pt {
    int x, y, id;
};

struct cmp_x {
    bool operator()(const pt & a, const pt & b) const {
        return a.x < b.x || (a.x == b.x && a.y < b.y);
    }
};

struct cmp_y {
    bool operator()(const pt & a, const pt & b) const {
        return a.y < b.y;
    }
};

int n;
vector<pt> a;

double mindist;
pair<int, int> best_pair;

void upd_ans(const pt & a, const pt & b) {
    double dist = sqrt((a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y));
    if (dist < mindist) {
        mindist = dist;
        best_pair = {a.id, b.id};
    }
}

vector<pt> t;

void rec(int l, int r) {
    if (r - l <= 3) {
        for (int i = l; i < r; ++i) {
            for (int j = i + 1; j < r; ++j) {
                upd_ans(a[i], a[j]);
            }
        }
        sort(a.begin() + l, a.begin() + r, cmp_y());
        return;
    }

    int m = (l + r) >> 1;
    int midx = a[m].x;
    rec(l, m);
    rec(m, r);

    merge(a.begin() + l, a.begin() + m, a.begin() + m, a.begin() + r, t.begin(), cmp_y());
    copy(t.begin(), t.begin() + r - l, a.begin() + l);

    int tsz = 0;
    for (int i = l; i < r; ++i) {
        if (abs(a[i].x - midx) < mindist) {
            for (int j = tsz - 1; j >= 0 && a[i].y - t[j].y < mindist; --j)
                upd_ans(a[i], t[j]);
            t[tsz++] = a[i];
        }
    }
}

void call_rec(){
    t.resize(n);
}
```

```
sort(a.begin(), a.end(), cmp_x());
mindist = 1E20;
rec(0, n);
}
```

2.10 Advanced Algorithms

fft.h

Description: TODO

cbf4b6, 63 lines

```
//from cp algorithm the inplace-computation fft part
using cd = complex<double>;
const double PI = acos(-1);

int reverse(int num, int lg_n) {
    int res = 0;
    for (int i = 0; i < lg_n; i++) {
        if (num & (1 << i))
            res |= 1 << (lg_n - 1 - i);
    }
    return res;
}

void fft(vector<cd> & a, bool invert) {
    int n = a.size();
    int lg_n = 0;
    while ((1 << lg_n) < n)
        lg_n++;

    for (int i = 0; i < n; i++) {
        if (i < reverse(i, lg_n))
            swap(a[i], a[reverse(i, lg_n)]);
    }

    for (int len = 2; len <= n; len <= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            cd w(1);
            for (int j = 0; j < len / 2; j++) {
                cd u = a[i+j], v = a[i+j+len/2] * w;
                a[i+j] = u + v;
                a[i+j+len/2] = u - v;
                w *= wlen;
            }
        }
    }

    if (invert) {
        for (cd & x : a)
            x /= n;
    }
}

vector<int> multiply(vector<int> const& a, vector<int> const& b) {
    vector<cd> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    int n = 1;
    while (n < (int)a.size() + (int)b.size())
        n <= 1;
    fa.resize(n);
    fb.resize(n);

    fft(fa, false);
    fft(fb, false);
    for (int i = 0; i < n; i++)
        fa[i] *= fb[i];
    fft(fa, true);

    vector<int> result(n);
```

```
for (int i = 0; i < n; i++)
    result[i] = round(fa[i].real());
return result;
}

mo2D.h
Description: TODO
9df2fb, 49 lines

/* always use zero based indexing*/
/* there N/B blocks so left move ~ N/B*B + Q*B, right move ~ N/
    B*B + (N/B)*B */
/* so O(N^2/B + N + QB) ~ O((N+Q)sqrt(N)) when B = sqrt(N) */
/* when Q~N it's ~ O(N^3/2) */
void remove(int idx); // TODO: remove value at idx from data
    structure
void add(int idx); // TODO: add value at idx from data
    structure
int get_answer(); // TODO: extract the current answer of the
    data structure

int block_size;

struct Query {
    int l, r, idx;
    bool operator<(Query other) const
    {
        return make_pair(l / block_size, r) <
            make_pair(other.l / block_size, other.r);
    }
};

vector<int> mo_s_algorithm(vector<Query>& queries) {
    vector<int> answers(queries.size());
    sort(queries.begin(), queries.end());

    // TODO: initialize data structure

    int cur_l = 0;
    int cur_r = -1;
    // invariant: data structure will always reflect the range
        [cur_l, cur_r]
    for (Query q : queries) {
        while (cur_l > q.l) {
            cur_l--;
            add(cur_l);
        }
        while (cur_r < q.r) {
            cur_r++;
            add(cur_r);
        }
        while (cur_l < q.l) {
            remove(cur_l);
            cur_l++;
        }
        while (cur_r > q.r) {
            remove(cur_r);
            cur_r--;
        }
        answers[q.idx] = get_answer();
    }
    return answers;
}

mo3D.h
Description: TODO
dc4a5e, 62 lines

/* always use zero based indexing*/
/* ~ O(N^(5/3)) */
int block_size;
```

```
struct Query {
    int l, r, t, idx;
    bool operator<(Query other) const
    {
        return make_tuple(l / block_size, r / block_size, t) <
            make_tuple(other.l / block_size, other.r /
                block_size, other.t);
    }
};

int ans[N];
void mo_s_algorithm(vector<Query>& queries) {
    sort(queries.begin(), queries.end());
    // TODO: initialize data structure

    int cur_l = 0;
    int cur_r = -1;
    int cur_t = -1;
    // invariant: data structure will always reflect the range
        [cur_l, cur_r]
    for (Query q : queries) {
        while (cur_l > q.l) {
            cur_l--;
            //add(cur_l)
        }
        while (cur_r < q.r) {
            cur_r++;
            //add(cur_r)
        }
        while (cur_l < q.l) {
            //remove(cur_l);
            cur_l++;
        }
        while (cur_r > q.r) {
            //remove(cur_r);
            cur_r--;
        }

        while(cur_t < q.t){
            cur_t++;
            //update
        }
        while(cur_t > q.t){
            //update rollback
            cur_t--;
        }
        ans[q.idx] = get_answer(); // declare array for this
    }
}

void getBlockSize(int n, int q){
    if (q >= n) {
        // most common: Q ~ N
        block_size = max(1, (int)pow(n, 2.0/3.0));
    } else {
        // general cube-root rule
        block_size = max(1, (int)pow((long double)n*n / q,
            1.0/3.0));
    }
    // then sort your queries by (L/B, R/B, T) or via Hilbert
}

divide-and-conquer-dp.h
Description: TODO
108b88, 55 lines

//TODO: initialize dp , initialize cost() function of use slide
    ()
//ll dp[N][M];
```

```
//generic implementation for sliding range technique for logn
cost()
//(persistent segtree alternative)
ll ccost = 0;
int cl = 0, cr = -1;
void slide(int l, int r){
    while(cr < r){
        ++cr;
        //add();
        //...
    }
    while(cl > l){
        --cl;
        //add();
        //...
    }
    while(cr > r){
        //remove();
        //...
        --cr;
    }
    while(cl < l){
        //remove();
        //...
        ++cl;
    }
}

void compute(int l, int r, int optl, int opt, int j){
    if(l>r) return;

    int mid = (l+r)>>1;
    //pair<ll, int> best = {0,-1};
    //pair<ll, int> best = {LINF,-1};

    //dp is satisfy quadrangle IE if cost() satisfy qudrangle
    IE
    //if cost() is QF => opt() is nondecreasing
    for(int k=optl;k<=min(mid,opt);++k){
        slide(k,mid);
        //best = max(best, {(k>0)?dp[k-1][j-1]:0} + ccost, k );
        //best = min(best, {(k>0)?dp[k-1][j-1]:0} + ccost, k );
    }

    //dp[mid][j] = max(dp[mid][j], best.first);
    //dp[mid][j] = min(dp[mid][j], best.first);
    int opt = best.second;
    if(l!=r){
        compute(l,mid-1,optl,opt,j);
        compute(mid+1,r,opt,opt,j);
    }
}

//TODO: set dp to LINF or -LINF
```

cellul4r (3)

2SAT.h

Description: solve 2 sat form of or to implies

Time: $O(N + M)$

025007, 70 lines

```
struct TwoSatSolver {
    int n_vars;
    int n_vertices;
    vector<vector<int>> adj, adj_t;
```

```
vector<bool> used;
vector<int> order, comp;
vector<bool> assignment;
TwoSatSolver(int n_vars) : n_vars(n_vars), n_vertices(2 *
    n_vars), adj(n_vertices), adj_t(n_vertices), used(
    n_vertices), order(), comp(n_vertices, -1), assignment
    (n_vars) {
    order.reserve(n_vertices);
}
void dfs1(int v) {
    used[v] = true;
    for (int u : adj[v]) {
        if (!used[u])
            dfs1(u);
    }
    order.push_back(v);
}
void dfs2(int v, int cl) {
    comp[v] = cl;
    for (int u : adj_t[v]) {
        if (comp[u] == -1)
            dfs2(u, cl);
    }
}
bool solve_2SAT() {
    order.clear();
    used.assign(n_vertices, false);
    for (int i = 0; i < n_vertices; ++i) {
        if (!used[i])
            dfs1(i);
    }
    comp.assign(n_vertices, -1);
    for (int i = 0, j = 0; i < n_vertices; ++i) {
        int v = order[n_vertices - i - 1];
        if (comp[v] == -1)
            dfs2(v, j++);
    }

    assignment.assign(n_vars, false);
    for (int i = 0; i < n_vertices; i += 2) {
        if (comp[i] == comp[i + 1])
            return false;
        assignment[i / 2] = comp[i] > comp[i + 1];
    }
    return true;
}

void add_disjunction(int a, bool na, int b, bool nb) {
    // na and nb signify whether a and b are to be negated
    a = 2 * a ^ na;
    b = 2 * b ^ nb;
    int neg_a = a ^ 1;
    int neg_b = b ^ 1;
    adj[neg_a].push_back(b);
    adj[neg_b].push_back(a);
    adj_t[b].push_back(neg_a);
    adj_t[a].push_back(neg_b);
}

static void example_usage() {
    TwoSatSolver solver(3);
    solver.add_disjunction(0, false, 1, true);
    // a or not b
    solver.add_disjunction(0, true, 1, true); // not a
    // or not b
    solver.add_disjunction(1, false, 2, false); // b
    // or c
    solver.add_disjunction(0, false, 0, false); // a
    // or a
    assert(solver.solve_2SAT() == true);
    auto expected = vector<bool>(True, False, True);
```

```
    assert(solver.assignment == expected);
}
};

kadane2D.h
Time:  $O()$ 
6227c1, 59 lines

int kadane(vector<int>& temp) {
    int rows = temp.size();
    int currSum = 0;
    int maxSum = INT_MIN;

    for (int i = 0; i < rows; i++) {
        currSum += temp[i];

        // Update maxSum if the current sum is greater
        if (maxSum < currSum) {
            maxSum = currSum;
        }

        // If the current sum becomes negative, reset it to 0
        if (currSum < 0) {
            currSum = 0;
        }
    }

    return maxSum;
}

// Function to find the maximum sum rectangle in a 2D matrix
int maxRectSum(vector<vector<int>> &mat) {
    int rows = mat.size();
    int cols = mat[0].size();

    int maxSum = INT_MIN;

    // Initialize a temporary array to store row-wise
    // sums between left and right boundaries
    vector<int> temp(rows);

    // Check for all possible left and right boundaries
    for (int left = 0; left < cols; left++) {

        // Reset the temporary array for each new left boundary
        for (int i = 0; i < rows; i++)
            temp[i] = 0;

        for (int right = left; right < cols; right++) {

            // Update the temporary array with the current
            // column's values
            for (int row = 0; row < rows; row++) {
                temp[row] += mat[row][right];
            }

            // Find the maximum sum of the subarray for the
            // current column boundaries
            int sum = kadane(temp);

            // Update the maximum sum found so far
            maxSum = max(maxSum, sum);
        }
    }

    return maxSum;
}
```


LCS.h

Time: $\mathcal{O}()$ 7b1c80, 90 lines

```
int lcs(string &s1, string &s2) {
    int m = s1.size();
    int n = s2.size();

    // Initializing a matrix of size (m+1)*(n+1)
    vector<vector<int>> dp(m + 1, vector<int>(n + 1, 0));

    // Building dp[m+1][n+1] in bottom-up fashion
    for (int i = 1; i <= m; ++i) {
        for (int j = 1; j <= n; ++j) {
            if (s1[i - 1] == s2[j - 1])
                dp[i][j] = dp[i - 1][j - 1] + 1;
            else
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
        }
    }

    // dp[m][n] contains length of LCS for s1[0..m-1]
    // and s2[0..n-1]
    return dp[m][n];
}

int lcs(string &s1, string &s2) {

    int m = s1.length(), n = s2.length();

    // dp vector is initialized to all zeros
    // This vector stores the LCS values for the current row.
    // dp[j] represents LCS of s1[0..i] and s2[0..j]
    vector<int> dp(n + 1, 0);

    // i and j represent the lengths of s1 and s2 respectively
    for (int i = 1; i <= m; ++i) {

        // prev stores the value from the previous
        // row and previous column (i-1), (j -1)
        // Used to keep track of LCS[i-1][j-1] while updating
        // dp[j]
        int prev = dp[0];

        for (int j = 1; j <= n; ++j) {

            // temp temporarily stores the current
            // dp[j] before it gets updated
            int temp = dp[j];

            // If characters match, add 1 to the value
            // from the previous row and previous column
            // dp[j] = 1 + LCS[i-1][j-1]
            if (s1[i - 1] == s2[j - 1])
                dp[j] = 1 + prev;
            else
                // Otherwise, take the maximum of the
                // left (dp[j-1]) and top (dp[j]) values
                dp[j] = max(dp[j - 1], dp[j]);

            // Update prev for the next iteration
            // This keeps the value of the previous
            // row (i-1) for future comparisons
            prev = temp;
        }
    }

    // The last element of the vector contains the length of
    // the LCS
    // dp[n] stores the length of LCS of s1[0..m] and s2[0..n]
```

LCS

```
    return dp[n];
}

// Function that returns the number of paths
int numberOfPaths(int source, int destination, int n, int fre
[])
{
    // make topological sorting
    vector<int> s = topological_sorting(fre, n);

    // to store required answer.
    int dp[n] = { 0 };

    // answer from destination
    // to destination is 1.
    dp[destination] = 1;

    // traverse in reverse order
    for (int i = s.size() - 1; i >= 0; i--) {
        for (int j = 0; j < v[s[i]].size(); j++) {
            dp[s[i]] += dp[v[s[i]][j]];
        }
    }

    return dp[source];
}
```

Mathematics (4)

4.1 Equations

$$ax^2 + bx + c = 0 \Rightarrow x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

The extremum is given by $x = -b/2a$.

$$\begin{aligned} ax + by &= e & x &= \frac{ed - bf}{ad - bc} \\ cx + dy &= f & y &= \frac{af - ec}{ad - bc} \end{aligned}$$

In general, given an equation $Ax = b$, the solution to a variable x_i is given by

$$x_i = \frac{\det A'_i}{\det A}$$

where A'_i is A with the i 'th column replaced by b .

Non-distinct roots r become polynomial factors, e.g. $a_n = (d_1n + d_2)r^n$.

4.2 Trigonometry

$$\begin{aligned} \sin(v + w) &= \sin v \cos w + \cos v \sin w \\ \cos(v + w) &= \cos v \cos w - \sin v \sin w \end{aligned}$$

$$\begin{aligned} \tan(v + w) &= \frac{\tan v + \tan w}{1 - \tan v \tan w} \\ \sin v + \sin w &= 2 \sin \frac{v + w}{2} \cos \frac{v - w}{2} \\ \cos v + \cos w &= 2 \cos \frac{v + w}{2} \cos \frac{v - w}{2} \end{aligned}$$

$$(V + W) \tan(v - w)/2 = (V - W) \tan(v + w)/2$$

where V, W are lengths of sides opposite angles v, w .

$$\begin{aligned} a \cos x + b \sin x &= r \cos(x - \phi) \\ a \sin x + b \cos x &= r \sin(x + \phi) \end{aligned}$$

where $r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a)$.

4.3 Geometry

4.3.1 Triangles

Side lengths: a, b, c
Semiperimeter: $p = \frac{a + b + c}{2}$
Area: $A = \sqrt{p(p - a)(p - b)(p - c)}$
Circumradius: $R = \frac{abc}{4A}$
Inradius: $r = \frac{A}{p}$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$
Length of bisector (divides angles in two):

$$s_a = \sqrt{bc \left[1 - \left(\frac{a}{b + c} \right)^2 \right]}$$

Law of sines: $\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}$
Law of cosines: $a^2 = b^2 + c^2 - 2bc \cos \alpha$

Law of tangents: $\frac{a + b}{a - b} = \frac{\tan \frac{\alpha + \beta}{2}}{\tan \frac{\alpha - \beta}{2}}$


4.3.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and $A = \sqrt{(p - a)(p - b)(p - c)(p - d)}$.

4.3.3 Spherical coordinates



$$\begin{aligned}x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\y &= r \sin \theta \sin \phi & \theta &= \arccos(z / \sqrt{x^2 + y^2 + z^2}) \\z &= r \cos \theta & \phi &= \operatorname{atan2}(y, x)\end{aligned}$$

4.4 Derivatives/Integrals

$$\begin{aligned}\frac{d}{dx} \arcsin x &= \frac{1}{\sqrt{1-x^2}} & \frac{d}{dx} \arccos x &= -\frac{1}{\sqrt{1-x^2}} \\ \frac{d}{dx} \tan x &= 1 + \tan^2 x & \frac{d}{dx} \arctan x &= \frac{1}{1+x^2} \\ \int \tan ax &= -\frac{\ln |\cos ax|}{a} & \int x \sin ax &= \frac{\sin ax - ax \cos ax}{a^2} \\ \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \operatorname{erf}(x) & \int x e^{ax} dx &= \frac{e^{ax}}{a^2} (ax - 1)\end{aligned}$$

Integration by parts:

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

4.5 Sums

$$c^a + c^{a+1} + \dots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$\begin{aligned}1 + 2 + 3 + \dots + n &= \frac{n(n+1)}{2} \\ 1^2 + 2^2 + 3^2 + \dots + n^2 &= \frac{n(2n+1)(n+1)}{6} \\ 1^3 + 2^3 + 3^3 + \dots + n^3 &= \frac{n^2(n+1)^2}{4} \\ 1^4 + 2^4 + 3^4 + \dots + n^4 &= \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}\end{aligned}$$

4.6 Series

$$\begin{aligned}e^x &= 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty) \\ \ln(1+x) &= x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1) \\ \sqrt{1+x} &= 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)\end{aligned}$$

$$\begin{aligned}\sin x &= x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty) \\ \cos x &= 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty)\end{aligned}$$

4.7 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2 V(X) + b^2 V(Y).$$

4.7.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is $\operatorname{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\operatorname{Bin}(n, p)$ is approximately $\operatorname{Po}(np)$ for small p .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\operatorname{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\operatorname{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

4.7.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\operatorname{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\operatorname{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

Techniques (A)

techniques.txt	159 lines
Recursion	
Divide and conquer	
Finding interesting points in N log N	
Algorithm analysis	
Master theorem	
Amortized time complexity	
Greedy algorithm	
Scheduling	
Max contiguous subvector sum	
Invariants	
Huffman encoding	
Graph theory	
Dynamic graphs (extra book-keeping)	
Breadth first search	
Depth first search	
* Normal trees / DFS trees	
Dijkstra's algorithm	
MST: Prim's algorithm	
Bellman-Ford	
Konig's theorem and vertex cover	
Min-cost max flow	
Lovasz toggle	
Matrix tree theorem	
Maximal matching, general graphs	
Hopcroft-Karp	
Hall's marriage theorem	
Graphical sequences	
Floyd-Warshall	
Euler cycles	
Flow networks	
* Augmenting paths	
* Edmonds-Karp	
Bipartite matching	
Min. path cover	
Topological sorting	
Strongly connected components	
2-SAT	
Cut vertices, cut-edges and biconnected components	
Edge coloring	
* Trees	
Vertex coloring	
* Bipartite graphs (=> trees)	
* 3^n (special case of set cover)	
Diameter and centroid	
K'th shortest path	
Shortest cycle	
Dynamic programming	
Knapsack	
Coin change	
Longest common subsequence	
Longest increasing subsequence	
Number of paths in a dag	
Shortest path in a dag	
Dynprog over intervals	
Dynprog over subsets	
Dynprog over probabilities	
Dynprog over trees	
3^n set cover	
Divide and conquer	
Knuth optimization	
Convex hull optimizations	
RMQ (sparse table a.k.a 2^k-jumps)	
Bitonic cycle	
Log partitioning (loop over most restricted)	
Combinatorics	

Computation of binomial coefficients
Pigeon-hole principle
Inclusion/exclusion
Catalan number
Pick's theorem
Number theory
Integer parts
Divisibility
Euclidean algorithm
Modular arithmetic
* Modular multiplication
* Modular inverses
* Modular exponentiation by squaring
Chinese remainder theorem
Fermat's little theorem
Euler's theorem
Phi function
Frobenius number
Quadratic reciprocity
Pollard-Rho
Miller-Rabin
Hensel lifting
Vieta root jumping
Game theory
Combinatorial games
Game trees
Mini-max
Nim
Games on graphs
Games on graphs with loops
Grundy numbers
Bipartite games without repetition
General games without repetition
Alpha-beta pruning
Probability theory
Optimization
Binary search
Ternary search
Unimodality and convex functions
Binary search on derivative
Numerical methods
Numeric integration
Newton's method
Root-finding with binary/ternary search
Golden section search
Matrices
Gaussian elimination
Exponentiation by squaring
Sorting
Radix sort
Geometry
Coordinates and vectors
* Cross product
* Scalar product
Convex hull
Polygon cut
Closest pair
Coordinate-compression
Quadtrees
KD-trees
All segment-segment intersection
Sweeping
Discretization (convert to events and sweep)
Angle sweeping
Line sweeping
Discrete second derivatives
Strings
Longest common substring
Palindrome subsequences

Knuth-Morris-Pratt
Tries
Rolling polynomial hashes
Suffix array
Suffix tree
Aho-Corasick
Manacher's algorithm
Letter position lists
Combinatorial search
Meet in the middle
Brute-force with pruning
Best-first (A*)
Bidirectional search
Iterative deepening DFS / A*
Data structures
LCA (2^k-jumps in trees in general)
Pull/push-technique on trees
Heavy-light decomposition
Centroid decomposition
Lazy propagation
Self-balancing trees
Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
Monotone queues / monotone stacks / sliding queues
Sliding queue using 2 stacks
Persistent segment tree