

DSA PRACTICE – 2

Name: Tharani Kumar

DEPT : IT

Date : 11/11/2024

1. Knapsack Problem

Given N items where each item has some weight and profit associated with it and also given a bag with capacity W, [i.e., the bag can hold at most W weight in it]. The task is to put the items into the bag such that the sum of profits associated with them is the maximum possible.

Note: The constraint here is we can either put an item completely into the bag or cannot put it at all [It is not possible to put a part of an item into the bag].

```
import java.util.*;

class KnapSack{

    public static void main(String[] args){

        Scanner sc=new Scanner(System.in);

        System.out.println("Size Sollra");

        int n=sc.nextInt();

        int weight=sc.nextInt();

        int[] prof=new int[n];

        int[] val=new int[n];

        for(int i=0;i<n;i++){

            prof[i]=sc.nextInt();

        }

        for(int i=0;i<n;i++){
```

```

        val[i]=sc.nextInt();
    }
    System.out.println(helper(n,weight,prof,val));

}

public static int helper(int n,int cap,int[] prof,int[] wt){
    int[][] pri=new int[n+1][cap+1];
    for(int i=0;i<n+1;i++){
        for(int j=0;j<cap+1;j++){
            if(i==0 || j==0) pri[i][j]=0;
            else if(wt[i-1]<=j){
                pri[i][j]=Math.max(prof[i-1]+pri[i-1][j-wt[i-1]],pri[i-1][j]);
            }
            else pri[i][j]=pri[i-1][j];
        }
    }
    return pri[n][cap];
}
}

```

Output:

```

C:\Users\thara\.jdk\openjdk-23\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA
Size of the array
3
6
10 15 40
1 2 3
65

```

Time Complexity: $O(n)$;

Space Complexity: $O(n)$;

2. Given a sorted array and a value **x**, the floor of x is the largest element in the array smaller than or equal to x. Write efficient functions to find the floor of x.

Input: arr[] = {1, 2, 8, 10, 10, 12, 19}, x = 20

Output: 6

Explanation: 19 is the largest element in arr[] smaller than 20

Input : arr[] = {1, 2, 8, 10, 10, 12, 19}, x = 0

Output : -1

Explanation: Since floor doesn't exist, output is -1.

Code:

```
class Solution {  
  
    public static int Floor(int[] arr, int k) {  
        int n=arr.length;  
        int l=0;  
        int r=n-1;  
        int ind=-1;  
        while(l<=r){  
            int mid=l+(r-l)/2;  
            if(arr[mid]==k) return mid;  
            else if(arr[mid]<k){  
                ind=mid;  
                l=mid+1;  
            }  
            else r=mid-1;  
        }  
    }  
}
```

```

    }
    return ind;
}

public static void main(String[] args){
    int k=0;
    int arr[] = {1, 2, 8, 9, 11, 17};
    System.out.println(Floor(arr,k));
}
}

```

Output:

```

C:\Users\thara\.jdk\openjdk-23\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA
-1
Process finished with exit code 0

```

3. Check equal arrays

Given two arrays, **arr1** and **arr2** of equal length **N**, the task is to determine if the given arrays are equal or not. Two arrays are considered equal if:

- Both arrays contain the same set of elements.
- The arrangements (or permutations) of elements may be different.
- If there are repeated elements, the counts of each element must be the same in both arrays.

Input: arr1[] = {1, 2, 5, 4, 0}, arr2[] = {2, 4, 5, 0, 1}

Output: Yes

Input: arr1[] = {1, 2, 5, 4, 0, 2, 1}, arr2[] = {2, 4, 5, 0, 1, 1, 2}

Output: Yes

Input: arr1[] = {1, 7, 1}, arr2[] = {7, 7, 1}

Output: No

Code:

```
import java.util.*;

class EqualArrays{

    public static boolean check(int[] arr1, int[] arr2) {
        // Your code here
        if(arr1.length!=arr2.length) return false;
        HashMap<Integer,Integer> hp=new HashMap<>();
        for(int i:arr1){
            hp.put(i,hp.getOrDefault(i,0)+1);
        }
        for(int i:arr2){
            if(!hp.containsKey(i)) return false;
            hp.put(i,hp.get(i)-1);
            if(hp.get(i)==0) hp.remove(i);
        }
        return hp.isEmpty();

    }

    public static void main(String[] args){
        int arr1[] = {1, 7, 1};
        int arr2[] = {7, 7, 1};
        System.out.println(check(arr1,arr2));
    }
}
```

OUTPUT:

```
C:\Users\thara\.jdk\openjdk-23\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA
false
```

Time Complexity: $O(n)$

Space Complexity: $O(n)$;

4. Palindrome Linked List

Given a singly linked list. The task is to check if the given linked list is palindrome or not.

Examples:

Input: head: 1->2->1->1->2->1

Output: true

Explanation: The given linked list is 1->2->1->1->2->1 , which is a palindrome and Hence, the output is true.

Input: head: 1->2->3->4

Output: false

Explanation: The given linked list is 1->2->3->4, which is not a palindrome and Hence, the output is false.

Code:

```
import java.util.*;

public class Main {

    public static void main(String... argv) {
```

```

Scanner scan = new Scanner(System.in);

    System.out.println("Enter the Size of the LinkedList :");

int n = scan.nextInt();

System.out.println("Enter the head of the LinkedList :");

int h = scan.nextInt();

Node head = new Node(h);

Node temp = head;

System.out.println("Enter the rem node val :");

for(int i=1;i<n;i++){

    int num = scan.nextInt();

    Node node = new Node(num);

    temp.next = node;

    temp = temp.next;

}

Node mid = middle(head);

Node secondHead = reverse(mid);

boolean polin = true;

while(head!=null && secondHead!=null){

    if(head.val != secondHead.val){

        polin = false;

        break;

    }

    head = head.next;

    secondHead = secondHead.next;

}

if(polin){

    System.out.println("Polindrome");

}else{

```

```

        System.out.println("Not a Polindrome");
    }

}

public static Node middle(Node head){
    Node fast = head;
    Node slow = head;
    while(fast != null && fast.next != null){
        fast = fast.next.next;
        slow = slow.next;
    }
    return slow;
}

public static Node reverse(Node head){
    Node prev = null;
    Node temp = head;
    while(temp!=null){
        Node front = temp.next;
        temp.next = prev;
        prev = temp;
        temp = front;
    }
    return prev;
}

}

public class Node{
    int val;

```



```

Node next;

public Node(int val){

    this.val = val;

    next = null;

}

}

```

Output:

```

C:\Users\thara\.jdk\openjdk-23\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA
Enter the Size of the LinkedList :
4
Enter the head of the LinkedList :
2
Enter the rem node val :
3 4 2
Not a Polindrome

```

5. Balanced Tree Check

Given a binary tree, find if it is height balanced or not. A tree is height balanced if difference between heights of left and right subtrees is not more than one for all nodes of tree.

Examples:

Input:

```

  1
 /
2
 \
 3

```

Output: 0

Explanation: The max difference in height of left subtree and right subtree is 2, which is greater than 1. Hence unbalanced

Code:

```
import java.util.*;

public class Main {

    public static void main(String... argv) {

        TreeNode root = new TreeNode(1);
        TreeNode node2 = new TreeNode(2);
        TreeNode node3 = new TreeNode(3);
        TreeNode node4 = new TreeNode(4);
        TreeNode node5 = new TreeNode(5);
        TreeNode node6 = new TreeNode(6);
        TreeNode node7 = new TreeNode(7);
        root.left = node2;
        root.right = node3;
        node2.left = node4;
        node3.right = node5;
        node5.left = node6;
        node5.right = node7;
        if(helper(root)!=-1){
            System.out.println("BALANCED");
        }else{
            System.out.println("NOT BALANCED");
        }
    }

    public static int helper(TreeNode root){
        if(root==null) return 0;
```

```

        int left = helper(root.left);
        int right = helper(root.right);
        if(left== -1 || right== -1) return -1;
        if(Math.abs(left-right)== -1) return -1;
        return Math.max(left,right)+1;
    }
}

```

```

class TreeNode {
    int val;
    TreeNode left;
    TreeNode right;

    TreeNode(int val) {
        this.val = val;
        left = null;
        right = null;
    }
}

```

Output:

```

C:\Users\thara\.jdk\openjdk-23\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA
BALANCED

```

6. TRIPLET SUM :

Given an array **arr[]** of size **n** and an integer **sum**. Find if there's a triplet in the array which sums up to the given integer **sum**.

Examples:

Input: *arr = {12, 3, 4, 1, 6, 9}, sum = 24;*

Output: *12, 3, 9*

Explanation: *There is a triplet (12, 3 and 9) present in the array whose sum is 24.*

Input: *arr = {1, 2, 3, 4, 5}, sum = 9*

Output: *5, 3, 1*

Explanation: *There is a triplet (5, 3 and 1) present in the array whose sum is 9.*

Code:

```
import java.util.*;

public class Main {

    public static void main(String... argv) {

        Scanner scan = new Scanner(System.in);

        System.out.println("Enter the Size of the Array :");

        int n = scan.nextInt();

        int[] arr = new int[n];

        System.out.println("Enter the Elements in Array :");

        for(int i=0;i<n;i++){

            arr[i] = scan.nextInt();

        }

        System.out.println("Enter the Number to find the Triplet ");

        int x = scan.nextInt();

        Arrays.sort(arr);

        boolean found = false;

        for (int i = 0; i < n - 2; i++) {
```

```

int l = i + 1;
int r = n - 1;
while (l < r) {
    int sum = arr[i] + arr[l] + arr[r];
    if (sum == x) {
        found = true;
        break;
    } else if (sum < x) {
        l++;
    } else {
        r--;
    }
}

if(found){
    System.out.println("EXIST");
}else{
    System.out.println("NOT EXIST");
}
}
}

```

Output:

```

C:\Users\thara\.jdk\openjdk-23\bin\java.exe "-javaagent:C:\Program Files\JetBrains\IntelliJ IDEA
Enter the Size of the Array :
6
Enter the Elements in Array :
12 3 4 1 6 9
Enter the Number to find the Triplet
24
EXIST

```

