

Evolution of Bio-Socially Inspired Strategies in Support of Dynamic Spectrum Access

Mohammad Abu Shattal
Electrical and Computer Engineering
Western Michigan University
1903 West Michigan Ave, Kalamazoo, MI, USA
Email: mohammad.a.shattal@wmich.edu

Ala Al-Fuqaha
Computer Science Department
Western Michigan University
1903 West Michigan Ave, Kalamazoo, MI, USA
Email: ala.al-fuqaha@wmich.edu

Bilal Khan, Kirk Dombrowski
Department of Sociology
University of Nebraska-Lincoln
Lincoln, NE 68583, USA
Email: {bkhan2, kdombrowski2}@unl.edu

Anna Wisniewska
Computer Science Department
City University of New York Graduate Center
New York, NY 10016, USA
Email: awisniewska@gradcenter.cuny.edu

Abstract—Human and animal societies exhibit complex cognitive and social processes of coordination, cooperation, and competition among their members. Among other functions, these processes can facilitate fairer sharing of resources among community members and enhance individual survival outcomes. In this work, three bio-socially inspired models for secondary users of spectrum in cognitive radio networks are defined and compared to one other within an evolutionary framework. The proposed models reflect successively more sophisticated capabilities of secondary users in distributed spectrum access. The simplest of the three, blind channel access, is shown to be evolutionarily dominant when residual channel capacities are homogeneous. The second more advanced model assumes a capability to sense channel utilization; this model is shown to dominate when the channels have intermediate load and heterogeneous capacities. Finally, the most complex model (additionally) allows for social coalitions and within-group deference; this model is seen to dominate in high load heterogeneous resource settings. We explore the long term evolutionary pressures within societies whose members choose between these three schemes, with natural selection operating via a utility-based fitness function. Our research is based on systematic ns-3 simulation experiments of heterogeneous societies under a range of assumed channel conditions, population sizes, resource demands, and initial user attributes. Our results demonstrate that the secondary user population always evolves to adopt a unique and stable strategy, but that the winning strategy selected depends strongly on channel conditions. Our results further show that this kind of leaderless evolution leads to a significant 12-116% overall improvement in performance compared to systems in which a fixed strategy is deployed. In summary, we conclude that evolving bio-social behavioral models can be applied to great advantage in understanding dynamic environments such as those envisioned by distributed spectrum access.

Index Terms—Dynamic Spectrum Access; Cognitive Radio; Bio-Social Spectrum Access Strategies; Strategy Evolution.

I. INTRODUCTION

The Federal Communications Commission (FCC), and similar regulatory bodies around the world are responsible for licensing the inherently scarce resource of radio spectrum. In

spite of this, spectrum bands are typically underutilized by their licensed owners (i.e. the “Primary Users” or PUs); indeed the findings of Wang et al. [1] and others show spectrum occupancy in the U.S. is presently below 6%. The FCC prompted the research community for innovative solutions to spectrum underutilization, resulting in the development of cognitive Radio (CR) and distributed spectrum (DSA) access models [2] which allow unlicensed “Secondary Users” (SUs) to access licensed spectrum while guaranteeing transmission priority for PUs.

In the DSA paradigm, managing SU-SU interactions is crucially important. Uncoordinated SU access to resources can lead to unbalanced resource usage, and leave some channels crowded and others underutilized. In this work, we investigate SU-SU interactions within a bio-socially inspired evolutionary framework, to obtain more efficient spectrum utilization strategies long term. In our framework, we allow SUs to adapt their strategies gradually over time by mimicking their more successful peers. Our approach to CR societies reflects what we know about its biological counterparts, wherein we observe a variety of individuals with different capabilities and behaviors, adapting over time. We consider three types of SUs:

- **Baseline:** Users select their transmission channel randomly, operating in the absence of external data about the states of the different channels.
- **Foraging Behavior:** Users can dynamically sense the channel state information, and use this external data to determine their channel selection and data transmission strategy.
- **Social Behavior:** Users can dynamically sense the channel state information as well as the properties of its co-users, and use this external data to determine their channel selection and data transmission strategy.

In this paper, we will consider heterogeneous ecosystems containing a mix of SUs spanning the three behav-




Fig. 5. Throughput improvement due to strategy evolution

VI. CONCLUSIONS AND FUTURE WORK

In this work we presented three bio-socially inspired strategies for DSA by secondary users. We demonstrated through simulation experiments that each of these strategies has the potential to dominate the others over long time scales where natural selection is at play. We showed that the winning strategy depends on the underlying channel conditions and the demographics of the SUs. ACUs emerge when the channel capacities are homogeneous and under light load; FCUs emerge when the channels capacities are heterogeneous and under intermediate load; SFCUs emerge when the channels capacities are heterogeneous and under heavy load.

In our future research work, we plan to replicate the experimental results of this paper formally using evolutionary game theory. We also plan to verify the conclusions in a experimental hardware testbed in which some of the simplifying assumptions of the simulation models are no longer present.

ACKNOWLEDGMENT

This project was supported by a grant from the National Science Foundation program for Enhancing Access to Radio Spectrum (#1443985 and #1638618), supported by the MPS, ENG and CISE Directorates. The opinions, findings, and conclusions or recommendations expressed in this publication are those of the authors and do not necessarily reflect those of the National Science Foundation.

REFERENCES

- [1] B. Wang and K. J. R. Liu, "Advances in cognitive radio networks: A survey," *IEEE Journal of Selected Topics in Signal Processing*, vol. 5, no. 1, pp. 5–23, Feb. 2011.
- [2] J. Genachowski, R. M. McDowell, M. Clyburn, and M. A. Baker, "Promoting More Efficient Use of Spectrum through Dynamic Spectrum Use Technologies," Federal Communications Commission, Tech. Rep. FCC 10-198, Nov. 2010.
- [3] W. Gabran, C. H. Liu, P. Pawelczak, and D. Cabric, "Primary User Traffic Estimation for Dynamic Spectrum Access," *IEEE Journal on Selected Areas in Communications*, vol. 31, no. 3, pp. 544–558, Mar. 2013.
- [4] S. Dixit, S. Periyalwar, and H. Yanikomeroglu, "A Distributed Framework with a Novel Pricing Model for Enabling Dynamic Spectrum Access for Secondary Users," in *Vehicular Technology Conference Fall (VTC 2009-Fall)*, 2009 IEEE 70th, Sep. 2009, pp. 1–5.
- [5] Y. Xing and R. Chandramouli, "Human behavior inspired cognitive radio network design," *IEEE Communications Magazine*, vol. 46, no. 12, pp. 122–127, Dec. 2008.
- [6] A. Wisniewska and B. Khan, "Contention-sensing and dynamic spectrum co-use in secondary user cognitive radio societies," in *2014 International Wireless Communications and Mobile Computing Conference (IWCMC)*, Aug. 2014, pp. 157–162.
- [7] S. Li, Z. Zheng, E. Ekici, and N. B. Shroff, "Maximizing social welfare in operator-based Cognitive Radio Networks under spectrum uncertainty and sensing inaccuracy," in *2013 Proceedings IEEE INFOCOM*, Apr. 2013, pp. 953–961.
- [8] X. Chen, J. Huang, and H. Li, "Adaptive Channel Recommendation for Opportunistic Spectrum Access," *IEEE Transactions on Mobile Computing*, vol. 12, no. 9, pp. 1788–1800, Sep. 2013.
- [9] T. AlShammari, B. Hamdaoui, M. Guizani, and A. Rayes, "Overcoming user selfishness in DSA systems through credit-based resource allocation," in *2014 IEEE International Conference on Communications (ICC)*, Jun. 2014, pp. 318–323.
- [10] O. Castillo, R. Martinez-Marroquin, P. Melin, F. Valdez, and J. Soria, "Comparative study of bio-inspired algorithms applied to the optimization of type-1 and type-2 fuzzy controllers for an autonomous mobile robot," *Information Sciences*, vol. 192, pp. 19–38, 2012, swarm Intelligence and Its Applications. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S0020025510001003>
- [11] C. Charalambous and S. Cui, "A biologically inspired networking model for wireless sensor networks," *IEEE Network*, vol. 24, no. 3, pp. 6–13, May 2010.
- [12] B. Atakan and O. Akan, "Biological Foraging-Inspired Communication in Intermittently Connected Mobile Cognitive Radio Ad Hoc Networks," *IEEE Transactions on Vehicular Technology*, vol. 61, no. 6, pp. 2651–2658, Jul. 2012.
- [13] M. Zeeshan and S. Ali, "A spectrum exploitation scheme with channel assignment for Genetic Algorithm based adaptive-array smart antennas in cognitive radio networks," in *2012 IEEE International Conference on Communications (ICC)*, Jun. 2012, pp. 1555–1559.
- [14] C. Gven, S. Bayhan, and F. Alagz, "Effect of social relations on cooperative sensing in cognitive radio networks," in *2013 First International Black Sea Conference on Communications and Networking (BlackSeaCom)*, Jul. 2013, pp. 247–251.
- [15] M. Roth and S. Wicker, "Termite: ad-hoc networking with stigmergy," in *IEEE Global Telecommunications Conference, 2003. GLOBECOM '03*, vol. 5, Dec. 2003, pp. 2937–2941.
- [16] C. R. Reid, D. J. T. Sumpter, and M. Beekman, "Optimisation in a natural system: Argentine ants solve the Towers of Hanoi," *Journal of Experimental Biology*, vol. 214, no. 1, pp. 50–58, 2010. [Online]. Available: <http://jeb.biologists.org/content/214/1/50>
- [17] E. A. Smith, R. L. Bettinger, C. A. Bishop, V. Blundell, E. Cashdan, M. J. Casimir, A. L. Christenson, B. Cox, R. Dyson-Hudson, B. Hayden, P. J. Richerson, E. A. Roth, S. R. Simms, and W. A. Stini, "Anthropological Applications of Optimal Foraging Theory: A Critical Review [and Comments and Reply]," *Current Anthropology*, vol. 24, no. 5, pp. 625–651, 1983. [Online]. Available: <http://www.jstor.org/stable/2743169>
- [18] C. Xin, M. Song, L. Ma, G. Hsieh, and C. C. Shen, "On Random Dynamic Spectrum Access for Cognitive Radio Networks," in *2010 IEEE Global Telecommunications Conference (GLOBECOM 2010)*, Dec. 2010, pp. 1–5.
- [19] X. Mao and H. Ji, "Biologically-Inspired Distributed Spectrum Access for Cognitive Radio Network," in *2010 6th International Conference on Wireless Communications Networking and Mobile Computing (WiCOM)*, Sep. 2010, pp. 1–4.
- [20] R. Yao, K. He, Y. Sun, and Y. Wang, "Learning engine for cognitive radio based on the immune principle," in *2014 NASA/ESA Conference on Adaptive Hardware and Systems (AHS)*, Jul. 2014, pp. 210–217.
- [21] "ns-3 yans-wifi-helper class reference [online]," https://www.nsnam.org/doxygen/yanswifihelper_8cc_source.html, 2016-12-16, accessed: 2016-12-16.
- [22] "ns-3 wifiphy class reference [online]," https://www.nsnam.org/doxygen/classns3_1_1_wifi_phy.html#details, accessed: 2016-12-16.