

Social Deference and Hunger as Mechanisms for Starvation Avoidance in Cognitive Radio Societies

Anna Wisniewska

Computer Science Department
City University of New York Graduate Center
New York, NY 10016, U.S.A.
Email: awisniewska@gradcenter.cuny.edu

Bilal Khan

Department of Sociology
University of Nebraska-Lincoln
Lincoln, NE 68583, U.S.A.
Email: bkhan2@unl.edu

Ala Al-Fuqaha

Computer Science Department
Western Michigan University
Kalamazoo, MI 49008, U.S.A.
Email: ala.al-fuqaha@wmich.edu

Kirk Dombrowski

Department of Sociology
University of Nebraska-Lincoln
Lincoln, NE 68583, U.S.A.
Email: kdombrowski2@unl.edu

Mohammad Abu Shattal

Electrical and Computer Engineering Department
Western Michigan University
Kalamazoo, MI 49008, U.S.A.
Email: mohammad.a.shattal@wmich.edu

Abstract—Wireless communication is an increasingly ubiquitous and important resource substrate of the digital ecosystem. In the face of the rapid growth in the population of Internet of Things (IoT), however, uncoordinated access to limited resources of radio spectrum is likely to lead to mass starvation. Here we put forward a new bio-social paradigm for cognitive radio, extending previous models in which the secondary users of spectrum alternate stochastically between foraging and consuming behaviors. In this paper, we ask and resolve two questions: (1) What costs and benefits does social deference to the group yield for each of the *individuals* therein? and (2) Can a notion of individual “hunger” form the basis of a distributed social deference scheme that is free of group coordination costs? Through a series of simulation experiments grounded in a well-specified formal model, we show that social deference improves both the fairness and the reliability of spectrum resource allocation, and moreover, that the concept of individual “hunger” can be used to implement social deference with minimal group coordination overhead. The results have consequences both in suggesting potential improvements for distributed spectrum access, and in understanding the evolutionary pressures on the behaviors of individual devices within emerging digital IoT societies.

Index Terms—Cognitive radio networks, bio-social networking, Internet of Things, self-coexistence, dynamic spectrum access, contention-sensing.

I. INTRODUCTION

Ubiquitous wireless service together with decreasing hardware costs have led to rapid population growth in the Internet of Things (IoT). Although the present IoT consists largely of primitive low power sensors, the demand to support richer data streams is unquestionable. As the population and sophistication of IoT devices increases, it is widely expected that they will engage Dynamic Spectrum Access (DSA) networks [3] as secondary users (SUs) of radio spectrum, using Cognitive Radio (CR) technologies [12], [14], [2].

Unfortunately, the FCC’s frequency assignment policies over the years have resulted in suboptimal use of spectral resources. Few segments of spectrum remain unallocated, and yet spectrum is underutilized because licensed (“primary”) users are frequently idle. To address this, the FCC proposed DSA within the CR paradigm. However, although the FCC reforms “allow unlimited numbers of unlicensed [secondary] users to share frequencies”, they do “not provide any right to protection from interference” [7]. Since there are many secondary users, each SU’s selection of band and decision to transmit, potentially impacts other secondary users, whose channel bandwidth degrades when greater numbers of SUs share a channel. Taken together, bandwidth scarcity and “no right to protection from interference” present serious challenges to performance for SUs in CR and DSA environments. In short, DSA can “kick the can further down the road” but the problem remains looming.

Prior research on resource allocation in networks recognizes the potential relevance of our knowledge on resource co-use in human and animal societies; for a recent survey of bio-socially inspired approaches, see [6], [13]. In particular, since SUs in CR and DSA environments are potentially capable of sensing, learning, and adaptation, there has been considerable prior work seeking to apply models of animal foraging strategies to the design of protocols in CR networks [1], [5], [11].

In their previous work [17] the authors considered cognitive radio societies in which secondary users (SUs) of radio spectrum can alternate stochastically between two distinct behavioral modes: searching for spectrum holes (“foraging”) and transmitting in a band (“consuming”), rather than always consuming. They showed that if, while in foraging mode, SUs measure (“sense”) congestion (i.e. number of other SUs transmitting) in a band, and then use this measurement to bias the individual decisions to start consuming the band, such **social contention avoidance** behaviors significantly improve channel utilization metrics (28%).

Here, we continue to extend the above bio-social model to leverage prior understanding of resource conflict/sharing in the context of humans and other social animals [8], [9], [18]. Specifically, we consider **social deference**, by which we mean

users are frequently idle. To address this, the FCC proposed DSA within the CR paradigm. However, although the FCC reforms “allow unlimited numbers of unlicensed [secondary] users to share frequencies”, they do “not provide any right to protection from interference” [7]. Since there are many secondary users, each SU’s selection of band and decision to transmit, potentially impacts other secondary users, whose channel bandwidth degrades when greater numbers of SUs share a channel. Taken together, bandwidth scarcity and “no right to protection from interference” present serious challenges to performance for SUs in CR and DSA environments. In short, DSA can “kick the can further down the road” but the problem remains looming.

- [3] C. Cordeiro, K. Challapali, D. Birru, and S. Shankar. IEEE 802.22: The first worldwide wireless standard based on cognitive radios. *Proc., IEEE Symposium of New Frontiers in Dynamic Spectrum Access Networks (DySPAN'2005)*, pages 328–337, Nov. 2005.
- [4] T. M. Cover and J. A. Thomas. *Elements of Information Theory*. John Wiley & Sons, July 2006.
- [5] P. Di Lorenzo, S. Barbarossa, and A. Sayed. Bio-inspired decentralized radio access based on swarming mechanisms over adaptive networks. *IEEE Transactions on Signal Processing*, Early Access Online, 2013.
- [6] F. Dressler and O. B. Akan. A survey on bio-inspired networking. *Computer Networks*, 54(6):881–900, Apr. 2010.
- [7] FCC. In the matter of unlicensed operation in the TV broadcast bands. *Second Report and Order and Memorandum Opinion and Order*, (FCC-08-260A1), Nov. 2008.
- [8] F. Ge, Q. Chen, Y. Wang, C. Bostian, T. Rondeau, and B. Le. Cognitive radio: From spectrum sharing to adaptive learning and reconfiguration. pages 1–10, march 2008.
- [9] S. Haykin. Cognitive radio: brain-empowered wireless communications. *Selected Areas in Communications, IEEE Journal on*, 23(2):201–220, feb. 2005.
- [10] B. Khan, K. Dombrowski, and M. Saad. A stochastic agent-based model of pathogen propagation in dynamic multi-relational social networks. *SIMULATION, Transactions of SCS*, 90(4):460–484, 2014.
- [11] X. Mao and H. Ji. Biologically-inspired distributed spectrum access for cognitive radio network. In *2010 6th International Conference on Wireless Communications Networking and Mobile Computing (WiCOM)*, pages 1–4, 2010.
- [12] M. Murrioni, R. Prasad, P. Marques, B. Bochow, D. Noguét, C. Sun, K. Moessner, and H. Harada. IEEE 1900.6: spectrum sensing interfaces and data structures for dynamic spectrum access and other advanced radio communication systems standard: technical aspects and future outlook. 49(12):118–127.
- [13] T. Nakano. Biologically inspired network systems: A review and future prospects. *IEEE Transactions on Systems, Man, and Cybernetics, Part C: Applications and Reviews*, 41(5):630–643, 2011.
- [14] H. Pohls, V. Angelakis, S. Suppan, K. Fischer, G. Oikonomou, E. Tragos, R. Diaz Rodriguez, and T. Mouroutis. RERUM: Building a reliable IoT upon privacy- and security- enabled smart objects. In *2014 IEEE Wireless Communications and Networking Conference Workshops (WCNCW)*, pages 122–127.
- [15] C. E. Shannon. Communication in the presence of noise. *Proc. Institute of Radio Engineers*, 37(1):10–21, 1949.
- [16] Y. Tan, S. Sengupta, and K. P. Subbalakshmi. Human society inspired dynamic spectrum access networks: The effect of parochialism. In *Global Telecommunications Conference (GLOBECOM 2011)*, 2011 IEEE, pages 1–5, 2011.
- [17] A. Wisniewska and B. Khan. Contention-sensing and dynamic spectrum co-use in secondary user cognitive radio societies. In *Wireless Communications and Mobile Computing Conference (IWCMC)*, 2014 International, pages 157–162, Aug. 2014.
- [18] Y. Xing and R. Chandramouli. Human behavior inspired cognitive radio network design. *Communications Magazine, IEEE*, 46(12):122–127, december 2008.