

Minimizing Communication Costs in Hierarchical Multi-Agent Systems

Kiran R. Bhutani* Bilal Khan†

Center for Computational Science

Naval Research Laboratory, Washington D.C.

ABSTRACT- In this paper, we consider several mathematical and algorithmic problems which arise naturally in the context of optimizing the performance of a network management system (NMS) whose architecture consists of a *distributed hierarchy* of cooperating intelligent agents.

Key Words: Distributed Hierarchy, Network Management, Multi-agent System.

1 Introduction

A network management system (NMS) must be able to coordinate thousands of network devices, and *scale* to perform well as the number of devices increases. To achieve this goal, the designers of the Optiprism [4] NMS drew upon the compelling analogies between scalable distributed computer systems and distributed human organizations, as presented by Fox [2] and others. Indeed, the architecture of Optiprism has its roots in the theory of human organizational hierarchies, as developed in the works of J. R. Galbraith [3], Mount and Reiter [5], Radner [7], Patrick and Dewatripont [6].

The Optiprism NMS is a hierarchy of (software) *managers*, each of which may act as a *supervisor* of several *subordinate* managers. State information about the network is aggregated and flows recursively upwards at each node of the hierarchy, facilitating decisions and actions which are then executed by recursive delegation of subtasks to subordinates [1, pp. 12]. In this way, decentralized information processing facilitates decentralized decision-making [8, pp. 1].

In most NMS' the human network administrator interacts with the management system using a *browser* application. For scalability, however, such a browser should not communicate with *all* of the NMS' managers at any point in time. In Optiprism, the browser application is itself a leaf node in the management hierarchy. The browser acts as “consultant”, changing its position within the hierarchy, and—following Galbraith’s mechanistic

* Department of Mathematics, The Catholic University of America, Washington DC 20064

† Advanced Engineering Sciences ITT at the Center for Computational Science, Naval Research Laboratory, Washington DC 20375. <http://www.nrl.navy.mil/ccs/project/public/DC/web/>

In each of these cases one can show that $C_*(t', V, U, g) \leq C_*(t, V, U, g)$, hence the function f minimizes C_* for the VISIBILITY-GRADED local cost function. \square

6 Conclusion

In this paper, we have developed algorithms for distributing a hierarchy of network management agents in a manner which minimizes the network communication required between browsers and managers. We showed that for three different natural local cost functions, it is possible to compute a globally optimal assignment. In this work, we considered the NMS agents to be distributed across a network of machines modelled as a complete graph, and charged unit cost for communication between any two distinct machines.

Acknowledgements: The first author thanks the Center for Computational Sciences at the Naval research Lab Washington D.C. for providing funding for this work during the summer of 2000. We would like to thank Dardo Kleiner and David Talmage for many spirited discussions about hierarchical network management and the Optiprism NMS.

References

- [1] M. M. Cheikhrouhou, P. Conti, and J. Labetoulle. Intelligent agents in network management, a state-of-the-art. *Networking and Information Systems*, 1(1):9–38, 1998.
- [2] M. S. Fox. An organizational view of distributed systems. *IEEE Transactions on Systems, Man, and Cybernetics*, 11(1):70–80, 1981.
- [3] J. R. Galbraith. *Organization Design*. Addison-Wesley Publishing Company, 1977.
- [4] B. Khan, D. D. Kleiner, and D. Talmage. Towards an agent-based distributed hierarchical network management system for all-optical networks. In *Proceedings of 3rd International Workshop on Mobile Agents in Telecommunications Applications*, Montreal, Canada, August 15-18, 2001.
- [5] K. Mount and S. Reiter. A model of computing with human agents. Technical Report 890, The Center for Mathematical Studies in Economics and Management Science, Northwestern University, Evanston, IL, 1990.
- [6] B. Patrick and M. Dewatripont. The firm as a communication network. *Quarterly Journal of Economics*, 109(4):809–839, 1994.
- [7] R. Radner. The organization of decentralized information processing. *Econometrica*, 61:5, 1993.
- [8] T. V. Zandt. Real-time hierarchical resource allocation. Technical report, Kellogg Graduate School of Management, Northwestern University, 1997.