

# PARSEARG: TURNS ARGPARSE ON ITS HEAD, THE DECLARATIVE WAY

THOMAS P. HARTE

## CONTENTS

|   |   |
|---|---|
| 1. Overview                             | 1 |
| 2. <code>parsearg.examples.todos</code> | 2 |
| 3. How <code>parsearg</code> works      | 4 |
| 3.1. The A-tree                         | 4 |
| 3.2. The A-A tree                       | 6 |

## 1. OVERVIEW

The “standard” Python module for writing command-line interfaces (“CLI”) is `argparse`. It is standard in so far as it is one of the batteries that comes included with the Python distribution, so no special installation is required. Probably because `argparse` is a bit clunky to use, many other (non-standard) packages have been developed for creating CLIs. Why “clunky”? Putting together a CLI with `argparse` alone is nothing if not an exercise in imperative programming, and this has three very negative consequences:

- (1) It obfuscates the intention of the CLI design;
- (2) It is prone to errors;
- (3) It discourages CLI design in the first instance; it makes debugging a CLI design very difficult; and it makes refactoring or re-configuring the CLI design overly burdensome.

In spite of this clunkiness, `argparse` has everything we need in terms of functionality. `parsearg`, then, is nothing more than a layer over `argparse` that exposes the `argparse` functionality via a dict. The dict is the View component of the [Model-View-Controller](#) (“MVC”) design pattern. The dict embeds callbacks from the Controller component, thereby achieving a clean separation of duties, which is what the MVC pattern calls for. By separating the View component into a dict, the CLI design can be expressed in a declarative way: `parsearg` manifests the *intention* of the CLI design without having to specify how that design is implemented in terms of `argparse`’s parsers and subparsers (`parsearg` does that for you).

Other packages—such as `click` and `plac`—effectively decorate functions that are part of the Controller with functionality from the View. Unfortunately, while this may expose the functionality of `argparse` in a more friendly way via the packages’ decorators, it dissipates the elements of the View across the Controller and in so doing it makes the CLI design difficult to grasp.

The `parsearg` philosophy is that `argparse` is already good enough in terms of the functionality that it provides, but that it just needs a little nudge in terms of how it’s used. Arguments to be added to a CLI with `argparse` can be clearly specified as data, as can the callbacks that consume these arguments. `parsearg` takes advantage of this by specifying everything (in the View component of MVC) as a dict, from which `parsearg` then generates a parser (or set of nested parsers) using `argparse`. The Controller is then free to use the generated parser.

The `parsearg` approach is declarative because it manifests the CLI design in a data structure: a dict, which is one of Python’s built-in data structures. The keys of this dict form a flattened tree of the CLI’s subcommands. Keys like `A|B|C` are easy to specify and neatly summarize the nested hierarchy of subcommands: `A -> B ->`

C. They are also easy to change. The magic, such as it is, of `parsearg` is that it unflattens this flattened tree into a tree of `argparse` parsers. `parsearg` requires nothing special: It works with Python out of the box, and therefore uses what's already available without introducing dependencies.

Simple? The following examples should help.

## 2. PARSEARG.EXAMPLES.TODOS

Yet another To-Do app? Yes, because:

- (1) It illustrates a sufficiently realistic, but not overly complex, problem;
- (2) It also illustrates the MVC pattern in the wild;
- (3) It shows how `parsearg` neatly segments the View component into a dict.

Let's start with the outer layer of the onion. How do we interact with `todos.py`? First, create some users in the User table with the `create user` subcommand of `todos.py`. Note that we do not (yet) have a phone number for user `bar`, nor do we have an email address for user `qux`:

```
1 python todos.py create user foo -e foo@foo.com -p 212-555-1234
2 python todos.py create user bar -e bar@bar.com
3 python todos.py create user qux -p 212-123-5555
```

```
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
```

Second, create some to-dos in the Todo table with the `create todo` subcommand of `todos.py`.

```
1 python todos.py create todo foo title1 -c description1 -d 2020-11-30
2 python todos.py create todo foo title2 -c description2 --due-date=2020-12-31
3 python todos.py create todo qux todo-1 --description=Christmas-party -d 2020-11-30
4 python todos.py create todo qux todo-2 --description=New-Year-party
```

```
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
```

Let's make some changes to the records entered so far. We can add an email address for user `qux` and a phone number for user `bar` using the `update user email` and `update user phone` subcommands, respectively:

```
1 python todos.py update user email qux qux@quxbar.com
2 python todos.py update user phone bar 203-555-1212
```

```
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
```

Now update two of the to-dos, changing the `title` and the `description` in the fourth to-do using the `update todo title` and `update todo description` subcommands, respectively:

```
1 python todos.py update todo title 4 most-important
2 python todos.py update todo description 4 2021-party
```

```
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
```

```
1 python todos.py show users
2 python todos.py show todos
```

```
python: can't open file 'todos.py': [Errno 2] No such file or directory
python: can't open file 'todos.py': [Errno 2] No such file or directory
```

The result of these commands is that the two tables (User and Todo) are populated in a [SQLite](#) database:

```
1 sqlite3 todo.db 'select * from User;'
```

```
Error: no such table: User
```

```
1 sqlite3 todo.db 'select * from Todo;'
```

```
Error: no such table: Todo
```

Let's look at the Python code for [todos.py](#).

The View component is entirely contained within a single dict, viz. `view`, which has been formatted here for clarity using `parsearg.utils.show`:

```
1 from parsearg.examples.todos import view
2 from parsearg.utils import show
3
4 show(view)
```

```
{'purge|users':
  'callback':
    <function purge_users at 0x7f11d6ff6700>
  'purge|todos':
    'callback':
      <function purge_todos at 0x7f11d6fcfaf0>
  'show|users':
    'callback':
      <function show_users at 0x7f11d6fcfb80>
  'show|todos':
    'callback':
      <function show_todos at 0x7f11d6fcfc10>
  'create|user':
    'callback':
      <function create_user at 0x7f11d6fcfca0>
    'name':
      {'help': 'create user name', 'action': 'store'}
    '-e|--email':
      {'help': 'create user's email address', 'action': 'store', 'default': ''}
    '-p|--phone':
      {'help': 'create user's phone number', 'action': 'store', 'default': ''}
  'create|todo':
    'callback':
      <function create_todo at 0x7f11d6fcfd30>
    'user':
      {'help': 'user name', 'action': 'store'}
    'title':
      {'help': 'title of to-do', 'action': 'store'}
    '-c|--description':
      {'help': 'description of to-do', 'action': 'store', 'default': ''}
    '-d|--due-date':
      {'help': 'due date for the to-do', 'action': 'store', 'default': None}
  'update|user|email':
    'callback':
      <function update_user_email at 0x7f11d6fcfdc0>
    'name':
      {'help': 'user name', 'action': 'store'}}
```

```

    'email':
    {'help': 'user email', 'action': 'store'}
  'update|user|phone':
    'callback':
    <function update_user_phone at 0x7f11d6fcfe50>
    'name':
    {'help': 'user name', 'action': 'store'}
    'phone':
    {'help': 'user phone', 'action': 'store'}
  'update|todo|title':
    'callback':
    <function update_todo_title at 0x7f11d6fcfee0>
    'id':
    {'help': 'ID of to-do', 'action': 'store'}
    'title':
    {'help': 'title of to-do', 'action': 'store'}
  'update|todo|description':
    'callback':
    <function update_todo_description at 0x7f11d6fcff70>
    'id':
    {'help': 'ID of to-do', 'action': 'store'}
    'description':
    {'help': 'description of to-do', 'action': 'store'}

```

We can generate a tree view of the CLI design specified by the above dict, namely `view`, as follows:

```

1 from parsearg.parser import ParseArg
2
3 print(
4     ParseArg(d=view, root_name='TODO').tree.show(quiet=True)
5 )

```

```

TODO
  purge
    todos
    users
  update
    user
      phone
      email
    todo
      description
      title
  show
    todos
    users
  create
    user
    todo


```

### 3. HOW PARSEARG WORKS

It is easier to explain how `parsearg` works with a simpler abstraction than the above example `parsearg.examples.todos.py`. Here, we will consider nested parsers as trees. We introduce two trees for this purpose:

- (1) The “A tree”, and
- (2) The “A-AA tree”.

**3.1. The A-tree.** The “A tree” has three levels. As each node of the tree must necessarily occupy a positional argument of the command line, `[-f]` and `[-g]` are correspondingly *optional arguments* that attach to the nodes (A and BB, respectively, in the below diagram).



Let's look at the Python code for [a.py](#).

Consider the dict that represents the View component:

```

1 from parsearg.examples.a import view
2
3 show(view)
    
```

```


'A':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7d10c10>
  '-c':
    {'help': 'A [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A verbosity', 'action': 'store_true'}
'A|B':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d70409d0>
  '-c':
    {'help': 'A B [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A B verbosity', 'action': 'store_true'}
'A|BB':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7040a60>
  '-c':
    {'help': 'A BB [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB erbosity', 'action': 'store_true'}
'A|BB|C':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7040af0>
  '-c':
    {'help': 'A BB C [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB C verbosity', 'action': 'store_true'}
'A|BB|CC':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7040b80>
  '-c':
    {'help': 'A BB CC [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB CC verbosity', 'action': 'store_true'}
'A|BB|CCC':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7040c10>
  '-c':
    {'help': 'A BB CCC [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB CCC verbosity', 'action': 'store_true'}
'A|BBB':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7040ca0>
  '-c':
    {'help': 'A BBB [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BBB verbosity', 'action': 'store_true'}
    
```

and then the tree that the parsed dict is represented by:

```
1 print(
2     ParseArg(d=view, root_name='TODO').tree.show(quiet=True)
3 )
```

```
TODO
  A
    B
    BBB
    BB
      C
      CC
      CCC
```

3.2. **The A-AA tree.** The A-AA tree simply extends the A tree one level:



Let's look at the Python code for [a\\_aa.py](#).

Consider the dict that represents the View component:

```
1 from parsearg.examples.a_aa import view
2
3 show(view)
```

```
{
  'A': {
    'callback':
      <function make_callback.<locals>.func at 0x7f11d7044670>
    '-c':
      {'help': 'A [optional pi]', 'action': 'store_const', 'const': 3.141593}
    '-v|--verbose':
      {'help': 'A verbosity', 'action': 'store_true'}
  },
  'A|B': {
    'callback':
      <function make_callback.<locals>.func at 0x7f11d70445e0>
    '-c':
      {'help': 'A B [optional pi]', 'action': 'store_const', 'const': 3.141593}
    '-v|--verbose':
      {'help': 'A B verbosity', 'action': 'store_true'}
  },
  'A|BB': {
    'callback':
      <function make_callback.<locals>.func at 0x7f11d7044550>
    '-c':
      {'help': 'A BB [optional pi]', 'action': 'store_const', 'const': 3.141593}
    '-v|--verbose':
      {'help': 'A BB erbosity', 'action': 'store_true'}
  }
}
```

```

'A|BB|C':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d70444c0>
  '-c':
    {'help': 'A BB C [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB C verbosity', 'action': 'store_true'}
'A|BB|CC':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044430>
  '-c':
    {'help': 'A BB CC [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB CC verbosity', 'action': 'store_true'}
'A|BB|CCC':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d70443a0>
  '-c':
    {'help': 'A BB CCC [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BB CCC verbosity', 'action': 'store_true'}
'A|BBB':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d70440d0>
  '-c':
    {'help': 'A BBB [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'A BBB verbosity', 'action': 'store_true'}
'AA':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044310>
  '-c':
    {'help': 'AA [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA verbosity', 'action': 'store_true'}
'AA|B':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044280>
  '-c':
    {'help': 'AA B [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA B verbosity', 'action': 'store_true'}
'AA|BB':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d70441f0>
  '-c':
    {'help': 'AA BB [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA BB verbosity', 'action': 'store_true'}
'AA|BB|C':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044160>
  '-c':
    {'help': 'AA BB C [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA BB C verbosity', 'action': 'store_true'}
'AA|BB|CC':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044040>
  '-c':
    {'help': 'AA BB CC [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA BB CC verbosity', 'action': 'store_true'}
'AA|BB|CCC':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044c10>
  '-c':
    {'help': 'AA BB CCC [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA BB CCC verbosity', 'action': 'store_true'}
'AA|BBB':
  'callback':
    <function make_callback.<locals>.func at 0x7f11d7044ca0>
  '-c':
    {'help': 'AA BBB [optional pi]', 'action': 'store_const', 'const': 3.141593}
  '-v|--verbose':
    {'help': 'AA BBB verbosity', 'action': 'store_true'}

```

and then the tree that the parsed dict is represented by:

```
1 print(
2     ParseArg(d=view, root_name='TODO').tree.show(quiet=True)
3 )
```

```

TODO
  AA
    B
    BBB
    BB
      C
      CC
      CCC
  A
    B
    BBB
    BB
      C
      CC
      CCC

```

We can now run the A-tree and the A-AA-tree examples, respectively:

```
1 from parsearg.examples.a import main
2 main()
```

```

NODE :: 'A':
-----
usage: A [-h] [-c] [-v] {B,BBB,BB} ...

positional arguments:
  {B,BBB,BB}

optional arguments:
  -h, --help      show this help message and exit
  -c              A [optional pi]
  -v, --verbose   A verbosity

'A':
----
args: {'c': None, 'verbose': False}
<Mock name='mock.A' id='139714611964512'>
'A -v':
-----
args: {'c': None, 'verbose': True}
<Mock name='mock.A' id='139714611964512'>
'A -c':
-----
args: {'c': 3.141593, 'verbose': False}
<Mock name='mock.A' id='139714611964512'>
'A -v -c':
-----
args: {'c': 3.141593, 'verbose': True}
<Mock name='mock.A' id='139714611964512'>

NODE :: 'A B':
-----
usage: A B [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              A B [optional pi]
  -v, --verbose   A B verbosity

'A B':
-----
args: {'c': None, 'verbose': False}
<Mock name='mock.A_B' id='139714598437792'>

```



```

'A B -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_B' id='139714598437792'>
'A B -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_B' id='139714598437792'>
'A B -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_B' id='139714598437792'>

NODE :: 'A BB':
-----
usage: A BB [-h] [-c] [-v] {C,CC,CCC} ...

positional arguments:
  {C,CC,CCC}

optional arguments:
  -h, --help      show this help message and exit
  -c              A BB [optional pi]
  -v, --verbose   A BB erbosity

'A BB':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB' id='139714598483088'>
'A BB -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB' id='139714598483088'>
'A BB -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB' id='139714598483088'>
'A BB -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB' id='139714598483088'>

NODE :: 'A BB C':
-----
usage: A BB C [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              A BB C [optional pi]
  -v, --verbose   A BB C verbosity

'A BB C':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB_C' id='139714598483280'>
'A BB C -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB_C' id='139714598483280'>
'A BB C -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB_C' id='139714598483280'>
'A BB C -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB_C' id='139714598483280'>

NODE :: 'A BB CC':
-----
usage: A BB CC [-h] [-c] [-v]

```

```

optional arguments:
-h, --help      show this help message and exit
-c              A BB CC [optional pi]
-v, --verbose  A BB CC verbosity

'A BB CC':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB_CC' id='139714598483472'>
'A BB CC -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB_CC' id='139714598483472'>
'A BB CC -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB_CC' id='139714598483472'>
'A BB CC -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB_CC' id='139714598483472'>

NODE :: 'A BB CCC':
-----
usage: A BB CCC [-h] [-c] [-v]

optional arguments:
-h, --help      show this help message and exit
-c              A BB CCC [optional pi]
-v, --verbose  A BB CCC verbosity

'A BB CCC':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB_CCC' id='139714598483664'>
'A BB CCC -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB_CCC' id='139714598483664'>
'A BB CCC -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB_CCC' id='139714598483664'>
'A BB CCC -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB_CCC' id='139714598483664'>

```

```

1 from parsearg.examples.a_aa import main
2 main()

```

```

NODE :: 'A':
-----
usage: A [-h] [-c] [-v] {B,BBB,BB} ...

positional arguments:
  {B,BBB,BB}

optional arguments:
-h, --help      show this help message and exit
-c              A [optional pi]
-v, --verbose  A verbosity

'A':
----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A' id='139714598483904'>
'A -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A' id='139714598483904'>

```

```

'A -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A' id='139714598483904'>
'A -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A' id='139714598483904'>

NODE :: 'A B':
-----
usage: A B [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              A B [optional pi]
  -v, --verbose   A B verbosity

'A B':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_B' id='139714598562448'>
'A B -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_B' id='139714598562448'>
'A B -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_B' id='139714598562448'>
'A B -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_B' id='139714598562448'>

NODE :: 'A BB':
-----
usage: A BB [-h] [-c] [-v] {C,CC,CCC} ...

positional arguments:
  {C,CC,CCC}

optional arguments:
  -h, --help      show this help message and exit
  -c              A BB [optional pi]
  -v, --verbose   A BB erbosity

'A BB':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB' id='139714598562592'>
'A BB -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB' id='139714598562592'>
'A BB -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB' id='139714598562592'>
'A BB -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB' id='139714598562592'>

NODE :: 'A BB C':
-----
usage: A BB C [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              A BB C [optional pi]
  -v, --verbose   A BB C verbosity

```

```

'A BB C':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB_C' id='139714598562256'>
'A BB C -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB_C' id='139714598562256'>
'A BB C -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB_C' id='139714598562256'>
'A BB C -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB_C' id='139714598562256'>

NODE :: 'A BB CC':
-----
usage: A BB CC [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              A BB CC [optional pi]
  -v, --verbose   A BB CC verbosity

'A BB CC':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB_CC' id='139714598562496'>
'A BB CC -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB_CC' id='139714598562496'>
'A BB CC -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB_CC' id='139714598562496'>
'A BB CC -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB_CC' id='139714598562496'>

NODE :: 'A BB CCC':
-----
usage: A BB CCC [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              A BB CCC [optional pi]
  -v, --verbose   A BB CCC verbosity

'A BB CCC':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.A_BB_CCC' id='139714598562016'>
'A BB CCC -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.A_BB_CCC' id='139714598562016'>
'A BB CCC -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.A_BB_CCC' id='139714598562016'>
'A BB CCC -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.A_BB_CCC' id='139714598562016'>

NODE :: 'AA':

```

```

-----
usage: AA [-h] [-c] [-v] {B,BBB,BB} ...

positional arguments:
  {B,BBB,BB}

optional arguments:
  -h, --help      show this help message and exit
  -c              AA [optional pi]
  -v, --verbose   AA verbosity

'AA':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.AA' id='139714598576960'>
'AA -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.AA' id='139714598576960'>
'AA -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.AA' id='139714598576960'>
'AA -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.AA' id='139714598576960'>

NODE :: 'AA B':
-----
usage: AA B [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              AA B [optional pi]
  -v, --verbose   AA B verbosity

'AA B':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.AA_B' id='139714598576912'>
'AA B -v':
-----
  args: {'c': None, 'verbose': True}
  <Mock name='mock.AA_B' id='139714598576912'>
'AA B -c':
-----
  args: {'c': 3.141593, 'verbose': False}
  <Mock name='mock.AA_B' id='139714598576912'>
'AA B -v -c':
-----
  args: {'c': 3.141593, 'verbose': True}
  <Mock name='mock.AA_B' id='139714598576912'>

NODE :: 'AA BB':
-----
usage: AA BB [-h] [-c] [-v] {C,CC,CCC} ...

positional arguments:
  {C,CC,CCC}

optional arguments:
  -h, --help      show this help message and exit
  -c              AA BB [optional pi]
  -v, --verbose   AA BB verbosity

'AA BB':
-----
  args: {'c': None, 'verbose': False}
  <Mock name='mock.AA_BB' id='139714598576864'>
'AA BB -v':
-----

```

```

    args: {'c': None, 'verbose': True}
    <Mock name='mock.AA_BB' id='139714598576864'>
'AA BB -c':
-----
    args: {'c': 3.141593, 'verbose': False}
    <Mock name='mock.AA_BB' id='139714598576864'>
'AA BB -v -c':
-----
    args: {'c': 3.141593, 'verbose': True}
    <Mock name='mock.AA_BB' id='139714598576864'>

NODE :: 'AA BB C':
-----
usage: AA BB C [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              AA BB C [optional pi]
  -v, --verbose   AA BB C verbosity

'AA BB C':
-----
    args: {'c': None, 'verbose': False}
    <Mock name='mock.AA_BB_C' id='139714598577824'>
'AA BB C -v':
-----
    args: {'c': None, 'verbose': True}
    <Mock name='mock.AA_BB_C' id='139714598577824'>
'AA BB C -c':
-----
    args: {'c': 3.141593, 'verbose': False}
    <Mock name='mock.AA_BB_C' id='139714598577824'>
'AA BB C -v -c':
-----
    args: {'c': 3.141593, 'verbose': True}
    <Mock name='mock.AA_BB_C' id='139714598577824'>

NODE :: 'AA BB CC':
-----
usage: AA BB CC [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              AA BB CC [optional pi]
  -v, --verbose   AA BB CC verbosity

'AA BB CC':
-----
    args: {'c': None, 'verbose': False}
    <Mock name='mock.AA_BB_CC' id='139714598577536'>
'AA BB CC -v':
-----
    args: {'c': None, 'verbose': True}
    <Mock name='mock.AA_BB_CC' id='139714598577536'>
'AA BB CC -c':
-----
    args: {'c': 3.141593, 'verbose': False}
    <Mock name='mock.AA_BB_CC' id='139714598577536'>
'AA BB CC -v -c':
-----
    args: {'c': 3.141593, 'verbose': True}
    <Mock name='mock.AA_BB_CC' id='139714598577536'>

NODE :: 'AA BB CCC':
-----
usage: AA BB CCC [-h] [-c] [-v]

optional arguments:
  -h, --help      show this help message and exit
  -c              AA BB CCC [optional pi]
  -v, --verbose   AA BB CCC verbosity

```

```
'AA BB CCC':  
-----  
  args: {'c': None, 'verbose': False}  
  <Mock name='mock.AA_BB_CCC' id='139714598576384'>  
'AA BB CCC -v':  
-----  
  args: {'c': None, 'verbose': True}  
  <Mock name='mock.AA_BB_CCC' id='139714598576384'>  
'AA BB CCC -c':  
-----  
  args: {'c': 3.141593, 'verbose': False}  
  <Mock name='mock.AA_BB_CCC' id='139714598576384'>  
'AA BB CCC -v -c':  
-----  
  args: {'c': 3.141593, 'verbose': True}  
  <Mock name='mock.AA_BB_CCC' id='139714598576384'>
```