Day - 19

String, List & Number Functions

in Python

SKILL COURSE

A.I. Powered 30 Days Python Micro Course By Satish Dhawale (Microsoft Certified Trainer)

Why Built-In Functions Are Important?

- **Layman Explanation**

  Built-in functions are like **shortcuts** in Python. Instead of writing long code, Python gives ready-made tools.

- Example:

  Instead of counting items manually, use len()

  Instead of finding max value manually, use max()

- **Technical Definition**

  Built-in functions are pre-defined functions in Python that help perform operations quickly and efficiently on strings, lists, and numbers.

STRING FUNCTIONS

- text = "banana"
- print(text.count("a"))
- print("hello.py".endswith(".py"))
- print("Sales_Report.csv".startswith("Sales"))
- print("123".isdigit())
- print("ABC".isalpha())
- print("A1B2".isalnum())
- print("Line1\nLine2".splitlines())
-

LIST FUNCTIONS

```
nums = [5, 2, 7, 1]
nums.sort()
print(nums)

fruits = ["Banana", "apple", "Mango"]
print(sorted(fruits))

marks = [10,20,30]
print(min(marks), max(marks), sum(marks))

mylist = [1,2,1,3,1]
print(mylist.count(1))
print(mylist.index(3))

a = [1,2]
b = [3,4]
a.extend(b)
print(a)
```

NUMBER FUNCTIONS

```
print(round(3.678, 2))
print(abs(-50))
print(pow(3, 4))
print(divmod(10, 3))
print(sum([5,5,5], 5))

# PRACTICAL EXAMPLES
products = [" mobile ", "Laptop", "  TABLET"]
clean = [p.strip().title() for p in products]
clean.sort()
print(clean)

emails = ["rohit@gmail.com", "sneha@yahoo.com"]
domains = [mail[mail.find("@")+1:] for mail in emails]
print(domains)


mobiles = ["9876543210", "9988AB2211", "12345"]
valid = [m for m in mobiles if m.isdigit() and len(m)==10]
print(valid)
```