

PROGRAM

```
# cassandra.yaml (on every node)
cluster_name: 'CollegeCluster'
seeds: "192.168.1.10"
listen_address: <node's own IP>
# Start Cassandra
sudo service cassandra start
# Verify cluster
nodetool status
# Open CQL shell
Cqlsh
```

```
CREATE KEYSPACE college_ks
WITH REPLICATION = {
  'class': 'SimpleStrategy',
  'replication_factor': 3
}
USE college_ks;
CREATE TABLE student (
  rollno INT PRIMARY KEY,
  name TEXT,
  dept TEXT
);
INSERT INTO student (rollno, name, dept)
VALUES (101, 'RAJA', 'CSE');
INSERT INTO student (rollno, name, dept)
VALUES (102, 'PRIYA', 'IT');
SELECT * FROM student;
```

OUTPUT

```
Datacenter: datacenter1
Status=Up/Down | State=Normal/Leaving/Joining
-- Address    Load    Owns    Host ID    Rack
UN 192.168.1.10 95 KB   34.0%    ...       rack1
UN 192.168.1.11 102 KB  33.0%    ...       rack1
UN 192.168.1.12 98 KB   33.0%    ...       rack1
rollno | dept | name
-----+-----+-----
  101 | CSE | RAJA
  102 | IT  | PRIYA
```