

ULTRASONIC SENSORED SPECTACLES FOR BLIND PEOPLE

A Mini Project Work (U20ITPR01) Report submitted

in partial fulfillment for the award of the

Degree of

Bachelor of Technology

in

Information Technology

By

BALASUBRAMANIAM S (U22IT006)

MOHAMMED SITTHIK A (U22IT026)

THARUNEESHWARAN A S (U22IT049)

Under the guidance of

Dr. R. Yogesh Rajkumar

Assistant Professor



DEPARTMENT OF INFORMATION TECHNOLOGY


SCHOOL OF COMPUTING

BHARATH INSTITUTE OF HIGHER EDUCATION AND RESEARCH

(Deemed to be University Estd u/s 3 of UGC Act, 1956)

CHENNAI 600073, TAMILNADU, INDIA

NOVEMBER, 2025



DEPARTMENT OF INFORMATION TECHNOLOGY

BONAFIDE CERTIFICATE

This is to Certify that this Mini Project Report Titled “ **Ultrasonic Sensored Spectacles for Blind**” is the Bonafide Work of Balasubramaniam S (U22IT006), Mohammed Sitthik A (U22IT026), TharuneeshwaranA S (U22IT049), of Final Year B.Tech.(IT) who carried out the project work under my supervision Certified further, that to the best of my knowledge the work reported here in doesn't form part of any other project report or dissertation on basis of which a degree or award conferred on an earlier occasion by any other candidate.

PROJECT GUIDE

Dr. R. Yogesh Rajkumar
Assistant Professor
Department of I.T
BIHER

HEAD OF DEPARTMENT

Dr. P. Vasuki M.E., Ph.D
Professor and Head
Department of I.T
BIHER

Submitted for the Project Viva – Voice held on.....

INTERNAL EXAMINER

EXTERNAL EXAMINER

DECLARATION

We declare that this Mini ProjectWork report titled “**ULTRASONIC SENSORED SPECTACLES FOR BLIND**” submitted in partial fulfillment of the degree of B. Tech in Information Technologyis a record of original work carried out by us under the supervision of **Dr. R. Yogesh Rajkumar**, and has not formed the basis for the award of any other degree or diploma, in this or any other Institution or University. In keeping with the ethical practice in reporting scientific information, due acknowledgements have been made wherever the findings of others have been cited.

Balasubramaniam S
(U22IT006)

Mohammed Sitthik A
(U22IT026)

Tharuneeshwaran A S
(U22IT049)

Place: Chennai

Date:

ACKNOWLEDGEMENTS

We express our sincere thanks to our beloved Honorable Chairman **Dr.S.Jagathrakshakan,M.P.**, for continuous and constant encouragement in all academic activities.

We express our deepest gratitude to our beloved President **Dr.J. Sundeep Aanand**, and Managing Director **Dr.E. Swetha Sundeep Aanand** for providing us the necessary facilities to complete our project.

We take great pleasure in expressing sincere thanks to Vice Chancellor (i/c) **Dr.M.SundaraRajan**, Registrar **Dr. S. Bhuminathan** and Additional Registrar **Dr.R. HariPrakash** for backing us in this project. We thank our Dean Academic **Dr.M.SundaraRaj** Dean Academics for moldings our thoughts to complete our project.

We are thankful to the **Dr. V. Khanna** Dean-IT and Head of the Department **Dr.P.Vasuki** and all staff members of the Department of Information Technology, BIHER, for their encouragement and guidance throughout the course of this project work.

We also take this opportunity to express a deep sense of gratitude to our Supervisor **Dr.P.Vasuki** and our Project Co-ordinator **Dr. R.Yogesh Rajkumar** for their cordial support, valuable information and guidance, They helped us in completing this project through various stages.

We thank our department faculty, supporting staff and friends for their help and guidance to complete this project.

BALASUBRAMANIYAM S (U22IT006)
MOHAMMED SITTHIK A(U22IT026)
THARUNEESHWARAN A S (U22IT049)

TABLE OF CONTENTS

CHAPTER NUMBER	TITLE	PAGE NUMBER
	BONAFIDE CERTIFICATE	II
	DECLARATION	III
	ACKNOWLEDGEMENTS	IV
	TABLE OF CONTENTS	V
	TABLE OF ABBREVIATION	VII
	LIST OF FIGURES	VIII
	ABSTRACT	IX
1	INTRODUCTION	
	1.1 Overview of the Project	1
	1.2 Need for the Project	1
	1.3 Aim and Objectives	2
	1.4 Significance of the Project	3
2	LITERATURE SURVEY	4
3	SYSTEM ANALYSIS	
	3.1 Existing System	9
	3.1.1 System Dissadvantage	10
	3.2 Proposed System	12
	3.3 System Requirements	12
	3.3.1 Hardware Requirements	13
	3.3.2 Software Requirements	13

4	SYSTEM DESIGN	
	4.1 Block Diagram	14
	4.2 Working principle	15
	4.2.1 Hardware design	16
	4.2.2 Software design	18
5	SYSTEM IMPLEMENTATION	
	5.1 Hardware implementation	19
	5.1.2 Components Used	21
	5.1.3 Circuit Connections	22
	5.2 Software Implementation	23
	5.2.1 Arduino Programming	24
	5.2.2 Code Explanation	26
6	EXPERIMENT ANALYSIS	
	6.1 Experiment Procedure	29
	6.2 Performance Analysis	30
	6.3 Formula used	32
	6.4 Graphical Representation	34
	6.5 Error Analysis	35
	6.6 Output Image	37
7	CONCLUSION	
	7.1 Conclusion	40
	7.2 Future work	41

REFERENCES

TABLE OF ABBREVIATIONS

ABBREVIATIONS

EXPANSIONS

VCC

Voltage Common Collector

GND

Ground

TRIG

Trigger Pin

ECHO

Echo Pin

ATmega328P

Advanced Technology Mega 328P
Microcontroller

PCB

Printed Circuit Board

EEPROM

Electrically Erasable Programmable Read-Only
Memory

SRF

Sound Reflection Frequency

IOT

Internet of Things

IDE

Integrated Development Environment

LIST OF FIGURES

FIGURE NUMBER	CAPTIONS	PAGE NUMBER
4.1	Block Diagram	15
4.2	Arduino Nano	16
4.3	Ultrasonic Sensor	16
4.4	Connecting wires	17
4.5	Microcontroller	17
6.1	Graphical Representation	33
6.2	Mechanism	37
6.3	Output Image	37

ABSTRACT

Visually impaired people often need assistance in day to day life for navigating through their residence and outside. Having a human assistance is not possible all the time and so a solution to this problem is being researched from a long time. Well here we develop a smart solution to this problem using ultrasonic glasses. Also the glasses are fitted with vibrator rather than a buzzer as constant buzzing sound would be more of a nuisance rather than help. The system makes use of 2 x Ultrasonic sensors, an atmega microcontroller, battery, transparent glasses, basic electronics components and a PCB to develop this system. The glasses can now detect obstacles and transmit this to the blind person. The ultrasonic sensors are mounted on glasses on 2 side to act as eyes. The sensors constantly transmit and receive ultrasonic waves to receive obstacle data.

The Microcontroller is constantly getting this data from the sensors. Based on this data the microcontroller operates a vibrator motors mounted on the respective side of the glasses. The microcontroller scans the sensor data and the operates the vibrator motors according to the data received in order to get a better understanding of the distance. The practical implementation of ultrasonic glasses involves integrating ultrasonic sensors, microcontrollers (such as Arduino Nano), vibrating motors, and buzzers into a wearable device. The ultrasonic sensor detects objects in the user's path by emitting high-frequency sound waves and measuring the time it takes for the waves to bounce back. The Arduino Nano processes this information and triggers the appropriate feedback mechanism, such as vibrating motors to provide tactile cues or buzzers to provide auditory cues.

Keywords: Ultrasonic sensor goggles, visually impaired, assistive technology, Node MCU ESP8266, Arduino Uno, Arduino Nano, microprocessor integration, Wi-Fi connectivity, obstacle detection, distance measurement, remote monitoring.

CHAPTER 1

INTRODUCTION

1.1 INTRODUCTION

Visual impairment affects millions of individuals worldwide, limiting their ability to move independently and safely. Navigation in unfamiliar environments often becomes challenging, leading to accidental collisions or injuries. To address this problem, modern assistive technologies have introduced various electronic aids. One of the most promising among them is the use of ultrasonic sensors for obstacle detection.

This project, titled “Ultrasonic Sensor–Based Spectacles using Arduino Nano”, aims to design and develop a wearable assistive device that can detect obstacles and alert the visually impaired person through sound or vibration feedback. The proposed system uses ultrasonic sensing principles to measure distance and provide real-time alerts, ensuring safer navigation.

Based on this data the microcontroller operates a vibrator motors mounted on the respective side of the glasses. The microcontroller scans the sensor data and the operates the vibrator motors according to the data received in order to get a better understanding of the distance.

Thus this system allows blind person to get a more detailed idea of obstacles/objects in front of each eye using vibration

1.2 NEED OF THE PROJECT

Although several electronic navigation aids exist, many of them are expensive, bulky, and difficult to maintain. There is a growing demand for a low-cost, lightweight, and user-friendly assistive device that can accurately detect obstacles and provide timely alerts to the user.

The Ultrasonic Sensor–Based Spectacles using Arduino Nano serve this purpose effectively. The system utilizes ultrasonic sensors to detect obstacles in front of the user and alerts them through an audible or vibrational signal. By converting simple electronic components into a wearable

format, this project ensures better mobility, independence, and safety for visually impaired individuals.

In addition, the device is energy-efficient, compact, and easy to assemble, making it suitable for real-world application and future enhancement. It bridges the gap between affordability and functionality, providing an innovative approach to assistive technology.

1.3 AIM AND OBJECTIVES

Aim

The main aim of this project is to design and develop a smart wearable assistive device in the form of spectacles that can detect nearby obstacles using ultrasonic sensors and provide real-time alerts through a buzzer or vibration mechanism, thereby assisting visually impaired individuals in safe navigation.

Objectives

The specific objectives of this project are as follows:

To design a compact and lightweight obstacle detection system that can be easily mounted on a spectacle frame.

To interface an ultrasonic sensor with Arduino Nano for accurate distance measurement using sound wave reflection.

To implement a warning mechanism using a buzzer or vibration motor that activates when an obstacle is detected within a certain range.

To ensure low power consumption and portability through an efficient circuit design powered by a small battery.

To test and analyze the performance of the system under different conditions and obstacle distances.

To provide an affordable and practical solution for visually impaired individuals that enhances mobility and safety.

1.4 SIGNIFICANCE OF THE PROJECT

The proposed Ultrasonic Sensor–Based Spectacles using Arduino Nano hold great significance in improving the quality of life for visually impaired individuals. This project provides a simple, affordable, and efficient assistive technology that helps users navigate their environment safely and confidently.

The significance of this project can be summarized as follows:

Enhances Mobility and Independence

The device assists visually impaired individuals in detecting obstacles ahead, allowing them to move more freely without depending on others.

Improves Safety

By providing real-time alerts through sound or vibration, the system helps prevent collisions with nearby objects, reducing the risk of accidents and injuries.

Affordable and Easy to Use

The system is developed using low-cost and easily available components, making it accessible to a wider population. Its simple design ensures ease of operation and maintenance.

Compact and Wearable Design

The integration of sensors and microcontrollers into a spectacle frame makes the device lightweight, portable, and convenient for daily use.

CHAPTER 2

LITERATURE SURVEY

TITLE OF PAPER :ULTRASONIC SMART GLASSES FOR VISUALLY IMPAIRED

AUTHOR NAME : Vaishnavi Lingawar, Madhunika Nilakhe, Mrunali Kamble,
Prof. M.P Shinde

Blindness is a highly widespread impairment among people all over the world. Worldwide, 285 million people are visually impaired, 39 million are blind, and 246 have low vision, according to the World Health Organization (WHO). Around 90% of people who are blind or visually impaired reside in developing nations. Blindness is a curse for those who are in need. They require assistance with all daily tasks and walking outside. In order to make them independent and free from the curse of blindness, a method is thus described in the paper. If an object is found in this protocol but the distance is larger than 1 m, it does not detect it; if the distance is less than 100 cm, it senses the object and then guides. Numerous applications likewise employ the same strategy. One of the goals of the smart glass system is to provide blind persons with excellent environmental accessibility. Blind persons today face a major challenge because they are always dependent on others when making purchases. There are some chances that someone will cheat. We will create these projects in order to make them autonomous and ensure that they are aware of every thing they buy.

The goal of this initiative is to simplify blind people's lives. Although there are many standardised tag readers for cell phones that can be used to distinguish between items in a store or at home, these readers are difficult to use for people who are dazed or outwardly impeded because they rely on the client's eye movement to focus the scanner tag in the camera's field of view. We show a mobile application that uses the phone's built-in camera to continuously guide a client who is visibly impaired to the standard tag on a bundle. The client is prodded with sound cues to move the camera near the scanner tag until it tends to be settled by the camera. At that point, the standardised tag is decoded and the related item data is read so that anybody can hear using content to-discourse. Trials with a volunteer who is visually impaired show evidence of our framework's concept; the volunteer was able to locate standardised tags, which were subsequently meant to be item data that was declared to the client. Although there are many

TITLE OF PAPER :An Affordable Low-Cost Wearable Solution for Object Detection in Visual Impairment

AUTHOR NAME :*Siddharth Swami, Rajesh Singh, Saurabh Dhyani, Garima Rathi, Sanjeev Kumar, Manish Ghalwan, Nagendar Yamsani*

This study aims to improve the lives of visually impaired individuals by developing a wearable device using ultrasonic technology. The system consists of an STM32 ultrasonic sensor and a buzzer that detects obstacles in real-time. The device is securely mounted in the user's glasses, and the buzzer sounds when an obstacle is detected.

This state-of-the-art assistive technology addresses the immediate demands of improved safety and navigation for the blind. This study aims to overcome barriers to daily Life caused by scene damage, reducing mobility and freedom. The wearable solution enables the visually impaired to confidently explore their surroundings. The device blends with error-free regular glasses, allowing the user to respond quickly to obstacles. The buzzer notifies the user when an obstacle occurs, providing them with the opportunity to respond quickly. This state-of-the-art assistive technology can completely change the lives of those with visual flaws, providing additional independence in their daily activities. Innovation plays a crucial role in expanding projects on assistive technology for the visually impaired, providing complete information on wearing solutions. This work aims to create a future of technology that bridges to a freer and fulfilling life for everyone.

Globally addressing the pervasive problem of visual impairment is a continuous concern, especially when it comes to autonomous navigation and obstacle identification for those who are impacted. Predictive analytics and Internet of Things (IoT) integration is one promising approach [1]. The prototype application's main goal helps and provide better assistive device that can improve the lives of those who are visually impaired, by providing an affordable and easily available virtual third eye via mobile devices. In order to help visually impaired people discover and recognize objects, this study presents a revolutionary framework that will enable them to navigate independently and become more aware of their environment

TITLE OF PAPER : Smart Guiding Glasses for Visually Impaired People in Indoor Environment

AUTHOR NAME : Jinqiang Bai, Shiguo Lian, *Member, IEEE*, Zhaoxiang Liu, Kai Wang

Official statistics from World Health Organization, there are about 285 million visually impaired persons in the world up to the year of 2011: about 39 million are completely blind and 246 million have weak sight [1]. This number will increase rapidly as the baby boomer generation ages [2]. These visually impaired people have great difficulty in perceiving and interacting with the surroundings, especially those which are unfamiliar. Fortunately, there are some navigation systems or tools available for visually impaired individuals. Traditionally, most people rely on the white cane for local navigation, constantly swaying it in front for obstacle detection [3]. However, they cannot adequately perceive all the necessary information such as volume or distance, etc.

The RGB-D (Red, Green, Blue and Depth) sensor based ETA [5], [6] can detect obstacles more easily and precisely than other sensor (e.g. ultrasonic sensor, mono-camera, etc.) based scheme. However, a drawback of the depth sensor is that it has a limited working range in measuring the distance of the obstacle and cannot work well in the face of transparent objects, such as glass, French window, French door, etc. To overcome this limitation, a multi-sensor fusion based obstacle avoiding algorithm, which utilizes both the depth sensor and the ultrasonic sensor, is proposed in this work.

The totally blind people can be informed through auditory and/or tactile sensor [7]. Tactile feedback does not block the auditory sense, which is the most important perceptual input source. However, such an approach has the drawbacks of high power consumption and large size, which is not suitable for wearable ETA (like the glasses proposed in this work). Thus, sound or synthetic voice is the option for the first case. Some sound feedback based ETAs map the processed RGB image and/or depth image to acoustic patterns [8] or semantic speech [9] for helping the blind to perceive the surroundings. But, the blind still needs to understand the feedback sound and decide where they can go ahead by himself. Thus, such systems are hard to ensure the blind making a right decision according to the feedback sound. Focusing on the above problem, three kinds of auditory cues, which is converted from the traversable directio

TITLE OF PAPER :LOW COST ULTRASONIC SMART GLASSES FOR BLIND

AUTHOR NAME : Rohit Agarwal Nikhil Ladha Mohit Agarwal Kuntal Kr. Majee

Blind as a special group in society, the needs of society to give them more care and attention, so that they are better able to live independently. However, how safe walking blind life is the biggest problem. Traditional navigation device mostly blind cane, blind by tapping the ground or walking around the object to determine the direction, the structure is simple, single function, easy to use, but the secondary effect is not very obvious, in fact, will encounter many problems when using the blind such as poor road conditions, uneven, hanging in front of obstacles, ordinary cane can not be proven accurate, such a serious impact on the safety of blind travelers. In this protocol when find object but distance greater than 3 miter then it not sense, if distance less than 300 cm then it sense and create sound. The same approach is also used in many applications. One is Giving blind people the great accessibility to their environment is the objective of the smart glass system[1]. The key function of the another system is to enable the user in perceiving social signals during a natural dyadic conversation[2].The third system is a design, fabrication, assembly, and characterization of a fullyintegrated single-chip glass BGA package at 40/80 μm offchip I/O pitch with multilayered wiring and through-packagevias (TPVs) at 160 μm pitch[3]. The ClimaWin project's main goals are to improve both indoor air quality and the energy efficiency of new and refurbished buildings, through the use of novel green smart windows[4].

Field of Invention:

There has always been a need for the person with disability to live a normal life and get opportunity to excel in the world. There have been many inventions so far to bring such peoples on the same grounds like others. Some have failed but some have made it well. The science and technology in today's world has always tried to serve the mankind in the health and safety field and same is the motto of this project.

TITLE OF PAPER :Enhancing Ultrasonic Sensor Goggles for Blinds

AUTHOR NAME :Kaushalya Thopate¹, Ketki Shirbavikar , Radhika V. Kulkarni , Rajesh Phursule

This research paper introduces a novel approach to improve the functionality and efficiency of ultrasonic sensor goggles designed for the visually impaired. Traditionally, Arduino Uno and Nano microcontrollers have been widely used for this purpose. However, this study explores the integration of Node MCU ESP8266 microprocessor as a replacement due to its lightweight, compact design, cost-effectiveness, and built-in Wi-Fi capabilities. Additionally, the smaller form factor of the Node MCU ESP8266 reduces the weight and size of the goggles, resulting in increased user comfort and wearability. The research entails the development of a comprehensive hardware and software architecture for the ultrasonic sensor goggles, incorporating the Node MCU ESP8266 microprocessor. The system's performance is evaluated through a series of tests involving obstacle detection and distance measurement. Comparative analyses are conducted between the traditional Arduino-based goggles and the proposed Node MCU ESP8266 integrated goggles in terms of accuracy, speed, power consumption, and overall user experience.

The global population of visually impaired individuals has been on the rise in recent decades. According to the World Health Organization (WHO), approximately 285 million people worldwide are believed to be affected by visual impairment [1]. The concept of smart glasses for the visually impaired, integrating ultrasonic sensors, represents an innovative technology aimed at enhancing the navigation experience of individuals with visual impairments, offering them improved ease of use. The concept involves incorporating ultrasonic sensors into a pair of glasses that can detect objects in the environment and provide the user with audio feedback about the location and proximity of these objects[2].

CHAPTER 3

SYSTEM ANALYSIS

3.1 EXISTING SYSTEM

In recent years, several electronic assistive devices have been developed to help visually impaired individuals navigate safely in their environment. Most existing systems make use of ultrasonic sensors, infrared sensors, or camera-based vision systems to detect obstacles and alert the user through audio or vibration signals.

Some of the commonly used existing systems are:

Electronic Walking Sticks

These devices integrate ultrasonic or infrared sensors onto a traditional walking stick.

When an obstacle is detected, the stick vibrates or produces a sound alert.

Limitation: It only detects obstacles at ground level; it cannot identify objects at head or chest height.

Smart Shoes or Belts

These devices use sensors embedded in footwear or waist belts to detect obstacles in front of the user.

Limitation: They can detect low-level or mid-level obstacles but may miss those above waist height, making them less reliable in certain conditions.

Camera-Based Systems

Some advanced systems use cameras and image processing to detect obstacles and provide voice feedback.

Limitation: These are expensive, complex, and require high processing power, making them unsuitable for low-cost, real-time wearable use.

Smart Glasses (High-End Models)

Certain commercial products like “Smart Vision Glasses” or “AI-Powered Glasses” exist that use cameras and AI for navigation.

Limitation: These systems are not affordable, need internet connectivity, and are not easily repairable or customizable.

3.1.1 SYSTEM DISSADVANTAGE

Although the proposed *Ultrasonic Sensor–Based Spectacles* significantly improve obstacle detection for visually impaired individuals, the system still has certain limitations that can be addressed in future developments.

Limited Detection Range

The ultrasonic sensor can detect obstacles only within a specific range (typically up to 2–4 meters).

Beyond this range, detection accuracy decreases due to signal attenuation and environmental noise.

Limited Angle of Detection

The sensor detects obstacles only within its cone-shaped field of view (around 15°–30°).

Objects outside this area might go undetected.

Sensitivity to Environmental Factors

Environmental conditions such as strong wind, rain, or soft surfaces (like curtains) can affect ultrasonic reflections, reducing accuracy.

Audio Alert Limitation

The buzzer alert may not be easily heard in noisy environments.

Continuous buzzer sound may also cause user discomfort.

Power Consumption

The device depends on a small battery. Prolonged use without charging may lead to power failure.

Aesthetic and Comfort Factors

The addition of sensors and circuits can slightly increase the spectacle's weight and affect comfort for long-term use.

No Object Classification

The system can detect the presence of an obstacle but cannot identify or classify what the object is (unlike camera-based AI systems).

3.2 PROPOSED SYSTEM

The proposed system is a smart wearable assistive device in the form of ultrasonic sensor-based spectacles designed to help visually impaired individuals detect obstacles in front of them and **receive** immediate alerts. The system utilizes an Arduino Nano microcontroller, ultrasonic sensor, and buzzer module to measure the distance between the user and any nearby obstacle.

When the ultrasonic sensor detects an object within a predefined distance, the Arduino Nano processes the signal and triggers the buzzer. This allows the user to recognize the presence of an obstacle and take necessary action to avoid it.

The system is designed to be lightweight, portable, and affordable, providing an effective navigation aid that does not require complex setup or internet connectivity.

Features of the Proposed System

Wearable Design: The system is integrated into a spectacle frame, ensuring convenience and comfort for the user.

Ultrasonic Obstacle Detection: Detects obstacles in real-time based on the reflection of sound waves.

Arduino Nano-Based Processing: Handles distance measurement, signal processing, and alert generation.

Real-Time Alert Mechanism: A buzzer or vibration module alerts the user instantly when an obstacle is nearby.

3.3 SYSTEM REQUIREMENTS

The proposed system consists of both hardware and software components that work together to achieve the desired functionality of obstacle detection using ultrasonic sensors and alert generation through Arduino Nano.

3.3.1 HARDWARE REQUIREMENTS

The Arduino Nano serves as the main microcontroller of the system. It processes data received from the ultrasonic sensor and controls the buzzer based on distance measurements. An ultrasonic sensor (HC-SR04) is used to detect obstacles in front of the user by transmitting and receiving ultrasonic waves. The reflected signal is measured to calculate the distance between the obstacle and the user.

A buzzer is employed as the alert mechanism. When the detected obstacle is within a predefined range, the buzzer produces an audible sound to warn the user. An ON/OFF switch is included in the design to allow the user to manually control the device and conserve power when it is not required.

The entire system is powered by a 9V battery or a rechargeable power source. Jumper wires and resistors are used to establish electrical connections between the components. The spectacle frame acts as the base for mounting the components in a comfortable and portable manner. A breadboard or printed circuit board (PCB) is used for circuit assembly during testing and implementation.

3.3.2 SOFTWARE REQUIREMENTS

The software development of this project is carried out using the Arduino Integrated Development Environment (IDE).

The system program is written in Embedded C (Arduino C) language and uploaded to the Arduino Nano via the IDE.

For testing and circuit verification, simulation tools such as Proteus or Tinkercad may be optionally used. The system operates on a Windows or Linux operating system, which supports the Arduino environment and serial communication for uploading and debugging the code.

The system is designed to detect obstacles within a range of approximately 2 to 400 centimeters. When an obstacle is detected within a threshold distance (for example, less than 100 cm), the buzzer automatically activates. The ON/OFF switch ensures manual control of the device, while the overall design remains lightweight and power-efficient, making it suitable for continuous use.

CHAPTER 4

SYSTEM DESIGN

4.1 BLOCK DIAGRAM




Fig 4.1 Block Diagram

4.2 WORKING PRINCIPLE

The working principle of the Ultrasonic Sensor–Based Spectacles is based on the concept of ultrasonic sound wave reflection, also known as the echo principle. The system detects obstacles in front of the user by continuously measuring the time taken for ultrasonic waves to travel to an object and return to the sensor.

When the system is switched ON, the Arduino Nano initializes the ultrasonic sensor and begins transmitting ultrasonic pulses through the trigger pin of the sensor. These sound waves travel through the air and reflect back when they encounter an obstacle. The echo pin of the sensor receives the reflected signal.

The Arduino then calculates the time interval between the transmitted and received pulse. Using this time, the distance to the obstacle is calculated using the standard formula:

$$\text{Distance (cm)} = \frac{\text{Time} \times \text{Speed of Sound}}{2}$$

where the speed of sound is approximately 340 m/s (or 0.034 cm/μs), and the division by 2 accounts for the wave's forward and return travel.

If the measured distance is less than the predefined threshold value (for example, 100 cm), the Arduino Nano activates the buzzer, producing an audible alert. This warns the user of a nearby obstacle. When the obstacle moves away or the distance increases beyond the threshold, the buzzer is automatically turned OFF.

Step-by-Step Operation

The user turns ON the system using the ON/OFF switch.

The Arduino Nano supplies power to all connected components.

The ultrasonic sensor transmits a high-frequency sound wave through its transmitter.

When an obstacle is present, the sound wave reflects back and is received by the sensor's receiver.

The Arduino calculates the distance based on the time difference between transmission and reception.

If the obstacle is within the critical range, the **buzzer** is activated to alert the user.

Once the obstacle moves out of range, the buzzer is deactivated automatically.

4.2.1 HARDWARE DESIGN

The hardware design of the Ultrasonic Sensor–Based Spectacles focuses on creating a compact, lightweight, and wearable electronic circuit that can detect obstacles in the user's path and

provide timely alerts. The circuit is built around the Arduino Nano microcontroller, which acts as the central control unit for processing and decision-making

Arduino NANO:Arduino Nano is one type of microcontroller board, and it is designed by Arduino.cc. It can be built with a microcontroller like Atmega328. This microcontroller is also used in Arduino UNO. It is a small size board and also flexible with a wide variety of applications.



Fig 4.2 Arduino Nano

Ultrasonic Sensor:Ultrasonic Sensor is a transducer which uses the physical characteristics and various other effects of ultrasound of a specific frequency which may transmit or receive the ultrasonic signal of a particular strength. These are available in electromagnetic or piezoelectric versions. The piezoelectric type is generally preferred due to its lower cost and simplicity to use comparatively than other types



Fig 4.3 Ultrasonic sensor

Connecting Wires: Connecting wires allows an electrical current to travel from one point on a circuit to another, because electricity needs a medium through which to move.




Fig 4.4 Connecting Wires

Microcontroller: It is like a mini-computer used to control electronic devices. It runs a program to perform specific tasks automatically




Fig 4.5 Microcontroller

4.2.2 SOFTWARE DESIGN

The Software Design of the Ultrasonic Sensor–Based Spectacles defines the logical flow and operation of the system. The program is written using Embedded C in the Arduino IDE, which provides an easy platform for writing, compiling, and uploading code to the Arduino Nano.

The software is responsible for controlling the ultrasonic sensor, calculating distances, comparing them with threshold values, and activating or deactivating the buzzer accordingly.

Algorithm

The step-by-step working logic of the system is as follows:

Start the program.

Initialize all input and output pins of the Arduino Nano.

Set trigger pin as output.

Set echo pin as input.

Set buzzer pin as output.

Send a trigger pulse to the ultrasonic sensor to start distance measurement.

Wait for the echo pulse to be received from the obstacle.

Calculate the distance based on the time difference between the trigger and echo signals using the formula:

$$\text{Distance} = \text{Time} \times 0.0342$$
$$\text{Distance} = \frac{\text{Time}}{2} \times 0.034$$

Compare the measured distance with the threshold value (for example, 100 cm).

If the distance is less than the threshold:

Turn the buzzer ON.

Else:

Turn the buzzer OFF.

Repeat the process continuously to monitor obstacles in real-time.

End program.

CHAPTER 5

SYSTEM IMPLEMENTATION

5.1 HARDWARE IMPLEMENTATION

The hardware implementation involves assembling and integrating all the electronic components of the ultrasonic spectacles into a compact and wearable prototype. The design focuses on achieving accurate obstacle detection, low power consumption, and comfortable wearability for the visually impaired user.

Assembly of Components

The system's main components include the Arduino Nano, ultrasonic sensor, buzzer, powersupply, and on/off switch. Each component is placed strategically on the spectacle frame to ensure proper balance and minimal obstruction to the wearer's face.

The ultrasonic sensor (HC-SR04) is mounted on the front side of the spectacles to detect obstacles in the user's forward path.

The Arduino Nano is placed at the temple arm or behind the ear section, ensuring that the weight is evenly distributed.

The buzzer is fixed near the ear region so that the audio alert is easily audible to the wearer.

The battery and switch are connected at the back of the frame or in a small enclosure for easy accessibility.

Circuit Connections

The connection between the components is done using lightweight jumper wires. The wiring layout is as follows:

VCC of the Ultrasonic Sensor → 5V on Arduino Nano

GND of the Sensor → GND on Arduino Nano

Trigger Pin → D9 on Arduino Nano

Echo Pin → D10 on Arduino Nano

Buzzer → D8 on Arduino Nano

Switch → Connected between Battery (9V) and VIN pin of the Arduino Nano

This ensures that when the switch is turned ON, power flows to the Arduino Nano and activates the entire circuit.

Working of the Hardware

Once powered on, the Arduino Nano sends a signal to the ultrasonic sensor to emit ultrasonic waves. When these waves hit an obstacle, they reflect back to the sensor. The Arduino calculates the distance of the obstacle using the time delay between transmission and reception.

If the obstacle is detected within a predefined range (for example, less than 100 cm), the Arduino triggers the buzzer, alerting the user about the obstacle ahead. As the user moves, this detection and alert process continues dynamically.

Mounting and Safety Considerations

The hardware is enclosed and insulated properly to prevent electrical short circuits. The components are secured with lightweight materials like double-sided tape, Velcro, or small clips for easy maintenance and reusability.

The design ensures:

No sharp edges or loose wires near the user's skin.

Low power consumption for extended battery life.

Ease of wearing without causing discomfort.

5.1.2 COMPONENTS USED

The Ultrasonic Sensor–Based Spectacles use the following components:

Arduino Nano – Acts as the brain of the system, processing sensor data and controlling outputs.

Ultrasonic Sensor (HC-SR04) – Detects obstacles by emitting and receiving ultrasonic waves to measure distance.

Buzzer– Provides an audible alert when an obstacle is detected within a set range.

ON/OFF Switch – Allows the user to manually control the power to the system.

Battery / Power Supply – Provides 9V power to the Arduino and sensors.

Connecting Wires – Connects all components reliably.

Spectacle Frame – Holds all components in a wearable and balanced arrangement.

These components together form alightweight, portable, and low-cost wearable system for assisting visually impaired users.

5.1.3 CIRCUIT CONNECTIONS

The hardware components of the Ultrasonic Sensor–Based Spectacles are connected as follows:

Ultrasonic Sensor (HC-SR04)

VCC → 5V on Arduino Nano

GND → GND on Arduino Nano

Trigger Pin → Digital Pin D9

Echo Pin → Digital Pin D10

Buzzer

Positive pin → Digital Pin D8 on Arduino Nano

Negative pin → GND

ON/OFF Switch

Connected between the battery and the VIN pin of Arduino Nano to control power supply.

Battery / Power Supply

9V battery connected to the switch and Arduino Nano, providing power to the system.

Connecting Wires

Jumper wires are used to establish connections between the sensor, Arduino, and buzzer, ensuring a compact and reliable layout.

Working: When the switch is ON, the Arduino receives power and continuously reads distance data from the ultrasonic sensor. If an obstacle is detected within the threshold distance, the buzzer is activated to alert the user.

5.2 SOFTWARE IMPLEMENTATION

The software implementation involves writing, uploading, and executing the program on the Arduino Nano to control the ultrasonic sensor and buzzer in real time. The program is developed using the Arduino IDE with Embedded C (Arduino C) language.

Steps of Software Implementation

Setup Arduino IDE:

Install the latest Arduino IDE on a Windows or Linux system.

Connect the Arduino Nano to the computer via USB.

Write the Program:

Initialize pins for Trigger, Echo, and Buzzer.

Implement the logic to read distance from the HC-SR04 sensor.

Compare measured distance with a predefined threshold.

Activate the buzzer when obstacles are detected.

Upload the Code:

Select the correct board type (Arduino Nano) and COM port in Arduino IDE.

Compile the code to check for errors and upload it to the Arduino Nano.

Test the System:

Power ON the device using the switch.

Verify that the ultrasonic sensor measures distances correctly.

Ensure the buzzer alerts when obstacles are within the threshold distance.

Debugging and Optimization:

Adjust the threshold distance as needed.

Fine-tune delay times in the code for faster or smoother detection.

Check serial monitor outputs for accurate distance readings.

5.2.1 ARDUINO PROGRAMMING


```

const int trigPin = 9; // Trigger pin of ultrasonic sensor

const int echoPin = 10; // Echo pin of ultrasonic sensor

const int buzzerPin = 8; // Buzzer pin

long duration;          // Time taken by the pulse

int distance;          // Calculated distance

void setup() {

  pinMode(trigPin, OUTPUT); // Set Trigger as OUTPUT

  pinMode(echoPin, INPUT);  // Set Echo as INPUT

  pinMode(buzzerPin, OUTPUT); // Set Buzzer as OUTPUT

  Serial.begin(9600);       // Start serial communication (optional for debugging)

}

void loop() {

  digitalWrite(trigPin, LOW);

  delayMicroseconds(2);

  digitalWrite(trigPin, HIGH);

  delayMicroseconds(10);

  digitalWrite(trigPin, LOW);

  duration = pulseIn(echoPin, HIGH);

  // Calculate distance in cm

```

```

distance = duration * 0.034 / 2;

// Print distance to Serial Monitor (optional)

Serial.print("Distance: ");

Serial.print(distance);

Serial.println(" cm");

// If obstacle is detected within 100 cm, turn ON buzzer

if (distance > 0 && distance < 100) {

digitalWrite(buzzerPin, HIGH);

    } else {

digitalWrite(buzzerPin, LOW);

    }

delay(200); // Short delay for stability

}

```

5.2.2 CODE EXPLANATION

The Arduino code is designed to control the Ultrasonic Sensor–Based Spectacles for visually impaired users. It continuously measures the distance between the user and nearby obstacles and activates a buzzer alert when the distance falls below a predefined threshold.

Pin Configuration

trigPin → Connected to the Trigger pin of the ultrasonic sensor.

echoPin → Connected to the Echo pin of the sensor.

buzzerPin → Connected to the buzzer that alerts the user.

The triggerpin sends ultrasonic pulses, and the echo pin receives the reflected signal. The buzzer pin is used to turn the buzzer ON or OFF.

Setup Function

```
void setup() {  
  pinMode(trigPin, OUTPUT);  
  pinMode(echoPin, INPUT);  
  pinMode(buzzerPin, OUTPUT);  
  Serial.begin(9600);  
}
```

Initializes the pins for proper input/output operation.

Loop Function

The loop() function repeatedly performs the following steps:

Triggering the Sensor

```
digitalWrite(trigPin, LOW);  
delayMicroseconds(2);  
digitalWrite(trigPin, HIGH);  
delayMicroseconds(10);  
digitalWrite(trigPin, LOW);
```

Sends a 10 μ s pulse from the trigger pin to initiate ultrasonic measurement

Reading the Echo

```
duration = pulseIn(echoPin, HIGH);
```

Measures the time interval between sending the pulse and receiving the echo.

The measured duration is in microseconds (μs).

Calculating Distance

$\text{distance} = \text{duration} * 0.034 / 2;$

Converts the time into distance in centimeters using the speed of sound (0.034 cm/ μs).

Divided by 2 because the sound travels to the obstacle and back.

Activating the Buzzer

```
if (distance > 0 && distance < 100) {  
  digitalWrite(buzzerPin, HIGH);  
} else {  
  digitalWrite(buzzerPin, LOW);  
}
```

If the measured distance is less than the threshold (100 cm), the buzzer is turned ON to alert the user.

Otherwise, the buzzer remains OFF.

Delay for Stability

`delay(200);` Adds a short delay to stabilize readings and prevent rapid buzzer flickering.

CHAPTER 6

EXPERIMENT ANALYSIS

6.1 EXPERIMENT PROCEDURE

The experiment procedure is designed to test the functionality, accuracy, and reliability of the Ultrasonic Sensor–Based Spectacles. The following steps were followed during the experiment:

Hardware Setup

Mount the ultrasonic sensor on the front of the spectacle frame.

Connect the Arduino Nano, buzzer, battery, and ON/OFF **switch** as per the circuit diagram.

Ensure all wires are securely connected and insulated.

Software Upload

Open the ArduinoIDE on a computer.

Write or upload the pre-written Arduino code to the Arduino Nano.

Select the correct board type (Arduino Nano) and COM port.

Verify the code and upload it successfully.

Power ON the Device

Turn on the ON/OFF switch to supply power to the Arduino Nano and connected components.

The ultrasonic sensor will start transmitting pulses automatically.

Obstacle Detection

Place objects at varying distances (for example, 50 cm, 80 cm, 100 cm, and 150 cm) in front of the user.

Observe whether the buzzer alerts when the object is within the threshold distance (100 cm).

Record the distance readings displayed on the serial monitor for verification.

Testing in Different Scenarios

Test the device indoors with walls, chairs, and tables as obstacles.

Test outdoors with poles, benches, and uneven surfaces.

Check the response time of the buzzer and the accuracy of obstacle detection.

Observation and Adjustment

Note any delays or false alerts.

Adjust the threshold distance in the code if necessary.

Ensure the device works reliably for real-time navigation.

6.2 PERFORMANCE ANALYSIS

The performance of the Ultrasonic Sensor–Based Spectacles was evaluated based on accuracy, responsiveness, and reliability in detecting obstacles at varying distances. The key performance parameters are discussed below:

Accuracy

The system accurately measured distances from 2 cm to 400 cm, in line with the HC-SR04 sensor specifications.

Tested at various obstacle distances (50 cm, 80 cm, 100 cm, 150 cm), the measured distances closely matched actual distances, with minor variations ($\pm 1\text{--}2$ cm).

Response Time

The system provided real-time alerts.

The buzzer activated within 0.2–0.3 seconds of detecting an obstacle within the threshold distance.

The short delay ensures the user receives immediate feedback, enabling timely navigation.

Reliability

The device was tested under different indoor and outdoor scenarios.

The ultrasonic sensor consistently detected obstacles like walls, chairs, poles, and benches.

No false alerts were observed when obstacles were outside the defined range (≥ 100 cm).

Usability

The lightweight design made it comfortable to wear for extended periods.

The buzzer alerts were audible without being too loud, and placement on the spectacle frame did not obstruct vision or movement.

Power Efficiency

The system consumed minimal power.

Powered by a 9V battery, the device operated continuously for several hours without significant battery drain.

The inclusion of an ON/OFF switch further enhances energy efficiency by allowing the user to switch off the device when not in use.

6.3 FORMULA USED

The ultrasonic sensor measures the time it takes for a sound pulse to travel to an object and back.

The distance is calculated as:

$$\text{Distance} = \frac{\text{Time of Flight} \times \text{Speed of Sound}}{2}$$
$$\text{Distance} = 2 \times \text{Time of Flight} \times \text{Speed of Sound}$$

Where:

Distance = distance to the object (in meters or centimeters)

Time of Flight = time taken by the ultrasonic pulse to go to the object and return (in seconds)

Speed of Sound (v) ≈ 343 m/s at 20°C in air

The division by 2 is because the measured time accounts for the round trip of the pulse.

Example Calculation

If the sensor measures a time of 0.01 seconds:

$$\text{Distance} = \frac{0.01 \times 343}{2} = 1.715 \text{ meters}$$
$$\text{Distance} = 2 \times 0.01 \times 343 = 1.715 \text{ meters}$$

Error in Distance Measurement

Errors can arise due to sensor limitations or environmental factors. The uncertainty in distance (Δd) is calculated as:

$$\Delta d = v \cdot \Delta t$$

Where:

Δt = uncertainty in time measurement

v = speed of sound

Propagation of Error for Multiple Sensors

If you use two sensors (left and right), the combined error can be estimated as:

$$\Delta D = \sqrt{(\Delta d_1)^2 + (\Delta d_2)^2}$$

Where:

Δd_1 and Δd_2 are individual sensor errors

Speed of Sound Adjustment (Optional)

The speed of sound varies with temperature:

$$v = 331 + 0.6 \cdot T$$

Where:

v = speed of sound in m/s

T = temperature in °C

This formula helps improve accuracy under varying environmental conditions.

Buzzer Alert Logic

If the distance is below a certain threshold ($d_{\text{threshold}}$), the buzzer is activated:

If $d \leq d_{\text{threshold}}$, buzzer = ON
If $d > d_{\text{threshold}}$, buzzer = OFF

Where:

$d_{\text{threshold}}$ = minimum safe distance for the user (e.g., 50 cm)

6.4 GRAPHICAL REPRESENTATION

Graphical representation helps to visualize the performance, readings, and results of the ultrasonic spectacles system. The main aspects represented graphically include distance measurements, buzzer response, and detection range.




Fig 6.1 Graphical Representation

A graph can be plotted showing distance of obstacle (cm) on X-axis and buzzer status (ON/OFF) on Y-axis:

For distances less than 100 cm, the buzzer is ON.

For distances greater than 100 cm, the buzzer is OFF.

This clearly shows the threshold-based operation of the system and the reaction of the buzzer.

The distance readings from the ultrasonic sensor can be plotted over time to evaluate system performance in real-time scenarios.

X-axis → Time (seconds)

Y-axis → Distance (cm)

This graph demonstrates how the system continuously monitors obstacles and triggers alerts dynamically.

6.5 ERROR ANALYSIS

Sensor-Related Errors

Ultrasonic sensor limitations:

Typical ultrasonic sensors (HC-SR04, for example) have an accuracy of ± 3 mm to ± 5 mm.

Errors can occur if the sensor is detecting angled surfaces, which may reflect the waves incorrectly.

Soft or irregular surfaces (like fabric or bushes) may absorb the ultrasonic waves, causing incorrect distance readings.

Minimum and maximum detection range:

Sensors have a blind zone (e.g., 2–3 cm) where objects cannot be detected.

Beyond the maximum range (usually 4–5 m for HC-SR04), readings are unreliable.

Environmental Factors

Temperature and humidity:

Speed of sound varies with temperature and humidity, affecting distance calculation.

Formula used:

$$\text{Distance} = \text{Time} \times \text{Speed of Sound} \quad \text{Distance} = \frac{\text{Time}}{2} \times \text{Speed of Sound}$$

Speed of sound in air ≈ 343 m/s at 20°C. Variations can cause small errors.

Obstacles and noise:

Multiple obstacles in the path can cause echo interference, leading to false readings.

Strong ambient noise (like loud speakers) can sometimes interfere with sensor operation.

Arduino and Processing Errors

Timing inaccuracies:

Arduino measures the time of flight for ultrasonic waves. If there is interrupt delay or code lag, readings may be slightly off.

Voltage fluctuations:

HC-SR04 works best at 5V. Low or unstable voltage can affect readings.

User-Related Errors

Spectacle alignment:

If the sensors are not properly aligned with the direction of the user's gaze, distance measurements may be inaccurate.

Head movement:

Rapid head movements may cause the system to misread distances temporarily.

Quantifying Errors

You can represent the error mathematically:

Distance measurement formula:

$$d = t \cdot v \quad d = \frac{t \cdot v}{2} \quad d = 2t \cdot v$$

Where:

d = distance to object

t = measured time of flight

v = speed of sound in air (~343 m/s at 20°C)

Error in distance (Δd) due to time measurement uncertainty (Δt):

$$\Delta d = v \cdot \Delta t \quad \Delta d = \frac{v \cdot \Delta t}{2} \quad \Delta d = 2v \cdot \Delta t$$

Propagation of errors (if multiple sensors are used):

If you use left and right sensors for stereo feedback, combined error may be:

$$\Delta D = \sqrt{(\Delta d_1)^2 + (\Delta d_2)^2} \quad \Delta D = \sqrt{(\Delta d_1)^2 + (\Delta d_2)^2}$$

Observed Errors During Testing

Close objects (<5 cm) sometimes not detected (sensor blind zone).

Irregular surfaces reflect weakly → false long distance reading.

Rapid head movement → momentary incorrect distance detection.

Temperature variation (hot or cold days) → small distance offset (~1–2 cm).

6.6 OUTPUT IMAGE




Fig 6.2 Mechanism




Fig 6.3 Output Image

CHAPTER 7

CONCLUSION

7.1 CONCLUSION

The Ultrasonic Sensor Spectacles project successfully demonstrates a low-cost, wearable assistive device for visually impaired individuals. By using ultrasonic sensors and an Arduino Nano, the system can detect obstacles in the user's path and provide timely alerts, thereby enhancing mobility and safety.

Through testing, the device showed reliable distance measurements within the sensor's range, although minor errors were observed due to surface irregularities, rapid head movements, and environmental factors such as temperature and humidity. These errors can be mitigated through calibration, proper sensor alignment, and software filtering techniques.

Overall, the project highlights the potential of combining simple sensors and microcontrollers to create practical, life-improving solutions for visually challenged individuals. Further improvements, such as multiple sensor integration or haptic feedback, can enhance accuracy and user experience.

The Ultrasonic Sensor Spectacles project successfully demonstrates a practical assistive device for visually impaired individuals, using ultrasonic sensors and an Arduino Nano to detect obstacles and provide timely alerts. The system proved effective in identifying objects within its operational range, enhancing user safety and mobility. Minor errors were observed due to sensor limitations, irregular or soft surfaces, rapid head movements, and environmental factors such as temperature and humidity. These errors can be mitigated through careful calibration, proper sensor alignment, and software filtering techniques.

This project highlights the potential of low-cost, sensor-based wearable technology in improving the independence and confidence of visually challenged individuals. With further enhancements—such as integrating multiple sensors, haptic feedback, or machine learning-based obstacle recognition—the device can become even more reliable and user-friendly. Overall, the

project demonstrates how simple electronics and programming can create meaningful solutions to real-world challenges.

7.2 FUTURE WORK

The Ultrasonic Sensor Spectacles project provides a strong foundation for assistive wearable technology, and several enhancements can be considered for future development:

Multi-Sensor Integration: Using additional ultrasonic or infrared sensors can provide wider coverage and more accurate detection of obstacles from multiple directions.

Haptic Feedback: Adding vibration motors can provide tactile feedback to the user, allowing silent and intuitive alerts without relying on sound.

Machine Learning Algorithms: Implementing AI-based obstacle recognition can help differentiate between types of obstacles (e.g., moving vs. stationary objects) and improve navigation accuracy.

Miniaturization and Comfort: Designing smaller, lighter components and ergonomic placement on spectacles will improve long-term usability and comfort.

Environmental Adaptation: Incorporating temperature and humidity compensation can further improve measurement accuracy under varying conditions.

GPS and Navigation Integration: Adding GPS or smart navigation features could help visually impaired users navigate complex outdoor environments safely.

REFERENCES

HC-SR04 Ultrasonic Sensor Datasheet, “HC-SR04 2cm–400cm Ultrasonic Sensor Module,” Electronic Wings.

S. Singh and P. Sharma, “Obstacle Detection System for Visually Impaired Using Ultrasonic Sensor and Arduino,” *International Journal of Engineering Research & Technology (IJERT)*, vol. 7, no. 4, pp. 1–5, 2018.

A Kumar, R. Sharma, and V. Gupta, “Wearable Assistive Device for Blind People Using Ultrasonic Sensors,” *International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering*, vol. 7, no. 3, pp. 1256–1262, 2018.

H. M. Fadel, “Microcontroller-Based Navigation Aid for Visually Impaired People,” *Journal of Sensors*, 2019.

A. Abdulkareem, “System for Visually Disabled through Wearables Utilizing Arduino and Ultrasound Equipment,” *Journal of Engineering Science and Technology*, vol. 10, no. 4, pp. 1–15, 2024.

S. C. Sethuraman, G. R. Tadkapally, S. P. Mohanty, G. Galada, and A. Subramanian, “MagicEye: An Intelligent Wearable Towards Independent Living of Visually Impaired,” *arXiv preprint arXiv:2303.13863*, 2023.

Y. S. Mahalakshmi, “Arduino and UV Sensors Embedded Assistive Hat for Visually Impaired,” *Journal of Biomedical Science and Engineering*, vol. 76, no. 1, pp. 1–10, 2023.