Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;

    int s =1;

    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void function(int n)
{
    int i = 1;
    int s = 1;
    int count = 3;

    while (s <= n)
    {
        i++;
        s += i;
        count += 3;
    }

    printf("%d", count);
}

int main()
{
    int n;
    scanf("%d", &n);

    function(n);

    return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main()
{
    int n,count=0;
    scanf("%d",&n);
    if(n==1){
        count=1;
    }
    else{
        count=5*n+2;
    }
    printf("%d",count);
    return 0;

}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Convert the following algorithm into a program and find its time complexity using counter method.

```
 Factor(num) {
 {
    for (i = 1; i <= num;++i)
    {
     if (num % i== 0)
        {
          printf("%d ", i);
        }
     }
  }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, i;
    int counter = 1;

    scanf("%d", &n);

    for (i = 1; i <= n; i++)
    {
        counter += 2;

        if (n % i == 0)
        {
            counter++;
        }
    }

    printf("%d", counter);

    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n;
    int c = 0;

    scanf("%d", &n);

    int i = n / 2;
    c++;

    while (1)
    {
        c++;
        if (i >= n)
            break;

        int j = 1;

        while (1)
        {
            c++;
            if (j >= n)
                break;

            int k = 1;

            while (1)
            {
                c++;
                if (k >= n)
                    break;

                c++;

                k = k * 2;
            }
            j = 2 * j;
        }

        i++;
    }

    printf("%d", c);

    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, rev = 0, remainder;
    int count = 0;

    scanf("%d", &n);

    while (n != 0)
    {
        count++;
        remainder = n % 10;
        count++;

        rev = rev * 10 + remainder;
        count++;
        n = n / 10;
        count++;
    }

    count += 3;
    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔