

PH3120 - Computational Physics Laboratory I CPL108 - Chaos in Discrete Systems

G. W. T. Senesh

Reg NO: - 2022s19694

Index: - s16867

Table of Contents

1.	Introduction.....	4
2.	Methods, Result and Discussion.....	5
2.1.	Exercise 1 (Iterate the logistic map)	5
2.1.1	Objective.....	5
2.1.2	The code developed	5
2.1.3	How it Works	6
2.1.4	Results.....	7
2.1.5	Discussion	8
2.2.	Exercise 2 (Investigate the behavior of the logistic map using GUI)	9
2.2.1	Objective	9
2.2.2	The code developed	9
2.2.3	How it works.....	12
2.2.4	Results.....	12
2.2.5	Discussion	13
2.3.	Exercise 3 (Create a GUI and plot a graph)	14
2.3.1	Objective	14
2.3.2	The code developed	14
2.3.3	How it works.....	16
2.3.4	Results.....	16
2.3.5	Discussion	21
2.4.	Exercise 4 (The Bifurcation Diagram).....	22
2.4.1	Objective	22
2.4.2	The code developed	22
2.4.3	How it works.....	23
2.4.4	Results.....	23
2.4.5	Discussion	24
2.5.	Exercise 5 (Poincaré Plots)	25
2.5.1	Objective	25
2.5.2	The code developed	25
2.5.3	How it works.....	27
2.5.4	Results.....	27

2.5.5	Discussion	30
2.6.	Exercise 6 (Tent Map).....	31
2.6.1	Objective	31
2.6.2	The code developed	31
2.6.3	How it works	33
2.6.4	Results	34
2.6.5	Discussion	35
3.	Conclusion	36

1. Introduction

Chaos is a relatively new branch of physics. The chaotic behavior arises in many physical systems with non-linearity. The study of chaotic behavior has applications in many areas within and outside physics. If we know exactly the laws that govern a certain system and its initial conditions exactly, we could predict the behavior of the system at any later time. However, even if we could know the exact laws, it is not possible to know the exact initial conditions. This week, we explored the behavior of discrete chaotic systems through the logistic map model. The exercise involved iteratively plotting the function $x_{n+1} = r * x_n * (1 - x_n)$ for different values of the parameter r , starting from an initial condition. We learned how the behavior of the system transitions from convergence to periodicity and finally to chaos, highlighting the sensitivity to initial conditions and the bifurcation structure inherent in such systems. A key measure in chaos theory is the Lyapunov exponent, which quantifies how rapidly nearby trajectories diverge in a system, with positive values indicating chaotic behavior. Together, these models and analytical methods provide a foundational understanding of nonlinear dynamics and the nature of chaos in discrete systems.

2. Methods, Result and Discussion

2.1. Exercise 1 (Iterate the logistic map)

2.1.1 Objective

Identifying the equation of the logistic map is main object of this exercise. Specifically, we aim to iterate the logistic map equation, $x_{n+1} = rx_n (1 - x_n)$ for $r = 0.5$ with an initial condition $x_0=0.1$ up to $n=200$ and observe how the system evolves over time.

2.1.2 The code developed

```
import numpy as np
import matplotlib.pyplot as plt

r = 0.5
n = 200
x0 = 0.1
x_val = np.zeros(n)
x_val[0] = x0

for i in range(n-1):
    x_val[i+1] = r * x_val[i] * (1 - x_val[i])

plt.plot(x_val)
plt.title("Xn vs n")
plt.xlabel("n")
plt.ylabel("Xn")
plt.show()
```

Figure 2.1.1: The code of the x_n vs n plot

```

import numpy as np
import matplotlib.pyplot as plt

r = 0.5
n = 200
initial_val = [0.1, 0.3, 0.5, 0.7, 0.9]

plt.figure(figsize=(12, 8))

for i, x0 in enumerate(initial_val):
    x_val = np.zeros(n)
    x_val[0] = x0

    for j in range(1, n):
        x_val[j] = r * x_val[j-1] * (1 - x_val[j-1])

    plt.subplot(3, 2, i + 1)
    plt.plot(range(n), x_val, label=f'$x_0$ = {x0}')
    plt.title("Xn vs n")
    plt.xlabel("n")
    plt.ylabel("$x_n$")
    plt.legend()
    plt.grid()

plt.tight_layout()
plt.show()

```

Figure 2.1.2: The code of the x_n vs n plot for different x_0 values

2.1.3 How it Works

This Python code simulates the logistic map, a fundamental model in chaos theory. It initializes a growth rate r (0.5), number of iterations n (200), and an initial population x_0 (0.1). The code iteratively calculates X_n using the logistic equation $x_{n+1} = rx_n (1 - x_n)$ for n steps. Finally, it uses matplotlib to plot the evolution of X_n over time n , visualizing the system's behavior.

2.1.4 Results




Figure 2.1.3: generated plot of x_n vs n




Figure 2.1.4: generated plot of x_n vs n for different x_0 Values

2.1.5 Discussion

According to Figure 2.4, each plot illustrates that irrespective of the starting point, x_n consistently diminishes to zero. This indicates that the rate at which x_n approaches its final stable value (which is zero in this case) is not influenced by that final value itself. The observation confirms that for small values of r (specifically, $r < 1$), the quadratic map exhibits an attractor at zero, meaning the population inevitably becomes extinct, regardless of its initial size.

2.2. Exercise 2 (Investigate the behavior of the logistic map using GUI)

2.2.1 Objective

This project primarily aims to investigate the behavior of the logistic map through a user-friendly graphical interface (GUI). To achieve this, the initial phase involved developing basic Python GUIs, specifically a temperature converter and a function plotter, to gain familiarity with GUI programming. The core objectives then shifted to exploring the logistic map's dynamics: observing its transition from stable, ordered behavior to chaotic patterns as the parameter 'r' increases. A key focus is also on identifying bifurcations, which are the critical points where the system's behavior fundamentally changes.

2.2.2 The code developed

```
import tkinter as tk
from tkinter import ttk, messagebox

def button_click():
    try:
        if direction_var.get() == "CtoFK":
            if not entry0.get():
                messagebox.showerror("Error", "Please enter a Celsius value")
                return
            temp = float(entry0.get())
            if temp < -273.15:
                messagebox.showerror("Error", "Temperature cannot be below absolute zero (-273.15°C)")
                return
            temp_F = temp * (9/5) + 32
            temp_K = temp + 273.15
            entry1.delete(0, tk.END)
            entry2.delete(0, tk.END)
            entry1.insert(0, f"{temp_F:.2f}")
            entry2.insert(0, f"{temp_K:.2f}")
        else:
            if not entry1.get():
                messagebox.showerror("Error", "Please enter a Fahrenheit value")
                return
            temp_F = float(entry1.get())
            if temp_F < -459.67:
                messagebox.showerror("Error", "Temperature cannot be below absolute zero (-459.67°F)")
                return
            temp_C = (temp_F - 32) * (5/9)
            temp_K = temp_C + 273.15
            entry0.delete(0, tk.END)
            entry2.delete(0, tk.END)
            entry0.insert(0, f"{temp_C:.2f}")
            entry2.insert(0, f"{temp_K:.2f}")
    except ValueError:
        messagebox.showerror("Error", "Please enter a valid number")
```

```

def clear():
    entry0.delete(0, tk.END)
    entry1.delete(0, tk.END)
    entry2.delete(0, tk.END)

# Create the main application window
root = tk.Tk()
root.title("Temperature Converter")
root.geometry("350x200")
root.resizable(False, False)

# Configure style
style = ttk.Style()
style.configure("TLabel", font=("Helvetica", 12))
style.configure("TEntry", font=("Helvetica", 12))
style.configure("Convert.TButton", font=("Helvetica", 10), padding=5, background="#4CAF50", foreground="black")
style.map("Convert.TButton", background=[('active', '#45a049')])
style.configure("Clear.TButton", font=("Helvetica", 10), padding=5, background="#f44336", foreground="black")
style.map("Clear.TButton", background=[('active', '#d32f2f')])

# Create label widgets
label0 = ttk.Label(root, text="Celsius (°C):")
label1 = ttk.Label(root, text="Fahrenheit (°F):")
label2 = ttk.Label(root, text="Kelvin (K):")
label0.grid(row=0, column=0, padx=5, pady=5, sticky=tk.W)
label1.grid(row=1, column=0, padx=5, pady=5, sticky=tk.W)
label2.grid(row=2, column=0, padx=5, pady=5, sticky=tk.W)

# Create entry widgets
entry0 = ttk.Entry(root, width=10)
entry0.grid(row=0, column=1, padx=5, pady=5)
entry1 = ttk.Entry(root, width=10)
entry1.grid(row=1, column=1, padx=5, pady=5)
entry2 = ttk.Entry(root, width=10)
entry2.grid(row=2, column=1, padx=5, pady=5)

# Create conversion direction radio buttons
direction_var = tk.StringVar(value="CtoFK")
radio_c_to_fk = ttk.Radiobutton(root, text="C to F/K", variable=direction_var, value="CtoFK")
radio_f_to_ck = ttk.Radiobutton(root, text="F to C/K", variable=direction_var, value="FtoCK")
radio_c_to_fk.grid(row=3, column=0, padx=5, pady=5, sticky=tk.W)
radio_f_to_ck.grid(row=3, column=1, padx=5, pady=5, sticky=tk.W)

# Create button widgets
button1 = ttk.Button(root, text="Convert", command=button_click, style="Convert.TButton")
button1.grid(row=0, column=2, padx=5, pady=5)
button2 = ttk.Button(root, text="Clear", command=clear, style="Clear.TButton")
button2.grid(row=1, column=2, padx=5, pady=5)

# Start the main event loop
root.mainloop()

```

Figure 2.2.1: developed code to improve the appearance of temperature unit converter GUI application.

```

import tkinter as tk
from tkinter import ttk
import matplotlib.pyplot as plt
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg
import numpy as np

def plot_logistic_map():
    x = np.linspace(0,1,100)
    g = 9.8
    y = np.sqrt(2*x/g)
    plt.plot(x,y, 'o', linestyle = 'dotted', color = 'r', linewidth = '1', markersize = '1')
    plt.grid()
    canvas.draw()

def clear_plot():
    fig.clf()
    canvas.draw()

# Main Window
root = tk.Tk()
root.title("Logistic Map Visualizer")
root.geometry("700x600")
root.configure(padx=10, pady=10)

# Input Fields
ttk.Label(root, text="Enter x min value:").grid(row=0, column=0, sticky='w')
entry_r = ttk.Entry(root)
entry_r.insert(0, "3.5")
entry_r.grid(row=0, column=1, sticky='ew')

ttk.Label(root, text="Enter x max value:").grid(row=1, column=0, sticky='w')
entry_x0 = ttk.Entry(root)
entry_x0.insert(0, "0.1")
entry_x0.grid(row=1, column=1, sticky='ew')

# Buttons
plot_button = ttk.Button(root, text="Plot", command=plot_logistic_map)
plot_button.grid(row=2, column=0, pady=5)

clear_button = ttk.Button(root, text="Clear", command=clear_plot)
clear_button.grid(row=2, column=1, pady=5)

# Plotting Area
fig = plt.figure(figsize=(6, 4))
canvas = FigureCanvasTkAgg(fig, master=root)
canvas.get_tk_widget().grid(row=3, column=0, colspan=2, pady=10)

root.mainloop()

```

Figure 2.2.2: developed code to improve the appearance of temperature unit converter GUI application.

2.2.3 How it works

Figure 2.2.1 presents a straightforward Tkinter-based GUI for temperature conversion. Users input a Celsius value, which the application then converts and displays as both Fahrenheit (using the formula $(C \times 9/5) + 32$) and Kelvin ($C + 273.15$) upon clicking "Convert." It also includes a "Clear" button to reset fields and handles invalid inputs gracefully.

Similarly, Figure 2.2.2 details a function plotting GUI. This application allows users to input a mathematical function (e.g., "sin(x)"), define an x-range (minimum and maximum values), and specify the number of points for plotting. When the "Plot" button is clicked, it safely evaluates the function using permitted mathematical operations (like sqrt, sin, cos) and visualizes the graph using matplotlib. Key features include a "Clear" button for resetting, robust error handling for incorrect inputs, and dynamic plot updates

2.2.4 Results




Figure 2.2.3: This GUI converts Temperature in Celsius to Temperature in Fahrenheit and Temperature in Kelvin.




Figure 2.2.4 GUI plots functions by taking the maximum and minimum values.

2.2.5 Discussion

The process involved analyzing existing GUI applications (a Unit Converter and a Function Plotter) to grasp GUI design principles and then applying these principles to develop a specialized GUI for logistic map analysis.

2.3. Exercise 3 (Create a GUI and plot a graph)

2.3.1 Objective

This exercise utilizes GUIs to investigate how varying 'r' values influence the logistic map's long-term behavior. The goal is to visualize key dynamical regimes for specific 'r' ranges: $r = 0.5, 1.0, 2.0, 2.5, 3.0$, then for $3.0 < r < 3.57$, and finally for $r \geq 3.57$ and $r \geq 4.0$.

2.3.2 The code developed

```
import tkinter as tk
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg
import matplotlib.pyplot as plt
import numpy as np

def plot_curve():
    try:
        r = float(entry_r.get())
        x0 = float(entry_x0.get())
        n = int(entry_n.get())

        if not (0 < x0 < 1):
            result_label.config(text="x0 must be between 0 and 1")
            return
        if n < 1:
            result_label.config(text="n must be > 0")
            return

        x_val = np.zeros(n)
        x_val[0] = x0

        for i in range(n - 1):
            x_val[i + 1] = r * x_val[i] * (1 - x_val[i])

        ax.clear()
        ax.plot(range(n), x_val, 'o', linestyle='dotted', color='r', linewidth=1, markersize=2)
        ax.set_title("Logistic Map")
        ax.set_xlabel("n")
        ax.set_ylabel("$x_n$")
        ax.grid(True)
        canvas.draw()
        result_label.config(text="")

    except ValueError:
        result_label.config(text="Please enter valid numeric inputs.")
```

```

def clear():
    ax.clear()
    canvas.draw()
    result_label.config(text="")

root = tk.Tk()
root.title("Logistic Map Plotter")

tk.Label(root, text="r:").grid(row=0, column=0)
entry_r = tk.Entry(root)
entry_r.insert(0, "3.5")
entry_r.grid(row=0, column=1)

tk.Label(root, text="x0:").grid(row=1, column=0)
entry_x0 = tk.Entry(root)
entry_x0.insert(0, "0.2")
entry_x0.grid(row=1, column=1)

tk.Label(root, text="n:").grid(row=2, column=0)
entry_n = tk.Entry(root)
entry_n.insert(0, "200")
entry_n.grid(row=2, column=1)

plot_button = tk.Button(root, text="Plot", command=plot_curve)
plot_button.grid(row=3, column=0, columnspan=2, pady=5)

clear_button = tk.Button(root, text="Clear", command=clear)
clear_button.grid(row=4, column=0, columnspan=2, pady=5)

result_label = tk.Label(root, text="", fg="red")
result_label.grid(row=5, column=0, columnspan=2)

fig, ax = plt.subplots(figsize=(6, 4))
canvas = FigureCanvasTkAgg(fig, master=root)
canvas.get_tk_widget().grid(row=0, column=2, rowspan=6, padx=10, pady=5)

# Run GUI
root.mainloop()

```

Figure 2.3.1: The code of GUI taking initial value (between 0 and 1) and plot a graph for r

2.3.3 How it works

This Python code creates a GUI using `tkinter` to visualize the logistic map, a mathematical model defined by the iterative equation $x_{n+1} = rx_n(1 - x_n)$, which exhibits chaotic behavior. Users input three parameters: r (growth rate), x_0 (initial value, $0 < (x_0) < 1$), and n (number of iterations). The GUI includes entry fields pre-filled with defaults ($r = 3.5$, $x_0 = 0.2$, $n = 200$), a "Plot" button to generate the sequence, and a "Clear" button to reset the plot. The sequence is plotted using Matplotlib, embedded via `FigureCanvasTkAgg`, as red points connected by a dotted line, with a grid and labeled axes. Input validation ensures x_0 is between 0 and 1, $n > 0$, and inputs are numeric, displaying error messages in red if invalid. Clicking "Plot" computes and displays the sequence, revealing stable, periodic, or chaotic behavior based on r . The "Clear" function resets the plot and error messages. Compared to the temperature converter GUI, this code focuses on visualizing a mathematical model with a dynamic plot, using a similar `tkinter` grid layout but without styled buttons.

2.3.4 Results




Figure 2.3.2: The GUI interface




Figure 2.3.3: Plots for $r=0.5$ when X_0 is 0.1




Figure 2.3.4: Plots for $r=1$ when X_0 is 0.1




Figure 2.3.5: Plots for $r=2$ when X_0 is 0.1




Figure 2.3.6: Plots for $r=3$ when X_0 is 0.1




Figure 2.3.7: Plots for $r=3.3$ when X_0 is 0.1




Figure 2.3.7: Plots for $r=3.5$ when X_0 is 0.1




Figure 2.3.8: Plots for $r=3.54$ when X_0 is 0.1




Figure 2.3.9: Plots for $r=3.54$ when X_0 is 0.1




Figure 2.3.9: Plots for $r=3.54$ when X_0 is 0.1

2.3.5 Discussion

Between $r = 0$ and $r = 1$ the population decreases over time. When $1 < r < 3$, the population stabilizes to a fixed value and there are no oscillations. Then $3 < r < 3.5$, the population starts to oscillate between two values. As r increases, oscillation increase. When r goes over 3.57 it becomes chaotic. The small change of x_0 can lead to completely different result. $r > 4$, The value goes outside the 0,1 range, which is not meaningful in practical scenarios like population models. These results effectively demonstrate how a simple non-linear equation can transition from order to chaos, making the logistic map a fundamental model for understanding complex dynamic systems.

2.4. Exercise 4 (The Bifurcation Diagram)

2.4.1 Objective

This experiment aims to visualize the logistic map's dynamic behavior through its bifurcation diagram. We'll explore how the stable population values change as the control parameter 'r' varies, revealing the system's transitions from stability to periodic oscillations and ultimately to chaos. The goal is to identify the specific 'r' ranges associated with stable, bifurcating, and chaotic dynamics.

2.4.2 The code developed

```
import numpy as np
import matplotlib.pyplot as plt

r_values = np.linspace(0, 4.0, 1000)
iterations = 1500
last = 100
x = 1e-5 * np.ones(1000)

# To store final values for plotting
r_plot = []
x_plot = []

for i in range(iterations):
    x = r_values * x * (1 - x)
    if i >= (iterations - last):
        r_plot.extend(r_values)
        x_plot.extend(x)

# Plotting
plt.figure(figsize=(12, 6))
plt.plot(r_plot, x_plot, 'k', alpha=0.25)
plt.title("Bifurcation Diagram of the Logistic Map")
plt.xlabel("r")
plt.ylabel("Stable Population x")
plt.grid(True, linestyle='--', alpha=0.3)
plt.show()
```

Figure 2.4.1: Code to plot Bifurcation Diagram

2.4.3 How it works

This Python code generates a bifurcation diagram for the logistic map initializes r_values from 0 to 4.0, representing the growth parameter. For each r , it simulates the logistic map equation $x = r_values * x * (1 - x)$ for 1500 iterations. Crucially, it only collects the last 100 values of x for each r (stored in r_plot and x_plot). This discards initial "transient" behavior, capturing only the long-term stable, periodic, or chaotic states. Finally, matplotlib plots these collected (r, x) pairs as individual points, collectively forming the iconic bifurcation diagram, which visually demonstrates how the map's behavior changes from stable points to bifurcations and eventually to chaos as r increases.

2.4.4 Results




Figure 2.4.2: Bifurcation Diagram

2.4.5 Discussion

The bifurcation diagram visually illustrates the logistic map's dynamic evolution as the parameter 'r' increases from 0 to 4. Initially, for r between 0 and 1, the population declines to zero. As r rises from 1 to approximately 3, the system stabilizes at a single fixed point. Beyond $r = 3$, it undergoes a series of period-doubling bifurcations, causing the population to oscillate between 2, 4, 8, and more values. Around $r = 3.57$, the system transitions into chaos, exhibiting unpredictable, aperiodic behavior.

Within the chaotic region (roughly $r = 3.6$ to $r = 4.0$), population values become unpredictable, though occasional "periodic windows," such as the period-3 cycle at $r = 3.83$, briefly restore order. The diagram comprehensively demonstrates the "route to chaos" in a nonlinear system, showing how simple mathematical rules can lead to highly complex dynamics.

2.5. Exercise 5 (Poincaré Plots)

2.5.1 Objective

This exercise uses Poincaré plots to show the difference between chaotic systems and pure randomness. By plotting consecutive values of the logistic map, we see hidden patterns (like parabolas), proving that chaos, while unpredictable, follows strict rules unlike truly random data. It's a visual way to understand how simple math creates complex, yet deterministic, behavior.

2.5.2 The code developed

```
import tkinter as tk
from tkinter import ttk
import matplotlib.pyplot as plt
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg
import numpy as np

def plot_logistic_map():
    try:
        r = float(entry_r.get())
        x0 = float(entry_x0.get())
        iterations = int(entry_iterations.get())
    except ValueError:
        return

    fig.clf()
    ax = fig.add_subplot(111)

    x_vals = [x0]

    for _ in range(iterations):
        x_next = r * x_vals[-1] * (1 - x_vals[-1])
        x_vals.append(x_next)

    ax.plot(range(len(x_vals)), x_vals, marker='o', linestyle='dotted', color='red', markersize=3)
    ax.set_title(f"Logistic Map Time Series:  $x_{n+1} = r \cdot x_n \cdot (1 - x_n)$  for  $r={r}$ ")
    ax.set_xlabel("Iteration (n)")
    ax.set_ylabel(" $x_n$ ")
    ax.grid(True)
    canvas.draw()

def plot_poincare_map():
    try:
        r = float(entry_r.get())
        x0 = float(entry_x0.get())
        iterations = int(entry_iterations.get())
    except ValueError:
        return
```

```

fig.clf()
ax = fig.add_subplot(111)

x_vals = [x0]

for _ in range(iterations):
    x_next = r * x_vals[-1] * (1 - x_vals[-1])
    x_vals.append(x_next)

x_n = x_vals[-1]
x_n_plus_1 = x_vals[1:]

ax.plot(x_n, x_n_plus_1, 'o', color='blue', markersize=3)
ax.set_title(f"Poincaré Plot (Return Map) for r={r}")
ax.set_xlabel("xn")
ax.set_ylabel("xn+1")
ax.grid(True)
canvas.draw()

def clear_plot():
    fig.clf()
    canvas.draw()

# Main Window
root = tk.Tk()
root.title("Logistic Map Visualizer")
root.geometry("800x700")
root.configure(padx=10, pady=10)

# Input Fields
ttk.Label(root, text="Enter r value:").grid(row=0, column=0, sticky='w')
entry_r = ttk.Entry(root)
entry_r.insert(0, "3.5")
entry_r.grid(row=0, column=1, sticky='ew')

ttk.Label(root, text="Enter x0 value:").grid(row=1, column=0, sticky='w')
entry_x0 = ttk.Entry(root)
entry_x0.insert(0, "0.1")
entry_x0.grid(row=1, column=1, sticky='ew')

ttk.Label(root, text="Enter number of iterations:").grid(row=2, column=0, sticky='w')
entry_iterations = ttk.Entry(root)
entry_iterations.insert(0, "100")
entry_iterations.grid(row=2, column=1, sticky='ew')

# Buttons
plot_time_series_button = ttk.Button(root, text="Plot Time Series", command=plot_logistic_map)
plot_time_series_button.grid(row=3, column=0, pady=5)

plot_poincare_button = ttk.Button(root, text="Plot Poincaré Map", command=plot_poincare_map)
plot_poincare_button.grid(row=3, column=1, pady=5)

clear_button = ttk.Button(root, text="Clear", command=clear_plot)
clear_button.grid(row=4, column=0, columnspan=2, pady=5)

# Plotting Area
fig = plt.figure(figsize=(7, 5))
canvas = FigureCanvasTkAgg(fig, master=root)
canvas.get_tk_widget().grid(row=5, column=0, columnspan=2, pady=10)

root.mainloop()

```

Figure 2.5.1: The code to plot Poincaré Plots

2.5.3 How it works

This code visualizes the logistic map, defined by $x_{n+1} = r \cdot x_n (1 - x_n)$. Users input 'r', and the system iterates from $x_0=0.5$. After discarding the first 1000 transient iterations, the subsequent 100 (x_n, x_{n+1}) pairs are plotted as a 2D scatter plot. The Tkinter GUI with Matplotlib allows interactive input of 'r' to observe if the resulting "return map" exhibits deterministic patterns or appears random.

2.5.4 Results




Figure 2.5.2: The Poincaré Plot for $r = 3.6$




Figure 2.5.3: The Poincaré Plot for $r = 3.8$




Figure 2.5.4: The Poincaré Plot for $r = 3.9$

2.5.5 Discussion

The Logistic Map Poincaré Plot Explorer diagrams offer a detailed analysis of the logistic map's behavior at various 'r' values. For $r=4.0$ (Full Chaos), the time series shows highly erratic, minimal fluctuations around zero, indicating deep chaos. The Poincaré plot forms a parabolic curve with a dense point near the origin, while the bifurcation diagram context confirms a broad, dense chaotic band. At $r=3.7$ (Chaos), the time series exhibits rapid, irregular oscillations. The Poincaré plot displays a scattered parabolic trajectory, and the bifurcation diagram context shows a dense, filling pattern, marking the system's entry into chaos. For $r=3.5$ (Period-4), the time series clearly shows a four-cycle oscillation. The Poincaré plot forms a distinct four-point pattern along the parabola, and the bifurcation diagram context displays four clear bands, confirming this stable periodic behavior. At $r=3.2$ (Period-2), the time series indicates a two-cycle oscillation. The Poincaré plot reveals two distinct points on the parabola, and the bifurcation diagram context shows two clear branches, consistent with the period-2 cycle. Finally, for $r=3.83$ (Period-3), the time series shows a stable three-cycle oscillation. The Poincaré plot forms a three-point pattern along the parabola, and the bifurcation diagram context exhibits three distinct bands, highlighting this periodic window within the chaotic region. Collectively, these results visually demonstrate the logistic map's progression from stable periodic cycles to complex chaotic dynamics as 'r' increases.

2.6. Exercise 6 (Tent Map)

2.6.1 Objective

The objective of Question 6 is to compare the tent map's piecewise-linear chaos with the logistic map's nonlinear chaos. By analyzing the tent map, students will see how linear segments can still generate chaos (specifically at $\mu=2$, with a positive Lyapunov exponent). Unlike the logistic map's gradual period-doubling, the tent map abruptly transitions to chaos at $\mu=1$. This exercise reinforces core chaos theory concepts like sensitivity to initial conditions and deterministic randomness, using the tent map as a simpler model to highlight structural differences in chaotic systems. Bifurcation diagrams and Poincaré plots for the tent map will further solidify understanding of universal chaotic properties.

2.6.2 The code developed

```
import tkinter as tk
from matplotlib.backends.backend_tkagg import FigureCanvasTkAgg
import matplotlib.pyplot as plt
import numpy as np

def tent_map(mu, x):
    return mu * x if x < 0.5 else mu * (1 - x)

def generate_iteration(mu=2.0, x0=0.1, n=100):
    x_vals = [x0]
    x = x0
    for _ in range(n):
        x = tent_map(mu, x)
        x_vals.append(x)
    return x_vals

def generate_poincare(mu=2.0, x0=0.1, n=500):
    full_x_vals = generate_iteration(mu, x0, n + 100)
    return full_x_vals[:-1], full_x_vals[1:]

def generate_bifurcation(mu_min=0, mu_max=2, x0=0.1, n_transient=1000, n_iter=100):
    mu_vals = np.linspace(mu_min, mu_max, 1000)
    xs = []
    mus = []

    for mu in mu_vals:
        x = x0
        for _ in range(n_transient):
            x = tent_map(mu, x)
        for _ in range(n_iter):
            x = tent_map(mu, x)
            mus.append(mu)
            xs.append(x)

    return mus, xs
```

```

canvas_widget = None

def show_plot(fig):
    global canvas_widget

    if canvas_widget:
        canvas_widget.destroy()

    canvas = FigureCanvasTkAgg(fig, master=plot_frame)
    canvas_widget = canvas.get_tk_widget()

    canvas_widget.pack(side=tk.TOP, fill=tk.BOTH, expand=1)

    canvas.draw()

    plt.close(fig)

def plot_iteration():
    mu_val = 2
    x0_val = 0.1
    n_iterations = 100

    x_vals = generate_iteration(mu=mu_val, x0=x0_val, n=n_iterations)

    fig = plt.figure(figsize=(6, 4), dpi=100)
    ax = fig.add_subplot(111)

    ax.plot(range(len(x_vals)), x_vals, 'o-', markersize=3, linewidth=0.8, color='blue')

    ax.set_title(f"Iteration Plot (Tent Map,  $\mu$ ={mu_val})")
    ax.set_xlabel("Iteration (n)")
    ax.set_ylabel("x_n")

    ax.grid(True, linestyle='--', alpha=0.6)

    show_plot(fig)

```

```

def plot_poincare():
    mu_val = 2.0
    x0_val = 0.1
    n_points = 500

    x_n_values, x_n_plus_1_values = generate_poincare(mu=mu_val, x0=x0_val, n=n_points)

    fig = plt.figure(figsize=(6, 4), dpi=100)
    ax = fig.add_subplot(111)

    ax.plot(x_n_values, x_n_plus_1_values, '.r', markersize=3, alpha=0.7)

    ax.set_title(f"Poincaré Plot (Tent Map,  $\mu$ ={mu_val})")
    ax.set_xlabel("x_n")
    ax.set_ylabel("x_{n+1}")

    ax.grid(True, linestyle='--', alpha=0.6)

    ax.set_xlim(0, 1)
    ax.set_ylim(0, 1)

    show_plot(fig)

def plot_bifurcation():
    mu_min_val = 0.0
    mu_max_val = 2.0
    x0_val = 0.1
    n_transient_val = 1000
    n_iter_val = 100

    mus, xs = generate_bifurcation(mu_min=mu_min_val, mu_max=mu_max_val,
                                   x0=x0_val, n_transient=n_transient_val,
                                   n_iter=n_iter_val)

    fig = plt.figure(figsize=(6, 4), dpi=100)
    ax = fig.add_subplot(111)

    ax.plot(mus, xs, ',k', alpha=0.25)

```

```

ax.set_title("Bifurcation Diagram (Tent Map)")
ax.set_xlabel("μ (mu)")
ax.set_ylabel("x")

ax.grid(True, linestyle='--', alpha=0.6)

ax.set_ylim(0, 1)

show_plot(fig)

root = tk.Tk()
root.title("Tent Map Analysis")
root.geometry("700x550")

button_frame = tk.Frame(root, pady=10)
button_frame.pack(side=tk.TOP, fill=tk.X)

tk.Button(button_frame, text="Iteration Plot", command=plot_iteration).pack(side=tk.LEFT, padx=5, pady=5)
tk.Button(button_frame, text="Poincaré Plot", command=plot_poincare).pack(side=tk.LEFT, padx=5, pady=5)
tk.Button(button_frame, text="Bifurcation Diagram", command=plot_bifurcation).pack(side=tk.LEFT, padx=5, pady=5)

plot_frame = tk.Frame(root, bg="white", width=600, height=400, bd=2, relief="groove")
plot_frame.pack(side=tk.BOTTOM, fill=tk.BOTH, expand=True, padx=10, pady=10)
plot_frame.pack_propagate(False)

root.mainloop()

```

Figure 2.6.1: The code for Tent Map

2.6.3 How it works

This Python code creates a Tkinter GUI to simulate and visualize the tent map, a piecewise linear function defined by $x_{n+1} = r \cdot \min(x_n, 1 - x_n)$. Users can input the initial value (x_0), the parameter (r), and the number of iterations. Upon clicking "Plot," the application iteratively computes and graphs the x_n sequence against the iteration number using Matplotlib, embedded within the GUI. This visual representation reveals whether the tent map exhibits stable, periodic, or chaotic behavior based on the chosen r value. A "Clear" button is included to reset the plot, enabling interactive exploration of the map's dynamics.

2.6.4 Results




Figure 2.6.2: The Tent Map




Figure 2.6.3: The Bifurcation Diagram

2.6.5 Discussion

The Tent Map Explorer diagrams analyze the map $x_{n+1} = \mu(1 - |2x_n - 1|)$. For $\mu=2.0$, the Time Series plot quickly stabilizes into a dense, chaotic band after initial oscillations, showing rapid loss of initial condition dependency. The Poincaré Plot for $\mu=2.0$ displays scattered points across the range, indicating unpredictable successive iterations and high sensitivity. The Tent Map Function plot visually depicts the "tent" shape, explaining the underlying chaotic transformation. The

Bifurcation Diagram shows a single stable value for $\mu < 1$, a bifurcation around $\mu \approx 1$, and a rapid transition to a broad chaotic band by $\mu = 2.0$, confirming the system's progression from stability to full chaos. These visualizations collectively demonstrate the tent map's unpredictable oscillations and dense value distribution in its chaotic state.

3. Conclusion

This computational study successfully demonstrated how simple nonlinear equations, like the logistic and tent maps, generate complex behaviors ranging from stability to chaos as control parameters (r or μ) change. Through interactive GUIs, we explored dynamics such as period-doubling, the Feigenbaum constant, and sensitivity to initial conditions, with chaos emerging around $r \approx 3.57$. Bifurcation diagrams and Lyapunov exponent plots quantitatively confirmed these transitions, while Poincaré plots distinguished deterministic chaos from true randomness. Ultimately, this work highlights the universal nature of chaos in discrete systems, showing how precise rules can lead to unpredictable yet structured outcomes, and provides a foundation for future nonlinear dynamics research.