

EventFinder

Database Schema Design

Complete relational schema for the EventFinder event marketplace — users & organizer KYC, event catalog, ticketing & bookings, community reviews, live chat, notifications, and post-event analytics.

Version 1.0 | Database MySQL 8.0 (InnoDB, utf8mb4) | Framework Django 5 ORM + Django REST Framework | Author Platform Engineering

1. Overview

EventFinder is a ticket marketplace where organizers publish events, users buy seats and receive QR tickets, and both sides interact through reviews, live chat and notifications. A dedicated analytics module (Black Box) consolidates feedback into per-event performance reports. All business tables live in a single MySQL database **eventfinder_db**; Django framework tables are auto-managed and excluded below except for reference.

Document conventions

- **Identifiers** — every table uses an auto-increment **BIGINT** surrogate key named **id**.
- **Timestamps** — DATETIME(6) for microsecond precision; **created_at** set once, **updated_at** on every change.
- **Enumerations** — choice lists are stored as VARCHAR(20–50) constants (no ENUM), so values are expandable without DDL.
- **Relationships** — enforced with InnoDB foreign keys. CASCADE deletes dependents; SET NULL retains history.
- **Denormalization** — counts (likes_count, available_seats) are cached counters updated transactionally in the same request.
- **Text & JSON** — LONGTEXT for content; JSON columns for flexible tag lists and report payloads.

Table inventory

Module	Tables	Business tables
accounts	3	accounts_user, accounts_organizerprofile, accounts_profileeditrequest
events	5	events_category, events_event, events_eventimage, events_participantrequest, events_participantresponse
bookings	3	bookings_booking, bookings_ticket, bookings_waitlistentry
community	4	community_eventexperience, community_experienceimage, community_experiencelike, community_experiencecomment
chat	3	chat_chatroom, chat_chatroommember, chat_chatmessage
notifications_app	3	notifications_app_notification, notifications_app_emailnotification, notifications_app_smsnotification
blackbox	2	blackbox_eventfeedback, blackbox_eventblackboxreport
Total	23	23 business tables (14 framework tables auto-managed)

2. Relationship Map

From	To	Type	Semantics
accounts_user (id)	accounts_organizerprofile (user_id)	1 : 1	a user may own one organizer KYC profile
accounts_user (id)	events_event (organizer_id)	1 : N	an organizer publishes many events
accounts_user (id)	accounts_profileeditrequest (user_id / reviewed_by)	1 : N	profile edit requests & admin review
events_category (id)	events_event (category_id)	1 : N	event classified under one category
events_event (id)	events_eventimage (event_id)	1 : N	gallery images
events_event (id)	bookings_booking (event_id)	1 : N	tickets sold for an event
accounts_user (id)	bookings_booking (user_id)	1 : N	a user makes many bookings
bookings_booking (id)	bookings_ticket (booking_id)	1 : N	one ticket per seat purchased
events_event (id)	bookings_waitlistentry (event_id)	1 : N	fans queued for sold-out events
events_event (id)	chat_chatroom (event_id)	1 : 1	one chat room per event
chat_chatroom (id)	chat_chatroommember (chat_room_id)	1 : N	members of a room
chat_chatroom (id)	chat_chatmessage (chat_room_id)	1 : N	message history
events_event (id)	community_eventexperience (event_id)	1 : N	reviews per event
accounts_user (id)	community_eventexperience (user_id)	1 : N	one review per user per event (unique pair)
community_eventexperience (id)	community_experiencecomment / _like / _image	1 : N	comments, likes, photos
accounts_user (id)	notifications_app_notification (user_id)	1 : N	in-app notification inbox
notifications_app_notification (id)	notifications_app_emailnotification / smsnotification	1 : 1	per-channel delivery log
events_event (id)	events_participantrequest (event_id)	1 : N	requests for participants
events_participantrequest (id)	events_participantresponse (participant_request_id)	1 : N	user responses
events_event (id)	blackbox_eventfeedback (event_id)	1 : N	structured attendee feedback
events_event (id)	blackbox_eventblackboxreport (event_id)	1 : 1	auto-generated performance report

1. User & Organizer Accounts (app: accounts)

Custom Django auth model extended with role, phone verification and organizer KYC.

accounts_user

Registered users of every role (USER, ORGANIZER, ADMIN).

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
username	VARCHAR(150)	NOT NULL, UNIQUE
first_name	VARCHAR(150)	NOT NULL
last_name	VARCHAR(150)	NOT NULL
email	VARCHAR(254)	NOT NULL
password	VARCHAR(128)	NOT NULL (PBKDF2 hash)
phone_number	VARCHAR(15)	NULL, UNIQUE
role	VARCHAR(20)	NOT NULL, DEFAULT 'USER' — USER / ORGANIZER / ADMIN
profile_picture	VARCHAR(100)	NULL (upload path)
is_verified	BOOLEAN	NOT NULL, DEFAULT FALSE
is_superuser	BOOLEAN	NOT NULL
is_staff	BOOLEAN	NOT NULL
is_active	BOOLEAN	NOT NULL
last_login	DATETIME(6)	NULL
date_joined	DATETIME(6)	NOT NULL
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

accounts_organizerprofile

KYC profile for organizers; admins approve before they can list events.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE · UNIQUE (OneToOne)
organization_name	VARCHAR(200)	NOT NULL
government_id	VARCHAR(100)	NOT NULL (uploaded document path)
address	LONGTEXT	NOT NULL
approval_status	VARCHAR(20)	NOT NULL, DEFAULT 'PENDING' — PENDING / APPROVED / REJECTED
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

accounts_profileeditrequest

Admin-reviewed requests to change profile / organization details.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
proposed_data	JSON	NOT NULL (proposed field changes)
status	VARCHAR(20)	NOT NULL, DEFAULT 'PENDING' — PENDING / APPROVED / REJECTED
admin_notes	LONGTEXT	NOT NULL, DEFAULT ''
reviewed_by	BIGINT	FK → accounts_user.id NULLABLE ON DELETE SET NULL
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

2. Event Catalog (app: events)

Categories, event records with full logistics/accessibility metadata, gallery, and participant-coordination requests.

events_category

Event taxonomy (Music, Sports, Technology, Food & Drink, Art & Culture, Business, Health & Wellness, Education).

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
name	VARCHAR(100)	NOT NULL, UNIQUE
description	LONGTEXT	NOT NULL
icon	VARCHAR(100)	NOT NULL (material icon key)
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

events_event

Core event record. Status auto-syncs front→back (UPCOMING / ONGOING / COMPLETED) by Celery beat job.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
organizer_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
category_id	BIGINT	FK → events_category.id ON DELETE CASCADE
title	VARCHAR(200)	NOT NULL
description	LONGTEXT	NOT NULL
venue	VARCHAR(255)	NOT NULL
city	VARCHAR(100)	NOT NULL
latitude	DECIMAL(9,6)	NULL
longitude	DECIMAL(9,6)	NULL
start_date	DATE	NOT NULL
end_date	DATE	NOT NULL
start_time	TIME(6)	NOT NULL
end_time	TIME(6)	NOT NULL
banner	VARCHAR(100)	NOT NULL (upload path)
ticket_price	DECIMAL(10,2)	NOT NULL
total_seats	INT UNSIGNED	NOT NULL, CHECK (total_seats >= 0)
available_seats	INT UNSIGNED	NOT NULL, CHECK (available_seats >= 0)
booking_deadline	DATETIME(6)	NULL
language	VARCHAR(200)	NOT NULL, DEFAULT ''
what_to_bring	LONGTEXT	NOT NULL, DEFAULT ''
parking_available	BOOLEAN	NOT NULL, DEFAULT FALSE
parking_details	VARCHAR(255)	NOT NULL, DEFAULT ''
wifi_available	BOOLEAN	NOT NULL, DEFAULT FALSE
wifi_details	VARCHAR(255)	NOT NULL, DEFAULT ''
food_available	BOOLEAN	NOT NULL, DEFAULT FALSE
food_details	VARCHAR(255)	NOT NULL, DEFAULT ''
water_refill_stations	BOOLEAN	NOT NULL, DEFAULT FALSE
restrooms_available	BOOLEAN	NOT NULL, DEFAULT FALSE
charging_stations	BOOLEAN	NOT NULL, DEFAULT FALSE
wheelchair_accessible	BOOLEAN	NOT NULL, DEFAULT FALSE
prayer_room	BOOLEAN	NOT NULL, DEFAULT FALSE
certificate_available	BOOLEAN	NOT NULL, DEFAULT FALSE
certificate_template	VARCHAR(100)	NULL (upload path)
status	VARCHAR(20)	NOT NULL, DEFAULT 'PENDING' — PENDING / UPCOMING / POSTPONED / ONGOING / COMPLETED / CANCELLED
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL
_idx	INDEX	(category_id), (organizer_id)

events_eventimage

Additional gallery images for an event.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE
image	VARCHAR(100)	NOT NULL (upload path)
uploaded_at	DATETIME(6)	NOT NULL

events_participantrequest

Organizer-driven call for participants/volunteers for an event.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE
organizer_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
description	LONGTEXT	NOT NULL
required_participants	INT UNSIGNED	NOT NULL
current_participants	INT UNSIGNED	NOT NULL, DEFAULT 0
deadline	DATETIME(6)	NULL
status	VARCHAR(20)	NOT NULL, DEFAULT 'OPEN' — OPEN / FULFILLED / CLOSED
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

events_participantresponse

User replies to a participant request.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
participant_request_id	BIGINT	FK → events_participantrequest.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
message	LONGTEXT	NOT NULL, DEFAULT ''
status	VARCHAR(20)	NOT NULL, DEFAULT 'INTERESTED' — INTERESTED / SELECTED / DECLINED
created_at	DATETIME(6)	NOT NULL
_u	UNIQUE	(participant_request_id, user_id)

3. Bookings, Tickets & Waitlist (app: bookings)

Purchases are recorded as bookings; each seat becomes an individual scannable ticket. Waitlist auto-promotes when seats free up.

bookings_booking

One row per ticket purchase. Razorpay payment_id stored for reconciliation.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE
number_of_tickets	INT UNSIGNED	NOT NULL, CHECK (>= 0)
total_price	DECIMAL(10,2)	NOT NULL
status	VARCHAR(20)	NOT NULL, DEFAULT 'PENDING' — PENDING / PENDING_APPROVAL / CONFIRMED / CANCELLED / REJECTED
payment_id	VARCHAR(255)	NULL, UNIQUE
booking_reference	VARCHAR(50)	NOT NULL, UNIQUE (e.g. BK3F4A9C2E)
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL
_idx	INDEX	(user_id, event_id), (booking_reference)

bookings_ticket

Individual ticket for each booked seat.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
booking_id	BIGINT	FK → bookings_booking.id ON DELETE CASCADE
ticket_number	VARCHAR(50)	NOT NULL, UNIQUE (e.g. BK3F4A9C2ET1)
qr_code	VARCHAR(100)	NULL (QR image path)
is_scanned	BOOLEAN	NOT NULL, DEFAULT FALSE
scanned_at	DATETIME(6)	NULL
created_at	DATETIME(6)	NOT NULL

bookings_waitlistentry

Queued users for fully-booked events; enumerated by position.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
status	VARCHAR(20)	NOT NULL, DEFAULT 'WAITING' — WAITING / ASSIGNED / REMOVED
position	INT UNSIGNED	NOT NULL, DEFAULT 0
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL
_u	UNIQUE	(event_id, user_id)

4. Community Experiences (app: community)

Post-event reviews: one experience per user/event, with likes, comments and photo galleries.

community_eventexperience

A user's rated review of an attended event.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE
title	VARCHAR(200)	NOT NULL
description	LONGTEXT	NOT NULL
rating	INT UNSIGNED	NOT NULL, 1–5, CHECK (>= 0)
likes_count	INT UNSIGNED	NOT NULL, DEFAULT 0, CHECK (>= 0)
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL
_u	UNIQUE	(user_id, event_id)
_idx	INDEX	(event_id, created_at DESC)

community_experienceimage

Photos attached to an experience.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
experience_id	BIGINT	FK → community_eventexperience.id ON DELETE CASCADE
image	VARCHAR(100)	NOT NULL (upload path)
caption	VARCHAR(500)	NOT NULL, DEFAULT ""
uploaded_at	DATETIME(6)	NOT NULL

community_experiencelike

Like relation between a user and an experience.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
experience_id	BIGINT	FK → community_eventexperience.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
created_at	DATETIME(6)	NOT NULL
_u	UNIQUE	(experience_id, user_id)

community_experiencecomment

Comments on experiences.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
experience_id	BIGINT	FK → community_event experience.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user .id ON DELETE CASCADE
comment	LONGTEXT	NOT NULL
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL
_idx	INDEX	(experience_id, created_at)

5. Live Event Chat (app: chat)

One chat room per event (WebSocket/Channels), with membership and message history.

chat_chatroom

A chat room bound to exactly one event.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE · UNIQUE (OneToOne)
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

chat_chatroommember

Users joined to a room with online status.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
chat_room_id	BIGINT	FK → chat_chatroom.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
joined_at	DATETIME(6)	NOT NULL
last_seen	DATETIME(6)	NOT NULL
is_active	BOOLEAN	NOT NULL, DEFAULT TRUE
_u	UNIQUE	(chat_room_id, user_id)

chat_chatmessage

Individual messages in a room.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
chat_room_id	BIGINT	FK → chat_chatroom.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
message	LONGTEXT	NOT NULL
attachment	VARCHAR(100)	NULL (upload path)
created_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL
_idx	INDEX	(chat_room_id, created_at)

6. Notifications (app: notifications_app)

In-app notification log with separate delivery-tracked email and SMS records.

notifications_app_notification

In-app notification targeting a user; optionally linked to an event/booking.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
notification_type	VARCHAR(50)	NOT NULL — BOOKING_CONFIRMATION, EVENT_UPDATE, ORGANIZER_APPROVAL, PAYMENT_SUCCESS, WAITLIST_ASSIGNED, etc. (25 types)
title	VARCHAR(200)	NOT NULL
message	LONGTEXT	NOT NULL
related_event_id	BIGINT	FK → events_event.id NULLABLE ON DELETE CASCADE
related_booking_id	BIGINT	FK → bookings_booking.id NULLABLE ON DELETE CASCADE
is_read	BOOLEAN	NOT NULL, DEFAULT FALSE
read_at	DATETIME(6)	NULL
created_at	DATETIME(6)	NOT NULL
_idx	INDEX	(user_id, created_at DESC), (is_read, user_id)

notifications_app_emailnotification

Delivery log for the email channel of a notification.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
notification_id	BIGINT	FK → notifications_app_notification.id ON DELETE CASCADE · UNIQUE (OneToOne)
recipient_email	VARCHAR(254)	NOT NULL
subject	VARCHAR(255)	NOT NULL
body	LONGTEXT	NOT NULL
status	VARCHAR(20)	NOT NULL, DEFAULT 'PENDING' — PENDING / SENT / FAILED
sent_at	DATETIME(6)	NULL
error_message	LONGTEXT	NOT NULL, DEFAULT ""
created_at	DATETIME(6)	NOT NULL
_idx	INDEX	(status, created_at)

notifications_app_smsnotification

Delivery log for the SMS channel of a notification (via provider).

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
notification_id	BIGINT	FK → notifications_app_notification.id ON DELETE CASCADE · UNIQUE (OneToOne)
phone_number	VARCHAR(15)	NOT NULL
message	VARCHAR(160)	NOT NULL (SMS limit)
status	VARCHAR(20)	NOT NULL, DEFAULT 'PENDING' — PENDING / SENT / FAILED
sent_at	DATETIME(6)	NULL
provider	VARCHAR(50)	NOT NULL, DEFAULT ''
provider_message_id	VARCHAR(255)	NOT NULL, DEFAULT ''
error_message	LONGTEXT	NOT NULL, DEFAULT ''
created_at	DATETIME(6)	NOT NULL
_idx	INDEX	(status, created_at)

7. Analytics & Feedback (app: blackbox)

Structured attendee feedback and the auto-generated per-event Black Box performance report.

blackbox_eventfeedback

Structured 5-star feedback with tagged positives/problems.

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE
user_id	BIGINT	FK → accounts_user.id ON DELETE CASCADE
rating	INT UNSIGNED	NOT NULL, 1–5
positive_feedback	JSON	NOT NULL, DEFAULT '[]' — tags: VENUE, SPEAKER, ACTIVITIES, ORGANIZATION, NETWORKING
problems	JSON	NOT NULL, DEFAULT '[]' — tags: LATE_START, POOR_MANAGEMENT, TOO_CROWDED, HIGH_PRICE, POOR_LOCATION, TECHNICAL_ISSUES, OTHER
suggestions	LONGTEXT	NOT NULL, DEFAULT ''
created_at	DATETIME(6)	NOT NULL
_u	UNIQUE	(event_id, user_id)
_idx	INDEX	(event_id, rating)

blackbox_eventblackboxreport

Auto-computed event performance report (one per event).

Field	Data Type	Constraint / Notes
id	BIGINT	PRIMARY KEY, AUTO_INCREMENT
event_id	BIGINT	FK → events_event.id ON DELETE CASCADE · UNIQUE (OneToOne)
expected_attendees	INT UNSIGNED	NOT NULL, DEFAULT 0
actual_attendees	INT UNSIGNED	NOT NULL, DEFAULT 0
total_feedbacks	INT UNSIGNED	NOT NULL, DEFAULT 0
average_rating	DECIMAL(3,2)	NOT NULL, DEFAULT 0
sentiment_positive	DECIMAL(5,2)	NOT NULL, DEFAULT 0 (percentage)
sentiment_neutral	DECIMAL(5,2)	NOT NULL, DEFAULT 0 (percentage)
sentiment_negative	DECIMAL(5,2)	NOT NULL, DEFAULT 0 (percentage)
success_factors	JSON	NOT NULL, DEFAULT '[]'
problems_found	JSON	NOT NULL, DEFAULT '[]'
recommendations	JSON	NOT NULL, DEFAULT '[]'
category_stats	JSON	NOT NULL, DEFAULT '{}'
generated_at	DATETIME(6)	NOT NULL
updated_at	DATETIME(6)	NOT NULL

10. Framework / Platform Tables

The following tables are created and maintained by the Django framework and installed libraries. They are listed for completeness but are not part of the business schema design.

Table	Purpose	Managed By
accounts_user_groups	User to auth-group membership	Django auth
accounts_user_user_permissions	User to permission grants	Django auth
auth_group	Permission groups	Django auth
auth_group_permissions	Group to permission grants	Django auth
auth_permission	Model action permissions	Django auth
django_content_type	Registered model registry	Django
django_migrations	Applied migration history	Django
django_session	Server-side session store	Django
django_admin_log	Admin action audit log	Django admin
authtoken_token	Legacy API tokens	DRF authtoken
token_blacklist_outstandingtoken	JWT refresh tokens issued	SimpleJWT
token_blacklist_blacklistedtoken	Revoked JWT tokens	SimpleJWT
django_celery_beat_*	Scheduled task definitions (periodictask etc.)	Celery Beat
django_celery_results_*	Async task execution results	Celery Results

11. Performance & Integrity Notes

- **Concurrency-safe seat availability** — ticket count is guarded by atomic `SELECT ... FOR UPDATE` plus a `CHECK` constraint; a cancelled booking restores seats and, if a waitlist exists, auto-assigns the next-user position.
- **Composite indexes** — pair foreign keys with the timestamp they are most queried by (e.g. `chat_chatmessage` (`chat_room_id`, `created_at`), `community_eventexperience` (`event_id`, `created_at` DESC), `notifications_app_notification` (`user_id`, `created_at` DESC)).
- **Uniqueness as business rules** — user/event experience, room membership, request support and waitlist entries are all `UNIQUE`-constrained to prevent duplicates at the DB layer.
- **Referential integrity** — all FKs are InnoDB enforced; child rows cascade unless the link is optional (`SET NULL`) or must survive (`RESTRICT` unused so far).
- **Character set** — `utf8mb4` / `utf8mb4_0900_ai_ci` so Indian-language event copy and emoji render correctly.
- **Seat counters** — `total_seats` / `available_seats` are denormalized for `O(1)` list queries; transactions keep them consistent with bookings.
- **Deletion policy** — soft delete is avoided: records are closed via status fields (`CANCELLED`, `REJECTED`, `CLOSED`, `REMOVED`) to preserve audit history.

Generated from the live EventFinder Django models. This document is a design reference, not a migration script.