

Started on	Tuesday, 2 April 2024, 10:30 PM
State	Finished
Completed on	Tuesday, 2 April 2024, 10:38 PM
Time taken	7 mins 43 secs
Marks	2.00/5.00
Grade	4.00 out of 10.00 (40%)

Question 1

Complete

Mark 0.00 out of 1.00

Consider the following code and answer the given question.

```
class Person:
    def __init__(self, title="default_title"):
        self._name = None
        self.title = title
    def talk(self, words):
        print("talk 1")
    def talk(self, words):
        print("talk 2")

class Employee(Person):
    def __init__(self,id,title):
        super().__init__(xx)
        self.id = id
```

Which of the following statements is false?

- ☐ a. The ‘_name’ attribute will have different values in different Person objects.
- ☐ b. The ‘title’ attribute will always have the same value in different Person objects.
- ☒ c. Accessing the ‘_name’ attribute from outside the class is not a good programming practice in Python.
- ☐ d. A getter and setter have to be defined for the ‘_name’ attribute.

Question 2

Complete

Mark 0.00 out of 1.00

Consider the following code and answer the given question.

```
class Person:
    def __init__(self, title="default_title"):
        self._name = None
        self.title = title
    def talk(self, words):
        print("talk 1")
    def talk(self, words):
        print("talk 2")

class Employee(Person):
    def __init__(self, id, title):
        super().__init__(xx)
        self.id = id
```

What will be the output of the following code?

```
person1 = Person ()
person1.talk("Hello")
```

- ☒ a. talk 1
- ☐ b. talk 2
- ☐ c. talk 1
talk 2
- ☐ d. None of the above

Question 3

Complete

Mark 1.00 out of 1.00

Consider the following code and answer the given question.

```
class Person:
    def __init__(self, title="default_title"):
        self._name = None
        self.title = title
    def talk(self, words):
        print("talk 1")
    def talk(self, words):
        print("talk 2")

class Employee(Person):
    def __init__(self, id, title):
        super().__init__(xx)
        self.id = id
```

What will be the output of the following code?

```
person2 = Person("Professor")
print (person2.title)
```

- ☐ a. default_title
- ☒ b. Professor
- ☐ c. Any of the above
- ☐ d. None of the above

Question 4

Complete

Mark 0.00 out of 1.00

Consider the following code and answer the given question.

```
class Person:
    def __init__(self, title="default_title"):
        self._name = None
        self.title = title
    def talk(self, words):
        print("talk 1")
    def talk(self, words):
        print("talk 2")

class Employee(Person):
    def __init__(self, id, title):
        super().__init__(xx)
        self.id = id
```

To achieve method overloading in the given code

- ☐ a. Add a talk() method to the Employee class with the exact same parameters as the talk() method in the Person class.
- ☐ b. Add a talk() method to the Employee class with parameters different to the talk() method in the Person class.
- ☒ c. Have more than one talk() methods in Person class, each taking a different set of parameters.
- ☐ d. Have a single talk() method in Person class, with parameters having default values.

Question 5

Complete

Mark 1.00 out of 1.00

Consider the following code and answer the given question.


```
class Person:
    def __init__(self, title="default_title"):
        self._name = None
        self.title = title
    def talk(self, words):
        print("talk 1")
    def talk(self, words):
        print("talk 2")


class Employee(Person):
    def __init__(self, id, title):
        super().__init__(xx)
        self.id = id
```


What should be given to *xx* in *Employee* class constructor?


Answer:


GET IN TOUCH


 University of Moratuwa
Centre for Open & Distance Learning
CODL

 011 308 2787/8

 011 265 0301 ext. 3850,3851

 open@uom.lk

-  [University Website](#)

 [CODL Website](#)

[Data retention summary](#)