MeteoSource

MENU

Client section

Interactive documentation

Interactive documentation for your Free plan

v1 OAS 3.1

/api/v1/free/openapi.json

This interactive documentation is using your API key which is filled in automatically, you can find and change this in your dashboard.

Using the `GET` button, open your selected endpoint and read the introduction. You will find a detailed description of available parameters. You can complete the `Parameters` section and hit `Execute` to view a full API response. You can then inspect the JSON response, copy the `curl` command to run it on your machine, or obtain a URL of the request. In this way, you can easily build request command for the data you need.

Servers

/api/v1/free

Point weather

GET `/point` Returns weather data for a single point (geographic name or GPS)

Current weather and forecast for single location

Location specification

The location of the weather data is the only parameter that is required and must be specified. There are two ways to do this:

1. Specify the GPS coordinates of the location using the parameters `lat` and `lon`
2. **OR** specify the name of the place using the parameter `place_id`. To obtain the `place_id` for the location you want, please use endpoints `/find_places_prefix` (search by prefix) or `/find_places` (search by full name).

Note: For mountains, it is usually better to specify the `place_id` rather than the `lat` and `lon`. When you use `place_id`, you are guaranteed to receive forecasts for the precise elevation of the peak. When you specify the coordinates, the elevation can be less precise.

Sections

The endpoint can return multiple sections of data. To obtain the best performance, we advise only requesting the sections you actually need. The available sections are as follows:

- Current weather situation
- Hourly forecast (for 24/48/96/168 hours, depending on the tier)
- Daily forecast (for 7/10/30 days, depending on the tier)
- Minutely precipitation forecast (for 60 minutes in the following hour, only for higher tiers)
- Weather alerts (only for higher tiers)

By default, only the current and hourly sections are returned. The division into daily parts (morning, afternoon and evening) is only available for the first 7 days of the forecast. For details regarding available parameters, see the parameter description below.

Notes

- **For a detailed description of variables (e.g. icons), please consult ⚠️ description of variables ⚠️ in Documentation or `Schema` of the response (link next to Example value in the Responses section below).**
- Variables can be instantaneous, averaged, or accumulated over certain time. For example, `precipitation` forecast provides the precipitation accumulated until the next hour (data with timestamp as `12:00:00` is rain accumulated from `12:00:00` to `13:00:00`).
- Do **not** make any assumptions about the number and ordering of the variables. New variables and sections may be introduced in the future. Always check the data are present before you try to use them.
- The response contains an `Expires` header, which defines the point at which the API response will not change for the same request. We highly recommend using this to avoid unnecessary requests and **increase the performance of your app**.
- Meteosource API supports HTTP compression. To enable it, simply add an `Accept-Encoding: gzip` header to your request.
- When daylight saving time starts, one hourly record will be missing (typically `2:00:00 AM`). When daylight saving time ends, the hourly forecast will contain two records with duplicate times (typically `2:00:00 AM`).
- The detailed description of weather alerts is only available in English. The alert category is translated into selected language.

Parameters

Cancel

Name	Description
place_id `string` *`(query)`*	Identifier of a place. To obtain the `place id` for the location you want, please use endpoints `/find_places_prefix` (search by prefix) or `/find_places` (search by full name). place_id
lat `string` *`(query)`*	Latitude in format 12N, 12.3N, 12.3, or 13S, 13.2S, -13.4 lat
lon `string` *`(query)`*	Longitude in format 12E, 12.3E, 12.3, or 13W, 13.2W, -13.4 lon
sections `string` *`(query)`*	Sections to be included in the response. You can specify more section by separating the values with a comma. The available values are: • `current` : Current weather situation • `daily` : Forecasts for each whole day • `hourly` : Forecasts with hourly resolution

Name	Description
	• `all` : All sections current,hourly
timezone `string` *`(query)`*	Timezone to be used for the date fields. If not specified, local timezone of the forecast location will be used. The format is according to the tzinfo database, so values like `Europe/Prague` or `UTC` can be used. Alternatively you may use the value `auto` in which case the local timezone of the location is used. The full list of valid timezone strings can be found here. timezone
language `string` *`(query)`*	The language of text summaries and place names (variable names are never translated). For the free tier, only `en` (English) is available. en
units `string` *`(query)`*	Unit system to be used. The available values are: • `auto` : Select the system automatically, based on the forecast location. • `metric` : Metric (SI) units (`°C` , `mm/h` , `m/s` , `cm` , `km` , `hPa`). • `us` : Imperial units (`°F` , `in/h` , `mph` , `in` , `mi` . `Hg`). • `uk` : Same as `metric` , except that visibility is in `miles` and wind speeds are in `mph` . • `ca` : Same as `metric` , except that wind speeds are in `km/h` and pressure is in `kPa` . auto
key `string` *`(query)`*	Your unique API key. You can either specify it in this parameter, or set it in `X-API-Key` header. u5wwkquvqz0avb57uvs0u3kpp7oqzymhig25

Execute

Responses

Code	Description	Links
200	Successful Response Media type application/json Controls `Accept` header. **Example Value** Schema	*No links*

Code	Description	Links


```
{
  "lat": "string",
  "lon": "string",
  "elevation": 0,
  "timezone": "string",
  "units": "string",
  "current": {
    "icon": "string",
    "icon_num": 0,
    "summary": "string",
    "temperature": 0,
    "wind": {
      "speed": 0,
      "angle": 0,
      "dir": "string"
    },
    "precipitation": {
      "total": 0,
      "type": "string"
    },
    "cloud_cover": 0
  },
  "hourly": {
    "data": [
      {
        "date": "2022-03-30T18:00:00",
        "weather": "string",
        "icon": 0,
```


400 Error in passed parameter. *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": "string"
}
```


402 Maximum requests per day limit exceeded. *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": "string"
}
```


403 API key not not specified or invalid. *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": "string"
}
```

Code	Description	Links
422	Validation Error Media type application/json **Example Value** Schema	*No links*

```
{
  "detail": [
    {
      "loc": [
        "string",
        0
      ],
      "msg": "string",
      "type": "string"
    }
  ]
}
```

429	Maximum requests per minute limit exceeded. Media type application/json **Example Value** Schema	*No links*

```
{
  "detail": "string"
}
```

Location endpoints

GET `/find_places` Search for places. Complete words required.

Search for places

You can use this endpoint to obtain `place_id` of the location you want, to be used in `point` endpoint. The response also contains detailed information about the location, such as coordinates, timezone and the country the place belongs to.

Unlike the `/find_place_prefix` endpoint, complete words are required here. You can search for cities, mountains, lakes, countries, ZIP codes, etc. The response can contain multiple places, sorted by relevance. You can then identify the one you want by coordinates, country, or the administrative area.

Parameters Cancel

Name	Description
text * required `string` *(query)*	Place name or ZIP code text
language `string` *(query)*	The language of text summaries and place names (variable names are never translated). For the free tier, only `en` (English) is available. en
key `string` *(query)*	Your unique API key. You can either specify it in this parameter, or set it in `X-API-Key` header. u5wwkquvqz0avb57uvs0u3kpp7oqzymhig25

Execute

Responses

Code	Description	Links
200	Successful Response Media type application/json Controls `Accept` header. **Example Value** Schema	*No links*
400	Error in passed parameter. Media type application/json **Example Value** Schema	*No links*

```
[
  {
    "name": "London",
    "place_id": "london",
    "adm_area1": "England",
    "adm_area2": "Greater London",
    "country": "United Kingdom",
    "lat": "23.2N",
    "lon": "15.3E",
    "timezone": "Europe/London",
    "type": "settlement"
  }
]
```

```
{
  "detail": "string"
```

Code	Description	Links

```
}
```

402 Maximum requests per day limit exceeded. *No links*

Media type

application/json

Example Value Schema

```
{
  "detail": "string"
}
```

403 API key not not specified or invalid. *No links*

Media type

application/json

Example Value Schema

```
{
  "detail": "string"
}
```

422 Validation Error *No links*

Media type

application/json

Example Value Schema

```
{
  "detail": [
    {
      "loc": [
        "string",
        0
      ],
      "msg": "string",
      "type": "string"
    }
  ]
}
```

429 Maximum requests per minute limit exceeded. *No links*

Media type

application/json

Example Value Schema

```
{
  "detail": "string"
}
```

GET `/find_places_prefix` Prefix search for places. Useful for autocomplete forms.

Search for places by prefix

You can use this endpoint to obtain `place_id` of the location you want, to be used in `point` endpoint. The response also contains detailed information about the location, such as coordinates, timezone and the country the place belongs to.

Unlike the `/find_places` endpoint, you should only specify the prefix of the place you are looking for. This is particularly useful for autocomplete forms. You can search for cities, mountains, lakes, countries, ZIP codes, etc. The response can contain multiple places, sorted by relevance. You can then identify the one you want by coordinates, country, or the administrative area.

Parameters

Cancel

Name	Description
text * required `string` *(query)*	Place name or ZIP code text
language `string` *(query)*	The language of text summaries and place names (variable names are never translated). For the free tier, only `en` (English) is available. en
key `string` *(query)*	Your unique API key. You can either specify it in this parameter, or set it in `X-API-Key` header. u5wwkquvqz0avb57uvs0u3kpp7oqzymhig25

Execute

Responses

Code	Description	Links
200	Successful Response Media type **application/json** Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "name": "London",
```

Code	Description	Links


```
      "place_id": "london",
      "adm_area1": "England",
      "adm_area2": "Greater London",
      "country": "United Kingdom",
      "lat": "23.2N",
      "lon": "15.3E",
      "timezone": "Europe/London",
      "type": "settlement"
    }
  ]
```


400 Error in passed parameter. *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": "string"
}
```


402 Maximum requests per day limit exceeded. *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": "string"
}
```


403 API key not not specified or invalid. *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": "string"
}
```


422 Validation Error *No links*

Media type

application/json

Example Value Schema


```
{
  "detail": [
    {
      "loc": [
        "string",
        0
```

Code	Description	Links

```
        ],
        "msg": "string",
        "type": "string"
      }
    ]
  }
```

429 Maximum requests per minute limit exceeded. *No links*

Media type

application/json

Example Value Schema

```
{
  "detail": "string"
}
```

GET `/nearest_place`
Returns the nearest named location for a given GPS coordinates.

Search for nearest place by coordinates

You can use this endpoint to find the nearest place from given coordinates.

Note: If you specify coordinates of a secluded place (e.g. middle of the ocean), the nearest point can be very far from the coordinates.

Parameters Cancel

Name	Description
lat * required `string` *(query)*	Latitude in format 12N, 12.3N, 12.3, or 13S, 13.2S, -13.4 lat
lon * required `string` *(query)*	Longitude in format 12E, 12.3E, 12.3, or 13W, 13.2W, -13.4 lon
language `string` *(query)*	The language of text summaries and place names (variable names are never translated). For the free tier, only `en` (English) is available. en
key `string` *(query)*	Your unique API key. You can either specify it in this parameter, or set it in `X-API-Key` header. u5wwkquvqz0avb57uvs0u3kpp7oqzymhig25ı

Execute

Responses

Code	Description	Links
200	Successful Response Media type **application/json** Controls `Accept` header. **Example Value** Schema `{ "name": "London", "place_id": "london", "adm_area1": "England", "adm_area2": "Greater London", "country": "United Kingdom", "lat": "23.2N", "lon": "15.3E", "timezone": "Europe/London", "type": "settlement" }`	*No links*
400	Error in passed parameter. Media type **application/json** **Example Value** Schema `{ "detail": "string" }`	*No links*
402	Maximum requests per day limit exceeded. Media type **application/json** **Example Value** Schema `{ "detail": "string" }`	*No links*
403	API key not not specified or invalid. Media type **application/json** **Example Value** Schema	*No links*

Code	Description	Links
	`{ "detail": "string" }`	
422	Validation Error Media type **application/json** **Example Value** Schema `{ "detail": [ { "loc": [ "string", 0 ], "msg": "string", "type": "string" } ] }`	*No links*
429	Maximum requests per minute limit exceeded. Media type **application/json** **Example Value** Schema `{ "detail": "string" }`	*No links*

Meteosource Weather API

Current Weather Data API

Weather Forecast Data API

Historical Weather Data API

Weather Maps & Layers API

Air Quality Data API

Maritime Forecast API

Pricing

Documentation

FAQ

API wrapper libraries

How our forecasts are made

Terms of service

Personal data protection

Customised solutions

Energy modelling

Insurance and Risk

Retail

Agriculture

Construction

Road and Rail

Contact

Other

Blog

Solar Power and Generation

Wind Power Forecast

GET IT ON Google Play

Meteosource © 2026