

Linux tar Command Options

Linux tar Command Options	
Option	Description
-A	Append one archive to the end of another archive.
-c	Create a new archive. Directories are archived recursively unless you use --no-recursion.
-d	Compare the archive with the file system to find differences.
--delete	Delete specific files from an archive.
-t	List contents of an archive.
-r	Append files to an archive (same as -A).
-u	Add files that are newer than the existing copies in the archive.
-x	Extract files from an archive.
--help	Display a summary of options and exit.
-k	Skip extracting files that already exist.
-O	Extract files to standard output.
-f	Specify the archive filename.
-v	Enable verbose output, showing the files being processed.
-z	Compress files with gzip.
-j	Compress files with bzip2.
-J	Compress files with xz.
-Z	Compress files with compress.
-a	Choose the compression type based on file extension.
-l	Verify symbolic links when creating archives.
-C	Switch to a specified directory before performing operations.
--exclude=FILE	Skip the specified file during archiving or extraction.
-P	Preserve leading slashes in filenames when creating archives.
-p	Maintain file permissions during extraction.
--wildcards	Enable interpretation of wildcards.
-m	Set the modification time to the current time during extraction.
-N	Archive only files newer than the specified date.
--remove-files	Delete original files from disk after archiving them.
--strip-components	Remove a set number of leading components from file paths during extraction.
--to-command	Send extracted files to a command for further processing.
--ignore-zeros	Ignore zeroed blocks, which are usually end-of-file markers in an archive.
--one-file-system	Stay within the current filesystem when creating an archive.
-W	Verify the archive after creation to ensure its integrity.