

Tools — Task Management

Session-scoped tasks for tracking multi-step work. `blocked` is a derived state computed from `blocked_by` dependencies — it cannot be set directly.

Tool	Description
<code>task_create</code>	Create a session-scoped task.
<code>task_update</code>	Update task status, subject, or dependencies.
<code>task_get</code>	Retrieve a single task by ID.
<code>task_list</code>	List all session tasks.

`task_create`

Create a task.

Arguments

Argument	Type	Required	Description	Typical value
<code>subject</code>	string	yes	Imperative title	"Fix config loader"
<code>description</code>	string	yes	Acceptance criteria	"Reproduce panic and fix root cause"
<code>active_form</code>	string	no	Present-continuous phrase for progress indicators	"Fixing config loader"
<code>owner</code>	string	no	Agent/worker label	"coder"
<code>metadata</code>	object	no	Arbitrary key/value pairs	{"phase": "2"}
<code>blocked_by</code>	array	no	Task IDs that must complete first	["task-001"]

`task_update`

Update an existing task. `blocked` status is rejected — pass blockedness via `add_blocked_by`. Completing a task auto-evaluates dependents.

Arguments

Argument	Type	Required	Description	Typical value
<code>task_id</code>	string	yes	Task identifier	"task-001"
<code>status</code>	enum	no	pending, in_progress, or completed (never blocked)	"in_progress"

Argument	Type	Required	Description	Typical value
subject / description / active_form	string	no	New field values	—
owner	string	no	New owner label (empty string clears)	—
metadata	object	no	Full replacement metadata	—
add_blocked_by	array	no	Task IDs this task is now blocked by	["task-002"]
add_blocks	array	no	Task IDs that should be blocked by this task	["task-003"]

task_get

Retrieve the full record of one task: status, owner, metadata, dependencies, timestamps.

Arguments

Argument	Type	Required	Description
task_id	string	yes	Task identifier

task_list

List all session tasks ordered by creation time.

Arguments

Argument	Type	Required	Description	Typical value
status	enum	no	pending, in_progress, completed, or all (default)	"pending"

Example:

```
task_create subject="Fix config loader" description="Reproduce panic and fix root cause"
task_update task_id="task-001" status="in_progress"
```