

Tools — Scheduling

Scheduled agent runs (cron events): one-shot or recurring prompts executed by a named agent. New events are enabled by default.

Tool	Description
<code>cron_add</code>	Create a scheduled agent run.
<code>cron_remove</code>	Delete a scheduled event.
<code>cron_list</code>	List all scheduled events.
<code>cron_enable</code>	Enable a scheduled event.
<code>cron_disable</code>	Disable a scheduled event.

`cron_add`

Create a cron event.

Schedule grammar:

- `at <timestamp>` — one-shot
- `from <timestamp> every <duration>` — repeating from a start time
- `every <duration>` — repeating from now

Timestamps accept ISO-8601 (2025-01-15T09:00:00Z) or natural language ("5pm", "5am tomorrow"). Durations use `<int><unit>` where unit is m, h, d, w, or mo.

Arguments

Argument	Type	Required	Description	Typical value
<code>id</code>	string	yes	Unique event name (primary key; duplicates fail)	"daily-audit"
<code>agent</code>	string	yes	Agent type to run	"general", "coder"
<code>schedule</code>	string	yes	Schedule expression per grammar above	"every 1h"
<code>prompt</code>	string	yes	Prompt executed when the event fires	"Run cargo clippy and report new warnings"

Example:

```
cron_add id="nightly-test" agent="general" schedule="every 1d" prompt="Run cargo test and summari
```

`cron_remove` / `cron_enable` / `cron_disable`

Delete an event permanently, or toggle whether the scheduler fires it.

Arguments

Argument	Type	Required	Description
id	string	yes	Event identifier

cron_list

List all cron events with id, agent, schedule, enabled status, next-due timestamp, and prompt preview. No arguments required.

Example:

```
cron_list
cron_disable id="nightly-test"
```