

/doctor

Run environment diagnostics: `/doctor help|check`

Overview

`/doctor` checks the environment ragent runs in and prints a diagnostic report. The check runs asynchronously after a “Running diagnostics...” line, so the report appears in the message window a moment later. Each row carries a status marker: `[ok]`, `[err]`, `[warn]`, or an informational note for optional items.

Syntax

```
/doctor
/doctor help
```

Options / Subcommands

Form	Description
(bare)	Run the diagnostics and print the report
help	Show the subcommand table

Checks performed

Check	Result marker	Notes on failure
git	<code>[ok]</code> / <code>[err]</code>	<code>git --version</code> must succeed
ripgrep	<code>[ok]</code> / <code>[err]</code>	suggests installing ripgrep
GitHub token	<code>[ok]</code> / <code>[warn]</code>	suggests <code>/github login</code>
config	<code>[ok]</code> / <code>[err]</code>	reports loaded file count or parse error
storage database	<code>[ok]</code> / <code>[err]</code>	SQLite journal mode and db path
provider / model	<code>[ok]</code> / <code>[warn]</code>	provider name, source (env/database/auto-discovered), model, health state
memory	<code>[ok]</code> / <code>[err]</code>	<code>~/.ragent/memory/</code>
directory		
memory system	<code>[ok]</code> / note when disabled	blocks/structured/semantic flags
project	<code>[ok]</code> / <code>[err]</code>	created if missing
<code>.ragent/</code>		
project	<code>[ok]</code> / note	AGENTS.md path, or global fallback, or absent
guidelines		
MCP servers	<code>[ok]</code> / note	count of configured MCP servers (optional)
tool registry	<code>[ok]</code>	number of registered tools
code index	<code>[ok]</code> / <code>[wait]</code> / note	files/symbols/size when enabled; busy/locked marker; note when disabled
update status	<code>[ok]</code> / <code>[warn]</code>	latest release version; suggests <code>/update</code>

The report ends with `*Diagnostics complete.*`

Examples

From: /doctor

Running diagnostics...

then, a moment later:

```
# Diagnostic Report
[ok] git
[ok] ripgrep (rg)
[warn] no GitHub token - run /github login
[ok] ragent config (loaded 2 config file(s))
[ok] storage database
    SQLite journal_mode=wal (/home/user/.local/share/agent/agent.db)
[ok] provider: Anthropic (anthropic via env)
    model=claude-sonnet-4-20250514 [ok] reachable
...
*Diagnostics complete.*

From: /doctor
(with ripgrep missing)
[err] ripgrep not found - install at https://github.com/BurntSushi/ripgrep

From: /doctor
(with code index busy)
[wait] code index: enabled, status busy/locked

From: /doctor help
| /doctor | Check git, ripgrep, GitHub token, config, and other environment
prerequisites, then print a diagnostic report |
| /doctor help | Show this help |
```

Output

Running diagnostics... appears immediately; the full # Diagnostic Report block is appended when the async check finishes. Every line starts with its status marker so failures are easy to scan. The status bar shows doctor: help for the help form.

Related

- /provider - configure a provider when the report flags none
- /github login - add the missing GitHub token
- /codeindex on - enable the code index when disabled
- /update - install an available update flagged by the report
- /bug-report - write a file report of session state instead