

## /log

Log panel: /log [clear subagents|panics|research|editlog|help]

### Overview

/log controls the log side panel and the on-disk log files. Invoked with no arguments it toggles the log panel: other side panels (profile, tasks, memory, telemetry) are dismissed and the buffered log-window history is spooled into the panel. With the `clear` subcommand it empties one of the five log directories that the agent writes to under `log/`.

### Syntax

```
/log                Toggle the log side panel
/log clear <name>   Clear one log directory
/log help           Print the usage table
```

### Options / Subcommands

| Form            | Description                                      |
|-----------------|--------------------------------------------------|
| (bare)          | Toggle the log side panel on/off.                |
| clear subagents | Empty log/subagents/ (background agent reports). |
| clear panics    | Empty log/panics/.                               |
| clear research  | Empty log/research/ (web-gather JSONL logs).     |
| clear editlog   | Empty log/editlog/.                              |
| clear logwindow | Empty log/logwindow/.                            |
| help            | Print the usage table.                           |

Unknown subcommands print the usage text.

### Examples

```
/log
```

Toggles the log panel. If it was closed it opens and the panel history is spooled; if it was open it closes.

```
/log clear subagents
```

Empties log/subagents/ so old background-agent reports no longer consume disk.

```
/log clear research
```

Empties log/research/, removing accumulated web-gather instrumentation logs (research-`<name>`-`<ts>`-`<rand>`-web.js).

```
/log clear editlog
```

Empties log/editlog/. The files are kept (emptied), so subsequent edit-log stats in `/editlog show` restart from zero.

```
/log clear logwindow
```

Empties log/logwindow/, removing accumulated TUI log-window session logs.

`/log help`

Prints the subcommand table shown above.

## Output

Bare invocation shows or hides the log side panel; when opening, any other side panel (profile, tasks, memory, telemetry) is dismissed and the buffered log-window history is spooled into the panel. `clear` reports which directory was emptied. `help` prints the table of valid clear targets.

## Related

- `/editlog` – edit-operation statistics (the `editlog clear` target).
- `/profile`, `/memory`, `/telemetry` – side panels dismissed when the log panel opens.
- `log/` directory layout: `log/subagents/`, `log/panics/`, `log/editlog/`, `log/logwindow/`, and `log/research/`.