

/mcp

MCP servers: `/mcp [status] | /mcp discover | /mcp connect | /mcp disconnect | /mcp help`

Overview

`/mcp` reports the state of Model Context Protocol servers and launches discovery. The bare form (the `status` token lands in the same arm) prints a server table from the current config and runtime state; `/mcp discover` scans for available servers and opens an interactive selection dialog.

Be aware of the implementation boundaries: only `help`, `discover`, `connect <id>`, and `disconnect <id>` subcommands exist. `connect <id>` is a stub that reports “not yet implemented” after validating the id, and `disconnect <id>` is always a stub. There is no `/mcp call` subcommand - it is mentioned in some README text but the dispatcher does not implement it, so do not document or attempt it. Tool calls to MCP servers go through the `mcp_tool` tool in chat instead.

Syntax

<code>/mcp</code>	# server status table (status token behaves the same)
<code>/mcp status</code>	# same table
<code>/mcp discover</code>	# scan for MCP servers, open selection dialog
<code>/mcp connect <id></code>	# stub: validates the id, then "not yet implemented"
<code>/mcp disconnect <id></code>	# stub: always reports "not yet implemented"
<code>/mcp help</code>	# usage help

Options / Subcommands

Form	Description
<code>/mcp</code>	Print the MCP server table
<code>/mcp status</code>	Same as the bare form
<code>/mcp discover</code>	Run <code>McpClient::discover()</code> and open the interactive dialog
<code>/mcp connect <id></code>	Look up <code><id></code> in config; found -> reports a not-yet-implemented stub
<code>/mcp disconnect <id></code>	Always reports a not-yet-implemented stub
<code>/mcp help</code>	Print usage help

Not implemented (do not use):

Form	Status
<code>/mcp call <server> <tool></code>	No such subcommand in the dispatcher

Examples

Show the server table:

```
/mcp
```

Scan for servers and pick one interactively:

```
/mcp discover
```

Validate a server id (expect the stub message):

```
/mcp connect filesystem
```

Expect a stub message even for a valid id:

```
/mcp disconnect filesystem
```

Print the usage help:

```
/mcp help
```

Call an MCP tool from chat (the supported path):

```
mcp_tool(server: "filesystem", tool: "read_file", arguments: {"path": "README.md"})
```

Output

Bare form (From: /mcp, MCP Servers):

- With no servers configured, an advisory line suggests running `/mcp discover` to scan for available servers and then adding them to the `mcp` section of `ragent.json` to activate them.
- Otherwise one line per server: the server id padded to a fixed width, a status glyph (rendered as an emoji in the terminal - described here as connected, disabled, needs auth, or failed with the error text), and tools: `<n>` when the server exposes tools.
- A summary line: `<connected>/<total> server(s) connected`.
- A footer listing the subcommands: `/mcp discover, /mcp connect <id>, /mcp disconnect <id>`.

`/mcp discover` produces no transcript output; it opens an interactive dialog (numbered selection list with a feedback line) fed by `McpClient::discover()`.

```
/mcp connect <id>:
```

- Missing id: Usage: `/mcp connect <id>`
- Id not in config: MCP '`<id>`' not found in config
- Id found: MCP connect not yet implemented for '`<id>`'

```
/mcp disconnect <id>:
```

```
MCP disconnect not yet implemented for '<id>'
```

Related

- `mcp_tool` - the chat tool for calling MCP server tools
- `/reload mcp` - rescan MCP configuration after editing `ragent.json`
- `mcp` section in `ragent.json` - server definitions and enablement
- `/doctor` - includes MCP connectivity in its diagnostics