

/skill

Load or inspect skill packs (/skill [name] | /skill list | /skill help)

Overview

/skill lists the registered skill packs and loads a named pack for invocation. It is the explicit form of the bare /<name> skill trigger: both resolve the pack through the same skill registry, so an AgentSkills pack discovered under .agents/skills/ (project) or ~/.agents/skills/ (user) can be listed and loaded by its frontmatter name (FR-005).

With no argument (or list) it prints the same listing as /skills. With a name it loads that pack and starts the invocation exactly as /<name> [args] would: the pack body is substituted with the arguments and injected into the session as a user turn for the model to act on.

Syntax

```
/skill                # list every registered pack
/skill list           # alias of the above
/skill <name> [args...] # load and invoke the named pack
/skill help           # usage help
```

Options / Subcommands

Form	Description
/skill	List every registered pack with scope, access, and description
/skill list	Alias of /skill
/skill <name> [args...]	Load the named pack and invoke it (same as /<name> [args])
/skill help	Print usage help

Examples

List the registry, including an AgentSkills pack:

```
/skill
```

Load and invoke the tiny AgentSkills pack:

```
/skill tiny
```

Load a pack with an argument:

```
/skill deploy staging
```

Output

The list form renders a fenced block per pack with the pack's /name, its scope (for example openskills-project for a .agents/skills/ pack, or project for .agent/skills/), its access level, and its description, then a footer line reporting the registered count.

The load form echoes `/name` as a user message and sets the status to invoking `skill /<name>....`. If the name is not registered, it reports `No skill named \‘ is registered` and points at `/skill`. A non-user-invokable pack reports the refusal; with no provider or model configured, it points at `/provider//model`.

Discovery

Packs are discovered from, lowest to highest priority:

- `~/.ragent/skills/<name>/SKILL.md` (personal)
- `.ragent/skills/<name>/SKILL.md` (project)
- the AgentSkills convention `~/.agents/skills/<name>/SKILL.md` (user) and `.agents/skills/<name>/SKILL.md` (project)

Each pack is a directory holding a `SKILL.md` whose YAML frontmatter declares at least `name` and `description`. On a name clash the existing higher-scope pack wins, so an AgentSkills pack never shadows a same-named `.ragent/skills/` pack. Reload with `/reload skills` after adding or editing packs.

Related

- `/skills` - list-only form of the same registry
- `/reload skills` - rescan skill directories after edits
- `skill_manage` - list/read/load/reload skills from chat