/alog

Activity log: /alog help|on|off|config|list|status|delete –yes|export –yes

Overview

`/alog` controls the activity log, which records each agent run as a JSONL activity file. Use it to enable or disable recording, inspect past runs, and – with the mandatory `--yes` guard – delete or export a specific run.

Syntax

```
/alog                        Print the help table (same as /alog help)
/alog on                     Enable activity logging
/alog off                    Disable activity logging
/alog config                 Show the activity-log configuration
/alog list                   List recorded runs
/alog status                 Show the activity-log runtime status
/alog delete <run-id> --yes   Delete one run (guard required)
/alog export <run-id> --yes   Export one run to a JSONL file (guard required)
/alog help                   Print the help table
```

Options / Subcommands

Form	Description
`on`	Enable activity logging via `persist_activity_log`.
`off`	Disable activity logging.
`config`	Show the current activity-log configuration.
`list`	List recorded runs.
`status`	Show the activity-log runtime status.
`delete <run-id>`	Delete the run. `--yes` is mandatory: run-id and the guard are validated
`--yes`	(FR-011/012/013/014/015) and the deletion runs on a blocking thread via `expire_run`. Confirmation reports the number of removed events.
`export <run-id>`	Export the run to `log/exports/export-<run-id>.jsonl`
`--yes`	(FR-018/019/020/021/022/023). `--yes` is mandatory here too.
`help`	Print the help table, including the current ON/OFF state.

`--help` and `-h` are accepted as aliases of `help`. Unknown subcommands print the usage text.

Examples

`/alog on`

Starts recording run activity.

`/alog list`

Lists the recorded runs so a `run-id` can be copied for delete/export.

`/alog status`

Shows the runtime status of activity logging.

`/alog delete 9c3f1b2a --yes`

Deletes run `9c3f1b2a` after the `--yes` guard, confirming the number of events removed.

`/alog export 9c3f1b2a --yes`

Writes `log/exports/export-9c3f1b2a.jsonl` containing that run's events.

`/alog help`

Prints the help table including the current ON/OFF state.

Output

`on`/`off` confirm the state change (persist failures surface as warnings). `config`, `list`, and `status` print their respective views. `delete` prints a confirmation with the event count; without `--yes` the command is refused. `export` prints the written path `log/exports/export-<run-id>.jsonl`; without `--yes` it is refused. `help` prints the table with the live ON/OFF state.

Related

- `/log clear research` clears `log/research/`, a sibling log directory.
- `/editlog` – the separate edit-operation log.
- `log/exports/` – destination for `/alog export`.