/config

> "Inspect, back up, and restore ragent configuration" (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

`/config` is the in-TUI configuration inspector and backup manager. The `show` form renders the resolved configuration without launching the agent: where the application stores its files, which config files were found on disk, and the final merged value of every key together with the source that supplied it. The `save` form writes a timestamped backup of the global configuration into the `config_dir/saves/` directory, and the `list` form opens an interactive picker over previously saved backups so one can be restored.

Handlers live in `crates/ragent-tui/src/app/slash.rs` (the `config` arm, approximately lines 2238-2652). All output accumulates under a `From: /config` header in the message window.

Syntax

```
/config show
/config save
/config list
/config help
```

Bare `/config` behaves like the unknown-args case and prints the usage line.

Options / Subcommands

Form	Description
`/config show`	Render application paths, discovered config files, and the fully resolved configuration table
`/config save`	Back up the global config to a timestamped file under `config_dir/saves/`
`/config list`	List saved configuration backups and open the restore picker
`/config help`	Show the subcommand summary

Examples

Inspect resolved configuration

```
/config show
```

Output (representative, condensed):

```
From: /config show

Application Paths
  Working directory:  /home/user/Projects/ragent
  Data directory:     ~/.local/share/ragent
  Config directory:   ~/.config/ragent
```

```
Config Files
  Path                                          Exists
  /home/user/Projects/ragent/.ragent/ragent.json   yes
  /home/user/.config/ragent/ragent.json            no
  $RAGENT_CONFIG                                   (unset)

Resolved Values
  key                            | source                | value
  ...
```

Back up the global configuration

```
/config save
```

Output:

```
From: /config save
[ok] Configuration backed up to /home/user/.config/ragent/saves/ragent.json.20260911-101500
```

If the backup cannot be written the command reports `[err]` with `No changes were made.` and leaves the configuration untouched.

List and restore a saved configuration

```
/config list
```

Output (picker state):

```
From: /config list
Saved configurations (newest first):
  1. ragent.json.20260911-101500
  2. ragent.json.20260910-183022
...
```

With no saved backups present the output is:

```
From: /config list
No saved configurations found
Hint: use /config save to create a backup
```

Show the subcommand summary

```
/config help
```

Output:

```
From: /config help
/config show | /config save | /config list | /config help
```

Output

`/config show` sections

- **Application Paths** - working directory, data directory, and config directory currently in use.

- **Config Files** - a table with exists checks for the project config (<cwd>/.ragent/ragent.json), the global config (<config_dir>/ragent.json), and the path given by the RAGENT_CONFIG environment variable.
- **Resolved Values** - a key | source | value table. Precedence is: defaults < global config < project config < env file < RAGENT_CONFIG_CONTENT. Every row names the source that supplied the winning value.
- **Union fields** - the merged-map fields permission, instructions, skill_dirs, hooks, bash, hidden_tools, yolo, edit_log, sdd, piegap, and experimental are labelled global + project (union) when a value is set in both layers.
- **Secret redaction** - keys matching *_api_key / *_key, plus the openalex_email, and gitlab sections, are redacted before display.
- **Storage** - the resolved SQLite database path.
- **Code Index** - the index directory .ragent/codeindex.
- **Memory** - project and global memory directories.
- **Custom Agents** - the custom agent directories being scanned.

`/config save`

Emits [ok] with the backup path, or [err] with No changes were made. when the backup could not be written.

`/config list`

Scans <config_dir>/saves/ for files matching ragent.json.* (excluding .tmp candidates), sorts newest-first by modification time, and opens the ConfigSavePickerState interactive picker. In the picker:

- Up / Down or k / j move the selection,
- Enter restores the selected snapshot,
- Esc cancels.

An empty directory produces No saved configurations found plus the /config save hint.

Unknown arguments

Prints the usage line /config show | /config save | /config list | /config help.

Related

- /init config - write a fresh default config file to disk
- /reload - re-read ragent.json into the running session
- /skills - view the skill registry loaded from skill_dirs
- QUICKSTART.md - configuration examples
- SPEC.md - full configuration schema