/connectors

Connector management: /connectors list [–verbose] [–category] | claude [query] [–category] [–refresh] | add <id|source> [–force] | remove | enable | disable | connect | disconnect | auth | test | stores [–check] | marketplace show | help

Overview

`/connectors` manages **connectors**: named, user-facing integrations (Google Drive, Slack, GitHub, Git, Postgres, Puppeteer, and the wider community catalogue) that reach an external system through one or more **MCP servers**. A connector is a catalogue entry carrying a display name, a category, an authentication requirement, and one or more MCP servers; the MCP server remains the transport ragent already speaks (`McpClient`), so the connector system is a management and catalogue layer over machinery that already exists.

A bare `/connectors`, `/connectors help`, and any unrecognised subcommand all print the same usage block and create or modify no files.

The same operations are available from a shell via the `ragent connectors <sub>` CLI parity surface; the two surfaces share one help text and one set of command handlers.

The system is specified in `specs/connectors/SPEC.md` (FR-001..FR-041); the manual test plan is `specs/connectors/TESTPLAN.md`.

Syntax

```
/connectors list [--verbose] [--category <name>]   # installed connectors + state
/connectors claude [query] [--category <name>] [--refresh]  # interactive catalogue browser
/connectors add <id|source> [--force]              # install (recorded enabled)
/connectors remove <id>                            # uninstall (refused while enabled)
/connectors enable <id>                            # enable + connect now
/connectors disable <id>                           # disable + disconnect
/connectors connect <id>                           # connect an enabled connector
/connectors disconnect <id>                        # disconnect, leave enabled
/connectors auth <id>                              # manage credential / report auth state
/connectors test <id>                              # isolated connect-and-invoke harness
/connectors stores [--check]                       # report catalogue endpoints + provenance
/connectors marketplace show                        # list configured marketplaces
/connectors marketplace claude list|add|remove      # manage added marketplaces
/connectors help                                   # usage block
```

Options / Subcommands

Form	Description
`/connectors list [--verbose] [--category <name>]`	One row per installed connector showing state, auth state, category, and bridged server/tool counts, sorted alphabetically by connector id (case-insensitive). `--verbose` adds detail. `--category` restricts the rows, which keep their alphabetical order; `ALL` (any case) or a blank value clears the filter; an unknown category is refused with an `[err]` row and changes no state.
`/connectors claude [query] [--category <name>] [--refresh]`	Open the interactive Claude connector-catalogue browser: a title line (catalogue name, query, active category, visible/total count, plus a `loading details...` hint while the manifest-description enrichment runs), a fixed dark-on-light column-heading row (`Id`, `Category`, `Marketplace`, `Description`) pinned above a scrollable result list with the block cursor on the highlighted row (each row shows the connector id, its category, the marketplace it came from, and its description), an `[installed]` marker and distinct colour on already-installed connectors, and a footer of key hints. The optional `query` pre-fills the search field, `--category <name>` pre-selects the category filter (an unknown category is refused in the footer and no row is hidden), and `--refresh` bypasses the catalogue cache. The panel merges the base catalogue endpoint and every marketplace added with `/connectors marketplace claude add`, and fills each entry's blank description from its own repository manifest off the event loop. A left-hand category navigator lists `ALL` plus the catalogue's categories: `Tab` moves focus between it and the results, `Up`/`Down` over the navigator apply the highlighted category, `ENTER` over the navigator applies and returns focus to the results, and `c` clears the filter back to `ALL`. Clicking a navigator row applies it and the wheel scrolls the navigator.
`/connectors add <id|source> [--force]`	Install a connector from a catalogue id, a local directory holding a connector manifest, a local `.zip`/`.tar.gz`, or an `https://` URL naming a package. A fresh install is recorded **enabled**; run `/connectors enable <id>` to connect its servers now in a running session. A duplicate id is refused unless `--force` is given.
`/connectors remove <id>`	Uninstall a connector. Refused while the connector is enabled.
`/connectors enable <id>`	Enable a connector and connect its servers now.

Form	Description
`/connectors disable <id>`	Disable a connector and disconnect its servers.
`/connectors connect <id>`	Connect an enabled connector's servers without a session restart.
`/connectors disconnect <id>`	Disconnect a connector's servers, leaving it enabled.
`/connectors auth <id>`	Manage a connector's credential (token, client secret) and report its auth state. Secrets live in the encrypted credential store; the manifest stores only the credential *name*.
`/connectors test <id>`	Connect in isolation with a throwaway probe, invoke one tool, and report per-step `[ ok ]/[fail]` results. Never touches the live session.
`/connectors stores [--check]`	Report each catalogue endpoint and its provenance (`default` or `config`); `--check` also probes each endpoint.
`/connectors marketplace show`	List the marketplaces configured for the Claude catalogue (the base endpoint plus each added marketplace, tagged `default`/`config`/`added`). A pure config read.
`/connectors marketplace claude list|add <source> [--force]|remove <name>`	List one catalogue's configured marketplaces, add an additional marketplace (an `owner/repo` slug, a `git@github.com:owner/repo.git` SSH remote, an `https://` marketplace-index URL, or a local directory), or remove one by name. Written to the user-global `connectors.stores.marketplaces`.
`/connectors help`	Print the usage block. A bare `/connectors` or an unknown subcommand does the same.

Sources accepted by `/connectors add`

- a catalogue connector id;
- a local directory holding a connector manifest;
- a local `.zip` or `.tar.gz` package;
- an `https://` URL naming a `.zip`/`.tar.gz` package (non-`https` URLs are refused).

Examples

List everything with the productivity filter:

```
/connectors list --category productivity
```

Browse the catalogue interactively, filtered by query and category, then install and enable the result:

```
/connectors claude drive --category productivity
/connectors add google-drive
/connectors auth google-drive
/connectors enable google-drive
```

Test a connector without touching the live session:

```
/connectors test google-drive
```

Check where the catalogue endpoint comes from:

```
/connectors stores --check
```

Output

Every report is prefixed with a `From: /connectors <sub>` attribution line (FR-006). A bare `/connectors`, `/connectors help`, and an unrecognised subcommand all render the same usage block (FR-017). All report text is ASCII.

`test` renders one line per harness step:

```
[ ok ] resolve servers (1 ms)
[ ok ] connect (12 ms)
[ ok ] tool invoke (3 ms)
```

and ends by confirming the harness was torn down with the live session untouched.

Configuration

The `connectors` block in `ragent.json` controls the subsystem (`enabled`, `store_dir`, the catalogue `stores` endpoints and fetch budgets, and the non-secret `credentials` name mapping). With `connectors.enabled: false`, every subcommand other than `help` reports the subsystem is disabled and no discovery, catalogue fetch, or connection occurs. Connectors are discovered under `.ragent/connectors/` (project), falling back to `~/.config/ragent/connectors/` (user-global).

See `docs/howtos/config.md` §7.37 and `specs/connectors/SPEC.md`.

Related

- `docs/howtos/connectors.md` - the full connector-system manual
- `/mcp` - MCP server status, discovery, and enable/disable
- `/plugins` - the sandboxed Codex/Claude plugin system (a sibling catalogue)
- `ragent connectors <sub>` - CLI parity for the same subcommands
- `specs/connectors/SPEC.md` - the full connector-system specification