/prompt

Agent system-prompt inspector: /prompt help|primary [agent]|subagent [agent]|list|

Overview

`/prompt` renders the system prompt that a given agent would receive, without calling the LLM and without writing anything. It is a read-only inspector: every form builds the report from live session context (model, tools, project guidelines) and prints it. Two modes exist: the primary (interactive) prompt, and the subagent prompt, which forces Subagent mode - gating the mandatory Sub-Agent Completion Protocol section and excluding interactive tools from the tool surface.

Syntax

```
/prompt
/prompt help
/prompt list
/prompt primary [agent]
/prompt subagent [agent]
/prompt <agent>
```

Notes:

- The bare form is equivalent to `/prompt help`.
- Agent names resolve case-insensitively; a bare `<agent>` form produces a primary-mode report.

Options / Subcommands

Form	Description
`/prompt` (or `/prompt help`)	Print the help page (status: `prompt: help`).
`/prompt list`	Print the roster of built-in and custom agents with the agent count (status: `prompt: list (N agents)`).
`/prompt primary [agent]`	Render the primary-mode system-prompt report for the session agent or the named agent.
`/prompt subagent [agent]`	Render the subagent-mode report; Subagent mode is forced regardless of the session mode.
`/prompt <agent>`	Case-insensitive agent-name shortcut for a primary-mode report.
unknown subcommand	Print a usage correction with no prompt content (status: `prompt: unknown subcommand{req}“`).

Examples

Inspect the prompt the coder agent would receive right now:

```
/prompt
/prompt primary coder
```

See what a spawned sub-agent actually gets (completion protocol on, interactive tools removed):

```
/prompt subagent coder
```

Check the roster before picking an agent:

```
/prompt list
```

Short form, case-insensitive:

```
/prompt CODE-REVIEW
```

Unknown subcommand prints a correction instead of a prompt:

```
/prompt foo bar
```

Output

- Report modes: `primary` renders the interactive-agent prompt; `subagent` renders the Subagent-mode prompt. Subagent mode gates the Sub-Agent Completion Protocol (MANDATORY - HARD REQUIREMENT) section and excludes interactive tools (for example `ask_user`) from the tool reference.
- The report is the rendered system prompt: agent instructions, project guidelines (`AGENTS.md`), tool reference, and mode-specific sections, all resolved against the live session (selected model, registered tools, working directory) rather than stored defaults.
- Status line on a report: `prompt: {agent} ({primary|subagent}, {N} tools)`; an agent with no tools shows `( ..., no tools)`.
- `list`: the built-in and custom agent roster plus the agent count.
- `help`: the help page (bare form included).
- Unknown subcommand: a usage correction only - no prompt body is printed.

Read-only guarantee: no LLM call is made, no config or session state is modified, and nothing is persisted.

Related

- Agent presets and custom agents (OASF JSON / Markdown profiles): `docs/custom-agents.md`.
- `/agents` to list loaded agents and diagnostics, `/agent` for the picker.
- `/system` for a session-scoped system-prompt override.
- Sub-agent spawning: `new_agent`, `wait_agents`, `agent_complete`.