/startup

> "Show startup timing report" (SlashCommandDef, crates/ragent-tui/src/app/state.rs).

Overview

`/startup` renders the startup timing report for the current session when the application recorded one, and warns when no timings were captured. Startup timings cover the phases between process launch and the TUI becoming interactive; the report is produced by the `StartupTimings::format_report` renderer. Timings are session-scoped: they are only available in the session that performed the startup work.

The handler is the `startup` arm in `crates/ragent-tui/src/app/slash.rs` (lines 3045-3056).

Syntax

```
/startup
```

No arguments. Additional text after the command is ignored.

Options / Subcommands

None. `/startup` takes no forms.

Examples

Show the timing report

```
/startup
```

Output (representative, condensed):

```
From: /startup
Startup timings:
  ...
```

The exact columns come from `StartupTimings::format_report()` in `crates/ragent-tui`; this doc does not enumerate them because the renderer was not traced for this page.

No timings recorded

```
/startup
```

Output (status line):

```
[warn] No startup timings recorded for this session.
```

This is the expected result when the session was resumed rather than freshly launched, or when timing instrumentation did not run.

Output

- With `Some(timings)` recorded for the session, the command delegates to `timings.format_report()` and prints the resulting report in the message window.

- With `None`, the status line shows `[warn] No startup timings recorded for this session.` and no report is produced.

Related

- `/inputdiag` - dump input and pane state for diagnostics
- `/doctor` - run environment health checks
- `/bug-report` - collect diagnostics into a report file