/status

Show status message history: /status [clear]

Overview

`/status` is registered in the slash-command registry (`SLASH_COMMANDS` in `crates/ragent-tui/src/app/state.rs`) with the description above and an autocomplete suggestion for `clear`. A `StatusHistory` backing type exists in `crates/ragent-tui/src/theme.rs` (line ~525).

However, no `/status` dispatch arm was found in the TUI command dispatcher (`crates/ragent-tui/src/app/slash.rs` in the sections verified. The `status` arms that do exist in that file are subcommands of other commands (`/alog status`, `/editlog status`, `/github status`, `/gitlab status`, `/router status`, `/triggers status`) – not a top-level `/status` handler.

Syntax

```
/status             (registered; no dispatch arm verified)
/status clear       (autocomplete suggestion; no dispatch arm verified)
```

Options / Subcommands

Form	Description
`clear`	The only autocomplete suggestion registered (slash.rs ~216-218). No dispatch arm was found, so behaviour is not verified.

Examples

`/status`

Registered in autocomplete, but no dispatch arm was located in the verified dispatcher sections. Typing `/status` completes the token; whether a handler executes is not verified here.

`/status clear`

Offered as a suggestion; no dispatch arm was found.

Output

Not verified. No handler was found, so the message-window behaviour of this command cannot be stated honestly. Do not rely on documented output.

Related

- `/triggers status`, `/alog status`, `/editlog status` – real `status` subcommands of other commands.
- `StatusHistory` (`crates/ragent-tui/src/theme.rs`) – the backing type.
- Recommendation: the dispatch arm is either missing or dead; add one or remove the command from `SLASH_COMMANDS`.