/toolchain

Language toolchain report: /toolchain list [lang] [–json] | /toolchain help

Overview

`/toolchain` reports the presence of language toolchains detected on this machine: which runtimes and compilers are installed, their versions, and their readiness status. It is strictly read-only - it never installs, upgrades, or configures anything; it only probes. For example, `/toolchain list rust` probes `cargo` and `rustc` and reports what was found.

Syntax

```
/toolchain
/toolchain help
/toolchain list
/toolchain list <language>
/toolchain list <language> --json
/toolchain list --json
```

Notes:

- The bare form is equivalent to `/toolchain help`.
- `--json` is position-independent: it may appear before or after the language filter.
- The language filter is case-insensitive.
- Probing is blocking; while it runs the status line shows `[wait] toolchain status`.

Options / Subcommands

Form	Description
`/toolchain` (or `/toolchain help`)	Print the help page.
`/toolchain list`	Probe and report every known language toolchain.
`/toolchain list <language>`	Probe and report only the given language (case-insensitive id).
`/toolchain list <language> --json`	Same report as a bare JSON document.
unknown language id	`Unknown language id{filter}. Valid ids: ...`
unknown subcommand	`Unknown subcommand{sub}. Usage: /toolchain [list [language] [--json] | help]. Run /toolchain help for details.`

Examples

Probe everything and show the plain table:

```
/toolchain list
```

Probe only the Rust toolchain (cargo + rustc):

`/toolchain list rust`

Machine-readable report for scripts or other tools:

`/toolchain list rust --json`

Flag position does not matter:

`/toolchain list --json rust`

Unknown subcommand prints the usage correction:

`/toolchain install rust`

Output

Table form

A fixed-width table (constant 93-column width) with 10/10/10/50 character columns:

Column	Width	Overflow
Language	10	clipped
Runtime	10	clipped
Status	10	word-wrapped
Version	50	word-wrapped

Wrapped rows continue on grid lines, so multi-word statuses and long versions remain readable inside the fixed grid.

JSON form

`--json` renders a bare JSON document (no table) with the same probe results, one entry per toolchain, suitable for piping into other tools.

Errors and status

- While probing: status `[wait] toolchain status`.
- Unknown language filter: `Unknown language id{filter}. Valid ids: ...`
- Unknown subcommand: `Unknown subcommand{sub}. Usage: /toolchain [list [language] [--json] | help]. Run /toolchain help for details.`

The command never installs or upgrades toolchains; missing toolchains simply report as not found.

Related

- Toolchain manual: `docs/howtos/toolchain.md`.
- README v1.0.95 notes the fixed-width `/toolchain list` table columns.
- `/new` scaffolding detects the runtime stack it needs; `/doctor` and `/update` cover other environment checks.