Tools — Memory

Three-tier memory: structured SQLite store (these tools), file blocks, and optional embedding-based semantic search. Structured memories carry a category, tags, and a confidence score.

Tool	Description
`memory_store`	Store a structured memory (category, tags, confidence).
`memory_recall`	Full-text search of structured memories.
`memory_forget`	Delete memories by ID or filter.
`conversation_search`	Search current session conversation history.
`session_search`	Search across all past sessions.

Confidence scale: 0.0 = uncertain, 1.0 = certain. Use 0.7 for ordinary observations, >= 0.9 for verified facts, <= 0.5 for hunches. Tags are free-form but should be lowercase and hyphenated (e.g. `rust`, `startup`).

---

memory_store

Store a structured memory.

Arguments

Argument	Type	Required	Description	Typical value
`content`	string	yes	The memory content — a fact, pattern, insight, etc.	`"We use anyhow::Result for errors"`
`category`	enum	yes	`fact`, `pattern`, `preference`, `insight`, `error`, `workflow`	`"preference"`
`tags`	array	no	Lowercase/hyphenated strings for filtering	`["rust","error-handling"]`
`confidence`	number	no	0.0–1.0 (default 0.7)	`0.9`
`source`	string	no	Source of the memory	`"manual"`, `"auto-extract"`

Example:

```
memory_store content="We use anyhow::Result for errors" category="preference" confidence=0.9
memory_recall query="error handling"
```

---

memory_recall

Full-text search of structured memories. All keyword terms must match (AND); broaden by removing terms. Access counts are incremented on return.

Arguments

Argument	Type	Required	Description	Typical value
`query`	string	yes	Space-separated search terms	`"error handling"`
`categories`	array	no	Restrict to these categories	`["pattern","workflow"]`
`tags`	array	no	Memories must have ALL these tags	`["rust"]`
`limit`	integer	no	Maximum results	`5`
`min_confidence`	number	no	Confidence threshold 0.0–1.0	`0.5`

---

memory_forget

Delete memories by ID or by filter criteria. At least one criterion is required as a safety measure.

Arguments

Argument	Type	Required	Description
`id`	integer	one criterion	Delete one memory by its row ID
`older_than_days`	integer	one criterion	Delete memories not updated in this many days
`max_confidence`	number	one criterion	Delete memories with confidence at or below this value
`category`	enum	one criterion	Delete all memories in the category
`tags`	array	one criterion	Delete memories that have ALL of these tags

Example: `memory_forget max_confidence=0.2`

---

conversation_search

Search the current session conversation history. Modes: `keyword` (default), `turn_range`, `stats`.

Arguments

Argument	Type	Required	Description	Typical value
`query`	string	yes for `keyword`	Search query	`"cargo fmt"`

Argument	Type	Required	Description	Typical value
`mode`	enum	no	`keyword` (default), `turn_range`, `stats`	`"keyword"`
`start_turn` / `end_turn`	integer	yes for `turn_range`	1-based inclusive turn range	`1` / `20`
`limit`	integer	no	Keyword match count	`10`
`context_turns`	integer	no	Surrounding turns per keyword match	`0`

Example: `conversation_search query="edit old_string" limit=5`

---

session_search

Search across all past sessions using FTS5 keyword search.

Arguments

Argument	Type	Required	Description	Typical value
`query`	string	yes	FTS5 keyword search (implicit AND across terms)	`"compaction runner"`
`since` / `until`	string	no	ISO-8601 date range bounds	`"2026-09-01"`
`working_dir`	string	no	Restrict to sessions in this directory	—
`roles`	array	no	Restrict to these roles	`["user","assistant"]`
`session_id`	string	no	Restrict to a single session id	—
`limit`	integer	no	Maximum total results	`10`
`max_per_session`	integer	no	Cap results from any one session	`3`
`include_tools`	boolean	no	Include tool-call content (default true)	`false`
`include_system`	boolean	no	Include system/compaction messages	`false`
`context_turns`	integer	no	Surrounding turns included per result	`0`

Example:

```
session_search query="govdoc spec" since="2026-09-01" limit=10
```