

Tools — MCP

Bridge to external Model Context Protocol (MCP) servers with auto-discovery of known server types and stdio clients.

Tool	Description
mcp_tool	Bridge to external Model Context Protocol servers.

MCP server tools surface dynamically as `mcp_<server>_<tool>` at runtime after discovery via the `/mcp discover` TUI command, or after `/mcp connect <id>` enables and connects a server live. Servers bridged from an enabled plugin's `mcpServers` section connect as `<plugin-id>.<server>` at startup.

mcp_tool

The `McpToolWrapper` calls a tool hosted on a connected MCP server.

Arguments

Argument	Type	Required	Description	Typical value
server	string	yes	MCP server name (as configured/discovered)	"filesystem"
tool	string	yes	Tool name exposed by the server	"read_file"
arguments	object	no	JSON payload forwarded to the server tool	{"path": "/tmp/x"}

Example:

```
mcp_tool server="github" tool="create_issue" arguments={"title": "Bug report"}
```

TUI commands: `/mcp /` `/mcp status` (server table), `/mcp discover` (probe for known servers), `/mcp connect <id>` and `/mcp disconnect <id>` (enable/disable and connect/disconnect live, persisted globally in `<state dir>/mcp_state.json`). The wrapper refuses to call a disabled server's tools even when the tool is still registered, and names the command that re-enables it.