

Tools — Utility

Introspection of the running ragent binary and the active LLM connection.

Tool	Description
<code>model_info</code>	Report the active provider/model, capabilities, context window, and cost tier.
<code>ragent_info</code>	Report the running ragent version, build time, git commit, and compiler.
<code>tool_info</code>	Dump the whole tool registry as JSON (name, description, schema, permission category, source).
<code>commands_info</code>	Dump the slash-command catalog as JSON (built-in TUI commands plus plugin-contributed ones).

`model_info`

Report the active provider/model pair, provider display name, capabilities, context window, max output tokens, cost tier, and thinking support. When the Model Router is active, also reports whether routing is enabled and that the effective downstream model is chosen per request.

Arguments

Argument	Type	Required	Description	Typical value
<code>format</code>	enum	no	<code>text</code> (human-readable markdown, default) or <code>json</code> (structured metadata only)	<code>"text"</code>

Example:

```
model_info
model_info format="json"
```

`ragent_info`

Report build and version information about the running ragent binary: the ragent version, the build timestamp, the git commit it was built from (best-effort), and the compiler version. Read-only and offline — it never shells out or hits the network — so the LLM can answer “which version am I running?” directly.

Arguments

Argument	Type	Required	Description	Typical value
format	enum	no	text (human-readable markdown, default) or json (structured metadata only)	"text"

Example:

```

agent_info
agent_info format="json"

```

tool_info

Return a JSON-encoded dump of the tool registry: every registered tool with its name, description, parameters JSON schema, permission category, source (`internal` / `mcp:<server>` / `plugin:<id>` / `visibility:<family>`), and hidden state, plus MCP server/tool provenance for bridged tools. Read-only, permission category `none`, hardwired auto-approved.

Arguments

None.

Example:

```

tool_info

```

commands_info

Return a JSON-encoded catalog of every slash command — the built-in TUI commands (trigger, description, subcommands, flags) plus the commands contributed by enabled plugins, resolved live at call time. Read-only, permission category `none`, hardwired auto-approved.

Arguments

None.

Example:

```

commands_info

```