

/profile

Toggle the agent-loop profiler panel (/profile on|off|help)

Overview

/profile toggles the agent-loop profiler side panel, which reads `AgentLoopProfiler::snapshot()` and displays the recorded action-loop timing samples. The profiler must be enabled before /actionloop has data to report.

Syntax

/profile	Print the help table (same as /profile help)
/profile on	Enable the profiler panel
/profile off	Disable the profiler panel
/profile help	Print the help table

Options / Subcommands

Form	Description
on	Enable the profiler panel via <code>set_profile_panel_enabled(true)</code> .
off	Disable the profiler panel.
help	Print the help table, which notes that it reads <code>AgentLoopProfiler::snapshot()</code> and that the alias <code>/perf</code> behaves identically.

--help and -h are accepted as aliases of help; the bare form also prints help. Any other argument prints the usage text.

Examples

/profile on

Opens the profiler side panel and starts collecting action-loop timing data.

/profile off

Closes the profiler side panel.

/profile help

Prints the help table including the alias note.

/profile on

/actionloop

Enable profiling, then read the timing report.

Output

on/off confirm the panel state change. help prints the table that cites the profiler snapshot source and mentions the /perf alias. Unknown arguments print the usage line.

Related

- `/perf` – full alias of `/profile` with identical semantics.
- `/actionloop` – prints the timing report the profiler records.