

Tools — Communications

Gmail access and outbound notifications to Telegram/Discord channels. See `docs/howtos/communications.md` for the full OAuth2 and channel setup guide.

Tool	Description
gmail	Search, read, draft, and send Gmail messages.
send_channel_message	Post to Telegram or Discord channels.

gmail

Search, read, draft, and send Gmail messages via the Gmail REST API (requires prior OAuth2 authentication through the `auth` action).

Arguments

Argument	Type	Required	Description	Typical value
action	enum	yes	search, read, draft, send, auth, status, logout	"search"
query	string	yes for search	Gmail search query	"from:ci@example.com is:unread"
id	string	yes for read	Message id	—
max_results	integer	no	search result cap (max 100)	10
to	string	yes for draft/send	Recipient address	"dev@example.com"
subject	string	yes for draft/send	Subject line	"Build report"
body	string	yes for draft/send	Plain-text body	—
cc / bcc	string	no	Cc/Bcc headers	—
access_token	string	for auth	OAuth2 access token to store	—
refresh_token	string	for auth	Refresh token (enables automatic access-token refresh)	—
client_id / client_secret	string	for auth	OAuth2 client credentials for refresh exchange	—

Example:

```
gmail action="search" query="from:ci@example.com is:unread"
gmail action="send" to="dev@example.com" subject="Build passed" body="All tests green"
```

send_channel_message

Send a message to a configured Telegram bot or Discord webhook. Channels are configured in `ragent.json` under the `channels` block; set `channels.enabled=true` to allow delivery.

Arguments

Argument	Type	Required	Description	Typical value
<code>action</code>	enum	no	send (default), list, status	"send"
<code>message</code>	string	yes for send	Message text (max 4096 bytes)	"Build passed"
<code>channel</code>	enum	no	telegram, discord, or all for every configured channel; omitted targets the first configured one	"telegram"

Example:

```
send_channel_message action="send" message="Build passed" channel="telegram"
```