

Tools — Teams

Multi-agent coordination inside an active team: named teammates, a shared task list, mailbox messaging, and plan approval. All team tools require an active team, and `team_name` is required by nearly every tool.

Tool	Description
<code>team_create</code>	Create a named team from a blueprint.
<code>team_spawn</code>	Spawn a teammate for a scoped task.
<code>team_message</code>	Direct message a teammate or lead.
<code>team_broadcast</code>	Message all active teammates.
<code>team_read_messages</code>	Check mailbox for unread messages.
<code>team_status</code>	Team and task status summary.
<code>team_task_list</code>	List all team tasks.
<code>team_task_create</code>	Lead adds a shared task.
<code>team_task_claim</code>	Teammate claims the next available task.
<code>team_task_complete</code>	Mark a claimed task done.
<code>team_assign_task</code>	Lead assigns a task to a teammate.
<code>team_submit_plan</code>	Teammate submits a plan to the lead.
<code>team_approve_plan</code>	Lead approves/rejects a plan.
<code>team_wait</code>	Block until teammates finish.
<code>team_idle</code>	Teammate signals no more work.
<code>team_shutdown_teammate</code>	Lead requests teammate shutdown.
<code>team_shutdown_ack</code>	Teammate acks shutdown and exits.
<code>team_cleanup</code>	Lead tears down the team.
<code>team_memory_read</code>	Read team memory bucket.
<code>team_memory_write</code>	Write team memory bucket.

Visibility switch: teams. See `docs/howtos/teams.md` for the full team manual and `docs/userdocs/TEAMS.md` for the guide.

`team_create`

Create a team from a blueprint. Always pass `context` — it is prepended to every teammate's spawn prompt with the specific request details.

Arguments

Argument	Type	Required	Description	Typical value
<code>blueprint</code>	string	yes	Team template	"code-review"
<code>context</code>	string	yes	Task details: target files, what to do, where to write output	"Review crates/ragent-server for security issues. Write findings to docs/COMPLIANCE.md"

Workflow: team_create -> team_wait (blocks until all teammates idle) -> team_status to collect findings.

team_spawn

Add a teammate for one scoped task.

Arguments

Argument	Type	Required	Description	Typical value
team_name	string	yes	Team name	"audit-team"
teammate_name	string	yes	Unique teammate name	"reviewer-1"
agent_type	string	yes	Agent profile to run	"coder"
prompt	string	yes	Scoped task prompt	—

team_message

Argument	Type	Required	Description
team_name	string	yes	Team name
to	string	yes	Recipient teammate name (or lead)
content	string	yes	Message text

team_broadcast

Argument	Type	Required	Description
team_name	string	yes	Team name
content	string	yes	Message sent to all active teammates

team_read_messages

Argument	Type	Required	Description
team_name	string	yes	Team name

team_status

Team and task status summary.

Arguments

Argument	Type	Required	Description
team_name	string	yes	Team name

team_task_list / team_task_create / team_task_claim / team_task_complete / team_assign_task

Argument	Type	Required	Applies to	Description
team_name	string	yes	all	Team name
title	string	yes	team_task_create	Shared task title
task_id	string	yes	team_task_complete, team_assign_task	Task identifier
to	string	yes	team_assign_task	Teammate to assign to

team_task_claim takes no extra arguments: the teammate claims the next available task from the shared list. team_task_complete takes team_name + task_id (not summary).

team_submit_plan / team_approve_plan

Argument	Type	Required	Applies to	Description
team_name	string	yes	both	Team name
plan	string	yes	team_submit_plan	Plan text proposed by a teammate
teammate	string	yes	team_approve_plan	Teammate whose plan is judged
approved	boolean	yes	team_approve_plan	Approve or reject

team_wait / team_idle / team_shutdown_teammate / team_shutdown_ack / team_cleanup

Argument	Type	Required	Applies to	Description
<code>team_name</code>	string	yes (optional for <code>team_wait</code> , uses active team)	all	Team name
<code>teammate</code>	string	yes	<code>team_shutdown_teachmate</code>	Teammate to shut down

`team_wait` blocks until spawned teammates finish — always use it after `team_create`/`team_spawn`.
`team_cleanup` tears down team state after all teammates have stopped.

`team_memory_read` / `team_memory_write`

Argument	Type	Required	Applies to	Description
<code>team_name</code>	string	yes	both	Team name
<code>content</code>	string	yes	<code>team_memory_write</code>	Content stored in the shared memory bucket