/github

GitHub integration: /github login | logout | status | help

Overview

`/github` manages GitHub authentication for the TUI session.

Token sources (highest priority first):

- The `GITHUB_TOKEN` environment variable
- The stored token file `~/.ragent/github_token`
- The authenticated `gh` CLI (`gh auth token`), used as a fallback

`/github login` runs the OAuth device flow. ragent reuses the OAuth application the Copilot provider registers, so the token `/github login` stores is a GitHub App token (`ghu_`) without repository-administration permission: it can read issues, PRs, and repositories, but it cannot create a repository (`POST /user/repos` answers `403 Resource not accessible by integration`). When the stored token is such an app token and `gh` is authenticated, the GitHub tools and the `/new --github` scaffolder use the CLI credential instead. Set `RAGENT_GITHUB_NO_GH_CLI=1` to disable the fallback.

Syntax

```
/github
/github login
/github logout
/github status
/github help
```

Options

Form	Description
`/github`	bare form, no subcommand
`/github login`	start the OAuth device flow
`/github logout`	remove stored credentials
`/github status`	report the current auth state
`/github help`	print command help

The login device flow

1. The command shows a user code in the message window.
2. A pending dialog opens.
3. The flow polls in the background until authorisation completes or the attempt times out.
4. On timeout the dialog reports:

`Device flow timed out - please try /github login again.`

`logout` removes stored credentials. `status` reports the current auth state.

Examples

Bare form:

```
/github
```

Start the device flow:

```
/github login
```

Check the auth state:

```
/github status
```

Remove stored credentials:

```
/github logout
```

Output

- `login` shows the user code and opens the pending dialog; completion and failure arrive via the dialog.
- `status` prints whether a token is loaded.

Notes

- The stored token lives in `~/.ragent/github_token`; `logout` removes stored credentials.
- `/spec reverse` fetches repos through the GitHub API.

Related

- `/gitlab` - the GitLab counterpart
- `/spec reverse` - uses the GitHub API