

/clip

Copy the rendered message-window contents to the system clipboard

Overview

`/clip` copies the message window to the system clipboard exactly as it was last rendered: it joins the plain-text rows the Messages pane produced (`message_content_lines`, the same buffer the text-selection copy feature reads) with newlines and places that text on the clipboard. What lands on the clipboard is therefore exactly what you see on screen, not the raw markdown source.

If nothing has been rendered yet (empty message window), the command reports there is nothing to copy.

Syntax

`/clip`

Options / Subcommands

Form	Description
<code>/clip</code>	Copy the rendered message-window contents to the system clipboard

No arguments or subcommands.

Examples

`/clip`

Success (status bar and bubble show the copied size):

Copied 12345 characters (312 rendered lines) to the clipboard.

`/clip`

Nothing rendered yet:

No rendered message content to copy yet.

Output

- On success the clipboard contains the joined rendered lines; an assistant bubble From: `/clip` reports the character count and rendered-line count, and the status bar shows `clip: copied <chars> chars`.
- On an empty window: assistant bubble No rendered message content to copy yet. and status `clip: nothing to copy`.

Related

- `/actionloop clip` - copy action-loop timing data to the clipboard
- `/cost` - session token usage summary (a common thing to clip)
- Text-selection copy reads the same rendered buffer directly