

/github

GitHub integration: `/github login` | `logout` | `status` | `help`

Overview

`/github` manages GitHub authentication for the TUI session.

Token sources:

- The `GITHUB_TOKEN` environment variable
- The stored token file `~/.ragent/github_token`

`/github login` runs the OAuth device flow.

Syntax

```
/github
/github login
/github logout
/github status
/github help
```

Options

Form	Description
<code>/github</code>	bare form, no subcommand
<code>/github login</code>	start the OAuth device flow
<code>/github logout</code>	remove stored credentials
<code>/github status</code>	report the current auth state
<code>/github help</code>	print command help

The login device flow

1. The command shows a user code in the message window.
2. A pending dialog opens.
3. The flow polls in the background until authorisation completes or the attempt times out.
4. On timeout the dialog reports:

Device flow timed out - please try `/github login` again.

`logout` removes stored credentials. `status` reports the current auth state.

Examples

Bare form:

```
/github
```

Start the device flow:

```
/github login
```

Check the auth state:

```
/github status
```

Remove stored credentials:

```
/github logout
```

Output

- `login` shows the user code and opens the pending dialog; completion and failure arrive via the dialog.
- `status` prints whether a token is loaded.

Notes

- The stored token lives in `~/.ragent/github_token`; `logout` removes stored credentials.
- `/reverse` fetches repos through the GitHub API.

Related

- `/gitlab` - the GitLab counterpart
- `/reverse` - uses the GitHub API